## MATERIAL SAFETY DATA SHEET

Manufactured For: Schaeffer Mfg. Company **Emergency Response Number:** Address: 102 Barton Street 314-865-4105 or **Address** St. Louis, MO 63104 800-325-9962 SECTION 1 - PRODUCT INFORMATION Chemical Family: Polyol Esters & Additives Trade Name: #620 Synquench FRH Fluid Formula: Proprietary formulation. **SECTION 2 – HAZARDOUS INGREDIENTS** COMPONENTS-CHEMICAL NAMES AND COMMON **Exposure Limits** CAS **NAMES** Number % TVL **PEL** ppm mg/m<sup>3</sup> ppm mg/m<sup>3</sup> 42222-50-4 97-99 Neopentyl glycol oleic acid ester 5 5 108-95-2 .001 5 19 5 19 Phenol **Butylated Phenols** NE .28-.35 NE Diphenylamine 122-39-4 .007-.01 10 10 PHYSICAL DATA Section 3 **Boiling Point:** .91 >400°F/190.22°C Specific Gravity: Not Determined Vapor Pressure (mm, Hg): Not Determined % Volatile: Vapor Density (Air = 1): Evaporation Rate: (=1) Not Determined >10 Solubility in Water: Insoluble pH: Not Applicable Appearance and Odor: SECTION 4 - FIRE AND EXPLOSION HAZARD DATA Flammability Limits UEL & LEL ---- Not Determined Flash Point (Method) °F/°C: 560°F/293.3°C C.O.C. (ASTM D-92) Extinguishing Media: Carbon dioxide foam, dry chemical foam, sand, earth, waterfog. Special Fire Fighting Procedures: For fires involving this material, do not enter any enclosed or confined space without protective equipment including self-contained breathing apparatus. Unusual Fire & Explosion Hazards: None expected. SECTION 5 - REACTIVITY HAZARD DATA STABILITY [X] WILL NOT OCCUR [X] STABLE **JUNSTABLE** Hazardous Decomposition [ ] WILL Conditions to Avoid: High heat, high energy ignition sources Incompatibility (Mat. to avoid): Strong oxidants Hazardous Decomposition Products: Oxides of carbon, sulfur, nitrogen, phosphorus, and molybdenum. Conditions to Avoid: None **SECTION 6 - HEALTH HAZARD DATA** Threshold Limit Value and Sources: 5.0/mg/m<sup>3</sup> for oil mist. OSHA & ACGIH. Acute Effects of Overexposure: Nausea and Diarrhea. Ingestion: Irritation and redness to eyes Eye Contact: Skin Contact: Prolonged and repeated contact with the skin can cause irritation and redness to skin. Inhalation: Vapors can be given off under high heat conditions excessive breathing of vapors can cause irritation of the respiratory tract. CHRONIC EFFECTS OF OVEREXPOSURE: None currently known **Emergency and First Aid Procedures:** Swallowing: If a large amount of this material is swallowed give a large amount of water to drink. Do not induce vomiting. Seek medical attention immediately Skin: Wash skin thoroughly with soap and water. Launder contaminated clothing. Inhalation: Remove victim to fresh air. If breathing is labored administer oxygen. If breathing has stopped start artificial respiration immediately. Flush eyes with clear, cool, clean water for 15 minutes. Seek medical attention immediately Eyes: **SECTION 7 – SPILL OR LEAK PROCEDURES** Environmental Impact: This material is not expected to present any environmental problems other than those associated with oil spills. If spilled into a watercourse, call the Coast Guard Toll Free No. 800-424-8802 Procedures To Be Taken If Material Is Released or Spilled: Immediately absorb spilled material with absorbent clay, diatomaceous earth or other suitable material. Keep out of sewers and waterways. Waste Disposal Method: Dispose of at an approved waste or disposal site facility in accordance with all applicable federal, state and local laws and regulations **SECTION 8 – SPECIAL PROTECTION INFORMATION Respiratory Protection:** None required under ordinary conditions of use. Ventilation: No special requirement under ordinary conditions of use and with adequate ventilation. **Eye Protection:** Goggles or face shield. **Protective Clothing:** None required

Date Prepared: 4/30/04 OF-1049 Rev. (1999)

# **SECTION 9 – SPECIAL PRECAUTIONS**

Precautions To Be Taken In Handling and Storage: Do not store near heat, spark, flame or strong oxidizers. Keep containers closed when not in use.

**Special Comments:** Remove oil soaked clothing, launder before reuse. Wash skin thoroughly with soap and water after handling. Throw away oil soaked shoes. Keep away from food and feed products.

## SECTION 10 - ADDITIONAL HEALTH AND TOXICOLOGICAL DATA

HMIS & NFPA Ratings: Health = 1 Fire = 1 Reactivity = 0

This product does not contain any of the chemicals listed on the National Toxicology Program Annual Reports on Carcinogens, the International Agency for Cancer Research Monographs and OSHA's 1910.10 Subpart Z list.

This product does not contain any chemicals that are found on the State of California's Proposition 65 List for chemicals classified as potential reproductive or cancer causing agent.

All of the components in this material are on the US TSCA Inventory. All of the components in this material are in compliance with the Canadian Environmental Protection Act.

#### SARA Title III Information

# I. Section 302/304 Extremely Hazardous

Component	CAS#	%	TPQ(lb.)	RQ (gal)*
Phenol	108-95-2	.001	500	69,022.64-72,790.8

### II. Section 102(a) CERCLA Hazardous Substances

	,			
Component	CAS#	%	RQ (lbs.)	RQ(gal)*
Phenol	108-95-2	.001	1000	138,045.3-145,581.6

<sup>\*</sup> Product RQ for Stationary Source in case of a spill in order to release the regulatory requirement.

### III. Section 313 Toxic Chemical

Component	%	CAS#
Phenol	.001	108-95-2

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any natures whatsoever resulting from the use or reliance upon information. No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers.