

# SAFETY DATA SHEET

### Nitric Acid 42 Baumé Industrial Grade

### Section 1. Identification

Product identifier : Nitric Acid 42 Baumé Industrial Grade

Other means of : Product code: 2504-14215 identification : Historic MSDS #:16051

Product type : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

Identified uses				
Manufacture of chemical products. Manufacture of specialty fertilizers.				
Uses advised against Reason				

Product is not intended for consumer use. Reserved for industrial and professional use only.

Supplier's details : Kgrium Canada Partnership 13131 Lake Fraser Drive, S.E.

Calgary, Alberta, Canada, T2J 7E8

Agrium U.S. Inc.

5296 Harvest Lake Drive Loveland, CO 80538

Company phone number (North America): 1-800-403-2861 (Customer Service)

Emergency telephone number (with hours of operation)

: Agrium 24 Hr Emergency Telephone Numbers:

English:

Transportation Emergencies: 1-800-792-8311 Medical Emergencies: 1-303-389-1653

French or Spanish:

Tranportation or Medical Emergencies: 1-303-389-1654

### Section 2. Hazard identification

Classification of the substance or mixture

: OXIDIZING LIQUIDS - Category 3 CORROSIVE TO METALS - Category 1 SKIN CORROSION - Category 1A SERIOUS EYE DAMAGE - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

**GHS** label elements

Hazard pictograms :







Signal word : Danger

**Hazard statements** : May intensify fire; oxidizer. May be corrosive to metals.

Causes severe skin burns and eye damage.

May cause respiratory irritation.

**Precautionary statements** 

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 1/15

# Section 2. Hazard identification

### **General**

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

### **Prevention**

: Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from clothing and other combustible materials. Keep only in original packaging. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.

### Response

Absorb spillage to prevent material damage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician.

IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

### **Storage**

: Store locked up. Store in a corrosion resistant container with a resistant inner liner.

### **Disposal**

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

### Supplemental label elements

: None known.

Other hazards which do not : None known. result in classification

# Section 3. Composition/information on ingredients

Substance/mixture : Substance

Ingredient name	% (w/w)	CAS number
	67.2 - 67.9	7697-37-2
Water	32.1 - 32.8	7732-18-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid measures

### Description of necessary first aid measures

### **Eye contact**

: CORROSIVE. Begin eye irrigation immediately. All eye exposures to nitric acid require medical evaluation following decontamination. Immediately rinse eyes with large quantities of water or saline for a minimum of 20-30 minutes depending on severity of exposure. If possible, remove contact lenses being careful not to cause additional eye damage. If the initial water supply is insufficient, keep the affected area wet with a moist cloth and transfer the person to the nearest place where rinsing can be continued for the recommended length of time. Call an ambulance for transport to hospital. Continue eye irrigation during transport. For additional advice call the medical emergency number on this safety data sheet or your poison center or medical provider.

### Inhalation

CORROSIVE. If gases or vapors exceed the IDLH or are present in unknown concentrations, rescuers must wear self-contained breathing apparatus and acid resistant protective clothing or coveralls under the requirements of the Hazwoper standard, 29CFR 1910.120.

REMOVE PERSON TO FRESH AIR. Watch closely for signs of wheezing and breathing difficulties. Maintain an open airway. If not breathing, begin CPR. Oxygen may be administered by trained personnel. Affected persons who have

Date of issue/Date of revision 2/15 : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4

### Section 4. First-aid measures

stopped breathing or are having difficulty breathing or are unconscious need immediate medical attention. Symptoms may be delayed after exposure to nitric acid or its thermal decomposition products. The exposed person may need to be kept under medical surveillance for 24-72 hours. Call an ambulance for transport to hospital. For additional advice call the medical emergency number on this SDS or your poison center or medical provider.

### Skin contact

: CORROSIVE. Causes severe burns. Immediately begin rinsing the affected areas with water. Remove contaminated clothing and shoes. Affected areas should be rinsed for a minimum of 20 - 30 minutes or longer depending on severity of exposure. Luke-warm water is recommended for exposures requiring prolonged irrigation. Conscious persons without breathing difficulties may benefit from prolonged irrigation in a fixed shower or bathing facility prior to transport to hospital. Call an ambulance for transport to hospital. Continue skin irrigation during transport. For additional advice call the medical emergency number on this safety data sheet or your poison center or medical provider.

### Ingestion

: CORROSIVE. May cause severe burns to the mouth, throat, and stomach. Oral exposures: If the affected person requires cardiopulmonary resuscitation, avoid mouth to mouth contact. Do not induce vomiting. If vomiting occurs, attempt to keep head lower than the chest so that vomit does not enter the lungs. Wash (decontaminate) face and mouth with water to remove visible material. If the exposed person is conscious and can swallow, give 1-2 sips of water. Do not give anything else by mouth. Loosen tight clothing such as collar, tie, belt or waistband to prevent any breathing restrictions. For signs of breathing difficulties, refer to the INHALATION section. Call an ambulance for transportation to hospital. For additional advice, call the medical emergency number on this safety data sheet or your poison center or medical provider.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye damage. **Inhalation** : May cause respiratory irritation.

**Skin contact**: Causes severe burns.

Ingestion : Corrosive to the digestive tract. May cause burns to the mouth, throat and stomach.
 May cause respiratory irritation.

### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation**: Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs. Adverse symptoms may

include the following:

coughing

respiratory tract irritation

wheezing and breathing difficulties

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur yellow staining of the skin

**Ingestion**: Adverse symptoms may include the following:

nausea or vomiting throat and stomach pain difficulty swallowing respiratory tract irritation

wheezing and breathing difficulties

### Indication of immediate medical attention and special treatment needed, if necessary

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 3/15

### Section 4. First-aid measures

### Notes to physician

: Nitric acid is an acid which may cause coagulative necrosis. Treatment is symptomatic and supportive. The extent of injury depends on duration of exposure and concentration of liquid. Do not attempt to use chemicals to neutralize the exposure. 24 Hr Medical Emergency telephone number for professional support: English: 1-303-389-1653; French or Spanish: 1-303-389-1654.

### **Specific treatments**

Outcomes can be improved by minimizing time to decontamination and extending decontamination times to reduce tissue damage. Expert opinion indicates extended decontamination is required to remove corrosive chemicals. Skin and eye decontamination should be performed for a minimum of 20 - 30 minutes. Extended decontamination times may be required depending on the exposure. To avoid hypothermia, irrigation water should be maintained at a comfortable temperature. If the patient is not in extremis, it may be necessary to delay transport to emergency care facilities to ensure adequate decontamination time. However, early patient transport may be necessary depending on the patient's condition or the availability of water. If possible, continue skin and/or eye irrigation during emergency medical transport. Double-bag contaminated clothing and personal belongings of the patient.

### **Protection of first-aiders**

: No action shall be taken involving any personal risk or without suitable training. Depending on the situation, the rescuer should wear an appropriate mask, gloves, protective clothing and possibly, a self-contained breathing apparatus. Mouth-to-mouth resuscitation of oral exposure patients is not recommended. First-aiders with contaminated clothing should be properly decontaminated.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing media

: Non-flammable. Material will not burn. The product acts as an oxidizing agent, and supports combustion by liberating oxygen even if smothered. Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

# Specific hazards arising from the chemical

Hazardous thermal decomposition products

- : Oxidizing material. May intensify fire. In a fire or if heated, a pressure increase will occur and the container may burst. Corrosive liquid. Reacts violently with water.
- : Decomposition products may include the following materials: Acidic corrosive material nitrogen oxides

# Special protective actions for fire-fighters

: No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Decontaminate tools, equipment and personal protective equipment in a segregated area.

# Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### **Remark**

: Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air. Contain and collect the water used to fight the fire for later treatment and disposal.

# Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Wear appropriate respirator when ventilation is inadequate. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product.

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 4/15

# Section 6. Accidental release measures

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". Refer to Emergency Response Guidebook, Guide 157 for further information regarding spill control and Isolation/ Protective Action Distances Guidelines.

### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused adverse impacts (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

### **Small spill**

: Put on appropriate personal protective equipment (see Section 8). Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. Neutralize acids by applying basic substances (soda ash or lime) or use an acid spill kit. Dispose of via a licensed waste disposal contractor.

### Large spill

: Put on appropriate personal protective equipment (see Section 8). Approach release from upwind. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. The spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Do not get in eves or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Handle the material in a fume hood/cupboard or under local exhaust ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from clothing, incompatible materials and combustible materials. Keep away from alkalis. Keep away from heat. Empty containers retain product residue and can be hazardous. Do not reuse container. Absorb spillage to prevent material damage.

### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Refer to NFPA 400 Hazardous Materials Code for further information on the safe storage and handling of hazardous materials. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Separate from alkalis. Separate from reducing agents and combustible materials. Do not store in unlabeled containers. Keep container tightly closed and sealed until ready for use. Do not allow water to enter container because a violent reaction may occur. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate containment to avoid environmental contamination.

> Contains nitric acid. Will corrode incompatible metals and many plastic materials. 304 or 347 stainless steel are acceptable materials of construction. Storage tanks should be designed to API Standard 650. Tanks should be vented and painted

Date of issue/Date of revision : 7/1/2017 : 6/1/2017 Version :2.4 5/15 Date of previous issue

# Section 7. Handling and storage

white or in light, heat-reflecting colors. Piping should be welded schedule 40 stainless steel. Ensure that all pumps, valves, meters, are of compatible material. Gaskets should be of Teflon. Secondary containment is recommended where practical or required by law. Refer to NFPA 400 Hazmat Code for further information.

# Section 8. Exposure controls/personal protection

### **Control parameters**

### Occupational exposure limits

Ingredient name	Exposure limits
Canadian Regulations:	
Nitric acid	CA Alberta Provincial (Canada, 4/2009).  15 min OEL: 4 ppm 15 minutes.  15 min OEL: 10 mg/m³ 15 minutes.  8 hrs OEL: 2 ppm 8 hours.  8 hrs OEL: 5.2 mg/m³ 8 hours.  CA British Columbia Provincial (Canada, 4/2014).  TWA: 2 ppm 8 hours.  STEL: 4 ppm 15 minutes.  CA Ontario Provincial (Canada, 1/2013).  TWA: 2 ppm 8 hours.  TWA: 5.2 mg/m³ 8 hours.  STEL: 4 ppm 15 minutes.  STEL: 10 mg/m³ 15 minutes.  CA Quebec Provincial (Canada, 1/2014).  TWAEV: 2 ppm 8 hours.  TWAEV: 5.2 mg/m³ 8 hours.  STEV: 4 ppm 15 minutes.  STEV: 4 ppm 15 minutes.  STEV: 4 ppm 15 minutes.
U.S. Federal Regulations: Nitric acid	ACGIH TLV (United States, 4/2014).  TWA: 2 ppm 8 hours.  TWA: 5.2 mg/m³ 8 hours.  STEL: 4 ppm 15 minutes.  STEL: 10 mg/m³ 15 minutes.  OSHA PEL 1989 (United States, 3/1989).  TWA: 2 ppm 8 hours.  TWA: 5 mg/m³ 8 hours.  STEL: 4 ppm 15 minutes.  STEL: 4 ppm 15 minutes.  STEL: 10 mg/m³ 15 minutes.  NIOSH REL (United States, 10/2013).  TWA: 2 ppm 10 hours.  TWA: 5 mg/m³ 10 hours.  STEL: 4 ppm 15 minutes.  STEL: 4 ppm 15 minutes.  STEL: 4 ppm 15 minutes.  OSHA PEL (United States, 2/2013).  TWA: 2 ppm 8 hours.  TWA: 5 mg/m³ 8 hours.
Water	None assigned.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 6/15

# Section 8. Exposure controls/personal protection

### Individual protection measures

### **Hygiene measures**

# : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection**

# : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product.

### **Skin protection**

### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended:

butyl rubber neoprene Viton®

Contact your personal protective equipment manufacturer to verify the compatibility of the equipment for the intended purpose.

### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Wear suitable coveralls capable of preventing significant penetration of the substance or chemical-resistant protective suit. Recommended:

DuPont Tychem® 4000, Tychem® 6000, Tychem® 6000 FR, or Tychem® 10000 Kappler Zytron® 200 or Zytron® 500

Lakeland ChemMax® 2, or Lakeland Interceptor®

or equivalent

Contact your personal protective equipment manufacturer to verify the compatibility of the equipment for the intended purpose.

### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Impervious rubber safety boots. Contact your personal protective equipment manufacturer to verify the compatibility of the equipment for the intended purpose.

### Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Air filtering respirators are not acceptable for use with this material. Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. For U.S. work sites where respiratory protection is required, ensure that a respiratory protection program meeting 29 CFR 1910.134 requirements is in place. Full chemical-resistant suit and self-contained breathing apparatus should be worn only by trained and authorized persons.

# Section 9. Physical and chemical properties

### **Appearance**

Physical state : Liquid. [Oily liquid.]

Color : Colorless to light yellow.

Odor threshold : Pungent.

Not available.

pH : <1

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 7/15

# Section 9. Physical and chemical properties

Melting point: Not available.Boiling point: Not available.Flash point: Not applicable.Evaporation rate: Not available.

Flammability (solid, gas) : Not applicable. The substance will not burn. Oxidizing liquid. Material supports

combustion.

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure

: Product:

rapor pressure : Product

1.04 kPa (7.8 mm Hg) [20°C] - based on the partial pressure of nitric acid, 2.4 mm

Hg, plus the partial pressure of water, 5.4 mm Hg

4.80 kPa (36 mm Hg) [50°C] - based on the partial pressure of nitric acid, 12.5 mm

Hg, plus the partial pressure of water, 23.5 mm Hg

**Vapor density** : 2.2 [Air = 1]

Relative density : 1.4

**Solubility** : Easily soluble in the following materials: cold water and hot water.

Solubility in water : Water-soluble liquid

Partition coefficient: n-

octanol/water

: -2.3

Auto-ignition temperature

Decomposition temperature

: Not applicable.: Not available.: Not available.

# Section 10. Stability and reactivity

### Reactivity

**Viscosity** 

Reactive or incompatible with the following materials:

Inorganic hydroxide. Organic chemicals.

Avoid contamination by any source including metals, dust and organic materials.

Reacts violently when water is added to this product.

Reacts violently with bases. Incompatible with halogens.

Refer to NFPA 400 Hazardous Materials Code for further information on the safe

storage and handling of hazardous materials.

**Chemical stability**: The product is stable.

# Possibility of hazardous reactions

: Hazardous reactions or instability may occur under certain conditions of storage or

use. Conditions may include the following: Contact with incompatible substances. contact with combustible materials

Reactions may include the following: risk of causing or intensifying fire

May be corrosive to metals. Contact your sales representative or a metallurgical

specialist to ensure compatability with your equipment.

### **Conditions to avoid**

: Drying on clothing or other combustible materials may cause fire. Keep away from clothing, incompatible materials and combustible materials. Refer to NFPA 400 Hazardous Materials Code for further information on the safe storage and handling

of hazardous materials.

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 8/15

# Section 10. Stability and reactivity

### Incompatible materials

: Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air.

Reactive or incompatible with the following materials:

alkalis

combustible materials reducing materials reactive metals

# Hazardous decomposition products

: Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air. Contact your sales representative or a metallurgical specialist to ensure compatability with your equipment.

# **Section 11. Toxicological information**

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Nitric acid Water	LC50 Inhalation Vapor LD50 Oral	Rat Rat	244 ppm >90 g/kg	30 minutes
vvaler	LD50 Oral	Rai	>90 g/kg	-

**Conclusion/Summary** 

: Corrosive to the digestive tract. Corrosive to eyes and skin.

### Irritation/Corrosion

Not available.

### **Conclusion/Summary**

Skin : Corrosive to the skin.

Eyes : Corrosive to eyes.

**Respiratory**: May cause respiratory irritation.

### **Sensitization**

Not available.

### **Conclusion/Summary**

Skin: No known significant effects or critical hazards.Respiratory: No known significant effects or critical hazards.

# Mutagenicity

Not available.

### **Conclusion/Summary**

: No known significant effects or critical hazards.

### **Carcinogenicity**

Not available.

# Conclusion/Summary

: No known significant effects or critical hazards.

### Reproductive toxicity

Not available.

### **Conclusion/Summary**

: No known significant effects or critical hazards.

### **Teratogenicity**

Not available.

### **Conclusion/Summary**: No known significant effects or critical hazards.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 9/15

# Section 11. Toxicological information

Not available.

Information on the likely routes of exposure

Skin contact
 Eye contact
 Inhalation

### Potential acute health effects

Eye contactInhalationCauses serious eye damage.May cause respiratory irritation.

Skin contact : Causes severe burns.

**Ingestion** : Corrosive to the digestive tract. May cause burns to the mouth, throat and stomach.

May cause respiratory irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs. Adverse symptoms may

include the following:

coughing

respiratory tract irritation

wheezing and breathing difficulties

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur yellow staining of the skin

**Ingestion**: Adverse symptoms may include the following:

nausea or vomiting throat and stomach pain difficulty swallowing respiratory tract irritation

wheezing and breathing difficulties

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : See above

effects

Potential delayed effects : Skin: scarring

Respiratory Tract: pulmonary edema

Long term exposure

Potential immediate : See above

effects

Potential delayed effects : Chronic bronchitis

Potential chronic health effects

**Conclusion/Summary**: Adverse effects are typically the result of acute overexposure. These effects may

be long term or permanent in nature.

General : See above

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Solvential in the property of the prop

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 10/15

# Section 11. Toxicological information

# **Section 12. Ecological information**

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Nitric acid	Acute LC50 180 mg/l Marine water	Crustaceans - Carcinus maenas - Adult	48 hours
	Acute LC50 72 mg/l Fresh water	Fish - Gambusia affinis - Adult	96 hours

**Conclusion/Summary** 

: Harmful to aquatic organisms.

### Persistence and degradability

Conclusion/Summary : Readily biodegradable

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Nitric acid	-	-	Readily

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Nitric acid	-2.3	-	low
Water	-1.38		low

### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	TDG Classification	DOT Classification	Mexico Classification	IMDG	IATA
UN number	2031	2031	2031	Not available.	Not available.
UN proper shipping name	NITRIC ACID, other than red fuming, with at least 65%, but not more than 70% nitric acid	Nitric acid other than red fuming, with at least 65%, but not more than 70% nitric acid	ACIDO NITRICO, excepto el ácido nítrico fumante rojo, con no más de 70% ácido nítrico	Not available.	Not available.

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 11/15

# **Section 14. Transport information**

Transport hazard class(es)	8 (5.1)	8, (5.1)	8 (5.1)	Not available.	Not available.
		CONCORD STATE OF THE PARTY OF T	8		
Packing group	II	OMDIZER 5.1	111	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	Explosive Limit and Limited Quantity Index 1  Passenger Carrying Ship Index Forbidden  Passenger Carrying Road or Rail Index Forbidden  Classification per the current revision, Transportation of Dangerous Goods Regulation, Part 2, Sec 2.3.	Reportable quantity 1000 lbs / 454 kg [85.667 gal / 324. 29 L] Packages of less than the reportable quantity are not subject to Hazmat transportation requirements.  Packaging instruction Passenger aircraft Quantity limitation: Forbidden.  Cargo aircraft Quantity limitation: 30 L  Special provisions A6, B2, B47, B53, IB2, IP15, T8, TP2	Special provisions P001 IBC02 PP81 B15 T8 TP2		-

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL and

the IBC Code

# Section 15. Regulatory information

**Canadian lists** 

**Canadian NPRI** : The following components are listed: Nitric acid

**CEPA Toxic substances** : None of the components are listed. : All components are listed or exempted.

Canada inventory

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

12/15 Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version :2.4

# Section 15. Regulatory information

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Inform Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

**Inventory list** 

**Australia** : All components are listed or exempted. China : All components are listed or exempted. **Europe** : All components are listed or exempted. **Japan** All components are listed or exempted. Malaysia : All components are listed or exempted. **New Zealand** : All components are listed or exempted. **Philippines** All components are listed or exempted. Republic of Korea : All components are listed or exempted. **Taiwan** : All components are listed or exempted.

: Not determined. **Turkey** 

**U.S. Federal Regulations:** : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

**TSCA 8(b) inventory:**: All components are listed or exempted.

Clean Water Act (CWA) 311: Nitric acid

Clean Air Act (CAA) 112 regulated toxic substances: Nitric acid

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** 

Clean Air Act Section 602 : Not listed

Class I Substances

Clean Air Act Section 602

Class II Substances

: Not listed

: Not listed

**DEA List I Chemicals** 

(Precursor Chemicals)

: Not listed

**DEA List II Chemicals** 

: Not listed

(Essential Chemicals)

### SARA 302/304 Composition/information on ingredients

		SARA 302 TPQ SARA 304 RQ		SARA 302 TPQ		RQ
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Nitric acid	67.2 - 67.9	Yes.	1000	85.7	1000	85.7

**SARA 304 RQ** : 1000 lbs / 454 kg [85.7 gal / 324.3 L]

**SARA 311/312** 

Classification : Immediate (acute) health hazard

Composition/information on ingredients

13/15 Date of issue/Date of revision : 7/1/2017 :2.4 Date of previous issue : 6/1/2017 Version

Nitric Acid 42 Baumé Industrial Grade

# **Section 15. Regulatory information**

Name		hazard	Sudden release of pressure	Reactive	(acute) health	Delayed (chronic) health hazard.
Nitric acid	67.2 - 67.9	Yes.	No.	No.	Yes.	No.

### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	Nitric Acid 42 Baumé	7697-37-2	67.2 - 67.9
Supplier notification	Nitric Acid 42 Baumé	7697-37-2	67.2 - 67.9

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### **State regulations**

Massachusetts: The following components are listed: Nitric AcidNew York: The following components are listed: Nitric AcidNew Jersey: The following components are listed: Nitric AcidPennsylvania: The following components are listed: Nitric Acid

California Prop. 65 : Not listed.

### Section 16. Other information

**History** 

Date of issue/Date of

revision

Date of previous issue : 6/1/2017 Version : 2.4

Indicates information that has changed from previously issued version.

: 7/1/2017

Prepared by : Agrium Wholesale

Environment, Health, Safety and Security e-mail: productsafety@agrium.com

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

HPR = Hazardous Products Regulations

### Procedure used to derive the classification

Classification	Justification
OXIDIZING LIQUIDS - Category 3 CORROSIVE TO METALS - Category 1 SKIN CORROSION - Category 1A SERIOUS EYE DAMAGE - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Expert judgment Expert judgment Expert judgment Weight of evidence Weight of evidence

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 14/15

## Section 16. Other information

### References

 Transportation of Dangerous Goods Act and Clear Language Regulations, current edition at time of (M)SDS preparation, Transport Canada;

Hazardous Products Act and Regulations, current revision at time of (M)SDS preparation. Health Canada:

Domestic Substances List, current revision at time of (M)SDS preparation, Environment Canada:

29 CFR Part 1910, current revision at time of SDS preparation, U.S. Occupational Safety and Health Administration:

40 CFR Parts 1-799, current revision at time of SDS preparation, U.S.

Environmental Protection Agency;

49 CFR Parts 1-199, current revision at time of SDS preparation, U.S. Department of Transport;

Threshold Limit Values for Chemical Substances, current edition at time of SDS preparation, American Conference of Governmental Industrial Hygienists; NFPA 400, National Fire Codes, National Fire Protection Association, current edition at time of SDS preparation;

NFPA 704, National Fire Codes, National Fire Protection Association, current edition at time of SDS preparation;

Corrosion Data Survey, Sixth Edition, 1985, National Association of Corrosion Engineers;

ERG 2016, Emergency Response Guidebook, U.S. Department of Transport, Transport Canada, and the Secretariat of Transportation and Communications of Mexico

Hazardous Substances Data Bank, current revision at time of SDS preparation, National Library of Medicine, Bethesda, Maryland

Integrated Risk Information System, current revision at time of SDS preparation, U. S. Environmental Protection Agency, Washington, D.C.

Pocket Guide to Chemical Hazards, current revision at time of SDS preparation, National Institute for Occupational Safety and Health, Cincinnati, Ohio; Agency for Toxic Substances and Disease Registry Databank, current revision at time of SDS preparation, U.S. Department of Health and Human Services, Atlanta, Georgia

National Toxicology Program, Report on Carcinogens, Division of the National Institute of Environmental Health Sciences, Research Triangle Park, North Carolina. Registry of Toxic Effects of Chemical Substances. National Institute for Occupational Safety and Health, Cincinnati, Ohio

The Fertilizer Institute, Product Toxicology Testing Program Results, TFI, Washington, D.C., 2003

### **Notice to reader**

### DISCLAIMER AND LIMITATION OF LIABILITY

The information and recommendations contained in this Safety Data Sheet ("SDS") relate only to the specific material referred to herein (the "Material") and do not relate to the use of such Material in combination with any other material or process. The information and recommendations contained herein are believed to be current and correct as of the date of this SDS. HOWEVER, THE INFORMATION AND RECOMMENDATIONS ARE PRESENTED WITHOUT WARRANTY, REPRESENTATION OR LICENSE OF ANY KIND, EXPRESS OR IMPLIED, WITH RESPECT TO THEIR ACCURACY, CORRECTNESS OR COMPLETENESS, AND THE SELLER, SUPPLIER AND MANUFACTURER OF THE MATERIAL AND THEIR RESPECTIVE AFFILIATES (COLLECTIVELY, THE "SUPPLIER") DISCLAIM ALL LIABILITY FOR RELIANCE ON SUCH INFORMATION AND RECOMMENDATIONS. This SDS is not a guarantee of safety. A buyer or user of the Material (a "Recipient") is responsible for ensuring that it has all current information necessary to safely use the Material for its specific purpose.

FURTHERMORE, THE RECIPIENT ASSUMES ALL RISK IN CONNECTION WITH THE USE OF THE MATERIAL. THE RECIPIENT ASSUMES ALL RESPONSIBILITY FOR ENSURING THE MATERIAL IS USED IN A SAFE MANNER IN COMPLIANCE WITH APPLICABLE ENVIRONMENTAL, HEALTH, SAFETY AND SECURITY LAWS, POLICIES AND GUIDELINES. THE SUPPLIER DOES NOT WARRANT THE MERCHANTABILITY OF THE MATERIAL OR THE FITNESS OF THE MATERIAL FOR ANY PARTICULAR USE AND ASSUMES NO RESPONSIBILITY FOR INJURY OR DAMAGE CAUSED DIRECTLY OR INDIRECTLY BY OR RELATED TO THE USE OF THE MATERIAL.

Date of issue/Date of revision : 7/1/2017 Date of previous issue : 6/1/2017 Version : 2.4 15/15