



J.P. Nissen Co.
2544 Fairhill Avenue
P.O. Box 339 Glenside, PA 19038

Phone: 215-886-2025
Fax: 215-886-0707
Emergency: 1-800-424-9300

Material Safety Data Sheet

January 5, 2011

Product Identification NISSEN JUMBO FELTIP PAINT MARKER - BLACK NISSEN NYLON TIP FELTIP PAINT MARKER FINE LINE – BLACK MARKER

HMIS Ratings- Health 1 Flammability 3 Reactivity 1
NFPA Ratings- Health 1 Flammability 3 Reactivity 0

Hazardous ingredients – The paint is contained in a valve action reservoir and will not leak under normal conditions.

<u>Ingredients</u>	<u>CAS#</u>	<u>%</u>	<u>Exposure Limits</u>
Ethyl Benzene	100-41-4	1-10	100 ppm/8 hrs pel
Xylol (Xylene)	1330-20-7	45-55	100 ppm/8 hrs pel
Black Pigment	1333-86-4	1-10	5 mg/cu.m Respirable dust
Hydrocarbon Resin	68131-77-1	10-20	15mg/m3

Physical Data

Boiling point: 246-404 F **Vapor density:** Heavier than air.

Volatile %: 66.7% by volume **Specific gravity:** Less than 1.

Evaporation rate: Slower than Ethyl Ether **Vapor Pressure:** 6.2 mm hg @ 20 deg. C

Appearance: Black viscous liquid with an aromatic odor.

Volatile Organic Compounds data not required because product only produced in quantities of less than 1 liter

Fire and Explosion Data

Flammability Class: IC **Flashpoint:** 75 deg..F **LEL:**1% **UEL** 7%

Extinguishing Media: Foam, Carbon dioxide, or any Class B extinguishing agent. Water may be unsuitable as an extinguishing medium, but helpful in keeping adjacent containers cool.

Health Hazard Data

Listed as possible carcinogen: NTP – No IARC – OSHA – No

Symptoms of over exposure: Headache, Dizziness, Nausea, Coughing, Eye, Throat and Skin Irritation.

Effects of overexposure: Slight to severe irritation to eyes and mucous membranes. Dermatitis.
Affects central nervous system.

Emergency first aid: Inhalation; seek fresh air. Give artificial respiration if not breathing.

Skin contact; Wash with soap and water. Ingestion; Call Physician. Do not induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs

Reactivity Data

Stability: Stable, **hazardous polymerization:** Will not occur.

Conditions to avoid: Heat, open flames and sparks.

Incompatibility: Do not expose to strong oxidizers.

Hazardous decomposition products: Carbon monoxide, carbon dioxide.

Environmental Protection Procedures

Remove all sources of ignition, ventilate area, and use absorbent material to clean spills.

Disposal method: Dispose of waste in accordance with all local, state and federal regulations.

Control Measures

Respiratory protection: None required under normal use.

Ventilation: Normal-working conditions.

Protective Equipment: Safety glasses and gloves. No special clothing required under normal conditions of use.

Transportation

Shipping Class ORM-D

UN Number 1263

Package Group III

Toxic Substances Control Act TSCA States:

All components of this product are listed in the EPA's Inventory of Chemical Substances as required under the Toxic Substances Control Act (TSCA)

For more information visit: <http://www.nissenmarkers.com/>