SAFETY DATA SHEET



Date of Issue/Date of Revision: January 29, 2020

Version 3

SECTION 1. IDENTIFICATION

Product Name

: White Intumescent Fire-Retardant Polyurethane Foam Kote

Product Code

: 6060A

Other Means of

: Not Available

Identification

NOT AVAIIADIO

Product Type

: Liquid

Relevant Identified uses of the substance or mixture and uses advised against

Product Use

: Industrial applications.

Use of the substance/

: Coating. Paints, Painting-related materials

Mixture

Use advised against

: Not Applicable

Supplier

: Flame Control Coatings 4120 Hyde Park Boulevard Niagara Falls, NY 14305

Emergency Telephone

Number

: 800-535-5053

352-323-3500 (International)

Technical Phone Number

: 716-282-1399 (8 am - 5 pm EST)

SECTION 2. Hazards Identification

OSHA/HCS Status

: This material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

Classification of the

: This material is not considered hazardous by the OSHA Hazard Communication ${\bf r}$

Standard (29 CFR 1910.1200).

Substance or mixture

GHS Label Elements



Hazard Pictograms

Signal Word

: Warning

Hazard Statements

: H303: May be harmful if swallowed

H317: May cause an allergic skin reaction

H333: May be harmful if inhaled

Precautionary Statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Do not breathe vapor.

Response

 $: \ \, \textbf{Get medical attention if you feel unwell. IF exposed or concerned: } \ \, \textbf{Get medical}$

attention.

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

Storage : Store locked up.

SECTION 2. Hazards Identification (Con't)

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Supplemental Label

Elements

: Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic

fumes when heated.

Hazards not Otherwise Classified : Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3. Composition/Information on Ingredients

Substance/Mixture : Mixture

Product name : Intumescent Fire-Retardant Paint and Tints

Ingredient Name	%	CAS Number	
Pentaerythritol	5 - 10	115-77-5	
Titanium Dioxide	10 - 30	13463-67-7	

SUB codes represent substances without registered CAS numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the suppler and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8

SECTION 4. First Aid Measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occurs during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of Necessary First Aid Measures

Eye Contact : Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing

is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen

by trained personnel.

Skin Contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Most Important Symptoms/Effects, Acute and Delayed

Potential Acute Health Effects

Eye Contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

SECTION 4. First Aid Measures (Con't)

Skin Contact : May cause skin dryness and irritation

Ingestion : No known significant effects or critical hazards.

Over-Exposure Signs/Symptoms

Eye Contact : No specific data. Inhalation : No specific data.

Skin Contact : Adverse symptoms may include the following:

> Irritation **Dryness** Cracking

Ingestion : No specific data

Indication of Immediate Medical Attention and Special Treatment Needed, if Necessary

Notes to Physician : In case of inhalation of decomposition products in a fire, symptoms may be

delayed. The exposed person may need to be kept under medical surveillance for

48 hours.

Specific Treatments : No specific treatment

Protection of First-Aiders : No action shall be taken involving any person risk or without suitable training. If

may be dangerous to the person providing aid to give mouth-to-mouth

resuscitation.

See toxicological information (Section 11)

SECTION 5. Fire-Fighting Measures

Extinguishing Media

Personnel

Suitable Extinguishing Media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable Extinguishing Media : None known.

Specific Hazards Arising : In a fire or if heated, a pressure increase will occur and the container may burst. From the Chemical

Hazardous Thermal : Decomposition products may include the following materials:

Decomposition products Carbon Dioxide **Nitrogen Oxides** Carbon Monoxide Metal Oxide/Oxides

Special Protective : Promptly isolate the scent by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or **Actions for Fire-Fighters**

without suitable training.

Special Protective : Fire-fighters should wear appropriate protective equipment and self-contained **Equipment for Fire-Fighters** breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency : No action shall be taken involving any personal risk or with suitable training.

> Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or

mist. Provide adequate ventilation. Wear appropriate respirator when

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

ventilation is inadequate. Put on appropriate personal protective equipment.

SECTION 6. Accidental Release Measures

For Emergency Responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "for non-emergency personnel.

Environmental Precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and Material for Containment and Cleaning Up

Small Spills

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spills

: Stop leak if with risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7. Handling and Storage

Conditions for Safe Storage

: Do not store below the following temperatures: 5°C (41°F). Store in accordance including any with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8. Exposure Controls/Personal Protection

Control Parameters

Occupational Exposure Limits

Ingredient Name	Exposure Limit
Pentaerythritol	OSHA PEL (United States, 2/2013)
	TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction
	TWA: 15 mg/m ³ 8 hours. Form: Total Dust
	ACGIH TLV (United States, 4/2014)
	TWA: 10 mg/m ³ 8 hours
Titanium Dioxide	OSHA PEL (United States, 2/2013)
	TWA: 15 mg/m ³ 8 hours. Form: Total Dust
	ACGIH TLV (United States, 4/2014)
	TWA: 10 mg/m ³ 8 hours

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

SECTION 8. Exposure Controls/Personal Protection (Con't)

Key to Abbreviations

A = Acceptable Maximum Peak

ACGIH = American Conference of Governmental Industrial Hygienists

C = Ceiling Limit

F = Fume

IPEL = Internal Permissible Exposure Limited

OSHA = Occupational Safety and Health Administration

R = Respirable

Z = OSHA 29CFR 1910, 1200 Subpart Z - Toxic and Hazardous Substances

S = Potential Skin Absorption SR = Respiratory Sensitization

SS = Skin Sensitization

STEL = Short Term Exposure Limit Values

TD = Total Dust

TLV = Threshold Limit Value TWA = Time Weighted Average

Consult Local Authorities for Acceptable Exposure Limits

Recommended Monitoring

Procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate Engineering Controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental Exposure

: Emissions from ventilation or work process equipment should be Controls checked to ensure them comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection

: Safety glasses with side shields.

Skin Protection

Hand Protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body Protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling the product.

Other Skin Protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

SECTION 8. Exposure Controls/Personal Protection (Con't)

Respiratory Protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate certified respirators. Use a properly fitted, air-purifying or air-fed r respirator complying with an approved standard if a risk assessment indicates this is necessary.

SECTION 9. Physical and Chemical Properties

Appearance

Physical State : Liquid
Color : White

Odor : Mild Odor

Odor Threshold : Not Available

pH : 8.0 to 11.5

Melting Point : Not Available

Boiling Point : 100°C (>200°F)

Flash Point : Not Available

Material Supports Combustion : Yes

Auto-Ignition Temperature : Not Available

Decomposition Temperature : Not Available

Flammability (Solid, Gas) : Not Available

Lower and Upper Explosive

(Flammable) Limits

: Not Available

Relative Density : 1.4 - 1.5

Density : 11.9 lb/gal

Solubility in Water : Dilutable

Partition Co-efficient: N-Octanol/Water : Not Available

Viscosity : Kinematic [40°C (104°F)]: >0.21 cm²/s (>21 cSt)

% Solid (w/w) : 66
% Volatiles by Volume : 49
Coating VOC : 38 g/L
Material VOC : 20 g/L

SECTION 10. Stability and Reactivity

Reactivity : No specific test data related to reactivity available for this product or its

ingredients.

Chemical Stability : The product is stable

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

SECTION 10. Stability and Reactivity

Possibility of Hazardous Reactions

Incompatible Materials

Conditions to avoid

: Under normal conditions of storage and use, hazardous reactions will not occur.

 $: \ When \ exposed \ to \ high \ temperatures \ may \ produce \ hazardous \ decomposition \\$

products. Refer to protective measures listed in Sections 7 and 8.

: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, and strong acids

Hazardous Decomposition : Decomposition products may include the following materials: carbon Products

monoxide, carbon dioxide, smoke, oxides of nitrogen.

SECTION 11. Toxicological Information

Information on toxicological Effects

Acute Toxicity

Product/Ingredient Name	Results	Species	Dose	Exposure
Pentaerythritol	LD50 Oral	Rat	18500 mg/kg	-
Titanium Dioxide	LD50 Oral	Rat	>10 g/kg	-

Conclusion/Summary : There is no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin : Not Classified (based on available data, classification criteria not met)

Eyes : Not Classified (based on available data, classification criteria not met)

Respiratory : Not Classified (based on available data, classification criteria not met)

Sensitization

Conclusion/Summary

Skin : Not Classified (based on available data, classification criteria not met)

Respiratory : Not Classified (based on available data, classification criteria not met)

Mutagenicity

Conclusion/Summary : Not Classified (based on available data, classification criteria not met)

Carcinogenicity

Conclusion/Summary : Not Classified (based on available data, classification criteria not met)

Classification

Product/Ingredient Name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-

^{*}Titanium Dioxide is in a form that is not available for respiration

Carcinogen Classification Code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; reasonably anticipated to be a human carcinogen

OSHA: +

Not Listed/No Regulated: -

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

SECTION 11. Toxicological Information (Con't)

Reproductive Toxicity

Conclusion/Summary : Not Classified (based on available data, classification criteria not met)

Teratogenicity

Conclusion/Summary : Not Classified (based on available data, classification criteria not met)

Specific Target Organ Toxicity

(Single Exposure)

: Not Classified (based on available data, classification criteria not met)

Specfic Target Organ Toxicity

(Repeated Exposure)

:

Aspiration Hazard : Not Classified (based on available data, classification criteria not met)

Information on the likely routes of exposure

Potential Acute Health Effects

Eye Contact : Not Classified (based on available data, classification criteria not met)

Inhalation : Not Classified (based on available data, classification criteria not met)

Skin Contact : Not Classified (based on available data, classification criteria not met)

Ingestion : Not Classified (based on available data, classification criteria not met) Over-

Exposure Signs/Symptoms

Eye Contact : Not Classified (based on available data, classification criteria not met)

Inhalation : Not Classified (based on available data, classification criteria not met)

Skin Contact : Adverse symptoms may include the following:

Irritation Dryness Cracking

Ingestion : Not Classified (based on available data, classification criteria not met)

Delayed and Immediate Effects and Also Chronic Effects From Short and Long Term Exposure

Conclusion/Summary : There is no data available on the mixture itself. If splashed in the eyes, the liquid

may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eve contact.

Short Term Exposure

Potential Immediate Effects : There is no data available on the mixture itself.

Potential Delayed Effects : There is no data available on the mixture itself.

Long Term Exposure

Potential Immediate Effects : There is no data available on the mixture itself.

Potential Delayed Effects : There is no data available on the mixture itself.

Potential Chronic Health Effects

General : May cause damage to organs through prolonged or repeated exposure. Prolonged

or repeated contact can defat the skin and lead to irritation, cracking and/or

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

dermatitis.

SECTION 11. Toxicological Information (Con't)

Carcinogenicity : Not Classified (based on available data, classification criteria not met), carcinogens

present are not in respirable form and do not pose a hazard

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental Effects : No known significant effects or critical hazards.

Fertility Effects : No known significant effects or critical hazards.

Numerical Measures of Toxicity

Acute Toxicity Estimates

Route	ATE Value		
Oral	8750.6 mg/kg		

SECTION 12. Ecological Information

Toxicity

Product/Ingredient Name	Result	Species	
Titanium Dioxide	Acute LC50 >100 mg/l Fresh Water	Daphnia - Daphnia Magna	48 hours

Persistence and Degradability

: Not available

Bioaccumulative Potential

Product/Ingredient Name	Log Pow	BCF	Potential
Pentaerythritol	-1.69	1.26	low

Mobility in Soil

Soil/Water Partition Coefficient (Koc): Not available

SECTION 13. Disposal Considerations

Disposal Methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should be not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PRESONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental Release Measures.

SECTION 14. Transport Information

	DOT	IMDG	IATA
UN Number	Not Regulated	Not Regulated	Not Regulated
UN Proper Shipping Name	-	-	-
Transport Hazard Class(es)	-	-	-
Packing Group	-	-	-
Environmental Hazards	No	No	No
Marine Pollutant Substances	Not Applicable	Not Applicable	Not Applicable

Additional Information

DOT

: None Identified

IMDG

: None Identified

IATA

: None Identified

Special Precautions for User

: Transport with user's premises: always transport in closed containers that are upright and secure. Ensure that person transporting the product know what to do in the event of an accident or spillage.

SECTION 15. Regulatory Information

United States Inventory (TSCA 8b)

: All components are listed or exempted

Australia Inventory (AICS)

: At least one component is not listed.

Canada Inventory (DSL)

: All components are listed or exempted

China Inventory (IECSC)

: At least one component is not listed.

Europe Inventory (REACH)

 $: \ Please \ contact \ your \ supplier \ for \ information \ on \ the \ inventory \ status \ of \ this$

material

Japan Inventory (ENCS)

: At least one component is not listed.

Korea Inventory (KECI)

: At least one component is not listed.

New Zealand (NZloC)

: At least one component is not listed.

Philippines Inventory (PICCS)

: At least one component is not listed.

Untied States

SARA 302/304

SARA 3-4 RO

: Not applicable

Composition/Information on Ingredients

No products were found.

SARA 311/312

Classification

: Immediate (acute) health hazard Delayed (chronic) health hazard

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

SECTION 15. Regulatory Information (Con't)

Composition/Information on Ingredients

Product/Ingredient Name	Fire Hazard	Sudden Release Of Pressure	Reactive	Immediate (Acute) Health Hazard	Delayed (Chronic) Health Hazard
Pentaerythritol	Yes	No	No	No	No
Titanium Dioxide	No	No	No	No	Yes

Chemical Name SARA 313 CAS Number Concentration

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

SECTION 16. Other Information

Hazardous Material Information System (U.S.A.)

Health: 2*

Flammability: 1

Physical Hazards: 0

(*) Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is registered mark of the National Paint & Coatings Association (NPCA).

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 2

Flammability: 1

Instability: 0

Date Previous Issue

: No previous validation

Organization that Prepared the SDS

: Flame Control Coatings

Key to Abbreviations

: ATE = Acute Toxicity Estimate **BCF** = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labeling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = Iogarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution from ships, 1973 as modified by the

protocol of 1978. ("Marpol" = Marine Pollution).

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Flame Control Coatings and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the

Product Name: White Intumescent Fire-Retardant Polyurethane Thermal Barrier

products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.