

**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.****W. F. Taylor Co., Inc.**11545 Pacific Avenue  
Fontana, CA 92337-8228  
951/360-6677

CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

---

PRODUCT NAME: **META-POXY X-LINK ADHESIVE**  
ITEM NUMBER: 2092-4  
ITEM DESCRIPTION: Meta-Poxy X-Link Adh 4-gal  
PRODUCT DESCRIPTION: Medium Viscosity adhesive  
CHEMICAL FAMILY: Amide-Ester-Acrylate Resin Blend  
REVISION DATE: 01/02/14 REVIEW DATE: / / PRINT DATE: 01/23/14 PRINT TIME: 12:19

## HMIS HAZARD RATING

LEAST: 0	HEALTH: 1
SLIGHT: 1	FLAMMABLE: 0
MODERATE: 2	REACTIVITY: 0
HIGH: 3	
EXTREME: 4	

PREPARED BY: ROBERT DDAMULIRA  
PREEMPTS PREVIOUS MSDS SHEETS

---

**SECTION II HAZARDOUS INGREDIENTS**

No Hazardous Ingredients Per Current OSHA Regulations.

---

**SECTION III PHYSICAL DATA**

<u>Hazard</u>	<u>CAS #</u>	<u>WT/Wt % Less Than</u>
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS		
BOILING POINT:	NO DATA	
LBS / GAL:	8.3 - 8.6	
EVAPORATION RATE:	LOW	
VAPOR DENSITY:	LOW	
VAPOR PRESSURE:	LOW	
PERCENT VOLATILE:	39 - 41 (BY WEIGHT)	
COLOR:	YELLOW	
ODOR:	MILD	

---

**SECTION IV FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT, PENSKY-MARTIN C.C.: NA  
AUTO IGNITION TEMPERATURE, DEGREES F: NA  
FLAMMABLE LIMITS IN AIR (% BY VOLUME): LEL: NA UEL: NA  
EXTINGUISHING MEDIA:

(X) WATER SPRAY (X) CARBON DIOXIDE ( ) OTHER  
(X) FOAM (X) DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: USE SELF CONTAINED BREATHING APPARATUS AND TURN OUT GEAR. WATER MAY BE INEFFECTIVE BUT SHOULD BE USED TO KEEP THE EXPOSED CONTAINERS COOL.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN

---

**SECTION V HEALTH HAZARD IDENTIFICATION**

---

PRODUCT NAME: **META-POXY X-LINK ADHESIVE**  
ITEM NUMBER: 2092-4  
ITEM DESCRIPTION: Meta-Poxy X-Link Adh 4-gal  
REVISION DATE: 01/02/14 REVIEW DATE: / / PRINT DATE:01/23/14 PRINT TIME: 12:19

---

SYMPTOMS OF OVER EXPOSURE:

INHALATION:MAY CAUSE SLIGHT IRRITATION TO THE UPPER RESPIRATORY TRACT.  
EYES:VAPOR MAY CAUSE IRRITATION.  
SKIN:MAY CAUSE SLIGHT SKIN IRRITATION.  
INGESTION: NOT A LIKELY ROUTE OF ENTRY UNDER PROPER HANDLING CONDITIONS. MAY CAUSE VOMITING. SYMPTOMS MAY BE SAME AS INHALATION.

HEALTH EFFECTS OR RISK FROM EXPOSURE:

ACUTE: INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTACT WITH EYES AND SKIN MAY RESULT TO IRRITATION. INGESTION MAY RESULT TO GASTRIC DISTURBANCES.  
CHRONIC: NOT KNOWN

FIRST AID PROCEDURES:

EYES CONTACT: WASH WITH WATER AT FOR LEAST 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.  
SKIN CONTACT: REMOVE FROM SKIN AND WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.  
INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN, IF NECESSARY. SEEK MEDICAL ATTENTION.  
INGESTION: IF SWALLOWED, CALL PHYSICIAN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN.

---

**SECTION VI REACTIVITY DATA**

STABILITY: STABLE  
CONDITIONS TO AVOID: PROTECT FROM FREEZING, EXCESSIVE HEAT.  
INCOMPATIBILITY (MATERIALS TO AVOID): METAL SALTS MAY COAGULATE THE PRODUCT.  
HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): OXIDES OF CARBON, WATER, AND ORGANIC COMPOUNDS OF UNKNOWN STRUCTURE  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

---

**SECTION VII SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED  
KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS.SCRAPE UP TO COLLECT AND PLACE INTO CLOSED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS.

---

**SECTION VIII SPECIAL PROTECTION INFORMATION**

---

PRODUCT NAME: **META-POXY X-LINK ADHESIVE**  
ITEM NUMBER: 2092-4  
ITEM DESCRIPTION: Meta-Poxy X-Link Adh 4-gal  
REVISION DATE: 01/02/14 REVIEW DATE: / / PRINT DATE:01/23/14 PRINT TIME:12:19

---

VENTILATION AND ENGINEERING CONTROLS: USE LOCAL EXHAUST. DO NOT USE CLOSED AIR-CIRCULATING SYSTEM. OPEN WINDOWS AND DOORS IF NECESSARY.  
RESPIRATORY PROTECTION: NIOSH RESPIRATOR IF NEEDED.  
CLOTHING: CHEMICAL RESISTANT GLOVES, APRON, COVERALLS, AND BOOTS AS NECESSARY TO PREVENT CONTACT.  
EYE PROTECTION: CHEMICAL GOGGLES OR FACE SHIELD  
OTHER CLOTHING AND EQUIPMENT: IF CLOTHING BECOMES CONTAMINATED, REMOVE AND CLEAN BEFORE REWEARING.  
WORK PRACTICES, HYGIENIC PRACTICES: FOLLOW LABEL INSTRUCTIONS.  
PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: USE GOGGLES AND GLOVES WHEN CLEANING ADHESIVE FROM EQUIPMENT. MAINTAIN PROPER VENTILATION.

---

**SECTION IX SPECIAL PRECAUTIONS**

KEEP OUT OF THE REACH OF CHILDREN. DO NOT INDUCE VOMITING IF INGESTED. AVOID BREATHING BUILDUP OF VAPORS. USE WITH ADEQUATE VENTILATION.  
PROTECT AGAINST PHYSICAL DAMAGE. STORE IN A COOL DRY PLACE (50 - 90 DEGREES F). KEEP AWAY FROM HEAT AND SPARKS. KEEP FROM FREEZING.

---

**SECTION X TOXICOLOGICAL PROPERTIES**

NOT KNOWN

**SECTION XI REGULATORY INFORMATION**

OSHA HAZARD COMMUNICATION STANDARD (29CFR 1910.1200) HAZARD CLASS (ES): NONE  
SARA TITLE III SECTION 312 HAZARD CLASS: NONE  
EPA SARA TITLE III SECTION 313: NONE

ALL COMPONENTS OF THIS PRODUCT ARE EITHER LISTED OR EXEMPT IN THE U.S. EPA TSCA INVENTORY LIST

CA PROPOSITION 65

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

**NOTICE**

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.

---