SAFETY DATA SHEET BISTITE II Primer 2

1. IDENTIFICATION

Revision Date 08/05/2014

Product Name BISTITE II Primer 2

Identified uses Dental Cement, a component of kit. For dental professionals only.

Supplier Tokuyama Dental America Inc. Tel: (877) 378 3548 (Toll-Free)

Contact Person http://www.tokuyama-dental.com/contact.htm

Manufacturer Tokuyama Dental Corporation

38-9, Taitou 1-chome, Taitou-ku, Tokyo

110-0016, Japan TEL: +81-3-3835-2261

Emergency Telephone

Washington

National Capital Poison Center 3201 New Mexico Avenue, Suite 310

Washington, DC 20016

Telephone: +1 202 362 3867

Emergency telephone: +1 800 222 1222

Fax: +1 202 362 8377 E-mail: pc@poison.org Web site: http://www.poison.org

San Francisco

California Poison Control System at San Francisco General Hospital

University of California San Francisco, Box 1369

1001 Potrero Avenue, Bldg 5 Rm 2A21 San Francisco, California 94143-1369 Telephone: +1 415 643 3200

Emergency telephone: +1 800 222 1222

Fax: +1 415 502 6010

E-mail: coadmin@calpoison.org Web site: http://www.calpoison.org

http://www.who.int/ipcs/poisons/centre/en/

2. HAZARD(S) IDENTIFICATION

Appearance Clear liquid.

ColorLight (or pale). YellowishOdorSlight odor. , Characteristic.

GHS Pictogram







Signal Word	Danger
Hazard Statements	

H225	Highly flammable liquid and vapour.

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P260 Do not breathe vapour/spray.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P403+233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local regulations.

Contains 2-HYDROXYETHYL METHACRYLATE

ACETONE

bisphenol A di(2-hydroxy propoxy) dimethacrylate

N,N-DIMETHYL-PARA-TOLUIDINE triethylene glycol dimethacrylate

GHS Classification

Physical and Chemical Hazards Flam. Liq. 2 - H225

Human health Acute Tox. 4 - H302; Acute Tox. 4 - H312; Acute Tox. 4 - H332; Skin Irrit. 2 -

H315;Eye Irrit. 2 - H319;Skin Sens. 1 - H317;STOT SE 3 - H336;STOT RE 2 -

H373

Environment Not classified.

Hazard Not Otherwise Classified (HNOC)

Repeated exposure may cause skin dryness or cracking.

OSHA Regulatory Status

This Product is Hazardous under the OSHA Hazard Communication Standard.

General Information

May cause irritation to the respiratory system. Vapors may cause drowsiness and dizziness. Harmful if swallowed. Irritating. (DIGESTIVE SYSTEM.) This chemical may cause skin/eye irritation. Product has a defatting effect on skin. May cause sensitization by skin contact.

3. COMPOSITION/INFORMATION ON INGREDIENTS

2-HYDROXYETHYL METHACRYLATE

30-60%

CAS No.: 868-77-9 EC No.: 212-782-2

GHS Classification

Skin Irrit. 2 - H315; Eye Irrit. 2 - H319; Skin Sens. 1 - H317

ACETONE 30-60%

CAS No.: 67-64-1 EC No.: 200-662-2

GHS Classification

Flam. Liq. 2 - H225; Eye Irrit. 2 - H319; STOT SE 3 - H336

bisphenol A di(2-hydroxy propoxy) dimethacrylate

5-10%

CAS No.: 1565-94-2 EC No.: 216-367-7

GHS Classification

Skin Sens. 1 - H317; Aquatic Chronic 3 - H412

dibutyl hydroxy toluene < 1%

CAS No.: 128-37-0 EC No.: 204-881-4

GHS Classification Aquatic Chronic 1 - H410

N,N-DIMETHYL-PARA-TOLUIDINE 1-5%

CAS No.: 99-97-8 EC No.: 202-805-4

GHS Classification

Acute Tox. 3 - H301; Acute Tox. 3 - H311; Acute Tox. 3 - H331; STOT RE 2 - H373; Aquatic Chronic 3 - H412

triethylene glycol dimethacrylate 1-5%

CAS No.: 109-16-0 EC No.: 203-652-6

GHS Classification

Skin Irrit. 2 - H315; Eye Irrit. 2 - H319; Skin Sens. 1 - H317

4. FIRST-AID MEASURES

Description of first aid measures

General Information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once.

Ingestion

Immediately rinse mouth and drink plenty of water (200-300 ml). Get medical attention if any discomfort continues.

Skin Contact

Wash the skin immediately with soap and water.

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

Most important symptoms and effects, both acute and delayed

Inhalation

Irritating to respiratory system. Vapors may cause drowsiness and dizziness.

Ingestion

Irritating. (DIGESTIVE SYSTEM.)

Skin Contact

Irritating to skin. Product has a defatting effect on skin. May cause sensitization by skin contact.

Eye Contact

Irritating and may cause redness and pain.

Indication of any immediate medical attention and special treatment needed

Notes To The Physician

CAUTION! First aid personnel must be aware of own risk during rescue! Wear suitable protective clothing.

5. FIRE-FIGHTING MEASURES

Auto Ignition Temperature (°C)

Not available.

Flammability Limit - Lower(%)

Not available.

Flammability Limit - Upper(%)

Not available.

Flash point (°C) -15°C

Extinguishing Media

Fire can be extinguished using: Foam. Carbon dioxide or dry powder.

Specific Hazards

When heated and in case of fire, irritating vapors/gases may be formed.

Special Fire Fighting Procedures

Avoid breathing fire vapors.

Protective Equipment For Fire-Fighters

Wear full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Wear protective clothing as described in Section 8 of this material safety data sheet.

Environmental Precautions

Do not discharge into drains, water courses or onto the ground.

Spill Clean Up Methods

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

Reference to other sections

For personal protection, see section 8.

7. HANDLING AND STORAGE

Handling

All handling to take place in well-ventilated area.

Storage

Store under refrigerated conditions at temperatures between 0 to 10°C (32 to 50°F). Keep away from heat, direct sunlight, sparks and open flames.

Storage Class

Flammable liquid storage.

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT	STD	TWA (8-hrs)		STEL (15 min)		Notes
ACETONE	PEL	1000 ppm	2400 mg/m3			
ACETONE	ACGIH	500 ppm		750 ppm		A4
dibutyl hydroxy toluene	ACGIH		2 mg/m3			A4

COMPONENT	IDLH
ACETONE	2500 ppm

ACGIH=American Conference of Governmental Industrial Hygienists.

A4: Not Classifiable as a Human Carcinogen.

Protective Equipment





Engineering Measures

Provide adequate general and local exhaust ventilation.

Respiratory Equipment

In case of inadequate ventilation use suitable respirator.

Hand Protection

Wear protective gloves.

Eye Protection

Wear approved safety goggles.

Other Protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene Measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear liquid.

 Color
 Light (or pale). Yellowish

 Odor
 Slight odor., Characteristic.

 Solubility
 No information available.

Initial boiling point and boiling range

Not available.

Melting point (°C)

Not available.

Relative density

Not available.

Vapor density (air=1)

Not available.

Vapor pressure

Not available.

Evaporation rate

Not available.

pH-Value, Conc. Solution 7

pH-Value, Diluted Solution

Not available. **Viscosity**Not available.

Decomposition temperature (°C)

Not available.

Odour Threshold, Lower

Not available.

Odour Threshold, Upper

Not available.

Flash point -15°C

Auto Ignition Temperature (°C)

Not available.

Flammability Limit - Lower(%)

Not available.

Flammability Limit - Upper(%)

Not available.

Partition Coefficient

(N-Octanol/Water)

Not available.

Explosive properties

Not available.

Other Flammability

Not available.

Oxidising properties

Not available.

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Stability

HIGHLY FLAMMABLE!

Hazardous reactions:

Not available.

Conditions To Avoid

Keep away from heat, sparks and open flame. Protect against direct sunlight.

Materials To Avoid

Strong oxidizing agents.

Hazardous Decomposition Products

Toxic gases are generated when heated.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Not available.

Skin Corrosion/Irritation:

Irritating to skin. Product has a defatting effect on skin.

Serious eye damage/irritation:

Irritating and may cause redness and pain.

Respiratory or skin sensitisation:

Respiratory sensitisation

Not available.

Skin sensitisation

.

May cause sensitization by skin contact.

Germ cell mutagenicity:

Not available.

Carcinogenicity:

Acetone

EPA: Data are inadequate for an assessment of human carcinogenic potential

IARC Carcinogenicity

Butylated hydroxytoluene (BHT): IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP - Carcinogenicity

Not listed.

OSHA - Carcinogenicity

Not listed.

Reproductive Toxicity:

Not available.

Specific target organ toxicity - single exposure:

May cause irritation to the respiratory system. Vapors may cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure:

STOT - Repeated exposure

Not available.

Aspiration hazard:

Viscosity

Not available.

12. ECOLOGICAL INFORMATION

Toxicity

No data available.

Degradability

No data available.

Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient

Not available.

Mobility:

No information available.

Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB Substances.

Other adverse effects

Not known.

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION

UN No. (DOT/TDG) 1133 UN No. (IMDG) 1133 UN No. (ICAO) 1133

DOT Proper Shipping Name

ADHESIVES, CONTAINING A FLAMMABLE LIQUID

TDG Proper Shipping Name

ADHESIVES, CONTAINING A FLAMMABLE LIQUID

DOT Hazard Class

3

DOT Hazard LabelFlammable Liquid

TDG Class 3
TDG Label(s) 3

IMDG Class 3
ICAO Class 3

Transport Labels



DOT Pack Group II

IMDG Pack Group II

Air Pack Group II

Environmentally Hazardous Substance/Marine Pollutant

No.

EMS F-E, S-D
Special precautions for user Not available.

Transport in Bulk according to Annex II of MARPOL 73/78 and the IBC Code Notes

Not applicable.

15. REGULATORY INFORMATION

Regulatory Status (US)

This Product is Hazardous under the OSHA Hazard Communication Standard. California Proposition 65. Warning: N, N-DIMETHYL-PARA-TOLUIDINE This product contains a chemical known to the State of California to cause cancer.

Regulatory References

29 CFR 1910. 1200(g) Federal Regulations (OSHA Standard).

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed.

ACETONE; 5, 000 lbs (2270 Kg)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed.

SARA 313 Emission Reporting

None of the ingredients are listed.

CAA Accidental Release Prevention

None of the ingredients are listed.

SARA (311/312) Hazard Categories

Fire Acute Chronic

OSHA Highly Hazardous Chemicals

None of the ingredients are listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed.

N, N-DIMETHYL-PARA-TOLUIDINE; Known to the State of California to cause cancer.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed.

Massachusetts "Right To Know" List

The following ingredients are listed.

ACETONE

dibutyl hydroxy toluene

Rhode Island "Right To Know" List

The following ingredients are listed.

ACETONE

dibutyl hydroxy toluene

Minnesota "Right To Know" List

The following ingredients are listed.

ACETONE

dibutyl hydroxy toluene

New Jersey "Right To Know" List

The following ingredients are listed.

ACETONE

dibutyl hydroxy toluene

Pennsylvania "Right To Know" List

The following ingredients are listed.

ACETONE

dibutyl hydroxy toluene

International Inventories

EU - EINECS/ELINCS

All ingredients are listed or exempt.

Canada - DSL/NDSL

All ingredients are listed or exempt.

US - TSCA

All ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed.

16. OTHER INFORMATION

Revision Comments

This is first issue.

Revision Date

08/05/2014

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such.

Disclaimer