



Material Safety Data Sheet (MSDS)

Section 1 - Chemical Product and Company Identification

<p>MANUFACTURER/SUPPLIER: US Office: WD-40 Company 1061 Cudahy Place San Diego, CA 92138 -0607</p> <p>Information Phone #: (619) 275-1400 Emergency Phone # 24 hr: Health Emergency only: 1-888-324-7596 (PROZAR) Chemtrec: (800) 424-9300 – Designated for use only in the event of chemical emergencies involving a spill, leak, fire exposure or accident involving chemicals.</p>	<p>Canadian Office: WD-40 Products [Canada] LTD. P.O. Box 220 Toronto, Ontario M9C 4V3</p> <p>Information Phone #: (416) 622-9881 Emergency Phone # 24 hr: Canutec: (613) 996-6666 – Designated for use only in the event of chemical emergencies involving a spill, leak, fire exposure or accident involving chemicals.</p>
---	---

PRODUCT NAME: 3-IN-ONE® Professional Garage Door Lube

FORMULA: Mixture

GENERAL CLASS: Aerosol Lubricant

MSDS DATE OF PREPARATION: January 23, 2015

HMIS Rating

Health: 2

Flammability: 4

Reactivity: 1

Section 2 – Hazards Identification

DANGER! EXTREMELY FLAMMABLE AEROSOL. CONTENTS UNDER PRESSURE. AVOID HEAT, SPARKS AND FLAMES. HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INTENTIONALLY INHALED.

Avoid breathing concentrated vapors. Use with adequate ventilation. Avoid eye contact.

Potential Health Effects:

Primary Routes of Entry: Inhalation, skin and eye contact.

Acute Effects:

Inhalation: High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

Skin Contact: May cause skin irritation with short-term exposure with redness, itching and burning of the skin. Prolonged and/or repeated contact may produce defatting and possible dermatitis. Repeated contact may cause an allergic skin reaction and/or a photosensitization (sensitivity to sunlight).

Eye Contact: Contact may be irritating to eyes. May cause redness, stinging, swelling and tearing.

Ingestion: This product has low oral toxicity. If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness, loss of consciousness, delirium and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

Chronic Effects: None expected.

Medical Conditions Aggravated by Exposure: Preexisting eye, skin and respiratory conditions may be aggravated by exposure.

Section 3 – Composition/Information on Ingredients

Ingredient	CAS #	Weight Percent
Aliphatic Petroleum Distillates	64742-47-8	50-60
White Mineral Oil	8009-03-8	2-4
Polydimethylsiloxane	63148-62-9	2-4
Propellant (propane, n-butane)	74-98-6/106-97-8	35-45

See Section 8 for Exposure Limits

Section 4 – First Aid Measures

Ingestion (Swallowed): Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

Eye Contact: Flush thoroughly with water for 15 minutes. Remove contact lenses if present after the first 5 minutes and continue flushing. Get medical attention if irritation persists.

Skin Contact: Wash with soap and water. If irritation develops and persists, get medical attention.

Inhalation (Breathing): If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

Section 5 – Fire Fighting Measures

Flammability Properties: Very flammable per CCCR criteria.

Flash Point: -34°C/-29.2°F closed cup (liquid)

Flammable Limits: LEL: 0.6% UEL: 9.5%

Extinguishing Media: Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

Special Fire Fighting Procedures: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting containers.

Unusual Fire and Explosion Hazards: Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Combustible liquid and vapor. This material can release flammable vapors when heated above ambient temperatures. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces.

Section 6 – Accidental Release Measures

Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required

Section 7 – Handling and Storage

Handling: Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty. Intentional misuse by deliberately concentrating vapors and inhaling can be harmful or fatal. Keep out of the reach of children.

Storage: Do not store above 120°F or in direct sunlight. U.F.C (NFPA 30B) Level 3 Aerosol. Do not place can in hot water or near radiators, stoves or other sources of heat. Protect from physical damage.

Section 8 – Exposure Controls/Personal Protection

Occupational Exposure Limits

Aliphatic Petroleum Distillates	1200 mg/m ³ TWA (manufacturer recommended)
Polydimethylsiloxane	None Established
White mineral oil	5 mg/m ³ TWA (inhalable) ACGIH TLV
Propane	None Established
n-Butane	1000 ppm STEL ACGIH TLV

The Following Controls are Recommended for Normal Consumer Use of this Product

Engineering Controls: Use in a well-ventilated area.

Personal Protection:

Eye Protection: Avoid eye contact. Always spray away from face.

Skin Protection: Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where prolonged skin contact is likely.

Respiratory Protection: None needed for normal use with adequate ventilation.

For Bulk Processing or Workplace Use the Following Controls are Recommended

Engineering Controls: Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

Personal Protection:

Eye Protection: Safety goggles recommended where eye contact is possible.

Skin Protection: Wear chemical resistant gloves.

Respiratory Protection: None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow provincial regulations and good Industrial Hygiene practice.

Section 9 – Physical and Chemical Properties

Vapor Pressure:	40-60 psig @ 70 F	Vapor Density (air = 1):	>1
Specific Gravity (Water = 1):	0.81	Evaporation Rate (Butyl Acetate = 1):	Less than 1
Boiling Range: -	161-257°C (322-495°F) (Petroleum Solvent)	% Volatiles by Volume:	>90%
Solubility in water (20 C):	Insoluble	VOC	49%
Appearance and Odor:	Clear, aerosol spray. Petroleum odor.	Coefficient of Water/Oil Distribution:	N/D

Section 10 – Stability and Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Avoid heat, sparks, flames and other sources of ignition. Do not puncture or incinerate containers.

Incompatibilities: Strong oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, silicon oxides, formaldehyde, smoke, fumes and unburned hydrocarbons.

Section 11 – Toxicological Information

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard. None of the components of this product is listed as a carcinogen or suspected carcinogen or is considered a reproductive hazard.

Section 12 – Ecological Information

No data is currently available.

Section 13 Disposal Considerations

Aerosol containers should not be punctured, compacted in home trash compactors or incinerated. Empty containers may be disposed of through normal waste management options. If this product becomes a waste, it would be expected to meet the criteria of a flammable hazardous waste. However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations.

Section 14 – Transportation Information

DOT Surface Shipping Description: DOT Surface Shipping Description: Consumer Commodity, ORM-D until 12/31/2013

After 1/1/2014 UN1950, Aerosols, 2.1 Ltd. Qty (Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)

IMDG Shipping Description: UN1950, Aerosols, 2.1

Canadian TDG Shipping Description: Limited Quantity

Section 15 – Regulatory Information

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian Domestic Substances List or non-Domestic Substances List.

Canadian WHMIS Classification Class B-5 (Flammable Aerosol), Class D-2-B (Toxic material causing other toxic effects)

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

Section 16 – Other Information

**HMIS Hazard Rating: Health – 1 (slight hazard), Fire Hazard – 4 (severe hazard),
Physical Hazard – 0 (minimal hazard)**

Prepared By: Industrial Health & Safety Consultants, Inc. 1-203-929-3473

Revision Date: 01/23/15

Supersedes: 02/27/12

This MSDS complies with OSHA guidelines set by 29 CFR 1910.1200 and the Canadian WHMIS regulations. The foregoing information has been compiled from sources believed to be accurate but is not warranted to be. Recipients are advised to confirm in advance of need that data is correct. Standards change without notice. It is the responsibility of the recipient to insure that their personnel have been notified of any changes which may affect them. The data provided on this MSDS are not meant to be used as specifications, only as guideline information as to the safe use of this product. User should refer to applicable laws before use.

N/D = Not Determined N/E = Not Established N/A = Not Applicable

4090100 / No.0068803