

MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name: Seche Gel Lacquer Cleanser
Formula: 30-8084
Item#: 83180
DATE: 04-14-11
REV: 01
Manufacturer: American International Industries
2220 Gaspar Ave
Los Angeles, CA 90040
Chem-Tel: (800) 255-3924

Section 2. Composition / Information on Ingredients

Hazardous Ingredients:

Component	CAS #	%	Exposure Limits ppm	
			ACGIH-TLV	OSHA-PEL
Ethyl Acetate	141-78-6	54.00%	400ppm	400ppm
Isopropyl Alcohol	67-63-0	31.00%	400ppm	400ppm

Section 3. Hazardous Identification

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: Eyes, skin or inhalation

Eye: Vapors are irritating to the eyes. Splashes may cause severe irritation, with stinging, tearing, redness and pain.

Skin: Irritating due to defatting action on skin. Causes redness, pain, drying and cracking of the skin.


Ingestion: Swallowing small amounts is not likely to produce harmful effects. Ingestion of larger amounts may produce abdominal pain, nausea and vomiting. Aspiration into lungs can produce severe lung damage and is a medical emergency. Other symptoms are expected to parallel inhalation.

Inhalation: Inhalation of vapors irritates the respiratory tract. May cause coughing, dizziness, dullness, and headache. Higher concentrations can produce central nervous system depression, narcosis, and unconsciousness.

Chronic Exposure: Prolonged or repeated skin contact may produce severe irritation or dermatitis.

Section 4. First Aid Measures

First Aid for Eye: Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention.



MATERIAL SAFETY DATA SHEET

First Aid for Skin: Immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

First Aid for Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

First Aid for Ingestion: Aspiration hazard. If swallowed, vomiting may occur spontaneously, but DO NOT INDUCE. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Never give anything by mouth to an unconscious person. Call a physician immediately.

Section 5. Fire Fighting Measures

Flash Point (°F/°C): 30.2°F / -1.0°C (Tag Closed Cup)

Flammable Limit (vol%): LEL: 2.0
UEL: 12.5
Extremely Flammable Liquid and Vapor!

Auto-ignition Temp. (vol%): Not available

Extinguisher Media: Dry chemical, alcohol foam or carbon dioxide. Water may be ineffective. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors.


Fire Fighting Procedures: Fire should be fought from a safe distance. Firefighters should wear full face, self-contained breathing apparatus and full protective clothing.

Unusual Fire and Explosion Hazards: Closed containers exposed to excessive heat may rupture. Do not crush or puncture containers.

Section 6. Accidental Release Measures

Spill or Release Procedures: Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak and to flush spills away from exposures. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

Section 7. Handling and Storage



MATERIAL SAFETY DATA SHEET

Handling & Storing: Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

Section 8. Exposure Controls / Personal Protective Equipment

Respiratory Protections (Specific Type):

Not normally needed under proper conditions of use and storage.

Ventilation to be Used:

Local and Mechanical recommend

Other Protective Clothing and Equipment:

Skin: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye: Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

Hygienic Work Practices:

Wash hand thoroughly after using this product and before eating, drinking, or smoking.

Section 9. Physical and Chemical Properties

Appearance @ 25°C: Green Liquid

Viscosity (RVT): Not applicable

Odor @ 25°C: Mild odor

Vapor Pressure: Not available.

pH Not applicable

Vapor Density: Not available.

Specific Gravity: ~0.90

Density: 7.47 lb/gl

Ignition: Not applicable

Material VOC: 5.64.lb/gl

Melting Point: Not applicable

Boiling Point: Not available

Solubility in Water Soluble


Section 10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide may form when heated to decomposition.

Incompatibility (Materials to Avoid):



MATERIAL SAFETY DATA SHEET

Concentrated nitric and sulfuric acid mixtures, oxidizing materials, chloroform, alkalis, chlorine compounds, acids, potassium t-butoxide.

Hazardous Polymerization:

Will not occur

Conditions to Avoid: Heat, flames, ignition sources and incompatibles.

Section 11. Toxicological Information

Toxicological data for Ethyl Acetate:

RTECS#:

CAS# 141-78-6: AH5425000

LD50/LC50:

CAS# 141-78-6:

Inhalation, mouse: LC50 = 45 gm/m³/2H;

Inhalation, rat: LC50 = 200 gm/m³;

Oral, mouse: LD50 = 4100 mg/kg;

Oral, rabbit: LD50 = 4935 mg/kg;

Oral, rat: LD50 = 5620 mg/kg;

Skin, rabbit: LD50 = >20 mL/kg;

Carcinogenicity:

CAS# 141-78-6: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

Section 12. Ecological Information

Ecological data for Ethyl Acetate:

Ecotoxicity: Fish: Fathead Minnow: 230mg/L; 96H; Daphnid LC50=2500 mg/L/96H Golden orfe LC50=270 mg/L/48H

Environmental: Terrestrial: Expected to have high mobility in soil. Volatilization of ethyl acetate from moist soil surfaces is expected to be important. Aquatic: Not expected to adsorb to suspended solids and sediment in water. Atmospheric: Expected to exist solely as a vapor in the ambient atmosphere. Vapor-phase ethyl acetate is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 10 days.


Physical: Substance biodegrades at a high rate with little bioconcentration.

Other: No information available.

Section 13. Disposable Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

Section 14. Transportation Information



MATERIAL SAFETY DATA SHEET

<DOT Information>

Proper Shipping Name (49CFR 172.101):	Flammable Liquid n.o.s. (Ethyl Acetate, Isopropyl Alcohol)
Hazard Class:	3
UN/NA:	UN1993
Packing Group:	II

Section 15. Regulatory Information

Chemical Inventory Status

TSCA: Yes
EC: Yes
Japan: Yes
Australia: Yes

Chemical Inventory Status

Korea: Yes
DSL: Yes
NDSL: No
Phil.: Yes

EU Dangerous Substances: Acetone

SARA Title III - Section 313, Toxic Materials:

Acetone (67-64-1), 80-90%

EPA Hazards:

Acute: Yes
Chronic: No
Flammability: Yes

Section 16. Other Information

No additional information available.