

MATERIAL SAFETY DATA SHEET

100% SOLIDS EPOXY GROUT PART "A" - WHITE BASE

1. Product And Company Identification			
Supplier CUSTOM BUILDING PRODUCTS 10400 Pioneer Blvd., Unit #3 Santa Fe Springs, CA 90670 UNITED STATES Company Contact: GEORGE MARCINA Telephone Number: (562) 968-2980 Ext 103 FAX Number: (562) 903-2697 E-Mail: georgem@cbpmail.net Web Site: www.custombuildingproducts.com	Manufacturer CUSTOM BUILDING PRODUCTS 10400 Pioneer Blvd., Unit #3 Santa Fe Springs, CA 90670 UNITED STATES Company Contact: GEORGE MARCINA Telephone Number: (562) 968-2980 Ext 103 FAX Number: (562) 903-2697 E-Mail: georgem@cbpmail.net Web Site: www.custombuildingproducts.com		
Supplier Emergency Contacts & Phone Number GEORGE MARCINA: (562) 968-2980	Manufacturer Emergency Contacts & Phone Number GEORGE MARCINA: (562) 968-2980		
Issue Date: 04/06/2006 Product Name: 100% SOLIDS EPOXY GROUT PART "A" - WHITE BASE CAS Number: Not Established Chemical Family: Epoxy Chemical Formula: Mixture MSDS Number: 558 Product Code: 3041 Product Identification Text THIS MSDS IS APPLICABLE TO THE FOLLOWING PRODUCTS: 100 % SOLIDS EPOXY GROUT PART "A" - WHITE BASE			
2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
C12 and C14 ALKYL GLYCIDYL ETHERS	68609-97-2		
BISPHENOLADIGLYCIDYL ETHERPOLYMER	25068-38-6		
SILICA, AMORPHOUS	7631-86-9		1 - 5
TITANIUMDIOXIDE	13463-67-7		25 - 35
3. Hazards Identification			
Primary Routes(s) Of Entry EYE, SKIN AND NOSE.			
Eye Hazards EYE IRRITATION (Rabbit) - MODERATE IRRITATION. PROLONGED EXPOSURE TO LOW CONCENTRATIONS OF VAPOR MAY CAUSE EYE IRRITATION.			
Skin Hazards SKIN IRRITATION (Rabbit) - MODERATE IRRITATION. REPEATED AND/OR PROLONGED CONTACT WITH THE SKIN MAY CAUSE ALLERGIC REACTION. DERMAL LD50 >4,000 MG/KG (RABBIT)			
Ingestion Hazards ACCUTE ORAL EFFECTS - LD50 > 5,0000 g/kg (RAT). INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION.			

MATERIAL SAFETY DATA SHEET

100% SOLIDS EPOXY GROUT PART "A" - WHITE BASE

3. Hazards Identification - Continued

Inhalation Hazards

INHALATION OF VAPORS MAY CAUSE IRRITATION IN THE RESPIRATORY TRACT.

Conditions Aggravated By Exposure

ALLERGY, ECXEMA, SKIN CONDITIONS

Conditions Aggravated By Overexposure

CAN CAUSE SKIN AND EYE IRRITATION AND ALERGIC SKIN REACTIONS. MAY CAUSE DEFATTENING AND DERMATITIS.

REMOVE CONTAMINATED CLOTHING. WASH BEFORE RE-USE.

4. First Aid Measures

Eye

IMMEDIATELY FLUSH WITH WATER FOR 15 MIN. HOLD EYELIDS APART TO INSURE RINSING OF ENTIRE EYE SURFACE AND LID WITH WATER. GET IMMEDIATE MEDICAL ATTENTION.

Skin

IMMEDIATELY WIPE OFF EXCESS MATERIAL WITH A DRY TOWEL. REMOVE CONTAMINATED CLOTHING AND SHOES. WASH AFFECTED AREAS THOROUGHLY WITH LARGE AMOUNTS OF SOAP AND WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

Ingestion

GIVE AT LEAST 3 GLASSES OF WATER. DO NOT INDUCE VOMITING. NEVER GIVE FLUIDS OR INDUCE VOMITING IF VICTIM IS UNCONSCIOUS OR HAVING CONVULSIONS. SEEK IMMEDIATE MEDICAL ATTENTION.

Inhalation

MOVE PERSON TO FRESH AIR. SEEK MEDICAL ATTENTION IF IRRATITION DEVELOPS OR IF BREATHING BECOMES DIFFICULT.

5. Fire Fighting Measures

Flash Point: 233 °F 93 °C

Flash Point Method: CLOSED CUP

Fire And Explosion Hazards

DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE TOXIC.

Extinguishing Media

FOAM, CO2, DRY CHEMICAL, WATER SPRAY.

Fire Fighting Instructions

USE SELF CONTAINING BREATHING APPARATUS.

6. Accidental Release Measures

IN CASE MATERIAL IS RELEASED OR SPILLED, AVOID ALL PERSONAL CONTACT. SOAK UP IN ABSORBENT MATERIAL AND SHOVEL INTO A CLOSABLE CONTAINER. FLUSH AREA WITH WATER SPRAY. AVOID INHALATION OF VAPORS.

7. Handling And Storage

Handling And Storage Precautions

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. AVOID BREATHING VAPOR, MIST OR SPRAY. USE ONLY IN AREAS WITH GOOD VENTILATION. WASH THOROUGHLY AFTER HANDLING. STORE IN DRY AREAS AWAY FROM HEAT OR OPEN FLAME.

Work/Hygienic Practices

PRACTICE CAUTION AND PERSONAL CLEANLINESS TO AVOID SKIN AND EYE CONTACT. AVOID BREATHING VAPORS OF HEATED PRODUCT.

MATERIAL SAFETY DATA SHEET

100% SOLIDS EPOXY GROUT PART "A" - WHITE BASE

8. Exposure Controls/Personal Protection

Engineering Controls

USE IN WELL VENTILATED AREAS.

Eye/Face Protection

WEAR SAFETY GLASSES WITH SIDE SHIELDS.

Skin Protection

WEAR CHEMICAL RESISTANT, PLASTIC OR RUBBER GLOVES.

Respiratory Protection

NONE REQUIRED UNDER NORMAL CONDITIONS.

Other/General Protection

WEAR APPROPRIATE CLOTHING TO PREVENT THE POSSIBILITY OF SKIN OR EYE CONTACT.

Ingredient(s) - Exposure Limits

SILICA, AMORPHOUS

ACGIH TLV-TWA 10 mg/m³ - inhalable

ACGIH - TLV- TWA 3 MG/M³ - respirable

OSHA PEL - 6 mg/m³

OEHHA REL 3 micrograms/m³

TITANIUM DIOXIDE

ACGIH TLV-TWA 10 mg/m³

OSHA PEL-TWA 15 mg/m³

9. Physical And Chemical Properties

Appearance

WHITE LIQUID

Odor

FAINT ODOR.

Chemical Type: Mixture

Physical State: Liquid

Boiling Point: >390 °F > 200 °C

Specific Gravity: 1.5 g/ml @ 77F

Percent Volatiles: NIL

Solubility: SLIGHT SOLUBILITY IN WATER

Evaporation Rate: NO DATA

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR.

Conditions To Avoid (Stability)

NONE KNOWN

Incompatible Materials

STRONG OXIDIZING AGENTS AND STRONG ACIDS.

Hazardous Decomposition Products

CARBON DIOXIDE AND CARBON MONOXIDE AND NITROGEN OXIDES

11. Toxicological Information

Eye Effects

MODERATE IRRITATION

MATERIAL SAFETY DATA SHEET

100% SOLIDS EPOXY GROUT PART "A" - WHITE BASE

11. Toxicological Information - Continued

Skin Effects

MODERATE IRRITATION

Acute Oral Effects

LD 5- > 5,000 MG/KG

12. Ecological Information

Acute Toxicity - Fish And Invertebrates

RAINBOW TROUT - 96 HRS - LC 50 = 1.5 MG/ML

ZEBRA FISH - 96 HRS - LC 50 = 2.4 MG /ML

DAPHNIN - 24 HRS - EC 50 = 3.6 MG/ML

13. Disposal Considerations

DISPOSE OF WASTE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

RCRA Information

NOT A HAZARDOUS WASTE UNDER RCRA (40 CFR 261).

14. Transport Information

Proper Shipping Name

NOT REGULATED

15. Regulatory Information

Ingredient(s) - State Regulations

SILICA, AMORPHOUS

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

TITANIUM DIOXIDE

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

New York City - Hazardous Substance

16. Other Information

HMIS Rating

Health: 3

Fire: 1

Reactivity: 0

Revision/Preparer Information

MSDS Preparer: GEORGE MARCINA

MSDS Preparer Phone Number: (562) 968-2980 ex103

This MSDS Supersedes A Previous MSDS Dated: 01/20/2004

Revision Summary

Product And Company Identification (03/10/2006)

Composition/Information On Ingredients (03/10/2006)

Hazards Identification (03/03/2006)

First Aid Measures (03/03/2006)

Fire Fighting Measures (03/03/2006)

Accidental Release Measures (11/12/2003)

Handling And Storage (03/03/2006)

Exposure Controls/Personal Protection (03/03/2006)

MATERIAL SAFETY DATA SHEET
100% SOLIDS EPOXY GROUT PART "A" - WHITE BASE

16. Other Information - Continued

Revision Summary - Continued

Physical And Chemical Properties (03/10/2006)
Stability And Reactivity (03/03/2006)
Toxicological Information (03/03/2006)
Ecological Information (03/03/2006)
Disposal Considerations (11/12/2003)
Transport Information (03/03/2006)
Regulatory Information (03/03/2006)
Other Information (04/06/2006)

Disclaimer

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE AND SUITABLE TO THEIR CIRCUMSTANCES.

CUSTOM BUILDING PRODUCTS

Printed Using MSDS Generator™ 2000