

SAFETY DATA SHEET

2159

Product Name 13 COMPONENT MIXTURE (BALANCE N2)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113

Telephone 131 262, (02) 8874 4400

Fax 132 427 (24 hours)

Emergency 1800 653 572 (24/7) (Australia only)

Web Site http://www.boc.com.au/

Synonym(s) 2159 - MSDS NUMBER • BOC 13 COMPONENT MIXTURE

Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS

SDS Date 14 Apr 2010

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. 1956 DG Class 2.2 Subsidiary Risk(s) None Allocated

Packing Group None Allocated Hazchem Code 2TE EPG 2C1

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content	
1-BUTENE	C4-H8	106-98-9	0.1%	
BUTANE	C4-H10	106-97-8	0.1%	
ETHANE	C2-H6	74-84-0	0.1%	
ETHYLENE	C2-H4	74-85-1	0.1%	
ISOBUTANE	C4-H10	75-28-5	0.1%	
ISOPENTANE	C5-H12	78-78-4	0.1%	
METHANE	C-H4	74-82-8	0.1%	
PENTANE	C5-H12	109-66-0	0.1%	
PROPANE	C3-H8	74-98-6	0.1%	
PROPYLENE	C3-H6	115-07-1	0.1%	
TRANS-2-BUTENE	C4-H8	624-64-6	0.1%	
NITROGEN	N2	7727-37-9	98.8%	
CIS-2-BUTENE	C4-H8	590-18-1	0.1%	



Printed: 14 Apr 2010

Product Name

13 COMPONENT MIXTURE (BALANCE N2)

4. FIRST AID MEASURES

Eye None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained

Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available.

Skin None required.

Ingestion Not considered a potential route of exposure.

Advice to Doctor Treat symptomatically

5. FIRE FIGHTING MEASURES

Flammability Non flammable.

Fire and Explosion Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot.

Extinguishing Use water fog to cool containers from protected area.

Hazchem Code 2TE

6. ACCIDENTAL RELEASE MEASURES

Spillage

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

7. STORAGE AND HANDLING

Storage

Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

Handling

Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds

Ingredient	Deference		TWA		STEL		
	Reference	ppm	mg/m3	ppm	mg/m3		
Butane	ASCC (AUS)	800	1900				
Ethane	ASCC (AUS)		Asphyxiant				
Ethylene	ASCC (AUS)	Asphyxiant					
Isobutane	ASCC (AUS)	1000					
Methane	ASCC (AUS)		Asphyxiant				
Nitrogen	ASCC (AUS)		Asphyxiant				
Pentane	ASCC (AUS)	600	1770	750	2210		
Propane	ASCC (AUS)		Asphyxiant				
Propylene	ASCC (AUS)		Asphyxiant				

Biological Limits No

No biological limit allocated.

Engineering Controls

Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure standard.

PPE

Wear safety boots, leather gloves and safety glasses. Where an inhalation risk exists, wear: an Air-line respirator or self Contained Breathing Apparatus (SCBA).









Product Name 13 COMPONENT MIXTURE (BALANCE N2)

9. PHYSICAL AND CHEMICAL PROPERTIES

 Appearance
 COLOURLESS GAS
 Solubility (Water)
 NOT AVAILABLE

 Odour
 ODOURLESS
 Specific Gravity
 NOT APPLICABLE

pH NOT APPLICABLE **% Volatiles** 100 %

Vapour Pressure **NOT AVAILABLE Flammability** NON FLAMMABLE **Vapour Density NOT AVAILABLE** Flash Point NOT RELEVANT **Boiling Point NOT AVAILABLE Upper Explosion Limit NOT RELEVANT Melting Point NOT AVAILABLE Lower Explosion Limit** NOT RELEVANT

Evaporation Rate NOT APPLICABLE

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to Avoid Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

Material to AvoidCompatible with most commonly used materials.DecompositionMay evolve toxic gases if heated to decomposition.

Hazardous Reactions Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Asphyxiant gas. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in minutes.

Eye Non irritant.

Inhalation Non irritant - Asphyxiant. Effects are proportional to oxygen displacement.

Skin Non irritant.

Ingestion Ingestion is considered unlikely due to product form.

Toxicity Data PENTANE (109-66-0)

LC50 (Inhalation): 364 g/m3/4 hours (rat) LCLo (Inhalation): 325 g/m3/2 hours (mouse) LD50 (Intravenous): 446 mg/kg (mouse)

12. ECOLOGICAL INFORMATION

Environment Product is not harmful to the environment.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Transport Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.





Page 3 of 5 RMT

Reviewed: 01 Jan 2007 Printed: 14 Apr 2010

13 COMPONENT MIXTURE (BALANCE N2) **Product Name**

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name COMPRESSED GAS, N.O.S. (Nitrogen)

UN No. 1956 **DG Class** 2.2 Subsidiary Risk(s) None Allocated

Hazchem Code 2TF **FPG Packing Group** None Allocated 2C1

15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform

Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794



RMT

Reviewed: 01 Jan 2007 Printed: 14 Apr 2010

Product Name 13 COMPONENT MIXTURE (BALANCE N2)

Email: info@rmt.com.au Web: www.rmt.com.au

> SDS Date: 14 Apr 2010 End of Report



Page 5 of 5 RMT Reviewed: 01 Jan 2007

Printed: 14 Apr 2010