

SAFETY DATA SHEET

1451

6 COMPONENT MIXTURE (CH4, C4H8, H2, C2H6, N2, BALANCE **Product Name**

C2H4)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)

10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113 **Address**

131 262, (02) 8874 4400 **Telephone Fax** 132 427 (24 hours)

Emergency 1800 653 572 (24/7) (Australia only)

Web Site http://www.boc.com.au/

Synonym(s) 1451 - SDS NUMBER • PRODUCT CODES: 177, 288 • SPECIAL GAS MIXTURE

Use(s) **CALIBRATION SDS Date** 09 Jul 2010

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. 1954 **DG Class** 2.1 Subsidiary Risk(s) None Allocated

Packing Group None Allocated Hazchem Code 2SE

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
ETHYLENE	C2-H4	74-85-1	50.5-60.3%
ETHANE	C2-H6	74-84-0	5.5%
HYDROGEN	H2	1333-74-0	5%
1-BUTENE	C4-H8	106-98-9	2%
METHANE	C-H4	74-82-8	0.5%
NITROGEN	N2	7727-37-9	27-37%

4. FIRST AID MEASURES

Eve Cold burns: Immediately flush with tepid water or with sterile saline solution. Hold eyelids apart and irrigate for 15

minutes. Seek medical attention.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained

Breathing Apparatus (SCBA). Be aware of possible explosive atmospheres. Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide)

or a doctor.

Skin Cold burns: Remove contaminated clothing and gently flush affected areas with warm water (30°C) for 15 minutes.

Apply sterile dressing and treat as for a thermal burn. For large burns, immerse in warm water for 15 minutes. DO

NOT apply any form of direct heat. Seek immediate medical attention.

Ingestion Due to product form and application, ingestion is considered unlikely.



RMT

Reviewed: 09 Jul 2010 Printed: 09 Jul 2010 **Product Name**

6 COMPONENT MIXTURE (CH4, C4H8, H2, C2H6, N2, BALANCE C2H4)

Advice to Doctor Treat for asphyxia and cold burns.

First Aid Facilities Eye wash facilities should be available.

5. FIRE FIGHTING MEASURES

Flammability

Highly flammable. Heating to decomposition produces acrid smoke and irritating fumes. Product will add fuel to a fire. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights etc. when handling.

Fire and Explosion

Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be activated. Heating to decomposition produces acrid smoke and irritating fumes. Product will add fuel to a fire. To fight fire stop flow of gas, if safe to do so, and use carbon dioxide, dry chemical extinguisher or fine water spray. Cool cylinders exposed to fire by applying water from protected location. Do not approach cylinders suspected of being hot. Remove cool cylinders from the path of the fire. Evacuate area if unable to keep cylinders cool. If flame from cylinder is impinging on flammable materials or other cylinders evacuate the area. If the cylinder is standing alone then let the flame continue until all gas has been consumed. Ensure working area is well ventilated before reentry. This material is capable of forming explosive mixtures in air.

Extinguishing

Dry agent, carbon dioxide, foam or water fog. Prevent contamination of drains or waterways.

Hazchem Code 2SE

6. ACCIDENTAL RELEASE MEASURES

Spillage

If the cylinder is leaking, eliminate all potential ignition sources and evacuate area of personnel. Prevent spreading of vapours through drains and ventilation systems. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

7. STORAGE AND HANDLING

Storage

Do not store near sources of ignition or incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

Handling

Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds

Ingredient	Reference	TWA	STEL	
Ethane	ASCC (AUS)	Asphy	Asphyxiant	
Ethylene	ASCC (AUS)	Asphy	Asphyxiant	
Hydrogen	ASCC (AUS)	Asphy	Asphyxiant	
Methane	ASCC (AUS)	Asphy	Asphyxiant	
Nitrogen	ASCC (AUS)	Asphy	Asphyxiant	

Biological Limits

No biological limit allocated.

Engineering Controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas.

PPF

Wear safety boots, cotton or leather gloves and safety glasses. If spraying, wear: self Contained Breathing Apparatus (SCBA) or an Air-line respirator.







9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance COLOURLESS GAS Solubility (water) 0.23 cm3/cm3 (Ethylene)

RMT Reviewed: 09 Jul 2010

Page 2 of 5

Printed: 09 Jul 2010



6 COMPONENT MIXTURE (CH4, C4H8, H2, C2H6, N2, BALANCE **Product Name** C2H4)

ODOURLESS NOT APPLICABLE Odour **Specific Gravity**

NOT APPLICABLE % Volatiles pН 100 %

NOT AVAILABLE Flammability HIGHLY FLAMMABLE Vapour Pressure NOT AVAILABLE **Vapour Density NOT AVAILABLE** Flash Point **NOT AVAILABLE NOT AVAILABLE Boiling Point Upper Explosion Limit NOT AVAILABLE Melting Point Lower Explosion Limit** 1.6 % (1-Butene)

Evaporation Rate NOT APPLICABLE

Autoignition Temperature 490°C (Ethylene) **Cylinder Pressure** 13000 kPa @ 15°C

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to Avoid Avoid heat, sparks, open flames and other ignition sources.

Material to Avoid Explodes spontaneously when mixed with chlorine in sunlight. Reacts vigorously with some oxidising

agents.

Hazardous Decomposition **Products**

Heating to decomposition produces acrid smoke and irritating fumes.

Hazardous Reactions Violent polymerisation catalysed by copper above 400°C and 5,400 kPa.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary

Asphyxiant. Also a weak anaesthetic. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular coordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in minutes. Ethylene is not classifiable as to its carcinogenicity (IARC Group 3).

Eye Non irritant. However, direct contact with evaporating liquid may result in severe cold burns with possible

permanent damage.

Inhalation Non irritant - Asphyxiant. Effects are proportional to oxygen displacement.

Non irritant. However, direct contact with the liquefied material or escaping compressed gas may cause frostbite Skin

Ingestion Ingestion is considered unlikely due to product form.

Toxicity Data No LD50 data available for this product.

12. ECOLOGICAL INFORMATION

Environment Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate

measures are taken to prevent this product from entering the environment.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Ensure cylinder is separated from driver and that outlet of relief device is not obstructed. **Transport**





Page 3 of 5 **RMT**

Reviewed: 09 Jul 2010 Printed: 09 Jul 2010 **Product Name**

6 COMPONENT MIXTURE (CH4, C4H8, H2, C2H6, N2, BALANCE C2H4)

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name COMPRESSED GAS, FLAMMABLE, N.O.S.

UN No. 1954 **DG Class** 2.1 Subsidiary Risk(s) None Allocated

Packing Group None Allocated **Hazchem Code** 2SE **GTEPG** 2A1

15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform

Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711



Page 4 of 5 **RMT**

Reviewed: 09 Jul 2010

Product Name

6 COMPONENT MIXTURE (CH4, C4H8, H2, C2H6, N2, BALANCE C2H4)

Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au

> SDS Date 09 Jul 2010 End of Report



Page 5 of 5

Reviewed: 09 Jul 2010 Printed: 09 Jul 2010