

SAFETY DATA SHEET

1775

8 COMPONENT MIXTURE (C2H2, CO, C2H6, C2H4, H2, CH4, CO2, **Product Name**

BALANCE N2)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113

131 262, (02) 8874 4400 **Telephone Fax** 132 427 (24 hours)

Emergency 1800 653 572 (24/7) (Australia only)

Web Site http://www.boc.com.au/

Synonym(s) 1775 - MSDS NUMBER • PRODUCT CODE: 285, 288 • SPECIAL GAS MIXTURE

Use(s) **CALIBRATION • INDUSTRIAL APPLICATIONS**

SDS Date 26 Mar 2010

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

RISK PHRASES

R20 Harmful by inhalation.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R61 May cause harm to the unborn child.

SAFETY PHRASES

S23 Do not breathe gas/fumes/vapour/spray (where applicable).

S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).

S7/9 Keep container tightly closed and in a well ventilated place.

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. 1956 **DG Class** 2.2 Subsidiary Risk(s) None Allocated

EPG Packing Group None Allocated Hazchem Code 2TE 2C1

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
CARBON MONOXIDE	C-O	630-08-0	1.5%
METHANE	C-H4	74-82-8	0.75%
ACETYLENE	C2-H2	74-86-2	0.6%
ETHANE	C2-H6	74-84-0	0.6%
ETHYLENE	C2-H4	74-85-1	0.6%
HYDROGEN	H2	1333-74-0	0.5%
CARBON DIOXIDE	CO2	124-38-9	2.5%
NITROGEN	N2	7727-37-9	remainder



Printed: 26 Mar 2010

8 COMPONENT MIXTURE (C2H2, CO, C2H6, C2H4, H2, CH4, CO2, **BALANCE N2)**

4. FIRST AID MEASURES

Eve None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained

Breathing Apparatus (SCBA). Be aware of possible explosive atmospheres. Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide)

or a doctor.

Skin None required.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Treat symptomatically

5. FIRE FIGHTING MEASURES

Flammability Non flammable.

Fire and

Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying **Explosion**

water from a protected location. Do not approach cylinders or containers suspected of being hot.

Extinguishing Use water fog to cool containers from protected area.

Hazchem Code 2TF

6. ACCIDENTAL RELEASE MEASURES

Spillage If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not

attempt to repair leaking valve or cylinder safety devices.

7. STORAGE AND HANDLING

Storage Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and

restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic

and emergency exits.

Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The Handling

uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder

movement.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds

	Deference	7	TWA		STEL	
Ingredient	Reference	ppm	mg/m3	ppm	mg/m3	
Acetylene	ASCC (AUS)		Asphyxiant			
Carbon dioxide	ASCC (AUS)	5000	9000	30000	54000	
Carbon dioxide in coal mines	ASCC (AUS)	12500	22500	30000	54000	
Carbon monoxide	ASCC (AUS)	30	34			
Ethane	ASCC (AUS)		Asphyxiant			
Ethylene	ASCC (AUS)		Asphyxiant			
Hydrogen	ASCC (AUS)		Asphyxiant			
Methane	ASCC (AUS)		Asphyxiant			
Nitrogen	ASCC (AUS)		Asphyxiant			

Biological Limits

Ingredient	Reference	Determinant	Sampling Time	BEI
CARBON MONOXIDE	ACGIH BEI	Carboxyhemoglobin in blood	End of shift	3.5% of hemoglobin
	ACGIH BEI	Carbon monoxide in end- exhaled air	End of shift	20 ppm



8 COMPONENT MIXTURE (C2H2, CO, C2H6, C2H4, H2, CH4, CO2, **BALANCE N2)**

Engineering Controls

Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure standard.

PPE

Wear safety boots, leather gloves and safety glasses. Where an inhalation risk exists, wear: an Air-line respirator or self Contained Breathing Apparatus (SCBA).







9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	COLOURLESS GAS	Solubility (Water)	INSOLUBLE
Odour	SWEET ODOUR	Specific Gravity	NOT APPLICABLE
рН	NOT APPLICABLE	% Volatiles	100 %
Vapour Pressure	NOT AVAILABLE	Flammability	NON FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT RELEVANT
Boiling Point	NOT AVAILABLE	Upper Explosion Limit	NOT RELEVANT
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT RELEVANT
Evaporation Rate	NOT APPLICABLE		
Cylinder Pressure	13,000 kPa @ 15°C		

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to Avoid Avoid contact with incompatible substances.

Material to Avoid Aluminium, chrome and manganese dust may explode when heated in carbon dioxide. Incompatible with

acryaldehyde, aziridine, metal acetylides and sodium peroxide. Avoid heating cylinders.

Decomposition May evolve toxic gases if heated to decomposition.

Hazardous Reactions Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary

Asphyxiant gas. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in minutes. When released into air the concentration of carbon dioxide is diluted. Carbon dioxide concentrations of 3 to 5 vol% in air cause increased respiration and headache. Adverse health affects to long term exposure to carbon dioxide have not been reported. However in environments such as submarines where exposure to levels of 0.5 - 1.0% may occur, specialist medical opinion should be sought on the effects of long term exposure.

Eve

Inhalation Non irritant - Asphyxiant. Effects are proportional to oxygen displacement.

Skin Non irritant.

Ingestion Ingestion is considered unlikely due to product form.

Toxicity Data CARBON MONOXIDE (630-08-0)

> LC50 (Inhalation): 1807 ppm/4H (rat) LCLo (Inhalation): 5000 ppm/5M (human)

ACETYLENE (74-86-2)

LCLo (Inhalation): 50pph/5M (human) TCLo (Inhalation): 20 pph (human) CARBON DIOXIDE (124-38-9)

LC50 (Inhalation): 470000 ppm/30M (rat)



Page 3 of 5

Reviewed: 26 Mar 2010 Printed: 26 Mar 2010

8 COMPONENT MIXTURE (C2H2, CO, C2H6, C2H4, H2, CH4, CO2, BALANCE N2)

LCLo (Inhalation): 9 pph/5M (human)

12. ECOLOGICAL INFORMATION

Environment

Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Transport

Ensure cylinder is separated from driver and that outlet of relief device is not obstructed. Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport.



CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name COMPRESSED GAS, N.O.S.

UN No. 1956 **DG Class** 2.2 **Subsidiary Risk(s)** None Allocated

Packing Group None Allocated Hazchem Code 2TE EPG 2C1

15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform

Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European Inventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible



Page 4 of 5

RMT

Reviewed: 26 Mar 2010 Printed: 26 Mar 2010

8 COMPONENT MIXTURE (C2H2, CO, C2H6, C2H4, H2, CH4, CO2, BALANCE N2)

scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794

Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au

> SDS Date: 26 Mar 2010 End of Report



Page 5 of 5 RMT

Reviewed: 26 Mar 2010 Printed: 26 Mar 2010