

# **SAFETY DATA SHEET**

# 1968

Product Name 5 COMPONENT MIXTURE (AR, HE, NH3, N2, BALANCE H2)

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113

**Telephone** 131 262, (02) 8874 4400 **Fax** 132 427 (24 hours)

**Emergency** 1800 653 572 (24/7) (Australia only)

Web Site http://www.boc.com.au/

Synonym(s) 1968 - MSDS NUMBER · PRODUCT CODE: 285, 288 · SPECIAL GAS MIXTURE

Use(s) CALIBRATION · INDUSTRIAL APPLICATIONS

SDS Date 26 April 2012

#### 2. HAZARDS IDENTIFICATION

#### CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

**RISK PHRASES** 

R12 Extremely Flammable. R20 Harmful by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin.

**SAFETY PHRASES** 

S9 Keep container in a well ventilated place.

S16 Keep away from sources of ignition - No smoking.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where

possible).

S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

## CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

**UN Number** 1954 **DG Division** 2.1

Packing Group None Allocated Subsidiary Risk(s) None Allocated

Hazchem Code 2SE

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content
AMMONIA	CAS: 7664-41-7 EC: 231-635-3	F;R10 T;R23 C;R34 N;R50	2%
HYDROGEN	CAS: 1333-74-0 EC: 215-605-7	F+;R12	Remainder
NITROGEN	CAS: 7727-37-9 EC: 231-783-9	Not Available	25%
ARGON	CAS: 7440-37-1 EC: 231-147-0	Not Available	1%

ChemAlert.

Page 1 of 6 SDS Date: 26 Apr 2012

# Product Name 5 COMPONENT MIXTURE (AR, HE, NH3, N2, BALANCE H2)

#### 4. FIRST AID MEASURES

Eye None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self

Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

**Skin** None required.

**Ingestion** Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

Flammability Highly flammable. Eliminate all ignition sources including cigarettes, open flames, spark producing

switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling.

**Fire and Explosion**Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be activated. Cool cylinders or containers exposed to fire by applying water from a protected location.

Do not approach cylinders or containers suspected of being hot. This material is capable of forming

explosive mixtures with air.

Extinguishing Stop flow of gas if safe to do so, such as by slowly closing the cylinder valve. If the gas source

cannot be isolated, do not extinguish the flame, since re-ignition and explosion could occur. Await arrival of emergency services or manufacturer's advisor. Drench and cool cylinders with water spray from protected area at a safe distance. If it is absolutely necessary to extinguish the flame, use only a dry chemical powder extinguisher. Do not move cylinders for at least 24 hours. Avoid shock and

bumps to cylinders.

Hazchem Code 2SE

2 Water Fog (or fine water spray if fog unavailable)

S Self Contained Breathing apparatus and protective gloves.

E Evacuation of people in the vicinity of the incident should be considered.

### 6. ACCIDENTAL RELEASE MEASURES

Spillage

If the cylinder is leaking, eliminate all potential ignition sources and evacuate area of personnel. Prevent spreading of vapours through drains and ventilation systems. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

# 7. STORAGE AND HANDLING

Storage Do not store near sources of ignition or incompatible materials. Cylinders should be stored below

45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor

(preferably concrete), away from areas of heavy traffic and emergency exits.

Handling Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll

cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a

suitable hand truck for cylinder movement.



#### **Product Name**

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure Standards**

Ingredient	Reference	TWA		STEL	
	Keierence	ppm	mg/m³	ppm	mg/m³
Ammonia	SWA (AUS)	25	17	35	24
Argon	SWA (AUS)		Asph	yxiant	
Helium	SWA (AUS)		Asph	yxiant	
Hydrogen	SWA (AUS)		Asph	yxiant	
Nitrogen	SWA (AUS)	Asphyxiant			

Biological Limits No biological limit allocated.

Engineering Controls Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be

adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure

standard.

**PPE** 

Eye / FaceWear safety glasses.HandsWear leather gloves.BodyWear safety boots.

Respiratory Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line

respirator.







### 9. PHYSICAL AND CHEMICAL PROPERTIES

**COLOURLESS GAS Appearance PUNGENT ODOUR** Odour **Flammability** HIGHLY FLAMMABLE Flash point NOT AVAILABLE **Boiling point** NOT AVAILABLE **Melting point NOT AVAILABLE Evaporation rate** NOT APPLICABLE Hq NOT APPLICABLE Vapour density NOT AVAILABLE Specific gravity **NOT APPLICABLE** Solubility (water) **INSOLUBLE** Vapour pressure **NOT AVAILABLE Upper explosion limit** 75 % (Hydrogen) Lower explosion limit 4 % (Hydrogen) Autoignition temperature 570°C (Hydrogen) **Decomposition temperature** NOT AVAILABLE **Viscosity** NOT AVAILABLE **Partition coefficient NOT AVAILABLE** 

% Volatiles 100 %

Cylinder pressure (when full) 13,000 kPa @ 15°C

# 10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

**Conditions to Avoid** Avoid heat, sparks, open flames and other ignition sources.

Material to Avoid Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), heat and ignition sources. Do not use natural rubber flexible hoses. Also incompatible (potentially violently) with

oxygen, halogens and metal halides.

This material will not decompose to form hazardous products other than that already present.

ChemAlert.

### Product Name 5 COMPONENT MIXTURE (AR, HE, NH3, N2, BALANCE H2)

**Hazardous Decomposition** 

**Products** 

Hazardous Reactions Polymerization will not occur.

## 11. TOXICOLOGICAL INFORMATION

Health Hazard Asphyxiant gas. Symptoms of exposure are directly related to displacement of oxygen. As the Summary amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the

rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in

minutes.

Eye Non irritant.

**Inhalation** Asphyxiant. Effects are proportional to oxygen displacement.

**Skin** Non irritant.

**Ingestion** Ingestion is considered unlikely due to product form.

Toxicity Data AMMONIA (7664-41-7)

LC50 (inhalation) 2000 ppm/4 hours (rat) LCLo (inhalation) 5000 ppm/5 minutes (human)

LD50 (ingestion) 350 mg/kg (rat)
TCLo (inhalation) 20 ppm (human)
TDLo (ingestion) 0.015 mL/kg (man)
TDLo (skin) 1000 mg/kg (human)

### 12. ECOLOGICAL INFORMATION

**Environment** No known ecological damage is caused by this product.

### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

**Legislation** Dispose of in accordance with relevant local legislation.

### 14. TRANSPORT INFORMATION

#### CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

LAND TO ANCHORT



CEA TRANSPORT

	(ADG)	(IMDG / IMO)	(IATA / ICAO)
UN Number	1954	-	-
Proper Shipping Name	COMPRESSED GAS, FLAMMABLE, N.O.S.	-	-
DG Class/ Division	2.1	-	-
Subsidiary Risk(s)	None Allocated	-	-
Packing Group	None Allocated	-	-
GTEPG	2A1		
Hazchem Code	2SE		

Other Information Ensure cylinder is separated from driver and that outlet of relief device is not obstructed. Refer to



Page 4 of 6 SDS Date: 26 Apr 2012

AID TO ANCOOR

# 5 COMPONENT MIXTURE (AR, HE, NH3, N2, BALANCE H2)

Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport.

### 15. REGULATORY INFORMATION

**Poison Schedule** 

A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Inventory Listing(s)

**AUSTRALIA: AICS (Australian Inventory of Chemical Substances)** 

All components are listed on AICS, or are exempt.

#### 16. OTHER INFORMATION

#### **Additional Information**

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this ChemAlert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

#### HEALTH EFFECTS FROM EXPOSURE:

Threshold Limit Value

**SUSMP** 

TLV TWA/OEL

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

#### **Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS#	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
GHS	Globally Harmonized System
IARC	International Agency for Research on Cancer
mg/m³	Milligrams per Cubic Metre
PEL	Permissible Exposure Limit
рН	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)

### **Revision History**

Revision	Description
1.0	Standard SDS Review.

Standard for the Uniform Scheduling of Medicines and Poisons

Time Weighted Average or Occupational Exposure Limit



Page 5 of 6

# Product Name 5 COMPONENT MIXTURE (AR, HE, NH3, N2, BALANCE H2)

#### **Report Status**

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared By** 

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794

Email: info@rmt.com.au Web: www.rmt.com.au

Revision: 1

SDS Date: 26 April 2012

**End of SDS** 



Page 6 of 6