

# **SAFETY DATA SHEET**

# 2527

Product Name 5 COMPONENT MIXTURE (C3H8, NO, 5% TO 10 % CO, CO2, BALANCE N2)

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113

**Telephone** 131 262, (02) 8874 4400

**Fax** 132 427 (24 hours)

**Emergency** 1800 653 572 (24/7) (Australia only)

Web Site http://www.boc.com.au/

Synonym(s) 2527 - SDS NUMBER · SPECIAL GAS MIXTURE Use(s) CALIBRATION · INDUSTRIAL APPLICATIONS

SDS Date 16 March 2012

## 2. HAZARDS IDENTIFICATION

#### CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

**RISK PHRASES** 

R23 Toxic by inhalation.

R48/23 Toxic: danger of serious damage to health by prolonged exposure through inhalation.

R61 May cause harm to the unborn child.

**SAFETY PHRASES** 

S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where

possible).

S53 Avoid exposure - obtain special instructions before use.

#### CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN Number 1956 DG Division 2.2

Packing Group None Allocated Subsidiary Risk(s) None Allocated

Hazchem Code 2TE

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	Cas No.	Content (v/v)
CARBON MONOXIDE	C-O	630-08-0	5 - 10%
PROPANE	C3-H8	74-98-6	<5%
CARBON DIOXIDE	C-O2	124-38-9	10 - 20%
NITRIC OXIDE	N-O	10102-43-9	<1%
NITROGEN	N2	7727-37-9	Remainder

## 4. FIRST AID MEASURES

**Eye** None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self

Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

None required.

ChemAlert.

Page 1 of 6

SDS Date: 16 Mar 2012

Skin

**Ingestion** Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Treat symptomatically.

First Aid Facilities Eye wash facilities should be available.

# 5. FIRE FIGHTING MEASURES

Flammability Non flammable.

Fire and Explosion Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by

applying water from a protected location. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Do not approach cylinders or containers suspected of being

hot.

**Extinguishing** Use water fog to cool containers from protected area.

Hazchem Code 2TE

2 Water Fog (or fine water spray if fog unavailable)

T Self Contained Breathing apparatus and protective gloves.

E Evacuation of people in the vicinity of the incident should be considered.

## 6. ACCIDENTAL RELEASE MEASURES

Spillage If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow

to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

# 7. STORAGE AND HANDLING

Storage Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area,

upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete),

away from areas of heavy traffic and emergency exits.

Handling Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll

cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a

suitable hand truck for cylinder movement.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure Standards**

Ingredient	Reference	TWA		STEL	
	Reference	ppm	mg/m³	ppm	mg/m³
Carbon dioxide	SWA (AUS)	5000	9000	30000	54000
Carbon dioxide in coal mines	SWA (AUS)	12500	22500	30000	54000
Carbon monoxide	SWA (AUS)	30	34		
Nitric oxide	SWA (AUS)	25	31		
Nitrogen	SWA (AUS)	Asphyxiant			
Propane	SWA (AUS)	Asphyxiant			

# **Biological Limits**

Ingredient	Reference	Determinant	Sampling Time	BEI
CARBON MONOXIDE	ACGIH BEI	Carboxyhemoglobin in blood	End of shift	3.5% of hemoglobin
	ACGIH BEI	Carbon monoxide in end-exhaled air	End of shift	20 ppm



SDS Date: 16 Mar 2012

**Engineering Controls** Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be

adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure

standard.

**PPE** 

Eye / FaceWear safety glasses.HandsWear leather gloves.BodyWear safety boots.

Respiratory Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line

respirator.







## 9. PHYSICAL AND CHEMICAL PROPERTIES

**COLOURLESS GAS Appearance** SLIGHT ODOUR Odour NON FLAMMABLE **Flammability** Flash point NOT RELEVANT **Boiling point NOT AVAILABLE Melting point NOT AVAILABLE Evaporation rate** NOT APPLICABLE **NOT APPLICABLE** Vapour density NOT AVAILABLE **NOT APPLICABLE** Specific gravity Solubility (water) REACTS (Nitric oxide) Vapour pressure NOT AVAILABLE **Upper explosion limit** NOT RELEVANT Lower explosion limit NOT RELEVANT **Autoignition temperature** NOT AVAILABLE **Decomposition temperature** NOT AVAILABLE **Viscosity** NOT AVAILABLE

% Volatiles 100 %

Partition coefficient

## 10. STABILITY AND REACTIVITY

**Chemical Stability** Stable under recommended conditions of storage.

NOT AVAILABLE

**Conditions to Avoid** Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

Material to Avoid Carbon monoxide can react with iron, nickel and other metals. Below 3,500 kPa corrosion is

negligible and common materials can be used. Incompatible with acrylaldehyde, aziridine, sodium peroxide. Corrosive when moist. Moist carbon dioxide is corrosive, hence acid resistant materials are required (stainless steel). Incompatible with oxidising agents (nitrates, oxygen), halogens (chlorine, bromine), acids (nitric acid) and some chlorides. Nitric oxide reacts in air to form nitrogen dioxide which is highly oxidising and reacts violently with fluorine and chlorine in the presence of moisture.

**Hazardous Decomposition** 

**Products** 

May evolve toxic gases if heated to decomposition.

Hazardous Reactions Polymerization will not occur.

## 11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Asphyxiant gas - toxic. Carbon monoxide effects depend on the percentage of carboxyhaemoglobin: 10-20% mild headache and breathlessness on mild exertion; 20-30% headache, irritability, rapid fatigue and impaired memory; 30-40% severe headache, weakness, nausea, vomiting, dizziness, visual impairment and confusion; 40-50% increasing confusion, ataxia and collapse; 50-60% coma; >80% rapid death. Chronic exposure to carbon monoxide may result in an increase in cardiovascular problems. Can aggravate some diseases of the cardiovascular system such as coronary artery disease. The effect is enhanced by cigarette smoking. Adverse behavioural effects have been noted including impairment of vigilance, co-ordination, timing, behaviour, visual perception and certain

ChemAlert.

Page 3 of 6 SDS Date: 16 Mar 2012

cognitive functions. Some adaptation occurs in individuals repeatedly exposed to moderate concentrations. Developmental defects on foetuses can occur without maternal symptoms. Carbon dioxide concentrations of 3-5 % in air cause increased respiration and headache. Concentrations of 8-15% cause headache, nausea and vomiting which may lead to unconsciousness if not moved to open air and given oxygen. Nitric oxide concentrations above 25 ppm may have an immediate effect of irritating the nose and throat followed by delayed onset of respiratory difficulties. Over exposure to concentrations of nitric oxide above 100 ppm may result in sudden onset pulmonary oedema which can be rapidly fatal. Mutation data reported for nitric oxide. Results in chronic irritation of the respiratory tract in low doses.

Eye Non irritant.

**Inhalation**Toxic. Over exposure to carbon monoxide may result in rapid breathing, nausea, lack of coordination,

unconsciousness and coma. Reacts with blood haemoglobin to prevent oxygen uptake.

Skin Non irritant.

**Ingestion** Ingestion is considered unlikely due to product form.

Toxicity Data CARBON MONOXIDE (630-08-0)

LC50 (inhalation) 1807 ppm/4H (rat) LCLo (inhalation) 5000 ppm/5M (human)

PROPANE (74-98-6)

LC50 (inhalation) > 800000 ppm/15M (rat)

CARBON DIOXIDE (124-38-9)

LC50 (inhalation) 470000 ppm/30M (rat) LCLo (inhalation) 9 pph/5M (human)

NITRIC OXIDE (10102-43-9)

LC50 (inhalation) 1068 mg/m<sup>3</sup>/4 hours (rat)

## 12. ECOLOGICAL INFORMATION

#### **Environment**

When discharged to the atmosphere, carbon dioxide may contribute to the greenhouse effect. Carbon monoxide is slowly oxidised in the atmosphere to carbon dioxide. Nitrogen oxides react with volatile organic compounds to produce ozone, a principal factor in photochemical smog. Will form nitric acid in contact with water. Nitrates can persist for prolonged periods in water. Not expected to concentrate in the food chain.

# 13. DISPOSAL CONSIDERATIONS

Waste Disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

**Legislation** Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

## CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN Number	1956	-	-
Proper Shipping Name	COMPRESSED GAS, N.O.S. (contains nitrogen)	-	-
DG Class/ Division	2.2	-	-
Subsidiary Risk(s)	None Allocated	-	-
Packing Group	None Allocated	-	-
GTEPG	2C1		
Hazchem Code	2TE		



Page 4 of 6 SDS Date: 16 Mar 2012

Other Information

Ensure cylinder is separated from driver and that outlet of relief device is not obstructed. Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport.

## 15. REGULATORY INFORMATION

**Poison Schedule** 

A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Inventory Listing(s)

**AUSTRALIA: AICS (Australian Inventory of Chemical Substances)** 

All components are listed on AICS, or are exempt.

## 16. OTHER INFORMATION

#### **Additional Information**

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this ChemAlert report is provided as a quide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

## HEALTH EFFECTS FROM EXPOSURE:

TWA/OEL

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**Abbreviations** 

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
GHS	Globally Harmonized System
IARC	International Agency for Research on Cancer
mg/m³	Milligrams per Cubic Metre
PEL	Permissible Exposure Limit
рН	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly
	alkaline).
ppm	Parts Per Million
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
TLV	Threshold Limit Value

# **Revision History**

Revision	Description
1.0	New SDS

Time Weighted Average or Occupational Exposure Limit



SDS Date: 16 Mar 2012

#### **Report Status**

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared By** 

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au

Web: www.rmt.com.au

Revision: 1.2

**SDS Date:** 16 March 2012

**End of SDS** 



Page 6 of 6

SDS Date: 16 Mar 2012