

SAFETY DATA SHEET

2563

Product Name 5 COMPONENT MIXTURE (CO2, CH4, CO, N2, BAL H2)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA

Telephone 131 262, (02) 8874 4400 **Fax** 132 427 (24 hours)

Emergency 1800 653 572 (24/7) (Australia only)

Web site http://www.boc.com.au/

Synonym(s) 2563 - MSDS NUMBER • PRODUCT CODES: 285, 288 • SPECIAL GAS MIXTURES

Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS • SCIENTIFIC APPLICATIONS

SDS date 27 May 2014

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Risk Phrases

R12 Extremely Flammable. R20 Harmful by inhalation.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R61 May cause harm to the unborn child.

Safety Phrases

S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where

possible).

S53 Avoid exposure - obtain special instructions before use.

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN Number1954Transport Hazard Class2.1Packing GroupNone AllocatedHazchem Code2SE

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content (v/v)
CARBON MONOXIDE	CAS: 630-08-0 EC: 211-128-3	F+;R12 T;R23 T;R48/23 Repr.;R61	1%
METHANE	CAS: 74-82-8 EC: 200-812-7	F+;R12	0.5%
HYDROGEN	CAS: 1333-74-0 EC: 215-605-7	F+;R12	Remainder
NITROGEN	CAS: 7727-37-9 EC: 231-783-9	Not Available	<32%
CARBON DIOXIDE	CAS: 124-38-9 EC: 204-696-9	Not Available	0.2%

ChemAlert.

Page 1 of 6 SDS Date: 27 May 2014

Product Name

4. FIRST AID MEASURES

Eye None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self

> Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin None required.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to doctor Hyperbaric oxygen treatment at 2 to 2.5 atmospheres reduces the biological half life of

carboxyhaemoglobin to 24 minutes. Avoid stimulant drugs including carbon dioxide. Do not inject methylene blue. Absolute bed rest for at least 48 hours should be ensured. After recovery observe for late neurological and or cardiac complaints. Carboxyhaemoglobin levels in blood used as

biological monitoring index.

5. FIRE FIGHTING MEASURES

Flammability Highly flammable. Eliminate all ignition sources including cigarettes, open flames, spark producing

switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling.

Fire and explosion Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be

activated. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot. This material is capable of forming

explosive mixtures in air.

Extinguishing Use water fog to cool containers from protected area.

Hazchem code 2SE

> 2 Water Fog (or fine water spray if fog unavailable)

S Self Contained Breathing apparatus and protective gloves.

Ε Evacuation of people in the vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use Personal precautions

personal protective equipment as detailed in Section 8 of this SDS.

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be **Environmental precautions**

dangerous.

Methods of cleaning up Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do

not attempt to repair leaking valve or cylinder safety devices.

References See Sections 8 and 13 for exposure controls and disposal.

7. STORAGE AND HANDLING

Storage Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area,

upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete),

away from areas of heavy traffic and emergency exits.

Handling Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll

> cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement. Do not drop, roll or drag cylinders. The uncontrolled release of any gas under pressure may cause physical harm. Use a suitable hand truck for cylinder

movement.



SDS Date: 27 May 2014

Page 2 of 6

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards

Ingredient	Reference	TWA		STEL	
ingredient		ppm	mg/m³	ppm	mg/m³
Carbon dioxide	SWA (AUS)	5000	9000	30000	54000
Carbon dioxide in coal mines	SWA (AUS)	12500	22500	30000	54000
Carbon monoxide	SWA (AUS)	30	34		
Hydrogen	SWA (AUS)	Asphyxiant			
Methane	SWA (AUS)	Asphyxiant			
Nitrogen	SWA (AUS)	Asphyxiant			

Biological limits

Ingredient	Determinant	Sampling Time	BEI
CARBON MONOXIDE	Carboxyhemoglobin in blood	End of shift	3.5% of hemoglobin
	Carbon monoxide in end-exhaled air	End of shift	20 ppm

Reference: ACGIH Biological Exposure Indices

Engineering controls Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be

adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure

standard.

PPE

Eye / FaceWear safety glasses.HandsWear leather gloves.BodyWear safety boots.

Respiratory Not required under normal conditions of use.







9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance COLOURLESS GAS
Odour ODOURLESS

Flammability HIGHLY FLAMMABLE

Flash point < 23°C

Boiling point NOT AVAILABLE Melting point NOT AVAILABLE Evaporation rate NOT APPLICABLE рΗ **NOT APPLICABLE** Vapour density **NOT AVAILABLE** Specific gravity **NOT APPLICABLE** Solubility (water) 0.018 L/L (Hydrogen) Vapour pressure **NOT AVAILABLE Upper explosion limit** 75 % (Hydrogen) Lower explosion limit 4 % (Hydrogen) **Partition coefficient** NOT AVAILABLE **Autoignition temperature NOT AVAILABLE Decomposition temperature NOT AVAILABLE Viscosity** NOT AVAILABLE **Explosive properties** NOT AVAILABLE **Oxidising properties** NOT AVAILABLE

% Volatiles 100 %

Cylinder pressure (when full) 13,000 kPa @ 15°C

NOT AVAILABLE



Odour threshold

Page 3 of 6 SDS Date: 27 May 2014

Product Name 5 COMPONENT MIXTURE (CO2, CH4, CO, N2, BAL H2)

10. STABILITY AND REACTIVITY

Chemical stability Stable under recommended conditions of storage.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources.

Material to avoid

At pressures above 7,000 kPa copper lining should be used to reduce corrosion. Stress corrosion

cracking can occur in steels especially if other acid gases (eg. Carbon Dioxide, Sulphur compounds) are present. Carbon monoxide reacts violently with oxygen difluoride, chlorine and barium peroxide.

Hazardous Decomposition

Products

May evolve toxic gases if heated to decomposition.

Hazardous Reactions Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Harmful. Carbon monoxide effects depend on the percentage of carboxyhaemoglobin: 10-20% mild headache and breathlessness on mild exertion; 20-30% headache, irritability, rapid fatigue and impaired memory; 30-40% severe headache, weakness, nausea, vomiting, dizziness, visual impairment and confusion; 40-50% increasing confusion, ataxia and collapse; 50-60% coma; >80% rapid death. Chronic exposure to carbon monoxide may result in an increase in cardiovascular problems. Can aggravate some diseases of the cardiovascular system such as coronary artery disease. The effect is enhanced by cigarette smoking. Adverse behavioural effects have been noted including impairment of vigilance, co-ordination, timing, behaviour, visual perception and certain cognitive functions. Some adaptation occurs in individuals repeatedly exposed to moderate concentrations. Developmental defects on foetuses can occur without maternal symptoms.

Eye Non irritant.

Inhalation Harmful. Over exposure to carbon monoxide may result in rapid breathing, nausea, lack of

coordination, unconsciousness and coma. Reacts with blood haemoglobin to prevent oxygen uptake.

Skin Non irritant.

Ingestion Ingestion is considered unlikely due to product form.

Toxicity data CARBON MONOXIDE (630-08-0)

LC50 (inhalation) 1807 ppm/4H (rat) LCLo (inhalation) 5000 ppm/5M (human)

METHANE (74-82-8)

LC50 (inhalation) 326 gm/m3/2h (mouse)

CARBON DIOXIDE (124-38-9)

LC50 (inhalation) 470000 ppm/30M (rat) LCLo (inhalation) 9 pph/5M (human)

12. ECOLOGICAL INFORMATION

Toxicity No information provided.

Persistence and degradability No information provided.

Bioaccumulative potential No information provided.

Mobility in soil No information provided.

Other adverse effects No information provided.

13. DISPOSAL CONSIDERATIONS

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

ChemAlert.

Page 4 of 6 SDS Date: 27 May 2014



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN Number	1954	1954	1954
Proper Shipping Name	COMPRESSED GAS, FLAMMABLE, N.O.S. (contains hydrogen)	COMPRESSED GAS, FLAMMABLE, N.O.S. (contains hydrogen)	COMPRESSED GAS, FLAMMABLE, N.O.S. (contains hydrogen)
Transport Hazard Class	2.1	2.1	2.1
Packing Group	None Allocated	None Allocated	None Allocated

Environmental hazards

No information provided

Special precautions for user

 Hazchem code
 2SE

 GTEPG
 2A1

 EMS
 F-D, S-U

Other information

Ensure cylinder is separated from driver and that outlet of relief device is not obstructed. Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which

affect gas storage and transport.

15. REGULATORY INFORMATION

Poison schedule

A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Inventory Listing(s) AL

AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.



Page 5 of 6

SDS Date: 27 May 2014

Product Name 5 COMPONENT MIXTURE (CO2, CH4, CO, N2, BAL H2)

Abbreviations ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

GHS Globally Harmonized System

IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit
PEL Permissible Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

REACH Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

Revision history

Revision	Description
1.2	Standard SDS Review
1.1	Standard SDS Review.
1.0	Initial SDS Creation Initial SDS Review

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au

Web: www.rmt.com.au.

Revision: 1.2

SDS Date: 27 May 2014

End of SDS



SDS Date: 27 May 2014