20062 ORO 74305 74309

MATERIAL SAFETY DATA SHEET

The Coastal Corporation

Coastal Oil New York, Inc.
Coastal Oil New England, Inc.
Coastal Fuels Marketing, Inc.
Coastal Mobile Refining Company
Coastal Derby Refining Company
Coastal Eagle Point Oil Company
Coastal Mart, Inc.
Coastal Refining & Marketing, Inc.

Coastal States Crude Gathering Co.
Coastal States Trading, Inc.
Coastal Unilube, Inc.
Coscol Marine Corporation
Coscol Petroleum Corporation
Pacific Refining Company
Western Fuel Oil Company
Coastal Fuel Terminals, Inc.

Address: 9 Greenway Plaza Houston, TX 77046

Info Phone: (901) 525-2300 Emergency Phone: (713) 877-1400

PRODUCT IDENTIFICATION

Trade Name:

O'REILLY AW 32, 46

Date Revised: November 28, 2001

Synonyms/Product Code:

N.A.

Chemical Name:

Petroleum Mineral Oil

Family Description:

A complex combination of hydrocarbons from a petroleum fraction obtained by

hydrogen treatment plus additives.

DOT Hazard Class:

Not Applicable

COMPOSITION

			Occupational Exposure Limits* OSHA ACGIH			
Product	CAS Number	<u>Wt%</u>	<u>PEL</u>	TLV	<u>Other</u>	<u>Units</u>
O'REILLY AW 32, 46	Mixture	100	N.A.	N.A.	N.A	N.A
Ingredient(s):						-
Severely Hydrotreated Heavy Naphthenic Distillate	64742-52-2	>99	5	5	10 STEL	mg/m³**
Additives containing Zinc salt of dialkyl dithiophosphate (ZDDP), 2,6-di-t-butylphenol and polymers	N.AP	<1	N.A.	N.A.	N.A.	N.A.

^{* = 8-}Hr. TWA unless otherwise specified.

N.A. = Not Available.

STEL = Short Term Exposure Limit; 15 minutes.

N.A.-P = Information for this component is claimed proprietary by supplier.

^{** =} As mineral oil mist.

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point 760 mmHg:

Vapor Pressure mmHg @ 100F:

Solubility in H₂O %:

Specific Gravity (H,O): % Volatile by Volume: Viscosity (method, temp):

Appearance: Light amber liquid

N.A. Melting Point: N.A

Vapor Density (air=1): N.A.

Nil pH: N.A. 0.9218

Evaporation Rate: (ethyl ether=1) N.A.

32 cSt @ 40C

Lower: N.A.

N.A.

N.A.

Odor: Slight hydrocarbon odor

N.A. = Not Available

FIRE AND EXPLOSION DATA

Flash Point:

350°

Flammable Limits in Air % by Vol.:

Autoignition Temperature:

N.A.

Extinguishing Media:

Dry chemical, foam, carbon dioxide, or water spray.

Special Fire Fighting Procedure:

Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Firefighters should wear self-

Upper: N.A.

contained breathing apparatus.

Unusual Fire or Explosion Hazard:

May ignite when sufficient heat is applied.

REACTIVITY DATA

Stability:

Stable

Hazardous Polymerization:

Will not occur.

Conditions to Avoid/Incompatibility:

Strong oxidizing agents, heat, spark, flame and build-up of static

electricity.

Hazardous Decomposition Products:

Carbon monoxide, carbon dioxide, aldehydes, ketones, and

combustion products of sulfur and nitrogen.

HEALTH HAZARD DATA

This product has not been tested as a whole to determine its specific health hazards. The information provided in this section is based on health hazard information on the product components.

Carcinogenicity: NTP: No

IARC Monographs: No

OSHA Regulated: No

Occupational Exposure Limits:

See COMPOSITION section.

Effects of Overexposure:

Acute:

Eyes:

Mildly irritating to the eyes.

Skin:

May cause slight skin irritation

Inhalation:

The inhalation hazards of the components are negligible to minimally irritating if airborne concentrations are kept below permissible occupational exposure limits. Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation, drowsiness,

dizziness, headache and nausea.

Ingestion: Ingestion of large amounts may cause headache, drowsiness, nausea,

vomiting or diarrhea. Aspiration hazard if vomiting occurs.

<u>Chronic</u>: Frequent or prolonged contact may cause skin irritation.

Additional Medical and

Toxicological Information: May aggravate preexisting dermatitis. The International Agency for Research on Cancer (IARC) has determined that there is sufficient

evidence for the carcinogenicity of used oils in experimental animals.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush thoroughly with water for at least 15 minutes, including under

the eyelids. Contact a physician immediately, preferably an

Ophthalmologist if redness or irritation occurs.

Skin Contact: Remove contaminated clothing. Wash affected areas with soap and

water. If irritation occurs, get medical help.

Inhalation: Remove to fresh air. If breathing has stopped, apply artificial

respiration. Get immediate medical attention.

Ingestion: Do not induce vomiting. If spontaneous vomiting occurs hold the

victim's head lower than hips to prevent aspiration.

SPECIAL PROTECTION INFORMATION

Eye Protection: Remove contact lenses and wear chemical safety goggles where contact

with liquid or mist may occur.

Skin Protection: Wear impervious gloves when contact with skin may occur. Use face

shield where splashing may occur. Wash with soap and water before eating, drinking or smoking. Launder contaminated before reuse.

Inhalation: Use approved respiratory protective equipment for cleaning large spills

or entry into large tanks, vessels or other confined spaces or in situations where exposure may exceed occupational exposure levels.

Ventilation: Provide adequate general and local exhaust ventilation: (1) to keep

mist or vapors below occupational exposure levels; and (2) to prevent the formation of an oxygen deficient atmosphere, particularly in a

confined space.

SPILL OR LEAK AND DISPOSAL PROCEDURES

Spill Procedures: Remove sources of heat or ignition including internal combustion

engines and power tools. Remove spill with vacuum trucks or pump and soak up residue with an absorbent. Use approved respirator

where occupational exposure limits may be exceeded.

Waste Disposal: Dispose through a licensed waste disposal company. Follow federal,

state and local regulations.

SPECIAL PRECAUTIONS AND COMMENTS

Storage Requirements: Store in tightly closed containers in a dry, cool place, away from

sources of heat, ignition or strong oxidizers. Ground and bond all transfer and storage equipment and equip with self closing valves,

pressure vacuum bungs and flame arrestors.

X

SARA TITLE III INFORMATION

Section 311/312 Hazard Categorization

Acute	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	<u>Reactive</u>

X X

SARA Hazardous Substances

<u>Ingredient</u>	CAS No.	%, Wt	Sec 313	Sec 302	RQ, lb	TPO, lb

<1

Zinc Compound

Key: Sec 313 = Toxic Chemicals, Section 313

N.A.

Sec 302 = Extremely Hazardous Substances (EHS)

RQ = Reportable Quantity of EHS

TPQ = Threshold Planning Quantity of EHS

CALIFORNIA PROPOSITION 65 WARNING

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be found in the petroleum products. Although it is possible to sufficiently refine the petroleum products to remove the potential for cancer, we are advising that one or more of the listed chemicals may be present in some detectable quantities. Read and follow directions and use care when handling these petroleum products.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THIS COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO THE ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABLENESS AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.