

SAFETY DATA SHEET

2758

Product Name 7 COMPONENT MIXTURE (N2, C2H6, C3H8, C4H10, CO2, BALANCE CH4)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA

Telephone 131 262, (02) 8874 4400 **Fax** 132 427 (24 hours)

Emergency 1800 653 572 (24/7) (Australia only)

Web site http://www.boc.com.au

Synonym(s) 2758 - SDS NUMBER • SPECIAL GAS MIXTURE Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS

SDS date 05 September 2014

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Risk Phrases

R12 Extremely Flammable.

Safety Phrases

S16 Keep away from sources of ignition - No smoking.

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN Number1954Transport Hazard Class2.1Packing GroupNone AllocatedHazchem Code2SE

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content (v/v)
ETHANE	CAS: 74-84-0 EC: 200-814-8	F+;R12	<40%
PROPANE	CAS: 74-98-6 EC: 200-827-9	F+;R12	<5%
BUTANE	CAS: 106-97-8 EC: 203-448-7	F+;R12	<2%
ISOBUTANE	CAS: 75-28-5 EC: 200-857-2	F+;R12	<2%
METHANE	CAS: 74-82-8 EC: 200-812-7	F+;R12	Remainder
CARBON DIOXIDE	CAS: 124-38-9 EC: 204-696-9	Not Available	<20%
NITROGEN	CAS: 7727-37-9 EC: 231-783-9	Not Available	<5%

4. FIRST AID MEASURES



Page 1 of 6 SDS Date: 05 Sep 2014

Product Name 7 COMPONENT MIXTURE (N2, C2H6, C3H8, C4H10, CO2, BALANCE CH4)

Eye None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self

Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin

Due to product form and application, ingestion is considered unlikely. Ingestion

Advice to doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Highly flammable. Eliminate all ignition sources including cigarettes, open flames, spark producing **Flammability**

switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling.

Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be Fire and explosion

activated. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot. This material is capable of forming

explosive mixtures with air.

Stop flow of gas if safe to do so, such as by slowly closing the cylinder valve. If the gas source **Extinguishing**

cannot be isolated, do not extinguish the flame, since re-ignition and explosion could occur. Await arrival of emergency services or manufacturer's advisor. Drench and cool cylinders with water spray from protected area at a safe distance. If it is absolutely necessary to extinguish the flame, use only a dry chemical powder extinguisher. Do not move cylinders for at least 24 hours. Avoid shock and

bumps to cylinders.

Hazchem code 2SE

> 2 Water Fog (or fine water spray if fog unavailable)

S Self Contained Breathing apparatus and protective gloves.

Ε Evacuation of people in the vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

Spillage

If the cylinder is leaking, eliminate all potential ignition sources and evacuate area of personnel. Prevent spreading of vapours through drains and ventilation systems. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

7. STORAGE AND HANDLING

Storage Do not store near sources of ignition or incompatible materials. Cylinders should be stored below

45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor

(preferably concrete), away from areas of heavy traffic and emergency exits.

Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll Handling

cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a

suitable hand truck for cylinder movement.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards

Ingredient	Reference	TWA		STEL	
Ingredient	Kelelelice	ppm	mg/m³	ppm	mg/m³
Butane	SWA (AUS)	800	1900		
Carbon dioxide	SWA (AUS)	5000	9000	30000	54000
Carbon dioxide in coal mines	SWA (AUS)	12500	22500	30000	54000
Ethane	SWA (AUS)		Asph	yxiant	
Isobutane	SWA (AUS)	1000			
Methane	SWA (AUS)		Asph	yxiant	
Nitrogen	SWA (AUS)		Asph	yxiant	
Propane	SWA (AUS)	Asphyxiant			



SDS Date: 05 Sep 2014

Page 2 of 6

Product Name 7 COMPONENT MIXTURE (N2, C2H6, C3H8, C4H10, CO2, BALANCE CH4)

Biological limits No biological limit allocated.

Engineering controls Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be

adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure

standard.

PPE

Eye / Face Wear safety glasses. Hands Wear leather gloves. **Body** Wear safety boots.

Respiratory Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line

respirator.







9. PHYSICAL AND CHEMICAL PROPERTIES

COLOURLESS GAS Appearance SLIGHT ODOUR Odour

Flammability EXTREMELY FLAMMABLE

Flash point **NOT AVAILABLE Boiling** point **NOT AVAILABLE NOT AVAILABLE Melting point** NOT APPLICABLE **Evaporation rate** рΗ NOT APPLICABLE Vapour density NOT AVAILABLE Specific gravity **NOT APPLICABLE** 0.033 L/L (Methane) Solubility (water) **NOT AVAILABLE** Vapour pressure 15 % (Methane) **Upper explosion limit** Lower explosion limit 5.3 % (Methane) Partition coefficient NOT AVAILABLE

Autoignition temperature 537°C (Methane) **Decomposition temperature** NOT AVAILABLE Viscosity NOT AVAILABLE **Explosive properties** NOT AVAILABLE Oxidising properties NOT AVAILABLE **Odour threshold** NOT AVAILABLE

% Volatiles 100 %

10. STABILITY AND REACTIVITY

Chemical stability Stable under recommended conditions of storage.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources.

Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), heat and ignition Material to avoid

sources. Do not use natural rubber flexible hoses. Also incompatible (potentially violently) with

oxygen, halogens and metal halides.

Hazardous Decomposition

Products

This material will not decompose to form hazardous products other than that already present.

Hazardous Reactions Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary

Asphyxiant gas. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to

ChemAlert.

SDS Date: 05 Sep 2014

Page 3 of 6

Product Name 7 COMPONENT MIXTURE (N2, C2H6, C3H8, C4H10, CO2, BALANCE CH4)

rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in

minutes.

Eye Non irritant.

Inhalation Asphyxiant. Effects are proportional to oxygen displacement.

Skin Non irritant.

Ingestion Ingestion is considered unlikely due to product form.

Toxicity data PROPANE (74-98-6)

> LC50 (inhalation) > 800000 ppm/15M (rat)

BUTANE (106-97-8)

658000 mg/m3/4H (rat) LC50 (inhalation)

METHANE (74-82-8)

LC50 (inhalation) 326 gm/m3/2h (mouse)

CARBON DIOXIDE (124-38-9)

LC50 (inhalation) 470000 ppm/30M (rat) LCLo (inhalation) 9 pph/5M (human)

12. ECOLOGICAL INFORMATION

Toxicity No information provided.

Persistence and degradability No information provided.

Bioaccumulative potential No information provided.

Mobility in soil No information provided.

Other adverse effects No known ecological damage is caused by this product.

13. DISPOSAL CONSIDERATIONS

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN Number	1954	-	-
Proper Shipping Name	COMPRESSED GAS, FLAMMABLE, N.O.S. (Contains methane)	-	-
Transport Hazard Class	2.1	-	-
Packing Group	None Allocated	-	-

Environmental hazards

No information provided

Special precautions for user

ChemAlert.

Page 4 of 6

SDS Date: 05 Sep 2014

Product Name 7 COMPONENT MIXTURE (N2, C2H6, C3H8, C4H10, CO2, BALANCE CH4)

Hazchem code 2SE GTEPG 2A1

Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which

affect gas storage and transport.

15. REGULATORY INFORMATION

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard

for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Inventory Listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
C 1 C #	Chamical Abatract Carries number used to uniquely identify

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

GHS Globally Harmonized System

IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit
PEL Permissible Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

REACH Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

Revision history

Revision	Description
1.1	Standard SDS Review
1.0	Initial SDS Creation



SDS Date: 05 Sep 2014

Page 5 of 6

Product Name 7 COMPONENT MIXTURE (N2, C2H6, C3H8, C4H10, CO2, BALANCE CH4)

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au

Web: www.rmt.com.au.

Revision: 1.1

SDS Date: 05 September 2014

End of SDS



Page 6 of 6

SDS Date: 05 Sep 2014