

# **Material Safety Data Sheet**

No. 35 Soluble

#### 1. **Product and company identification**

: No. 35 Soluble **Product name** 

**Material uses** : Petroleum lubricating oil

: LUBRIPLATE® Lubricants Co. Supplier/Manufacturer

129 Lockwood St. Newark, NJ 07105

Telephone no.: 1-973-589-9150

: 11/3/2011. Validation date

: Atrion Regulatory Services, Inc. Prepared by

In case of emergency : CHEM-TEL 1-800-255-3924 (24 hour)

## Hazards identification

**Physical state** : Liquid. [oil [Transparent]]

Color : Brown. Odor Mineral oil.

**Emergency overview** 

Signal word : WARNING!

: MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. PROLONGED **Hazard statements** 

OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL

DATA. CANCER HAZARD - CAN CAUSE CANCER.

**Precautions** : Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist.

Do not get on skin or clothing. Avoid contact with eyes. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash

thoroughly after handling.

**OSHA/HCS** status This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation : Slightly irritating to the respiratory system.

: No known significant effects or critical hazards. Ingestion

Skin Moderately irritating to the skin. : Moderately irritating to eyes. **Eyes** 

Potential chronic health effects

**Chronic effects** : Contains material that may cause target organ damage, based on animal data.

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

Can cause cancer. Risk of cancer depends on duration and level of exposure. Carcinogenicity

Mutagenicity No known significant effects or critical hazards. **Teratogenicity** : No known significant effects or critical hazards. **Developmental effects** : No known significant effects or critical hazards. : No known significant effects or critical hazards.

: Contains material which may cause damage to the following organs: lungs, upper Target organs

respiratory tract, skin, eyes.

#### Over-exposure signs/symptoms

Fertility effects

11/3/2011. **United States/Canada** 1/10

## 2. Hazards identification

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Ingestion**: No specific data.

**Skin**: Adverse symptoms may include the following:

irritation redness dryness cracking

**Eyes**: Adverse symptoms may include the following:

irritation watering redness

Medical conditions aggravated by overexposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

# 3. Composition/information on ingredients

#### **United States**

Name	CAS number	%
- · · · · · · · · · · · · · · · · · ·	64742-53-6 64742-52-5 132-27-4	30-60 30-60 0.1-1

#### <u>Canada</u>

Skin contact

Inhalation

Ingestion

**Protection of first-aiders** 

Notes to physician

Name	CAS number	%
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	30-60
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30-60
sodium 2-biphenylate	132-27-4	0.1-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## 4. First aid measures

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

11/3/2011. United States/Canada 2/10

#### 5. Fire-fighting measures

Flammability of the product : In a fire or if heated, a pressure increase will occur and the container may burst.

**Extinguishing media** 

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon dioxide

carbon monoxide sulfur oxides

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### Accidental release measures 6.

**Personal precautions** 

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

**Environmental precautions** 

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods for cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

#### 7. Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Handling and storage

#### **Storage**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# 8. Exposure controls/personal protection

#### **United States**

Ingredient	Exposure limits
Distillates (petroleum), hydrotreated light naphthenic	ACGIH TLV (United States, 2/2010).  TWA: 5 mg/m³ 8 hour(s). Form: Inhalable fraction  NIOSH REL (United States, 6/2009).  TWA: 5 mg/m³ 10 hour(s). Form: Mist  STEL: 10 mg/m³ 15 minute(s). Form: Mist  OSHA PEL (United States, 6/2010).  TWA: 5 mg/m³ 8 hour(s).
Distillates (petroleum), hydrotreated heavy naphthenic	ACGIH TLV (United States, 2/2010).  TWA: 5 mg/m³ 8 hour(s). Form: Inhalable fraction  NIOSH REL (United States, 6/2009).  TWA: 5 mg/m³ 10 hour(s). Form: Mist  STEL: 10 mg/m³ 15 minute(s). Form: Mist  OSHA PEL (United States, 6/2010).  TWA: 5 mg/m³ 8 hour(s).

#### Canada

Occupational exposure limits		TWA (8 hours)		STEL (15 mins)		Ceiling					
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
Distillates (petroleum), hydrotreated light naphthenic	US ACGIH 2/2010	-	5	-	-	-	-	-	-	_	[a]
	ON 7/2010	-	5	-	-	10	-	-	-	-	[b]
	QC 6/2008	-	5	-	-	10	-	-	-	-	[b]
Distillates (petroleum), hydrotreated heavy naphthenic	US ACGIH 2/2010	-	5	-	-	-	-	-	-	_	[a]
, ,	ON 7/2010	-	5	-	-	10	-	-	-	-	[b]
	QC 6/2008	-	5	-	-	10	-	-	-	-	[b]

Form: [a]Inhalable fraction [b]mist

#### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

**Engineering measures** 

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking, using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection
Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# 8. Exposure controls/personal protection

**Hands** 

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eyes** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# 9. Physical and chemical properties

Physical state : Liquid. [oil [Transparent]]

Flash point : Open cup: 179°C (354.2°F) [Cleveland.]

Auto-ignition temperature : Not available.
Flammable limits : Not available.
Color : Brown.
Odor : Mineral oil.

**pH** : 8.9

**Boiling/condensation point** : >40.5°C (>104.9°F) **Melting/freezing point** : Not available.

Relative density : 0.919

Density : Not available.Vapor pressure : Not available.Vapor density : Not available.Odor threshold : Not available.

**Evaporation rate** : <0.01 (butyl acetate = 1)

Viscosity : Not available.

**Solubility** : Easily soluble in the following materials: cold water and hot water.

LogK<sub>ow</sub>: Not available.

## 10. Stability and reactivity

**Chemical stability** 

: The product is stable.

**Conditions to avoid** 

: Keep away from heat, sparks and flame. Keep away from sources of ignition.

**Incompatible materials** 

: Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

# 11. Toxicological information

## **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
sodium 2-biphenylate	LD50 Oral		591 mg/kg	-
Distillates (petroleum), hydrotreated light naphthenic	LC50 Inhalation Vapor	Rat	2180 mg/m3	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Oral	Rat	>5000 mg/kg	-

## **Chronic toxicity**

Not available.

## **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
sodium 2-biphenylate	Skin - Mild irritant	Rabbit	-	24 hours 25 milligrams	-
	Skin - Severe irritant	Rabbit	-	24 hours 50 milligrams	-
Distillates (petroleum), hydrotreated light naphthenic	Skin - Moderate irritant	Rabbit	-	24 hours 0.5 Mililiters	-

#### **Sensitizer**

Not available.

### **Carcinogenicity**

## **Classification**

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Distillates (petroleum), hydrotreated light naphthenic	A4	-	-	-	-	-
Distillates (petroleum), hydrotreated heavy naphthenic	A4	-	-	-	-	-
sodium 2-biphenylate	-	2B	-	-	-	-

### **Mutagenicity**

Not available.

## **Teratogenicity**

Not available.

## **Reproductive toxicity**

Not available.

# 12. Ecological information

## **Ecotoxicity**

: No known significant effects or critical hazards.

## **Aquatic ecotoxicity**

Product/ingredient name	Result	Species	Exposure
sodium 2-biphenylate	Acute EC50 3.8 ppm Fresh water	Daphnia - Daphnia magna - Larvae	48 hours
	Acute LC50 6.1 ppm Fresh water	Fish - Lepomis macrochirus	96 hours

## Persistence/degradability

# 12. Ecological information

Not available.

# 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

# 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	Not regulated.	-	-	•		-
TDG Classification	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-

PG\*: Packing group

# 15. Regulatory information

**United States** 

**HCS Classification** 

: Irritating material Carcinogen

Target organ effects

**U.S. Federal regulations** 

: TSCA 8(a) IUR: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Commerce control list precursor: 2,2',2"-nitrilotriethanol

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: No. 35 Soluble

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: No.

35 Soluble: Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Water Act (CWA) 311: Sodium hydroxide

Clean Air Act (CAA) 112 accidental release prevention: No products were found.

# Regulatory information

 Not listed Clean Air Act Section

112(b) Hazardous Air **Pollutants (HAPs)** 

Clean Air Act Section 602 : Not listed

Class I Substances

Clean Air Act Section 602 : Not listed

**Class II Substances** 

**DEA List I Chemicals** 

(Precursor Chemicals)

: Not listed

**DEA List II Chemicals** (Essential Chemicals)

: Not listed

#### **SARA 313**

	Product name	CAS number	Concentration
Form R - Reporting requirements	sodium 2-biphenylate	132-27-4	0.1-1
Supplier notification	sodium 2-biphenylate	132-27-4	0.1-1

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

#### State regulations

**Massachusetts** : The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES,

HYDROTREATED LIGHT NAPHTHENIC

: None of the components are listed. **New York** 

**New Jersey** : The following components are listed: SODIUM o-PHENYLPHENATE; [1,1'-BIPHENYL]-

2-OL, SODIUM SALT

**Pennsylvania** : None of the components are listed.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	Reproductive		Maximum acceptable dosage level
sodium 2-biphenylate	Yes.	No.	Yes.	No.

#### Canada

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic).

**Canadian lists** 

**Canadian NPRI** : None of the components are listed. **CEPA Toxic substances** : None of the components are listed. Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

#### International regulations

International lists : Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory: Not determined.

**Korea inventory**: All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): All components are listed or exempted. No. 35 Soluble

# 15. Regulatory information

Chemical Weapons
Convention List Schedule I

**Chemicals** 

Chemical Weapons
Convention List Schedule

Il Chemicals

Not listed

: Not listed

Chemical Weapons
Convention List Schedule

Convention List Schedule

**III Chemicals** 


Not listed

## 16. Other information

Label requirements

: MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. CANCER HAZARD - CAN CAUSE CANCER.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

**Date of issue** : 11/3/2011.

Date of previous issue : No previous validation.

Version : 1

Indicates information that has changed from previously issued version.

**Notice to reader** 

No. 35 Soluble

## 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.