

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **361-97650 DULUX PROFESSIONAL QUICK DRY PRIMER SURFACER**

Recommended use of the chemical and restrictions on use: Solvent based surface coating. Applied by brush, roller or spray.

Supplier: Dulux New Zealand, a division of DuluxGroup (New Zealand) Pty Ltd
ABN 55 133 404 118
Co. 2355191

Street Address: 150 Hutt Park Road
Lower Hutt,
New Zealand

Telephone Number: +64 4 576 6400

Facsimile: +64 4 576 6496

Emergency Telephone: **0 800 734 607 (ALL HOURS)**

2. HAZARDS IDENTIFICATION

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

SIGNAL WORD: WARNING

Subclasses:

Subclass 3.1 Category C (medium hazard) - Flammable Liquids.

Subclass 6.1 Category E - Substances which are acutely toxic.

Subclass 6.3 Category B - Substances that are mildly irritating to the skin.

Subclass 6.4 Category A - Substances that are irritating to the eye.

Subclass 6.5 Category B - Substances that are contact sensitisers.

Subclass 6.7 Category A - Substances that are known or presumed human carcinogens.

Subclass 6.8 Category B - Substances that are suspected human reproductive or developmental toxicants.

Subclass 6.9 Category B - Substances that are harmful to human target organs or systems.

Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.

Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006



Safety Data Sheet



Hazard Statement(s):

H226 Flammable liquid and vapour.
H305 May be harmful if swallowed and enters airways.
H313+H333 May be harmful in contact with skin or if inhaled.
H316 Causes mild skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention:

P102 Keep out of reach of children.
P103 Read label before use.
P104 Read Safety Data Sheet before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required.
P273 Avoid release to the environment.

Response:

P370+P378 In case of fire: Use extinguishing media as outlined in Section 5 of this Safety Data Sheet for extinction.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 Do NOT induce vomiting.
P304+P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see First Aid Measures on the Safety Data Sheet).
P363 Wash contaminated clothing before re-use.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P391 Collect spillage.

Storage:

P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 In case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Product Name: 361-97650 DULUX PROFESSIONAL QUICK
DRY PRIMER SURFACER
Substance No: 000000022310

Issued: 14/05/2013

Version: 2



3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Pigments	-	30-60%	-
Synthetic polymer(s)	-	10-<30%	-
Mineral turpentine	-	10-<30%	H226 H304 H315 H411
Xylene	1330-20-7	1-<10%	H226 H332 H312 H315
Methyl ethyl ketoxime	96-29-7	<1%	H351 H312 H318 H317
Kerosine	8008-20-6	<1%	H226 H304
White spirit (Stoddard solvent)	8052-41-3	<1%	H350 H340 H304
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

If swallowed, do NOT induce vomiting. Give a glass of water. Get to a doctor or hospital quickly.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used.

Hazchem or Emergency Action Code: · 3Y

Specific hazards arising from the substance or mixture:

Flammable liquid. On burning will emit toxic fumes.

Special protective equipment and precautions for fire-fighters:

Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES



6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

SMALL SPILLS: Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS: Shut off all possible sources of ignition. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep out of reach of children. Avoid skin and eye contact and breathing in vapour. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Vapour may travel a considerable distance to source of ignition and flash back.

Conditions for safe storage, including any incompatibilities: Store in a well ventilated area away from foodstuffs, oxidising agents and sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace Exposure Standards: No value assigned for this specific material by the New Zealand Department of Labour (Health & Safety). However, Workplace Exposure Standard(s) for constituent(s):

White spirits (Stoddard solvent): WES-TWA 100 ppm, 525 mg/m³

Xylene (o-, m-, p-isomers): WES-TWA 50 ppm, 217 mg/m³

No value assigned for this specific material by the New Zealand Department of Labour (Health & Safety).

No Exposure Standards assigned to other constituents.

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

WES - STEL (Workplace Exposure Standard - Short Term Exposure Limits) - The 15 minute average exposure standard. Applies to any 15 minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both short-term and eight-hour, time-weighted average exposures should be determined.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.

Product Name: 361-97650 DULUX PROFESSIONAL QUICK

DRY PRIMER SURFACER

Substance No: 000000022310

Issued: 14/05/2013

Version: 2

Safety Data Sheet



Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: G - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.



MANUFACTURE, PACKAGING AND TRANSPORT: Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

FOR CONSUMER USE: Use with adequate ventilation. If risk of inhalation exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Viscous liquid
Colour:	Coloured
Odour:	Solvent
Solubility:	Insoluble in water. Soluble in organic solvents.
Specific Gravity:	1.4 @ 20°C
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	>23
Flammability Limits (%):	Not available
Autoignition Temperature (°C):	Not available
% Volatile by Volume:	Not available
Solubility in water (g/L):	Insoluble
Melting Point/Range (°C):	Not applicable
Boiling Point/Range (°C):	Not available
Decomposition Point (°C):	Not available
pH:	Not applicable
Viscosity:	Not available
Evaporation Rate:	Not available

10. STABILITY AND REACTIVITY

Reactivity:	No information available.
Chemical stability:	Stable under normal conditions of use.
Possibility of hazardous reactions:	Hazardous polymerisation will not occur.

Conditions to avoid: Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame.

Product Name: 361-97650 DULUX PROFESSIONAL QUICK
DRY PRIMER SURFACER
Substance No: 000000022310

Issued: 14/05/2013

Version: 2

Safety Data Sheet



Incompatible materials: Incompatible with oxidising agents.

Hazardous decomposition products: Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs.

Eye contact: May be an eye irritant.

Skin contact: Contact with skin will result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.

Inhalation: Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

Acute toxicity: No LD50 data available for the product.

Chronic effects: No information available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

Refer to local government authority for disposal recommendations. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as a Dangerous Good according to NZS 5433:2012 Transport of Dangerous Goods on Land.



UN No: 1263

Product Name: 361-97650 DULUX PROFESSIONAL QUICK
DRY PRIMER SURFACER
Substance No: 000000022310

Issued: 14/05/2013

Version: 2

Safety Data Sheet



Transport Hazard Class: 3 Flammable Liquid
Packing Group: III
Proper Shipping Name or Technical Name: PAINT
Hazchem or Emergency Action Code: · 3Y

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1263
Transport Hazard Class: 3 Flammable Liquid
Packing Group: III
Proper Shipping Name or Technical Name: PAINT

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1263
Packing Group: III
Proper Shipping Name or Technical Name: PAINT

15. REGULATORY INFORMATION

Classification:

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

Subclasses:

Subclass 3.1 Category C (medium hazard) - Flammable Liquids.
Subclass 6.1 Category E - Substances which are acutely toxic.
Subclass 6.3 Category B - Substances that are mildly irritating to the skin.
Subclass 6.4 Category A - Substances that are irritating to the eye.
Subclass 6.5 Category B - Substances that are contact sensitisers.
Subclass 6.7 Category A - Substances that are known or presumed human carcinogens.
Subclass 6.8 Category B - Substances that are suspected human reproductive or developmental toxicants.
Subclass 6.9 Category B - Substances that are harmful to human target organs or systems.
Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.

Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006

Safety Data Sheet

**Hazard Statement(s):**

H226 Flammable liquid and vapour.
H305 May be harmful if swallowed and enters airways.
H313+H333 May be harmful in contact with skin or if inhaled.
H316 Causes mild skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

16. OTHER INFORMATION

Reason(s) for Issue:

Revised Primary SDS

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

DuluxGroup owns the Dulux trade mark in Australia, New Zealand, PNG and Fiji. It is not associated with and has no connection to the owners of the Dulux trade mark in other countries, nor does it sell Dulux products in other countries.