

## ITEM: 2KVC9 - Super Trim Adhesive

DELIVERY: 6192668020

HU NUMBER: U847399890

MSDS B0565

## MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with the respective product with which it is associated.

## MATERIAL SAFETY DATA SHEET - B0565

Associated Grainger Items

3M

## MATERIAL SAFETY DATA SHEET

3M(TM) BRAND SUPER TRIM ADHESIVE P/N 08090

11/06/2006

3M

## MATERIAL SAFETY DATA SHEET

COPYRIGHT, 2006, 3M COMPANY. ALL RIGHTS RESERVED. COPYING AND/OR DOWNLOADING OF THIS INFORMATION FOR THE PURPOSE OF PROPERLY UTILIZING 3M PRODUCTS IS ALLOWED PROVIDED THAT:

(1) THE INFORMATION IS COPIED IN FULL WITH NO CHANGES UNLESS PRIOR WRITTEN AGREEMENT IS OBTAINED FROM 3M, AND

(2) NEITHER THE COPY NOR THE ORIGINAL IS RESOLD OR OTHERWISE DISTRIBUTED WITH THE INTENTION OF EARNING A PROFIT THEREON.

## -----SECTION 1: PRODUCT AND COMPANY IDENTIFICATION -----

PRODUCT NAME: 3M(TM) BRAND SUPER TRIM ADHESIVE P/N 08090

MANUFACTURER: 3M

DIVISION: AUTOMOTIVE AFTERMARKET

ADDRESS:  
3M CENTER  
ST. PAUL, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 OR (651) 737-6501 (24 HOURS)

ISSUE DATE: 11/06/2006

SUPERCEDES DATE: 01/12/2005

DOCUMENT GROUP: 17-8581-5

PRODUCT USE:  
INTENDED USE: AUTOMOTIVE  
SPECIFIC USE: AEROSOL ADHESIVE

## -----SECTION 2: INGREDIENTS -----

INGREDIENT	C.A.S. NO.	% BY WT
DIMETHYL ETHER	115-10-6	30 - 40
METHYL ACETATE	79-20-9	25 - 35
CYCLOHEXANE	110-82-7	10 - 20
NONVOLATILE COMPONENTS - TRADE SECRET	TRADE SECRET	10 - 20
TOLUENE	108-88-3	3 - 7
METHYL ALCOHOL	67-56-1	<0.4

## -----SECTION 3: HAZARDS IDENTIFICATION -----

3.1 EMERGENCY OVERVIEW:

SPECIFIC PHYSICAL FORM: AEROSOL

ODOR, COLOR, GRADE: LIQUID IN AEROSOL CAN, SOLVENT ODOR

GENERAL PHYSICAL FORM: LIQUID

IMMEDIATE HEALTH, PHYSICAL, AND ENVIRONMENTAL HAZARDS:  
AEROSOL CONTAINER CONTAINS FLAMMABLE GAS UNDER PRESSURE. CLOSED CONTAINERS EXPOSED TO HEAT FROM FIRE MAY BUILD PRESSURE AND EXPLODE. EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY TRAVEL LONG DISTANCES ALONG THE GROUND OR FLOOR TO AN IGNITION SOURCE AND FLASH BACK. MAY CAUSE TARGET ORGAN EFFECTS. CONTAINS A CHEMICAL OR CHEMICALS WHICH CAN CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

3.2 POTENTIAL HEALTH EFFECTS:

EYE CONTACT:

MODERATE EYE IRRITATION:  
SIGNS/SYMPTOMS MAY INCLUDE REDNESS, SWELLING, PAIN, TEARING, AND BLURRED OR HAZY VISION.

SKIN CONTACT:

SKIN IRRITATION:  
SYMPTOMS MAY INCLUDE LOCALIZED REDNESS, SWELLING, AND ITCHING.

MAY BE ABSORBED THROUGH SKIN AND CAUSE TARGET ORGAN EFFECTS.

INHALATION:  
INTENTIONAL CONCENTRATION AND INHALATION MAY BE HARMFUL OR FATAL.

RESPIRATORY TRACT IRRITATION:  
SIGNS/SYMPTOMS MAY INCLUDE COUGH, SNEEZING, NASAL DISCHARGE, HEADACHE, HOARSENESS, AND NOSE AND THROAT PAIN.

SINGLE EXPOSURE, ABOVE RECOMMENDED GUIDELINES, MAY CAUSE:

SIMPLE ASPHYXIATION:  
SIGNS/SYMPTOMS MAY INCLUDE INCREASED HEART RATE, RAPID RESPIRATIONS, DROWSINESS, HEADACHE, INCOORDINATION, ALTERED JUDGMENT, NAUSEA, VOMITING, LETHARGY, SEIZURES, COMA, AND MAY BE FATAL.

MAY BE ABSORBED FOLLOWING INHALATION AND CAUSE TARGET ORGAN EFFECTS.

INGESTION:

GASTROINTESTINAL IRRITATION:  
SIGNS/SYMPTOMS MAY INCLUDE ABDOMINAL PAIN, STOMACH UPSET, NAUSEA, VOMITING AND DIARRHEA.

MAY BE ABSORBED FOLLOWING INGESTION AND CAUSE TARGET ORGAN EFFECTS.

TARGET ORGAN EFFECTS:

MAY CAUSE BLINDNESS.

CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION:

SIGNS/SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, DROWSINESS, INCOORDINATION, NAUSEA, SLOWED REACTION TIME, SLURRED SPEECH, GIDDINESS, AND UNCONSCIOUSNESS.

PROLONGED OR REPEATED EXPOSURE MAY CAUSE:

CENTRAL NEUROPATHY:

SIGNS/SYMPTOMS MAY INCLUDE IRRITABILITY, MEMORY IMPAIRMENT, PERSONALITY CHANGES, SLEEP DISORDERS, AND DECREASED ABILITY TO CONCENTRATE.

LIVER EFFECTS:

SIGNS/SYMPTOMS MAY INCLUDE LOSS OF APPETITE, WEIGHT LOSS, FATIGUE, WEAKNESS, ABDOMINAL TENDERNESS AND JAUNDICE.

KIDNEY/BLADDER EFFECTS:

SIGNS/SYMPTOMS MAY INCLUDE CHANGES IN URINE PRODUCTION, ABDOMINAL OR LOWER BACK PAIN, INCREASED PROTEIN IN URINE, INCREASED BLOOD UREA NITROGEN (BUN), BLOOD IN URINE, AND PAINFUL URINATION.

CONTAINS A CHEMICAL OR CHEMICALS WHICH CAN CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

## -----SECTION 4: FIRST AID MEASURES -----

4.1 FIRST AID PROCEDURES:

THE FOLLOWING FIRST AID RECOMMENDATIONS ARE BASED ON AN ASSUMPTION THAT APPROPRIATE PERSONAL AND INDUSTRIAL HYGIENE PRACTICES ARE FOLLOWED.

EYE CONTACT:

FLUSH EYES WITH LARGE AMOUNTS OF WATER. IF SIGNS/SYMPTOMS PERSIST, GET MEDICAL ATTENTION.

SKIN CONTACT:

WASH AFFECTED AREA WITH SOAP AND WATER. IF SIGNS/SYMPTOMS DEVELOP, GET MEDICAL ATTENTION.

INHALATION:

REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS DEVELOP, GET MEDICAL ATTENTION.

IF SWALLOWED:

DO NOT INDUCE VOMITING UNLESS INSTRUCTED TO DO SO BY MEDICAL PERSONNEL. GIVE VICTIM TWO GLASSES OF WATER. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET MEDICAL ATTENTION.

## -----SECTION 5: FIRE FIGHTING MEASURES -----

5.1 FLAMMABLE PROPERTIES:

AUTOIGNITION TEMPERATURE: NO DATA AVAILABLE

FLASH POINT: -50 DEG. F

FLAMMABLE LIMITS - LEL: NO DATA AVAILABLE

FLAMMABLE LIMITS - UEL: NO DATA AVAILABLE

5.2 EXTINGUISHING MEDIA:

USE FIRE EXTINGUISHERS WITH CLASS D EXTINGUISHING AGENTS (E.G. DRY POWDER).

USE FIRE EXTINGUISHERS WITH CLASS B EXTINGUISHING AGENTS (E.G., DRY CHEMICAL, CARBON DIOXIDE).

5.3 PROTECTION OF FIRE FIGHTERS:

SPECIAL FIRE FIGHTING PROCEDURES:

WATER MAY NOT EFFECTIVELY EXTINGUISH FIRE; HOWEVER, IT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS AND SURFACES COOL AND PREVENT EXPLOSIVE RUPTURE. WEAR FULL PROTECTIVE EQUIPMENT (BUNKER GEAR) AND A SELF-CONTAINED BREATHING APPARATUS (SCBA).

UNUSUAL FIRE AND EXPLOSION HAZARDS:

CLOSED CONTAINERS EXPOSED TO HEAT FROM FIRE MAY BUILD PRESSURE AND EXPLODE. EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY TRAVEL LONG DISTANCES ALONG THE GROUND OR FLOOR TO AN IGNITION SOURCE AND FLASH BACK. AEROSOL CONTAINER CONTAINS FLAMMABLE MATERIAL UNDER PRESSURE.

NOTE:

SEE STABILITY AND REACTIVITY (SECTION 10) FOR HAZARDOUS COMBUSTION AND THERMAL DECOMPOSITION INFORMATION.

## -----SECTION 6: ACCIDENTAL RELEASE MEASURES -----

ACCIDENTAL RELEASE MEASURES:

IF POSSIBLE, SEAL LEAKING CONTAINER. PLACE LEAKING CONTAINERS IN A WELL-VENTILATED AREA, PREFERABLY AN OPERATING EXHAUST HOOD, OR IF NECESSARY OUTDOORS ON AN IMPERMEABLE SURFACE UNTIL APPROPRIATE PACKAGING FOR THE LEAKING CONTAINER OR ITS CONTENTS IS AVAILABLE.

REFER TO OTHER SECTIONS OF THIS MSDS FOR INFORMATION REGARDING PHYSICAL AND HEALTH HAZARDS, RESPIRATORY PROTECTION, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT. CALL 3M-HELPS LINE (1-800-364-3577) FOR MORE INFORMATION ON HANDLING AND MANAGING THE SPILL.

EVACUATE UNPROTECTED AND UNTRAINED PERSONNEL FROM HAZARD AREA. THE SPILL SHOULD BE CLEANED UP BY QUALIFIED PERSONNEL. REMOVE ALL IGNITION SOURCES SUCH AS FLAMES, SMOKING MATERIALS, AND ELECTRICAL SPARK SOURCES. USE ONLY NON-SPARKING TOOLS. VENTILATE THE AREA WITH FRESH AIR. CONTAIN SPILL. CLEAN UP RESIDUE. COLLECT THE RESULTING RESIDUE CONTAINING SOLUTION IN A CLOSED CONTAINER APPROVED FOR TRANSPORTATION BY APPROPRIATE AUTHORITIES. DISPOSE OF COLLECTED MATERIAL AS SOON AS POSSIBLE.

IN THE EVENT OF A RELEASE OF THIS MATERIAL, THE USER SHOULD DETERMINE IF THE RELEASE QUALIFIES AS REPORTABLE ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS.

-----SECTION 7: HANDLING AND STORAGE -----

**7.1 HANDLING:**  
DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. WASH EXPOSED AREAS THOROUGHLY WITH SOAP AND WATER. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME, PILOT LIGHTS AND OTHER SOURCES OF IGNITION. DO NOT PIERCE OR BURN CONTAINER, EVEN AFTER USE. DO NOT SMOKING WHILE HANDLING THIS MATERIAL. DO NOT SPRAY NEAR FLAMES OR SOURCES OF IGNITION. AVOID BREATHING OF VAPORS, MISTS OR SPRAY. AVOID PROLONGED OR REPEATED SKIN CONTACT. AEROSOL CONTAINER CONTAINS FLAMMABLE GAS UNDER PRESSURE. AVOID STATIC DISCHARGE. AVOID EYE CONTACT WITH VAPORS, MISTS, OR SPRAY. FOR INDUSTRIAL OR PROFESSIONAL USE ONLY.

**7.2 STORAGE:** STORE AWAY FROM HEAT. STORE OUT OF DIRECT SUNLIGHT.

-----SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION -----

**8.1 ENGINEERING CONTROLS:**  
DO NOT USE IN A CONFINED AREA OR AREAS WITH LITTLE OR NO AIR MOVEMENT. USE IN A WELL-VENTILATED AREA. USE WITH APPROPRIATE LOCAL EXHAUST VENTILATION. IF EXHAUST VENTILATION IS NOT AVAILABLE, USE APPROPRIATE RESPIRATORY PROTECTION. USE GENERAL DILUTION VENTILATION AND/OR LOCAL EXHAUST VENTILATION TO CONTROL AIRBORNE EXPOSURES TO BELOW OCCUPATIONAL EXPOSURE LIMITS AND/OR CONTROL MIST, VAPOR, OR SPRAY. IF VENTILATION IS NOT ADEQUATE, USE RESPIRATORY PROTECTION EQUIPMENT.

**8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE):**

**8.2.1 EYE/FACE PROTECTION:**  
AVOID EYE CONTACT.

THE FOLLOWING EYE PROTECTION(S) ARE RECOMMENDED:  
SAFETY GLASSES WITH SIDE SHIELDS.

**8.2.2 SKIN PROTECTION:**  
AVOID PROLONGED OR REPEATED SKIN CONTACT. AVOID SKIN CONTACT. GLOVES NOT NORMALLY REQUIRED.

**RESPIRATORY PROTECTION:**  
AVOID BREATHING OF VAPORS, MISTS OR SPRAY.

SELECT ONE OF THE FOLLOWING NIOSH APPROVED RESPIRATORS BASED ON AIRBORNE CONCENTRATION OF CONTAMINANTS AND IN ACCORDANCE WITH OSHA REGULATIONS: HALF FACEPIECE AIR-PURIFYING RESPIRATOR WITH ORGANIC VAPOR/ACID GAS CARTRIDGES AND N95 PARTICULATE PREFILTERS.

CONSULT THE CURRENT 3M RESPIRATORY SELECTION GUIDE FOR ADDITIONAL INFORMATION OR CALL 1-800-243-4630 FOR 3M TECHNICAL ASSISTANCE.

**8.2.4 PREVENTION OF SWALLOWING**  
DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. WASH EXPOSED AREAS THOROUGHLY WITH SOAP AND WATER.

**8.3 EXPOSURE GUIDELINES:**

INGREDIENT AUTHORITY TYPE LIMIT ADDITIONAL INFORMATION

CYCLOHEXANE	ACGIH	TWA	100 PPM	
CYCLOHEXANE	OSHA	TWA	300 PPM	TABLE Z-1
DIMETHYL ETHER	AIHA	TWA	1000 PPM	
DIMETHYL ETHER	CMRG	TWA	1000 PPM	
METHYL ACETATE	ACGIH	TWA	200 PPM	
METHYL ACETATE	ACGIH	STEL	250 PPM	
METHYL ACETATE	OSHA	TWA	200 PPM	TABLE Z-1 A
METHYL ACETATE	OSHA	STEL	250 PPM	TABLE Z-1 A
METHYL ALCOHOL	ACGIH	TWA	200 PPM	SKIN NOTATION*
METHYL ALCOHOL	ACGIH	STEL	250 PPM	SKIN NOTATION*
METHYL ALCOHOL	OSHA	TWA	200 PPM	SKIN NOTATION*; TABLE Z-1A
METHYL ALCOHOL	OSHA	STEL	250 PPM	SKIN NOTATION*; TABLE Z-1A
TOLUENE	ACGIH	TWA	50 PPM	SKIN NOTATION*; TABLE A4
TOLUENE	CMRG	STEL	75 PPM	SKIN NOTATION*
TOLUENE	OSHA	TWA	100 PPM	VACATED
TOLUENE	OSHA	STEL	150 PPM	VACATED
TOLUENE	OSHA	TWA	200 PPM	TABLE Z-2
TOLUENE	OSHA	CEIL	300 PPM	TABLE Z-2

\* SUBSTANCE(S) REFER TO THE POTENTIAL CONTRIBUTION TO THE OVERALL EXPOSURE BY THE CUTANEOUS ROUTE INCLUDING MUCOUS MEMBRANE AND EYE, EITHER BY AIRBORNE OR, MORE PARTICULARLY, BY DIRECT CONTACT WITH THE SUBSTANCE. VEHICLES CAN ALTER SKIN ABSORPTION.

VAC VACATED PEL:  
VACATED PERMISSIBLE EXPOSURE LIMITS (PEL) ARE ENFORCED AS THE OSHA PEL IN SOME STATES. CHECK WITH YOUR LOCAL REGULATORY AGENCY.

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

CMRG: CHEMICAL MANUFACTURER RECOMMENDED GUIDELINE

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

AIHA:  
AMERICAN INDUSTRIAL HYGIENE ASSOCIATION WORKPLACE ENVIRONMENTAL EXPOSURE LEVEL (WEEL)

-----SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES -----

SPECIFIC PHYSICAL FORM: AEROSOL

ODOR, COLOR, GRADE: LIQUID IN AEROSOL CAN, SOLVENT ODOR

GENERAL PHYSICAL FORM: LIQUID

AUTOIGNITION TEMPERATURE: NO DATA AVAILABLE

FLASH POINT: -50 DEG. F

FLAMMABLE LIMITS - LEL: NO DATA AVAILABLE

FLAMMABLE LIMITS - UEL: NO DATA AVAILABLE

BOILING POINT: NOT APPLICABLE

VAPOR DENSITY: >1=2

VAPOR PRESSURE: NOT APPLICABLE

SPECIFIC GRAVITY: 0.812

pH: NOT APPLICABLE

MELTING POINT: NOT APPLICABLE

SOLUBILITY IN WATER: NIL

EVAPORATION RATE: >1=2 (REFSTD: ETHER=1)

HAZARDOUS AIR POLLUTANTS: 0.0 - 6.0 % WEIGHT

VOLATILE ORGANIC COMPOUNDS: 55 % WEIGHT

PERCENT VOLATILE: 78 % WEIGHT

VOC LESS H2O & EXEMPT SOLVENTS: NO DATA AVAILABLE

-----SECTION 10: STABILITY AND REACTIVITY -----

STABILITY: STABLE.

MATERIALS AND CONDITIONS TO AVOID: HEAT

HAZARDOUS POLYMERIZATION: HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

SUBSTANCE	CONDITION
CARBON MONOXIDE	DURING COMBUSTION
CARBON DIOXIDE	DURING COMBUSTION

-----SECTION 11: TOXICOLOGICAL INFORMATION -----

PLEASE CONTACT THE ADDRESS LISTED IN THE SECTION 1 OF THIS MSDS FOR TOXICOLOGICAL INFORMATION ON THIS MATERIAL AND/OR ITS COMPONENTS.

-----SECTION 12: ECOLOGICAL INFORMATION -----

ECOTOXICOLOGICAL INFORMATION: NOT DETERMINED.

CHEMICAL FATE INFORMATION: NOT DETERMINED.

-----SECTION 13: DISPOSAL CONSIDERATIONS -----

WASTE DISPOSAL METHOD:  
INCINERATE IN A PERMITTED HAZARDOUS WASTE INCINERATOR. AS A DISPOSAL ALTERNATIVE, DISPOSE OF WASTE PRODUCT IN A PERMITTED HAZARDOUS WASTE FACILITY.

FACILITY MUST BE CAPABLE OF HANDLING AEROSOL CANS. DISPOSE OF EMPTY PRODUCT CONTAINERS IN A SANITARY LANDFILL.

EPA HAZARDOUS WASTE NUMBER (RCRA): D001 (IGNITABLE)

SINCE REGULATIONS VARY, CONSULT APPLICABLE REGULATIONS OR AUTHORITIES BEFORE DISPOSAL.

-----SECTION 14: TRANSPORT INFORMATION -----

ID NUMBER(S): 60-4550-3006-8, 60-9800-4438-6

PLEASE CONTACT THE EMERGENCY NUMBERS LISTED IN THE SECTION 1 OF THIS MSDS FOR TRANSPORTATION INFORMATION FOR THIS MATERIAL.

-----SECTION 15: REGULATORY INFORMATION -----

US FEDERAL REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

311/312 HAZARD CATEGORIES:

FIRE HAZARD: YES  
PRESSURE HAZARD: YES  
REACTIVITY HAZARD: NO  
IMMEDIATE HAZARD: YES  
DELAYED HAZARD: YES

SECTION 313 TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF THAT SECTION AND 40 CFR PART 372 (EPCRA):

INGREDIENT	C.A.S. NO	% BY WT
TOLUENE	108-88-3	3 - 7
CYCLOHEXANE	110-82-7	10 - 20

THIS MATERIAL CONTAINS A CHEMICAL WHICH REQUIRES EXPORT NOTIFICATION UNDER TSCA SECTION 12(B):

INGREDIENT (CATEGORY IF APPLICABLE)	C.A.S. NO	REGULATION	STATUS
CYCLOHEXANE	110-82-7	TOXIC SUBSTANCES CONTROL ACT (TSCA) 4 TEST RULE CHEMICALS	APPLICABLE
METHYL ACETATE	79-20-9	TOXIC SUBSTANCES CONTROL ACT (TSCA) 4 TEST RULE CHEMICALS	APPLICABLE

STATE REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

CALIFORNIA PROPOSITION 65:

INGREDIENT	C.A.S. NO.	CLASSIFICATION
TOLUENE	108-88-3	*DEVELOPMENTAL TOXIN

\* WARNING:  
CONTAINS A CHEMICAL OR CHEMICALS WHICH CAN CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

CHEMICAL INVENTORIES:  
THE COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE CHEMICAL NOTIFICATION REQUIREMENTS OF TSCA.

ALL APPLICABLE CHEMICAL INGREDIENTS IN THIS MATERIAL ARE LISTED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICAL SUBSTANCES (EINECS), OR ARE EXEMPT POLYMERS WHOSE MONOMERS ARE LISTED ON EINECS.

CONTACT 3M FOR MORE INFORMATION.

INTERNATIONAL REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

WHMIS: HAZARDOUS

MSDS HAS BEEN PREPARED TO MEET THE U.S. OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200.

---SECTION 16: OTHER INFORMATION ---

NFPA HAZARD CLASSIFICATION:

HEALTH 2  
FLAMMABILITY 4  
REACTIVITY 0  
SPECIAL HAZARDS NONE

AEROSOL STORAGE CODE: 3

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD RATINGS ARE DESIGNED FOR USE BY EMERGENCY RESPONSE PERSONNEL TO ADDRESS THE HAZARDS THAT ARE PRESENTED BY SHORT-TERM, ACUTE EXPOSURE TO A MATERIAL UNDER CONDITIONS OF FIRE, SPILL, OR SIMILAR EMERGENCIES. HAZARD RATINGS ARE PRIMARILY BASED ON THE INHERENT PHYSICAL AND TOXIC PROPERTIES OF THE MATERIAL BUT ALSO INCLUDE THE TOXIC PROPERTIES OF COMBUSTION OR DECOMPOSITION PRODUCTS THAT ARE KNOWN TO BE GENERATED IN SIGNIFICANT QUANTITIES.

REVISION CHANGES:

SECTION 1: PRODUCT USE INFORMATION WAS MODIFIED.

COPYRIGHT WAS MODIFIED.

SECTION 3: POTENTIAL EFFECTS FROM INHALATION INFORMATION WAS MODIFIED.

SECTION 3: POTENTIAL EFFECTS FROM INGESTION INFORMATION WAS MODIFIED.

SECTION 6: RELEASE MEASURES INFORMATION WAS MODIFIED.

SECTION 13: WASTE DISPOSAL METHOD INFORMATION WAS MODIFIED.

SECTION 4:  
FIRST AID FOR INGESTION (SWALLOWING) - DECONTAMINATION - WAS MODIFIED.

SECTION 4:  
FIRST AID FOR INGESTION (SWALLOWING) - MEDICAL ASSISTANCE - WAS MODIFIED.

SECTION 3: OTHER HEALTH EFFECTS INFORMATION WAS MODIFIED.

SECTION 14: ID NUMBER(S) WAS MODIFIED.

DISCLAIMER:

THE INFORMATION IN THIS MATERIAL SAFETY DATA SHEET (MSDS) IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. USER IS RESPONSIBLE FOR DETERMINING WHETHER THE 3M PRODUCT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR USER'S METHOD OF USE OR APPLICATION. GIVEN THE VARIETY OF FACTORS THAT CAN AFFECT THE USE AND APPLICATION OF A 3M PRODUCT, SOME OF WHICH ARE UNIQUELY WITHIN THE USER'S KNOWLEDGE AND CONTROL, IT IS ESSENTIAL THAT THE USER EVALUATE THE 3M PRODUCT TO DETERMINE WHETHER IT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR USER'S METHOD OF USE OR APPLICATION.

3M PROVIDES INFORMATION IN ELECTRONIC FORM AS A SERVICE TO ITS CUSTOMERS.

DUE TO THE REMOTE POSSIBILITY THAT ELECTRONIC TRANSFER MAY HAVE RESULTED IN ERRORS, OMISSIONS OR ALTERATIONS IN THIS INFORMATION, 3M MAKES NO REPRESENTATIONS AS TO ITS COMPLETENESS OR ACCURACY. IN ADDITION, INFORMATION OBTAINED FROM A DATABASE MAY NOT BE AS CURRENT AS THE INFORMATION IN THE MSDS AVAILABLE DIRECTLY FROM 3M.

3M MSDSS ARE AVAILABLE AT WWW.3M.COM