

Page: 1 of 7 Printed: 07/13/2017

Revision: 07/13/2017 Supersedes Revision: 01/05/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code:

QS A

Product Name:

Quik-Shield A

Company Name:

SWD URETHANE

539 S. Drew St. Mesa, AZ 85210,

Web site address:

www.swdurethane.com

Emergency Contact:

CHEMTREC (800) 424-9300

2. HAZARDS IDENTIFICATION

Acute Toxicity: Oral, Category 5 Skin Corrosion/Irritation, Category 2 Skin Sensitization, Category 1

Serious Eye Damage/Eye Irritation, Category 2B

Acute Toxicity: Inhalation, Category 4
Respiratory Sensitization, Category 1

Carcinogenicity, Category 2





GHS Signal Word:

Danger

GHS Hazard Phrases:

H303 - May be harmful if swallowed.

H315 - Causes skin irritation.

H317 - Health Hazards: Suspected of causing cancer. May cause damage to organs

through prolonged or repeated exposure.

H320 - Causes eye irritation. H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351 - Suspected of causing cancer.

H401 - Toxic to aquatic life.

GHS Precaution Phrases:

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P284 - Wear respiratory protection.

P285 - In case of inadequate ventilation wear respiratory protection.

GHS Response Phrases:

P302+352 - IF ON SKIN: Wash with plenty of soap and water.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P341 - If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+313 - IF exposed or concerned: Get medical attention/advice. P332+313 - If skin irritation occurs, get medical advice/attention.

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 2 of 7 Printed: 07/13/2017

Revision: 07/13/2017 Supersedes Revision: 01/05/2016

P337+313 - If eye irritation persists, get medical advice/attention.

P342+311 - If experiencing respiratory symptoms call a POISON CENTER or

doctor/physician.

P362 - Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal

Phrases:

P405 - Store locked up.

Inhalation:

Causes respiratory tract irritation.

Skin Contact:

May be harmful if absorbed through the skin. Causes skin irritation.

Eye Contact:

Causes eye irritation.

Ingestion:

May be harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#

Hazardous Components (Chemical Name)

Concentration

101-68-8

Methylenebis(phenylisocyanate) {MBI;

30.0 -60.0 %

Methylene diphenyl diisocyanate; MDI; Diphenylmethane-4,4'-diisocyanate}

NA

MDI, mixed isomers

30.0 -60.0 %

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

In Case of Inhalation:

If breathed in, move person into fresh air. If not breathing give artificial respiration.

In Case of Skin Contact:

Wash off with soap and plenty of water. Consult a physician.

In Case of Eye Contact:

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

In Case of Ingestion:

Never give anything by mouth to an unconscious person. Rinse mouth with water.

Consult a physician.

Signs and Symptoms Of

Exposure:

Cough, Shortness of breath, Headache. Nausea. Vomiting, Pulmonary edema. Effects

may be delayed.

Note to Physician:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of

dangerous area.

5. FIRE FIGHTING MEASURES

Flash Pt:

> 150.00 C Method Used: Closed Cup

Explosive Limits:

LEL:

UEL:

Wear self contained breathing apparatus for fire fighting if necessary.

Autoignition Pt:

NA

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

Fire Fighting Instructions: Flammable Properties and

Hazards:

Hazardous Combustion

Products:

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 3 of 7 Printed: 07/13/2017 Revision: 07/13/2017

Supersedes Revision: 01/05/2016

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case

Personal precautions.

Material Is Released Or Spilled:

Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Ensure

adequate ventilation.

Environmental precautions. Do not let product enter drains.

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers

for disposal.

7. HANDLING AND STORAGE

Precautions To Be Taken in

Handling:

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed. Normal

measures for preventive fire protection.

Precautions To Be Taken in

Keep container tightly closed in a dry and well-ventilated place.

Storing:

Recommended storage temperature: 15 - 38 deg.C.

Store under inert gas. Moisture sensitive.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS# **Partial Chemical Name** **OSHA TWA**

ACGIH TWA

Other Limits

101-68-8

Methylenebis(phenylisocyanate) {MBI;

CEIL: 0.02 ppm

TLV: 0.005 ppm

Methylene diphenyl diisocyanate; MDI;

Diphenylmethane-4,4'-diisocyanate}

NA

MDI, mixed isomers

Respiratory Equipment

(Specify Type):

When the product is sprayed or heated without adequate ventilation, an approved

MSHA/NIOSH positive-pressure, supplied air respirator may be required. Air purifying respirators equipped with organic vapor cartridges and HEPA (P100) particulate filter may be used under certain conditions when the cartridge change-out schedule has been developed in accordance with the OSHA respiratory protection standard (29 CFR

1910.134).

Eye Protection:

Face shield and safety glasses.

Protective Gloves:

Handle with gloves.

Other Protective Clothing:

Choose body protection according to the amount and concentration of the dangerous

substance at the work place.

Engineering Controls

(Ventilation etc.):

Practices:

Work/Hygienic/Maintenance Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 4 of 7 Printed: 07/13/2017

Revision: 07/13/2017 Supersedes Revision: 01/05/2016

9. PHYSICAL AND CHEMICAL PROPERTIES Physical States: [] Gas [X] Liquid [] Solid Appearance and Odor: Slightly. Musty. pH: **Melting Point:** 42.00 C - 45.00 C **Boiling Point:** 200.00 C Flash Pt: > 150.00 C Method Used: Closed Cup **Evaporation Rate:** Flammability (solid, gas): **Explosive Limits:** LEL: UEL: Vapor Pressure (vs. Air or mm Hg): Vapor Density (vs. Air = 1): Specific Gravity (Water = 1): Density: 1.18 G/CM3 Solubility in Water: Octanol/Water Partition Coefficient: Autoignition Pt: NA Decomposition Temperature: Viscosity: 10. STABILITY AND REACTIVITY Stability: Unstable [] Stable [X] Contact with moisture, other materials that react with isocyanates, or temperatures abovr Conditions To Avoid -Instability: 350 °F (177 °C), may cause polymerization. Incompatibility - Materials To Water. Amines, Strong bases, Alcohols. Avoid: Hazardous Decomposition or formed under fire conditions. Carbon oxides, Byproducts: nitrogen oxides (NOx). Possibility of Hazardous Will occur [] Will not occur [X] Reactions:

Conditions To Avoid - Hazardous Reactions:



Page: 5 of 7 Printed: 07/13/2017

Revision: 07/13/2017 Supersedes Revision: 01/05/2016

11. TOXICOLOGICAL INFORMATION

Toxicological Information:

Irritation or Corrosion:

Serious eye damage/eye irritation:

Eyes - rabbit - Moderate eye irritation.

Carcinogenicity/Other

Carcinogenicity.

Information:

This product is or contains a component that is not classifiable as to its carcinogenicity

based on its IARC, ACGIH, NTP, or EPA classification.

Limited evidence of carcinogenicity in animal studies.

IARC: Group 3: Not classifiable as to its carcinogenicity to humans 3.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by OSHA.

CAS#

Hazardous Components (Chemical Name)

MDI, mixed isomers

NTP

ACGIH

OSHA

101-68-8

Methylenebis(phenylisocyanate) {MBI; Methylene diphenyl

IARC

OSHA

NA

vietnylenebis(prienylisocyanate) (wibi, ivietnylene dipnen

diisocyanate; MDI; Diphenylmethane-4,4'-diisocyanate}

____~

12. ECOLOGICAL INFORMATION

Persistence and

Degradability:

No data available.

Bioaccumulative Potential:

No data available.

Mobility in Soil:

No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Product.

Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an

afterburner and scrubber.

Contaminated packaging.

Dispose of as unused product.

14. TRANSPORT INFORMATION

GHS Classification:

Acute Toxicity: Oral, Category 5 - Warning! May be harmful if swallowed

Skin Corrosion/Irritation, Category 2 - Warning! Causes skin irritation

Skin Sensitization, Category 1 - Warning! May cause an allergic skin reaction Serious Eye Damage/Eye Irritation, Category 2B - Warning! Causes eye irritation

Acute Toxicity: Inhalation, Category 4 - Warning! Harmful if inhaled

Respiratory Sensitization, Category 1 - Danger! May cause allergy or asthma symptoms

or breathing difficulties if inhaled

Carcinogenicity, Category 2 - Warning! Suspected of causing cancer

Aquatic Toxicity (Acute), Category 2 - Toxic to aquatic life

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 6 of 7

Printed: 07/13/2017 Revision: 07/13/2017

Supersedes Revision: 01/05/2016

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Other regulated substances, Liquid, N.O.S. (Methylene Diphenyl Diisocyanate)

DOT Hazard Class:

CLASS 9

UN/NA Number:

NA3082

Packing Group:

Ш

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name:

Not Regulated.

UN Number:

3082

Packing Group:

III

S. 313 (TRI)

Yes-Cat. N120

Yes-Cat. N120

Hazard Class:

9 - CLASS 9

TDG Classification:

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name:

Not Regulated.

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Not Regulated.

Additional Transport

Containers shipped with less than 20,000 LBS are classified as Non-Hazardous.

S. 302 (EHS)

No

No

Information:

CAS#

NA

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS# Hazardous Components (Chemical Name) 101-68-8

Methylenebis(phenylisocyanate) {MBI;

Methylene diphenyl diisocyanate; MDI;

Diphenylmethane-4,4'-diisocyanate}

NA MDI, mixed isomers

Hazardous Components (Chemical Name)

101-68-8 Methylenebis(phenylisocyanate) {MBI;

Methylene diphenyl diisocyanate; MDI;

Diphenylmethane-4,4'-diisocyanate}

Other US EPA or State Lists

CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes -

S. 304 RQ

No

Yes 5000 LB

Inventory, 8C; CA PROP.65: No; CA TAC, Title 8: TAC, Title

8; MA Oil/HazMat: No; MI CMR, Part 5: Part 5; NC TAP: Yes:

NJ EHS: Yes - Cat.; NY Part 597: Yes; PA HSL: Yes - E; SC

TAP: Yes; WI Air: Yes

MDI, mixed isomers CAA HAP, ODC: No; CWA NPDES: No; TSCA: Yes -

> Inventory, 8C, 8D TERM; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - Cat.; NY Part 597: No; PA HSL: No; SC TAP:

No; WI Air: No

CAS# Hazardous Components (Chemical Name)

101-68-8 Methylenebis(phenylisocyanate) {MBI;

Methylene diphenyl diisocyanate; MDI;

Diphenylmethane-4,4'-diisocyanate}

NA MDI, mixed isomers International Regulatory Lists

Canadian DSL: Yes; Canadian NDSL: No

Canadian DSL: Yes; Canadian NDSL: No

Regulatory Information:

This product contains chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40

CFR part 372.

Incipient fire responders should wear eye protection. Firefighters must wear

Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible,

prevent runoff water from entering storm drains, bodies of water, or other

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 7 of 7 Printed: 07/13/2017

Revision: 07/13/2017 Supersedes Revision: 01/05/2016

environmentally sensitve areas.

Incipient fire responders should wear eye protection. Firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitve areas.

16. OTHER INFORMATION

Revision Date:

07/13/2017

Additional Information About

This Product:

Company Policy or

Disclaimer:

While the information and recommendations in this publication are given to the best of our knowledge, and information at the date of publication, nothing herein is to be construed as a warranty, expressed or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information, and recommendations or the suitability of any product for its own particular purpose.

The product may present hazards and should be used with caution. While certain hazards are described in this Safety Data Sheet, no guarantee is made that these are the only hazards that exist. Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED SWD EMPLOYEE SHALL PROVIDE, OR MAKE AVAILABLE, DATA SHEETS FOR SWD PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT THE WRITTEN PERMISSION OF SWD. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET OR QUESTIONS REGARDING THIS DATA SHEET SHOULD BE DIRECTRED TO SWD AT 800-828-1394.