

Material Safety Data Sheet

Revision Date Prepared by Technical Information

August 3, 2011 Patti Rogers 1-800-201-8822 or support@mgchemicals.com

Head OfficeEmergency9347 - 193 Street, Surrey, B.C., V4N 4E7Phone Canutech (613) 996-6666 Collect 24 hrs

For updates please download from www.mgchemicals.com or fax requests to 1-800-708-9888

Section 1: Product Identification

MSDS Code: 422A - P Name: Silicone Conformal Coating Pen

Related Part Numbers: 422A-PUse: Protective coating for pc boards.

Section 2: Hazardous Ingredients

CAS#	Chemical Name	Percentage by weight	ACGIH TWA	Osha Pel	Osha Stel
67-64-1	2-propanone	25 – 50%	750ppm	1000ppm	1000ppm
1330-20-7	Xylenes	15 – 40%	100ppm	100ppm	150ppm
N/A	Polymethylphenylsiloxanes	8 – 20%	N/A	N/A	N/A
9003-01-4	Acrylic resins	8 – 20%	N/A	N/A	N/A
108-65-6	1-methoxy-2- propanol acetate	2 – 8%	N/E	N/E	N/E

Section 3: Hazards Identification

Eyes: Causes eye irritation.

Skin: Irritant. Can cause redness, dryness, and loss of natural oils.

Inhalation: May cause headaches.

Ingestion: Harmful if swallowed. May cause headaches.

Chronic: No effects known.

Section 4: First Aid Measure

Eyes: Remove contact lenses. Flush with water or saline.

Skin: Wash skin with soap and water.

Inhalation: Immediately remove from exposure to fresh air.

Ingestion: May cause digestive tract irritation.

Section 5: Fire Fighting Measures

Autoignition 272°C Flash Point: -18°C LEL / UEL: 4 / 19

Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or chemical foam.

General Information: Will burn if involved in a fire. Containers may explode in the heat of a fire. Flash back along

vapor trail is possible.

Section 6: Accidental Release Measures

Spill Procedure: Remove all sources of ignition. Provide adequate ventilation. Wipe up with paper towel and place in container. Wash spill area with soap and water.



Section 7: Handling and Storage

Handling: Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not ingest or inhale. Do

not expose container to heat or flame.

Storage: Keep away from sources of ignition. Store in a cool, dry, well-ventilated area, away from incompatible

substances. Keep from freezing.

Section 8: Exposure Controls

Routes of entry: Eyes, ingestion, inhalation, and skin.

Ventilation: Use adequate general or local exhaust ventilation to keep airborne concentrations below

exposure limits.

Personal Protection: Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate

protective clothing to prevent skin contact. Use a NIOSH approved respirator when

necessary.

Section 9: Physical and Chemical Properties

Physical Liquid Odor: Ethereal Solubility Insoluble Evaporation Moderate

State: in water: Rate:

Boiling 150°C Specific 0.96 Vapor 1 PSI Vapor 3.1 pH: 7

Point: Gravity: Pressure: @21°C Density: (Air=1)

Section 10: Stability and Reactivity

Stability: Stable at normal temperatures and pressures.

Conditions to avoid: Temperatures over 40°C, ignition sources, and incompatible substances.

Incompatibilities: Strong acids, bases, and oxidizing agents

Polymerization: Will not occur.

Decomposition: Formaldehyde (only at temperatures over 160°C), dimethylcyclosiloxanes,

methylphenylcyclosiloxanes, carbon monoxide, and carbon dioxide, halogens, halogen acids,

possibly carbonyl halides.

Section 11: Toxicological Information

Sensitization: (effects of repeated exposure) Prolonged or repeated skin contact may cause dermatitis.

Carcinogenicity: (risk of cancer) No

Teratogenicity: (risk of malformation in an unborn No

etus)

Reproductive Toxicity: (risk of sterility)

The CCOHS list Xylene as a reproductive hazard.

Mutangenicity: (risk of heritable genetic effects) No

Lethal Exposure Concentrations:	Ingestion (LD50):	Inhalation (LC50):	Skin (LD50):	Inhalation (TCLo):
Acetone	3gm/kg Mouse	50,100 mg/m3/8H	>9400 uL/Kg Guinea Pig	30,000 mg/m3/2H Mouse
Xylene	2119 mg/kg Rat	5000 ppm/4H Rat	>1700 mg/kg Rabbit	1600 ppm/20H/7D (Intermittent) Rat
Polymethylphenylsiloxanes	N/A	N/A	N/A	N/A
Acrylic resins	2500 mg/kg Rat	N/A	N/A	N/A
1-methoxy-2- propanol acetate	8532 mg/kg Rat	N/A	>5 gm/kg Rabbit	N/A

PAGE 2 / 4 MSDS Code: 422A-P



Section 12: Ecological Information

General Avoid runoff into storms and sewers, which lead into waterways. Water runoff can cause

Information: environmental damage.

Volatile Organic compounds, % by weight: 28.5%
Volatile Organic compounds, grams per litre: 273.6 g/L

Section 13: Disposal Information

General Information: Dispose of in accordance with all local, provincial, state, and federal regulations. Water

runoff can cause environmental damage.

Section 14: Transportation Information

Ground Canada:

Classified as **Consumer Commodity**. Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations).

Ground USA:

Classified as ORM-D. Refer to USA CFR 49 Regulations.

Air: (all sizes).

Shipper must be trained and certified. Refer to IATA Dangerous Goods Regulations.

Shipping Name: **PAINT RELATED MATERIAL**, UN number: **1263**, Class: **3**, Packing Group: **II**, Flash Point: -18°C. Subsidiary Risk – nil, Recommend using original MG Chemicals certified outer cartons. Tape all seams on the carton. Hazard Label required – Flammable Liquid. A double arrow orientation label is required and is already printed on the original outer carton.

Sea - All Sizes:

Shipper must be trained and certified. Refer to IMDG regulations.

Shipping Name: **PAINT RELATED MATERIAL**, UN number: **1263**, Class: **3**, Packing Group: **II**, Flash Point: -18°C. Storage category "A", segregation as for class 9 but away from sources of heat and separated from goods of class 1 except for those in division 1.4.

Section 15: Regulatory Information

CANADA

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

DSL

All ingredients in this product are listed on the Domestic Substances List

WHMIS

This product belongs to the following categories: B2, D2A

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.

<u>USA</u>

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product contains xylene and ethyl benzene, two chemicals listed as hazardous air pollutants.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

This product contains a toxic chemical, which has a reportable quantity. (Xylene CAS# 1330-20-7, 15%)

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does contain Xylene CAS# 1330-20-7 15%, a toxic chemical subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.


PAGE 3 / 4 MSDS Code: 422A-P



California Proposition 65 (Chemicals know to cause cancer or reproductive toxicity, May 1, 1997 revision, USA) This product does not contain any chemicals listed.

HMIS RATING

HEALTH:	1
FLAMMABILITY:	4
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	



EUROPE

RoHS

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

Definitions: N/A = not applicable, N/E = not established

Disclaimer: This material safety data sheet is provided as an information resource only. M.G. Chemicals believes

the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to verify its validity. The buyer assumes all responsibility of using and handling the product in accordance with forest participations.

in accordance with federal, state, and local regulations.