Valvoline	
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

NP75128

Trade name : NAPA® PREM PERF UFMO SAE 15W40

MOTOR OIL

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet

Valvoline LLC

3499 Blazer Parkway Lexington, KY 40509

United States of America (USA)

1-800-TEAMVAL

Emergency telephone number

Page: 1

1-800-VALVOLINE

Regulatory Information Number

1-800-TEAMVAL

Product Information

1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : Suspected of damaging fertility or the unborn child.

Precautionary Statements : Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Wear protective gloves/ protective clothing/ eye protection/ face

protection. Response:

IF exposed or concerned: Get medical advice/ attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

	Val	vol	ine
SAFETY DAT	A SHEET		YM

 SAFETY DATA SHEET
 Revision Date: 09/27/2016

 Print Date: 9/27/2016

 SDS Number: 000000205480

303

NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL

Version: 1.3

NP75128

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

nazaradad dempendine			
Chemical name	CAS-No.	Classification	Concentration (%)
MIXTURE OF SEVERELY		Not a hazardous	82.10
HYDROTREATED AND		substance or mixture.	
HYDROCRACKED BASE OIL			
(PETROLEUM)			
Phosphorodithioic acid, mixed	113706-15-3	Skin Irrit. 2; H315	1.08
O,O-bis(sec-Bu and isooctyl)			
esters, zinc salts		Eye Dam. 1; H318	
Dodecylphenol, mixed isomers	74499-35-7	Skin Irrit. 2; H315	0.1449
(branched)		Evo Irrit 2A, H210	
		Eye Irrit. 2A; H319	
		Repr. 2; H361	
		1.001. 2, 1.001	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

Page: 3

atemach ar intentional

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Suspected of damaging fertility or the unborn child.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing media

: High volume water jet

Specific hazards during firefighting

: Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion

: carbon dioxide and carbon monoxide

Hydrocarbons

Nitrogen oxides (NOx)

Sulphur oxides hydrogen sulfide mercaptans zinc oxide

Specific extinguishing

methods

products

•

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

: Use personal protective equipment.

Ensure adequate ventilation.

emergency procedures Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

Page: 4

respective authorities.

Methods and materials for containment and cleaning up

NP75128

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters /	Basis
		exposure)	Permissible concentration	
HYDROTREATED LIGHT PARAFFINIC DISTILLATE		TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL

ST	10 mg/m3 Mist	NIOSH REL
PEL	5 mg/m3 particulate	CAL PEL
	31	Mist PEL 5 mg/m3

Hazardous components without workplace control parameters

Components	CAS-No.

Engineering measures : Provide suffici

: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate

cartridge and/or filter may be permissible under certain

circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, airsupplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not

provide adequate protection.

In the case of vapour formation use a respirator with an

approved filter.

Hand protection

NP75128

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Revision Date: 09/27/2016 Print Date: 9/27/2016

SDS Number: 000000205480

Version: 1.3

NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL NP75128

> Odour : No data available

Odour Threshold : No data available

pΗ No data available

: No data available Melting point/freezing point

Boiling point/boiling range : No data available

> 199 °C Flash point

Method: Cleveland open cup

Evaporation rate No data available

: No data available Flammability (solid, gas)

Upper explosion limit 6 %(V)

GLP: Calculated Explosive Limit

Lower explosion limit : 1 %(V)

GLP: Calculated Explosive Limit

: 0.055 hPa (20 °C) Vapour pressure

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density No data available

Solubility(ies)

Water solubility No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic $: > 20.5 \text{ mm2/s} (40 ^{\circ}\text{C})$

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Valvoline	Ü
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016

NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL

Page: 7

SDS Number: 000000205480 Version: 1.3

NP75128

: No decomposition if stored and applied as directed. Reactivity

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Acids

Oxidizing agents

water

Hazardous decomposition

products

carbon dioxide and carbon monoxide

hydrogen sulfide Nitrogen oxides (NOx)

Sulphur oxides zinc oxide mercaptans

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL

(PETROLEUM):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): 2,900 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Valvoline.	Page: 8
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3

Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Remarks: Information given is based on data obtained from similar substances.

Skin corrosion/irritation

Not classified based on available information.

Product:

NP75128

Result: Repeated exposure may cause skin dryness or cracking.

Components:

MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL (PETROLEUM):

Result: Slight, transient irritation

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

Dodecylphenol, mixed isomers (branched):

Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL (PETROLEUM):

Result: Slight, transient irritation

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Result: Corrosive

Remarks: Information given is based on data obtained from similar substances.

Dodecylphenol, mixed isomers (branched):

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Test Type: Buehler Test Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3

: Remarks: In vitro tests showed mutagenic effects which were Genotoxicity in vitro

not observed with in vivo test.

Genotoxicity in vivo : Test Type: chromosome aberration assay

Test species: Mouse

Cell type: peripheral blood cells

Result: negative

Carcinogenicity

NP75128

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

: Species: Rat Effects on fertility

> Application Route: Oral Dose: 100 mg/kg bw/day

Symptoms: No effects on reproduction parameters

Effects on foetal : Species: Rat

Application Route: Oral development

Developmental Toxicity: No observed adverse effect level F1:

100 mg/kg body weight

Dodecylphenol, mixed isomers (branched):

Reproductive toxicity -: Some evidence of adverse effects on sexual function and Assessment

fertility, and/or on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Valvoline	
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

NP75128

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

: Chronic aquatic toxicity Category 3; Harmful to aquatic life Chronic aquatic toxicity

with long lasting effects.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

Page: 10

similar substances.

Dodecylphenol, mixed isomers (branched):

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.

Remarks: Information given is based on data obtained from

similar substances.

No data available

Bioaccumulative potential

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Bioaccumulation : Bioconcentration factor (BCF): 3

Remarks: Information given is based on data obtained from

similar substances.

No data available Mobility in soil No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

		VO	linc				Page: 11
777	VOI	VU	line	TM			
SAFETY DA	ATA SHEET					Revision	Date: 09/27/2016
							t Date: 9/27/2016
						SDS Numbe	er: 000000205480
NAPA® PREM F	PERF UFMO SAE 15	W40 MOTO	R OIL				Version: 1.3
NP75128							
SECTION 14. T	ted packaging RANSPORT INFORI	chemical Send to a Dispose of federal ref Empty ref Dispose of Empty contained in the con	ontaminate pon or used contain a licensed wast of in accordance egulations. maining conter of as unused proportainers should site for recycline-use empty con	ner. The managements. The take taken or dispersion of the taken or dispersion of the taken of taken	gement co Il applicat en to an a posal.	ompany. ole local, state	
ID NUMBER	PROPER SHIPPIN	G NAME	*HAZARD CLASS	SUBS HAZA	IDIARY RDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
U.S. DOT - RO	AD		1	1			
CIGIZOT RO	Not dangerous goo	ds					
	0 0						
CFR_RAIL_C							
<u> </u>	Not dangerous goo	ds					
	3 5						
U.S. DOT - INI AI	ND WATERWAYS						
	Not dangerous goo	ds					
	<u> </u>						
TDG ROAD C							

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Val	voline			Page: 12
SAFETY DATA SHEET			Revision Date: 09	9/27/2016
			Print Date: 9	
NADA		SI	DS Number: 00000	
NAPA® PREM PERF UFMO SAE 1	5W40 MOTOR OIL		Ver	sion: 1.3
NP75128				
Not dangerous go	oods			
rtot dangerede ge				
NTERNATIONAL AIR TRANSPORT Not dangerous go		ER .		
IX_DG Not dangerous go	oods			
rtot dangerede ge				
ORM = ORM-D, CBL = COMBUSTI	BLE LIQUID			
Marine pollutant	no			
Dangerous goods descriptions (if in exceptions that can be applied. Coshipment.				
CERCLA Reportable Quantit This material does not contain SARA 304 Extremely Hazard	ng and Community Right-to-K	_A RQ. Quantity		
SARA 311/312 Hazards	: Chronic Health Hazard			
SARA 313	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3	1.08 %	
Pennsylvania Right To Knov MIXTURE OF HYDROTREA BASE OIL (P	SEVERELY ATED AND HYDROCRACKED	Not Assigned		
Proprietary of	Infineum D3501L	Not Assigned		
	S (PETROLEUM), ATED HEAVY PARAFFINIC	64742-54-7		

Not Assigned

Not Assigned

New Jersey Right To Know

MIXTURE OF SEVERELY

BASE OIL (PETROLEUM)

Proprietary of Infineum D3501L

HYDROTREATED AND HYDROCRACKED

Valvoline			
SAFETY DATA SHEET			

Revision Date: 09/27/2016 Print Date: 9/27/2016

SDS Number: 000000205480

NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL

Version: 1.3

NP75128

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7

Phosphorodithioic acid, mixed O,O-bis(sec-

113706-15-3

Bu and isooctyl) esters, zinc salts

Distillates (petroleum), solvent-dewaxed

64742-65-0

heavy paraffinic

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer. **BENZENE** 71-43-2

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm.

TOLUENE 108-88-3

BENZENE 71-43-2

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

: On the inventory, or in compliance with the inventory **ENCS**

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : Not in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)


SECTION 16. OTHER INFORMATION

Further information

Revision Date: 09/27/2016

NFPA: HMIS III:





NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

NP75128

Full text of H-Statements

H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

Valvoline	
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3

Page: 15

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

NP75128

OECD: Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit
P-Statement: Precautionary Statement
PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System