SAFETY DATA SHEET



1. Identification

Product identifier 42H PLASTERS

Product list DENSCAL® Ram Process K-40 BR-840, BR-842, NV-840

DENSCAL® TL-30 BR-830

DENSCAL® TL BR-711, NV-711, NV-871

DENSITE® K-12 BR-812

DENSITE® High Plasticity K-13 BR-813, NV-813

DENSITE® LE K-33 BR-833

DENSITE® LE K-25 BR-825, NV-825

Plate Glass Stucco BR-222

Other means of identification

SDS number GP-42H

Recommended use Industrial plasters

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company name Georgia-Pacific Gypsum LLC
Address 133 Peachtree Street, NE

Atlanta, GA 30303

Telephone Technical Information 800.225.6119

(M)SDS Request 404.652.5119

E-mail MSDSREQ@GAPAC.COM

Emergency phone number Chemtrec - Emergency 800.424.9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Serious eye damage Category 1
Sensitization, skin Category 1
Carcinogenicity Category 1A
Specific target organ toxicity, repeated Category 1 (lung)

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statementHarmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. May cause cancer. Causes damage to organs (lung) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. After mixing with water, do not allow prolonged contact with skin until the product has completely hardened and cooled.

Material name: 42H PLASTERS SDS US

If swallowed: Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water Response

> for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If exposed or concerned: Get medical advice/attention. Specific treatment (see section 4 on the SDS).

Storage Keep container tightly closed. Store away from incompatible materials (see Section 10 of the

SDS). Protect from moisture.

Disposal Dispose of contents/container in accordance with applicable regulations.

Hazard(s) not otherwise classified (HNOC)

Heat develops as product hardens. May cause serious burns during hardening (rehydration)

resulting in possible permanent injury.

Supplemental information

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
CALCIUM SULFATE HEMIHYDRATE		10034-76-1	< 130
PORTLAND CEMENT		65997-15-1	3.0 - < 8
GYPSUM (CALCIUM SULFATE)		7778-18-9	0.1 - < 2
IRON OXIDE		1309-37-1	< 2
CRYSTALLINE SILICA (QUARTZ)		14808-60-7	0.1 - 1.0
Other components below reportable	e levels		< 89

The specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments Gypsum (calcium sulfate) and Portland Cement contain naturally occurring crystalline silica

(quartz) which is listed as a lung carcinogen. See Section 8 for exposure information.

4. First-aid measures

Move to fresh air. Call a physician if symptoms develop or persist. Inhalation

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove Eve contact

> contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important

symptoms/effects, acute and

delayed

Ingestion

Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with

skin. Handling can cause dry skin. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special

treatment needed **General information** Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding

environment.

Unsuitable extinguishing

media

None known.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Material name: 42H PLASTERS SDS US Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Sweep up or gather material and place in appropriate container for disposal. Minimize dust generation and accumulation. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Contain the spill, then place in a suitable container. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. If large quantities enter a waterway, advise local authorities.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in a dry place. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep away from food, drink and animal feedingstuffs.

8. Exposure controls/personal protection

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Occupational exposure limits

7778-18-9)

Components	Туре	Value	Form
CALCIUM SULFATE HEMIHYDRATE (CAS 10034-76-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)	PEL	0.05 mg/m3	
GYPSUM (CALCIUM SULFATE) (CAS 7778-18-9)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
IRON OXIDE (CAS 1309-37-1)	PEL	10 mg/m3	Fume.
PORTLAND CEMENT (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
US ACGIH Threshold Limit Values:	Time Weighted Average (ΓWA): mα/m3. non-standard unit	8
Components	Туре	Value	Form
CALCIUM SULFATE HEMIHYDRATE (CAS 10034-76-1)	TWA	10 mg/m3	Inhalable fraction.
CRYSTALLÍNE SILICA (QUARTZ) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
GYPSUM (CALCIUM SULFATE) (CAS	TWA	10 mg/m3	Inhalable fraction.

Material name: 42H PLASTERS

Components	Туре	Value	Form
IRON OXIDE (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction
PORTLAND CEMENT (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
GYPSUM (CALCIUM SULFATE) (CAS 7778-18-9)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
IRON OXIDE (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.
PORTLAND CEMENT (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.
•		10 mg/m3	Total

Biological limit values No biological exposure limits noted for the ingredient(s).

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica **Exposure guidelines**

should be monitored and controlled.

Appropriate engineering

controls

When using product, provide local and general exhaust ventilation to keep airborne dust

concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of

dust.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Ensure compliance with OSHA's PPE standard Eye/face protection

(29 CFR 1910.132 and .133) for eye and face protection. Safety shower/eye wash fountain must

be readily available in the workplace area (29 CFR 1910.151(c)).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Other

Ensure compliance with OSHA's PPE standards (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR

1910.151 (c)).

Respiratory protection A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or

when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection

(Z88.2).

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene

Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, considerations

drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

9. Physical and chemical properties

Appearance

Solid. **Physical state Form** Powder.

Color Light grey to white

Odor Low odor **Odor threshold** Not available.

8 - 11 pН

Melting point/freezing point 2642 °F (1450 °C) estimated

Initial boiling point and boiling Not applicable

range

Material name: 42H PLASTERS SDS US Flash point Not applicable Not available **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable

Flammability limit - upper

(%)

Not applicable

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Not applicable

Vapor pressure Vapor density Not applicable Relative density 2.3 - 2.7 g/cm3

Solubility(ies)

0.2 - 0.7 % @ 22°C Solubility (water)

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not applicable **Decomposition temperature** Not available. Not available. **Viscosity**

Other information

Explosive properties Not explosive. Flash point class Not flammable Not oxidizing. **Oxidizing properties** Specific gravity 2.3 - 2.7

10. Stability and reactivity

Reactivity Reacts with water (normal condition of use). Material is stable under normal conditions. **Chemical stability** Not expected under normal conditions of use. Possibility of hazardous

reactions

Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air). Exposure to moisture.

Acids. Incompatible materials

Hazardous decomposition

Conditions to avoid

products

May include, and are not limited to: calcium oxide and sulfur dioxide.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may

irritate respiratory system.

Skin contact Dust or powder may irritate the skin. May cause an allergic skin reaction. Skin contact during

hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow

continuous, prolonged contact with skin. Handling can cause dry skin.

Eve contact Causes serious eve damage.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Product Species Test Results

42H PLASTERS

Acute

Oral

LD50 Rat 1193 mg/kg estimated

Components Species Test Results

CALCIUM SULFATE HEMIHYDRATE (CAS 10034-76-1)

Acute Oral

LD50 Rat > 1581 mg/kg

GYPSUM (CALCIUM SULFATE) (CAS 7778-18-9)

Acute

Oral

LD50 Rat > 1581 mg/kg

IRON OXIDE (CAS 1309-37-1)

Acute Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Skin contact during hardening (rehydration)

may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged

contact with skin. Handling can cause dry skin.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Exposure to respirable crystalline silica in the form of quartz or cristobalite from occupational

sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) 1 Carcinogenic to humans.

IRON OXIDE (CAS 1309-37-1)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs (lung) through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

Material name: 42H PLASTERS SDS US

^{*} Estimates for product may be based on additional component data not shown.

12. Ecological information

12. Ecological illiorillatio

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

CALCIUM SULFATE HEMIHYDRATE (CAS 10034-76-1)

Aquatic

Ecotoxicity

Fish LC50 Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)

Aquatic Acute

Fish LC50 Zebra danio (Danio rerio) > 10000 mg/l, 96 Hours OECD SIDS

GYPSUM (CALCIUM SULFATE) (CAS 7778-18-9)

Aquatic

Fish LC50 Fish 2980 mg/l, 96 Hours

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of this product.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsUnder RCRA, it is the responsibility of the user of the product to determine, at the time of disposal,

whether the product meets RCRA criteria for hazardous waste.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Material name: 42H PLASTERS
4186 Version #: 02 Revision date: February-19-2017 Issue date: March-04-2015

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)

US. California Proposition 65

WARNING: This product can expose you to chemicals including Crystalline Silica (Quartz), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

CRYSTALLINE SILICA (QUARTZ) (CAS Listed: October 1, 1988

14808-60-7)

International Inventories

Country(s) or region Inventory name On inventory (yes/no)*

Canada Domestic Substances List (DSL) Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue dateMarch-04-2015Revision dateFebruary-19-2017

Version # 02

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 1

NFPA ratings Health: 3

Flammability: 0 Instability: 0

Disclaimer This SDS is intended to quickly provide useful information to the user(s) of this material or product.

It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other

safety and health information about this product is inaccurate or incomplete.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: 42H PLASTERS SDS US