

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019


Revision: March 28, 2019

## 1 Identification

- **Product identifier**
- **Trade name:** Rislone® Diesel Treat Left Side
- **Product code:** 4740
- **Recommended use and restriction on use**
- **Recommended use:** Additive
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Rislone  
P.O. Box 187  
Holly, MI 48442 USA  
Phone: (810) 603-1321
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)



## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Flam. Liq. 3 H226 Flammable liquid and vapor.  
Skin Irrit. 2 H315 Causes skin irritation.  
Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.  
STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.  
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**  


GHS02 GHS07 GHS08
- **Signal word:** Danger
- **Hazard statements:**  
H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H351 Suspected of causing cancer. Route of exposure: Inhalation.  
H372 Causes damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.  
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Cont'd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

**Trade name: Rislone® Diesel Treat Left Side**

(Cont'd. of page 1)














P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist/vapors/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P331	Do NOT induce vomiting.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

8052-41-3	Stoddard solvent  Flam. Liq. 3, H226  STOT RE 1, H372; Asp. Tox. 1, H304	60-80%
64742-94-5	Solvent naphtha (petroleum), heavy arom.  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336 Flam. Liq. 4, H227	<10%
111-84-2	nonane  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H335	<10%
25551-13-7	trimethylbenzene  Flam. Liq. 3, H226  Skin Irrit. 2, H315; Eye Irrit. 2A, H319	<5%
64742-95-6	Solvent naphtha (petroleum), light arom.  Flam. Liq. 3, H226  Asp. Tox. 1, H304	<3%
95-63-6	1,2,4-trimethylbenzene  Flam. Liq. 3, H226  Asp. Tox. 1, H304	<3%

(Cont'd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

**Trade name: Rislone® Diesel Treat Left Side**

(Cont'd. of page 2)

	⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
27247-96-7	2-Ethylhexyl Nitrate ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 Flam. Liq. 4, H227	<3%
91-20-3	Naphthalene ⚠ Flam. Sol. 2, H228 ☠ Carc. 2, H351 ⚠ Acute Tox. 4, H302	<1%
108-67-8	mesitylene ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H335	<1%
103-65-1	propylbenzene ⚠ Flam. Liq. 3, H226 ☠ Carc. 2, H351; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H302; STOT SE 3, H335	<1%
64742-81-0	Kerosine (petroleum), hydrodesulfurized ⚠ Flam. Liq. 3, H226 ☠ Asp. Tox. 1, H304	<1%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.  
For the wording of the listed Hazard Statements, refer to section 16.

## 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.  
Provide oxygen treatment if affected person has difficulty breathing.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.

· **After eye contact:**

Remove contact lenses if worn.  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; immediately call for medical help.  
A person vomiting while lying on their back should be turned onto their side.

· **Most important symptoms and effects, both acute and delayed:**

Coughing  
Dizziness  
Breathing difficulty  
Nausea  
Cramp  
Causes skin irritation.

· **Danger:**

May be fatal if swallowed and enters airways.  
Danger of impaired breathing.

(Cont'd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

**Trade name: Rislone® Diesel Treat Left Side**

(Cont'd. of page 3)

Suspected of causing cancer. Route of exposure: Inhalation.

Causes damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

· **Indication of any immediate medical attention and special treatment needed:**

If swallowed, gastric irrigation with added, activated carbon.

If swallowed or in case of vomiting, danger of entering the lungs.

Medical supervision for at least 48 hours.

Later observation for pneumonia and pulmonary edema.

## 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Foam

Fire-extinguishing powder

Gaseous extinguishing agents

Water fog / haze

· **For safety reasons unsuitable extinguishing agents:**

Water stream.

Water spray

· **Special hazards arising from the substance or mixture**

Flammable liquid and vapor.

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information:** Cool endangered containers with water fog.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

· **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up**

Towel or mop up material and collect in a suitable container.

For larger spills, add non-combustible inert binding material, then sweep up and discard.

Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Cont'd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

**Trade name: Rislone® Diesel Treat Left Side**

(Cont'd. of page 4)

## 7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
  - Keep out of reach of children.
  - Open and handle receptacle with care.
  - Avoid contact with the eyes and skin.
  - Avoid breathing mist, vapors, or spray.
- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**
  - Store in cool, dry conditions in well sealed receptacles.
  - Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
  - Store away from foodstuffs.
  - Store away from oxidizing agents.
- **Specific end use(s)** No relevant information available.

## 8 Exposure controls/personal protection

### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

##### 8052-41-3 Stoddard solvent

PEL (USA)	Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min
TLV (USA)	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm
EL (Canada)	Short-term value: 580 mg/m <sup>3</sup> Long-term value: 290 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 525 mg/m <sup>3</sup>
LMPE (Mexico)	Long-term value: 100 ppm

##### 111-84-2 nonane

REL (USA)	Long-term value: 1050 mg/m <sup>3</sup> , 200 ppm
TLV (USA)	Long-term value: 1050 mg/m <sup>3</sup> , 200 ppm
EL (Canada)	Long-term value: 200 ppm
EV (Canada)	Long-term value: 1,050 mg/m <sup>3</sup> , 200 ppm
LMPE (Mexico)	Long-term value: 200 ppm

##### 95-63-6 1,2,4-trimethylbenzene

REL (USA)	Long-term value: 125 mg/m <sup>3</sup> , 25 ppm
TLV (USA)	Long-term value: 123 mg/m <sup>3</sup> , 25 ppm

##### 91-20-3 Naphthalene

PEL (USA)	Long-term value: 50 mg/m <sup>3</sup> , 10 ppm
REL (USA)	Short-term value: 75 mg/m <sup>3</sup> , 15 ppm

(Cont'd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

**Trade name: Rislone® Diesel Treat Left Side**

(Cont'd. of page 5)

TLV (USA)	Long-term value: 50 mg/m <sup>3</sup> , 10 ppm Long-term value: 52 mg/m <sup>3</sup> , 10 ppm Skin; BEI
EL (Canada)	Long-term value: 10 ppm Skin; IARC 2B
EV (Canada)	Short-term value: 78 mg/m <sup>3</sup> , 15 ppm Long-term value: 52 mg/m <sup>3</sup> , 10 ppm
LMPE (Mexico)	Short-term value: 15 ppm Long-term value: 10 ppm A4, PIEL
<b>108-67-8 mesitylene</b>	
REL (USA)	Long-term value: 125 mg/m <sup>3</sup> , 25 ppm
TLV (USA)	Long-term value: 123 mg/m <sup>3</sup> , 25 ppm
<b>64742-81-0 Kerosine (petroleum), hydrodesulfurized</b>	
REL (USA)	Long-term value: 100 mg/m <sup>3</sup> Kerosene only
TLV (USA)	Long-term value: 200 mg/m <sup>3</sup> as total hydrocarbon vapor; Skin; P
EV (Canada)	Long-term value: 200(G) mg/m <sup>3</sup> as total hydrocarbon vapour, Skin
LMPE (Mexico)	Long-term value: 200 mg/m <sup>3</sup> A3, PIEL

· **Exposure controls**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Wash hands before breaks and at the end of work.
- Avoid breathing mist, vapors, or spray.
- Avoid contact with the eyes and skin.

· **Engineering controls:** No relevant information available.

· **Breathing equipment:**

- Use suitable respiratory protective device in case of insufficient ventilation.
- For spills, respiratory protection may be advisable.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

No relevant information available.

· **Risk management measures** No relevant information available.

(Cont'd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

Trade name: Rislone® Diesel Treat Left Side

(Cont'd. of page 6)

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · Appearance:

Form:	Liquid
Color:	Green
Odor:	Petroleum-like
Odor threshold:	Not determined.

pH-value:	Not determined.
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	>150 °C (>302 °F)

Flash point:	>38 °C (>100.4 °F)
--------------	--------------------

Flammability (solid, gaseous):	Not applicable.
--------------------------------	-----------------

Auto-ignition temperature:	Not determined.
----------------------------	-----------------

Decomposition temperature:	Not determined.
----------------------------	-----------------

Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
----------------------	--

#### · Explosion limits

Lower:	Not determined.
Upper:	Not determined.

Oxidizing properties:	Non-oxidizing.
-----------------------	----------------

Vapor pressure:	Not determined.
-----------------	-----------------

#### · Density:

Relative density:	0.8-0.9
Vapor density:	Not determined.
Evaporation rate:	Not determined.

#### · Solubility in / Miscibility with

Water:	Not miscible or difficult to mix.
--------	-----------------------------------

Partition coefficient (n-octanol/water):	Not determined.
--	-----------------

#### · Viscosity

Dynamic:	Not determined.
Kinematic:	Not determined.

Other information	No relevant information available.
-------------------	------------------------------------

## 10 Stability and reactivity

· **Reactivity:** No relevant information available.

· **Chemical stability:**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.

· **Possibility of hazardous reactions**

Flammable liquid and vapor.

(Cont'd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

**Trade name: Rislone® Diesel Treat Left Side**

(Cont'd. of page 7)

Reacts with oxidizing agents.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Used empty containers may contain product gases which form explosive mixtures with air.

- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**

Under fire conditions only:

Carbon monoxide and carbon dioxide

Nitrogen oxides

## 11 Toxicological information

### · Information on toxicological effects

- **Acute toxicity:** Based on available data, the classification criteria are not met.

### · LD/LC50 values that are relevant for classification:

#### 64742-94-5 Solvent naphtha (petroleum), heavy arom.

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>3400 mg/kg (rab)
--------	------	-------------------

#### 95-63-6 1,2,4-trimethylbenzene

Oral	LD50	5000 mg/kg (rat)
------	------	------------------

#### 91-20-3 Naphthalene

Oral	LD50	490 mg/kg (rat)
------	------	-----------------

Dermal	LD50	5000 mg/kg (rat)
--------	------	------------------

### · Primary irritant effect:

- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** No sensitizing effects known.

### · IARC (International Agency for Research on Cancer):

91-20-3	Naphthalene	2B
---------	-------------	----

98-82-8	Cumene	2B
---------	--------	----

### · NTP (National Toxicology Program):

91-20-3	Naphthalene	R
---------	-------------	---

98-82-8	Cumene	R
---------	--------	---

### · OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

### · Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

- **Carcinogenicity:** Suspected of causing cancer. Route of exposure: Inhalation.

(Cont'd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

**Trade name: Rislone® Diesel Treat Left Side**

(Cont'd. of page 8)

- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:**  
Causes damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity**  
Toxic to aquatic life with long lasting effects.

### 64742-94-5 Solvent naphtha (petroleum), heavy arom.

LC50	3.6 mg/l (Oncorhynchus mykiss)
------	--------------------------------

### 27247-96-7 2-Ethylhexyl Nitrate

LC50	2 mg/l (zebra fish) (96hr)
------	----------------------------

### 91-20-3 Naphthalene

LC50	1-10 mg/l (daphnia)
------	---------------------

- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**  
Avoid transfer into the environment.  
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Contact waste processors for recycling information.  
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

(Cont'd. on page 10)



**Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

**Trade name: Rislone® Diesel Treat Left Side**

(Cont'd. of page 10)

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Remarks:**

Transport labeling is not required for non-bulk single package shipments by motor vehicle, rail car or aircraft. Bulk packaging consists of a maximum capacity of greater than 450L (119 gallons) for a liquid and a maximum net mass greater than 400kg (882 pounds) for a solid.

· **ADR/RID/ADN**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1)

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)

· **IATA**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **United States (USA)**

· **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

(Cont'd. on page 12)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

**Trade name: Rislone® Diesel Treat Left Side**

(Cont'd. of page 11)

· **Section 313 (Specific toxic chemical listings):**

95-63-6	1,2,4-trimethylbenzene
---------	------------------------

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

91-20-3	Naphthalene
---------	-------------

98-82-8	Cumene
---------	--------

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

95-63-6	1,2,4-trimethylbenzene	II
---------	------------------------	----

91-20-3	Naphthalene	C, CBD
---------	-------------	--------

108-67-8	mesitylene	II
----------	------------	----

· **IARC (International Agency for Research on Cancer):**

91-20-3	Naphthalene	2B
---------	-------------	----

98-82-8	Cumene	2B
---------	--------	----

· **Canadian Domestic Substances List (DSL) (Substances not listed.):**

All ingredients are listed.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health Administration

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Flam. Sol. 2: Flammable solids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Cont'd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: March 28, 2019

Revision: March 28, 2019

**Trade name: Rislone® Diesel Treat Left Side**

(Cont'd. of page 12)

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))

Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sor\\_internet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sor_internet/registry/substreg/home/overview/home.do))

Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)