MATERIAL SAFETY DATA SHEET 29 CFR 1910.1200 OSHA Hazard Communication Rule Format Chem-Tel 24 Hour Emergency # 1-800-255-3924 MINE SAFETY APPLIANCES COMPANY P.O. Box 426 Pittsburgh, PA 15230 PHONE (412) 967-3000

This product contains methane, oxygen and nitrogen, substances subject to the Pennsylvania Worker and Community Right-To-Know Act.

PRODUCT IDENTITY

LABEL IDENTITY - MSA P/N 482698 Calibration Gas, 0.5% Methane in Air, 10% LEL

CHEMICAL NAME - Methane, Oxygen, Nitrogen Mixture

ADDITIONAL IDENTITIES - MSA P/N 482698 Calibration Gas

FORMULA - CH₄ in Air

APPLICABLE CHEMICAL CONTENTS

NOTE: Gas Under Pressure, 120 PSIG at 70°F, Approx. 4 Liters Gas at Atmospheric Pressure

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR - Colorless, Odorless Gas

BOILING POINT - N/A SPECIFIC GRAVITY $(H_2O = 1)$ - N/A VAPOR PRESSURE - N/A PERCENT VOLATILE BY VOLUME - N/A

VAPOR DENSITY (AIR = 1) - < 1

SOLUBILITY IN WATER - Methane - 9 cm³/100 ml (20°C)

Oxygen - 3.2 cm³/100 ml (25°C) Nitrogen - 2.3 cm³/100 ml (0°C)

N/A - Not Applicable

PHYSICAL HAZARD INFORMATION

PHYSICAL HAZARD - Compressed Gas, 120 PSIG at 70°F

CONDITIONS OR MATERIALS TO AVOID - None

FLASH POINT - N/A LEL - N/A UEL - N/A

EXTINGUISHING MEDIA - This Calibration Gas Mixture Is Not Flammable

SPECIAL FIRE FIGHTING PROCEDURES - See Next Item

UNUSUAL FIRE AND EXPLOSION HAZARDS - Gas Under Pressure, 120 PSIG at 70°F. Do Not Exceed 120°F.

^{*}Methane is a simple asphyxiant (ACGIH 1995-96)

HEALTH HAZARDS

HEALTH HAZARDS - Methane is a simple asphyxiant, ACGIH 1995-96.

SIGNS AND SYMPTOMS OF EXPOSURE - None known for 0.5% Methane in air.

PRIMARY ROUTES OF ENTRY - Inhalation

TARGET ORGANS - Lungs

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE - No Information

EXPOSURE LIMITS - None. Methane is a simple asphyxiant (ACGIH 1995-96).

CARCINOGENICITY DATA - Component gases are not listed by NIOSH RTECS, OSHA, NTP or IARC.

EMERGENCY AND FIRST AID PROCEDURES - None

SAFE HANDLING AND USE

HYGIENIC PRACTICES - Avoid Breathing Gas

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate Area

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust.

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

CONTROL MEASURES

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 5, June 1999

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.