www.jnj-industries.com / email: sales@jnj-industries.com

JNJ Industries 800-554-9994 / 508-553-0529 Fax: 508-553-9973 290 Beaver Street

MATERIAL SAFETY DATA SHEET

Date of Last Revision: 1/09

Franklin, MA 02038

GlobalTech®

Isopropyl Alcohol w/ DI Water, 70-30%

Product Code:

IPA/DI

FOR CHEMICAL EMERGENCY call INFOTRAC at 1-800-535-5053

24 Hrs. per day, 7 days per week

Section 1 ... Composition/Information on Ingredients

Ingredients CAS# Weight % TWA/TLV Isopropyl Alcohol 67-63-0 70 400ppm TWA DI Water 30 NE

Section 2 ... First Aid Measures

Eve Contact: Flush with large amount of water. Contact physician.

Skin Contact: Flush with large amount of water. Contact physician. Remove contaminated clothing, wash before

reuse.

Inhalation: Move subject to fresh air. Give artificial respiration if breathing has stopped, call physician. Ingestion: If conscious give two glasses of water/milk and induce vomiting. Get medical attention.

Section 3 ... Health Hazards, Routes of Entry and Effects of Overexposure

Work Place Exposure Limits: 500 ppm STEL OSHA & ACG1H

Eye Contact: Slight to moderate irritation, may cause corneal injury.

Skin Contact: Prolonged contact results in skin drying.

Inhalation: May cause mild irritation to nose, throat or above TLV-headache.

May cause vomiting, diarrhea, drowsiness, cramps. Ingestion:

Section 4 ... Special Protection Information

Ventilation: Use local exhaust ventilation to prevent build-up of explosive vapor concentrations and keep below

TLV - also see Section 3.

Respiratory Protection: None required during normal use with adequate ventilation.

Chemically resistant gloves, vinyl not recommended. Safety Glasses. Gloves & Glasses:

Other Protective Equipment: Eye bath, safety shower.

Section 5 ... Reactivity Data

Stability: Stable **Conditions to Avoid:** Keep away from ignition sources: sparks, heat

and flame

Conditions to Avoid: Hazardous Polymerization: Will not occur

Incompatibility (material to avoid): Concentrated Nitric & Sulfuric Acids, Oxidizers, Aldehydes, Halogens, Halogen Compounds

Hazardous Decomposition: Will not occur

Section 6 ... Spill or Leak Procedures and Waste Disposal

Precautions in Case of Release: Eliminate ignition source. Ground handling equipment to prevent sparking. Wear respirator and

protective clothing. Dike and contain spill. Suppress vapors with water fog. Soak up residue with

absorbent clay or sand. Place in non-leaking containers for disposal.

Waste Diposal Method: Incinerate waste in accordance with Federal, State and Local regulations.

Section 7 ... Handling and Storage Precautions

Drum containers should be grounded. Keep containers closed when not in use. Avoid eye and skin contact. Keep away from children.

Keep away from heat and flame. Use with adequate ventilation. Wash with soap and water after use.

Storage Temperature: Ambient Indoor: Ambient Heated: NA Outdoor: Ambient

Refrigerated: NA

Date of Last Revision: 1/09

Section 8 ... Hazard Data

Hazard Class (Hazard Rating Scale: 0=minimal, 1=slight, 2=moderate, 3=high, 4=extreme):

Health: 1 Flammability: 3

Reactivity: 0 Personal Protection:

Hazard Class: Flammable liquid

Explosive Limits (volume %):

Lower: NA Upper: NA

Flash Point: 64° F(18° C,TCC)

Auto Ignition Temp: Will not occur

Extinguishing Media: Foam, C0₂, dry chemical, water spray

Fire and Explosion Hazards: Liquid is invisible and flammable, vapors may travel in low areas to ignition source.

Fire Fighting Procedures: Use water spray to cool containers and prevent flammable vapor from escaping. Water may be in-

effective on direct flame, but can be used to flush spills from ignition or disperse vapor.

Section 9 ... Physical Data

Boiling Point (approx):	179°F (82°C)	Vapor Density (air=1):	2.0
Evaporation Rate (butyl acetate=1):	2.88	% Volatile (by weight):	100
Vapor Pressure (mmHg):	33	% Water Soluble:	Complete
Specific Gravity (water=1):	0.88	Melting Point:	-88.5°C F.P.
Appearance:	water clear liquid	Viscosity:	NA
:Hq	7		

Section 10 ... Regulatory Information

SARA Title III: Acute Health: Yes Sudden release of pressure: No

Chronic Health: No Reportable quantity (RQ): NE Fire: Yes 313 Toxic Chemical: Yes

TSCA: This material or it's components are listed in the TSCA inventory.

Section 11 ... Miscellaneous Information

UN1219, Isopropanol - 3, PGII

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

The information contained herein is based on data believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the material. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk for his use thereof. JNJ accepts no responsibility for any personal injury, property damage, or other type of loss due to negligence or otherwise resulting from the use or handling of this material.