

Safety Data Sheet

Printing date 06/10/2022

Revised On 06/10/2022

1 Identification of the substance and manufacturer

Trade name: ULTRA PROMAX LIGHT GRAY PRIMER
Product code: 80-884
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Kimball Midwest
 4800 Roberts Road
 Columbus, OH 43228
 800-233-1294
 www.kimballmidwest.com
Emergency telephone number: ChemTrec: 800-424-9300

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.
 Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.
 Eye Irritation 2A H319 Causes serious eye irritation.
 Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
 Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.
 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:
GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes serious eye irritation.
 Suspected of causing cancer. Route of exposure: Inhalation.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	15-25%
74-98-6	propane	10-15%
110-19-0	Isobutyl Acetate	10-15%
106-97-8	n-butane	5-10%
13463-67-7	titanium dioxide	5-10%
64742-89-8	VM&P Naphtha	5-10%
14807-96-6	Talc	1-5%
64-17-5	ethyl alcohol	1-5%
64742-47-8	Mineral Spirits	1-5%
123-86-4	butyl acetate	1-5%
108-65-6	PM acetate	1-5%
67-63-0	Isopropyl Alcohol	1-5%
67-56-1	methanol	0.19%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 2)

Trade name: ULTRA PROMAX LIGHT GRAY PRIMER

(Contd. of page 1)

After swallowing: Rinse out mouth and then drink plenty of water.
Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects: Dizziness

Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.

Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling: Use only in well ventilated areas.
Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

74-98-6 propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)

110-19-0 Isobutyl Acetate

PEL (USA)	Long-term value: 700 mg/m ³ , 150 ppm
REL (USA)	Long-term value: 700 mg/m ³ , 150 ppm
TLV (USA)	Short-term value: 150 ppm Long-term value: 50 ppm

106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 1000 ppm (EX)

64-17-5 ethyl alcohol

PEL (USA)	Long-term value: 1900 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV (USA)	Short-term value: 1000 ppm A3

123-86-4 butyl acetate

PEL (USA)	Long-term value: 710 mg/m ³ , 150 ppm
REL (USA)	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV (USA)	Short-term value: 150 ppm Long-term value: 50 ppm

108-65-6 PM acetate

WEEL (USA)	Long-term value: 50 ppm
------------	-------------------------

67-63-0 Isopropyl Alcohol

PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
-----------	--

(Contd. on page 3)

Trade name: ULTRA PROMAX LIGHT GRAY PRIMER

(Contd. of page 2)

REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

67-56-1 methanol

REL (USA)	Long-term value: 260 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV (USA)	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA)	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

67-63-0 Isopropyl Alcohol

BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----------	---

67-56-1 methanol

BEI (USA)	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----------	---

Hygienic protection: Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Nitrile gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.
pH-value: Not determined.
Melting point/Melting range Undetermined.
Boiling point: -44 °C (-47.2 °F)
Flash point: -19 °C (-2.2 °F)
Flammability (solid, gas): Extremely flammable.
Decomposition temperature: Not determined.
Auto igniting: Product is not self-igniting.
Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: 1.7 Vol %
Upper Explosion Limit: 10.9 Vol %
Vapor pressure: Not determined.
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapor density Not determined.
Evaporation rate Not applicable.
Partition coefficient: n-octonal/water: Not determined.
Solubility: Not determined.
Viscosity: Not determined.
Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

(Contd. on page 4)

Trade name: ULTRA PROMAX LIGHT GRAY PRIMER

(Contd. of page 3)

Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****110-19-0 Isobutyl Acetate**

Oral LD50 4,763 mg/kg (rbt)

13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat)

Dermal LD50 >10,000 mg/kg (rbt)

Inhalative LC50/4 h >6.82 mg/l (rat)

64-17-5 ethyl alcohol

Oral LD50 7,060 mg/kg (rat)

Inhalative LC50/4 h 20,000 mg/l (rat)

123-86-4 butyl acetate

Oral LD50 14,000 mg/kg (rat)

Inhalative LC50/4 h >21 mg/l (rat)

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

67-63-0 Isopropyl Alcohol

Oral LD50 4,570 mg/kg (rat)

Dermal LD50 13,400 mg/kg (rab)

Inhalative LC50/4 h 30 mg/l (rat)

67-56-1 methanol

Oral LD50 5,628 mg/kg (rat)

Dermal LD50 15,800 mg/kg (rbt)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950
DOT UN1950
DOT DOT
ADR Aerosols, flammable
Transport hazard class(es): 1950 Aerosols
Class 2.1 Gases
Marine pollutant: No
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
Packaging Group: --
UN "Model Regulation": UN1950, Aerosols, 2.1

(Contd. on page 5)

Trade name: ULTRA PROMAX LIGHT GRAY PRIMER

(Contd. of page 4)

15 Regulatory information

SARA Section 355 (extremely hazardous substances):
None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):
67-63-0 Isopropyl Alcohol

Toxic Substances Control Act (TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List (DSL): All ingredients are listed or exempted.

Consumer Product Safety Commission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7	titanium dioxide
108-10-1	methyl isobutyl ketone
100-41-4	ethyl benzene
1333-86-4	Carbon black

Prop 65 chemicals known to cause birth defects or reproductive harm:

67-56-1	methanol
108-10-1	methyl isobutyl ketone

EPA:

67-64-1	Acetone	I
110-19-0	Isobutyl Acetate	D

16 Other information

Contact: Regulatory Affairs