# SAFETY DATA SHEET

## 1. Identification

**Product identifier** **Belt Conditioner**

**Other means of identification**

**Product code** 05350, 05350AZ

**Recommended use** Belt dressing

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.

**Address** 885 Louis Dr.
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service** 800-272-4620

**24-Hour Emergency (CHEMTREC)** 800-424-9300 (US)
703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

| | | |
|---|---|---|
| **Physical hazards** | Flammable aerosols | Category 1 |
| | Gases under pressure | Liquefied gas |
| **Health hazards** | Skin corrosion/irritation | Category 2 |
| | Reproductive toxicity (fertility) | Category 2 |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects |
| | Specific target organ toxicity, repeated exposure | Category 2 |
| | Aspiration hazard | Category 1 |
| **Environmental hazards** | Hazardous to the aquatic environment, long-term hazard | Category 3 |

**OSHA defined hazards** Not classified.

**Label elements**

**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs (nervous system, upper respiratory tract, skin, eyes) through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe gas. Do not breathe mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

**Response** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical attention.

| | |
|---|---|
| **Storage** | Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. |
| **Disposal** | Dispose of contents/container in accordance with local/regional/national regulations. |
| **Hazard(s) not otherwise classified (HNOC)** | Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. |

**Supplemental information**

84.39% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

## 3. Composition/information on ingredients

**Mixtures**

| Chemical name | Common name and synonyms | CAS number | % |
|---|---|---|---|
| Naphtha (petroleum), hydrotreated light | | 64742-49-0 | 40 - 50 |
| Liquefied Petroleum Gas | | 68476-86-8 | 20 - 30 |
| 2-Methylpentane | | 107-83-5 | 10 - 20 |
| Isobutylene polymer | | 9003-29-6 | 5 - 10 |
| n-Hexane | | 110-54-3 | 1 - 3 |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

| | |
|---|---|
| **Inhalation** | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| **Skin contact** | Wash off with soap and water. Take off contaminated clothing and wash before reuse. |
| **Eye contact** | Rinse with plenty of water. |
| **Ingestion** | Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis. |
| **Most important symptoms/effects, acute and delayed** | Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause drowsiness or dizziness. Prolonged exposure may cause chronic effects. |
| **Indication of immediate medical attention and special treatment needed** | Provide general supportive measures and treat symptomatically. |
| **General information** | IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

## 5. Fire-fighting measures

| | |
|---|---|
| **Suitable extinguishing media** | Water spray. Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. |
| **Unsuitable extinguishing media** | Do not use water jet as an extinguisher, as this will spread the fire. |
| **Specific hazards arising from the chemical** | Contents under pressure. Pressurized container may explode when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. |
| **Special protective equipment and precautions for firefighters** | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| **Fire-fighting equipment/instructions** | In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. In the event of fire, cool tanks with water spray. |
| **General fire hazards** | Extremely flammable aerosol. |

## 6. Accidental release measures

| | |
|---|---|
| **Personal precautions, protective equipment and emergency procedures** | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate personal protective equipment. Do not breathe gas. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop the flow of material, if this is without risk. Collect spillage. Dike far ahead of spill for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist or vapor. Do not breathe gas. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

**Conditions for safe storage, including any incompatibilities**

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

## 8. Exposure controls/personal protection

**Occupational exposure limits**

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components | Type | Value |
|---|---|---|
| n-Hexane (CAS 110-54-3) | PEL | 1800 mg/m3<br>500 ppm |

**US. ACGIH Threshold Limit Values**

| Components | Type | Value |
|---|---|---|
| 2-Methylpentane (CAS 107-83-5) | STEL | 1000 ppm |
| | TWA | 500 ppm |
| n-Hexane (CAS 110-54-3) | TWA | 50 ppm |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components | Type | Value |
|---|---|---|
| 2-Methylpentane (CAS 107-83-5) | Ceiling | 1800 mg/m3<br>510 ppm |
| | TWA | 350 mg/m3<br>100 ppm |
| n-Hexane (CAS 110-54-3) | TWA | 180 mg/m3<br>50 ppm |

**Biological limit values**

**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|---|---|---|---|---|
| n-Hexane (CAS 110-54-3) | 0.4 mg/l | 2,5-Hexanedion, without hydrolysis | Urine | * |

* - For sampling details, please see the source document.

**Exposure guidelines**

**US - California OELs: Skin designation**

| | |
|---|---|
| n-Hexane (CAS 110-54-3) | Can be absorbed through the skin. |

**US ACGIH Threshold Limit Values: Skin designation**

| | |
|---|---|
| n-Hexane (CAS 110-54-3) | Can be absorbed through the skin. |

**Appropriate engineering controls** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton®.

**Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** Wear positive pressure self-contained breathing apparatus (SCBA). Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations** When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance**

**Physical state** Liquid.

**Form** Aerosol.

**Color** Light amber.

**Odor** Mild solvent.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -244.7 °F (-153.7 °C) estimated

**Initial boiling point and boiling range** 118.4 °F (48 °C) estimated

**Flash point** < 0 °F (< -17.8 °C) Tag Closed Cup

**Evaporation rate** Fast.

**Flammability (solid, gas)** Not available.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** 1 % estimated

**Flammability limit - upper (%)** 8 % estimated

**Vapor pressure** 1682.1 hPa estimated

**Vapor density** > 1 (air = 1)

**Relative density** 0.64 estimated

**Solubility (water)** Negligible.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** 489.2 °F (254 °C) estimated

**Decomposition temperature** Not available.

**Viscosity (kinematic)** Not available.

**Percent volatile** 92.8 % estimated

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Heat, flames and sparks. Contact with incompatible materials.

| | |
|---|---|
| **Incompatible materials** | Chlorine. |
| **Hazardous decomposition products** | Carbon oxides. |

## 11. Toxicological information

**Information on likely routes of exposure**

| | |
|---|---|
| **Ingestion** | May be fatal if swallowed and enters airways. |
| **Inhalation** | Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful. May cause damage to organs by inhalation. |
| **Skin contact** | Prolonged skin contact may cause temporary irritation. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. |
| **Eye contact** | Direct contact with eyes may cause temporary irritation. |
| **Symptoms related to the physical, chemical and toxicological characteristics** | Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. |

**Information on toxicological effects**

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

| Product | Species | Test Results |
|---|---|---|
| Belt Conditioner | | |
| **Acute** | | |
| *Dermal* | | |
| LD50 | Rabbit | 3558.8184 mg/kg estimated |
| *Inhalation* | | |
| LC50 | Rat | 11984.4893 ppm, 4 hours estimated |
| | | 315.9885 mg/l, 4 hours estimated |
| *Oral* | | |
| LD50 | Rat | 23333.2285 mg/kg estimated |

* Estimates for product may be based on additional component data not shown.

| | |
|---|---|
| **Skin corrosion/irritation** | Prolonged skin contact may cause temporary irritation. |
| **Serious eye damage/eye irritation** | Direct contact with eyes may cause temporary irritation. |
| **Respiratory sensitization** | Not available. |
| **Skin sensitization** | This product is not expected to cause skin sensitization. |
| **Germ cell mutagenicity** | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| **Carcinogenicity** | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. |
| **Reproductive toxicity** | Suspected of damaging fertility. |
| **Specific target organ toxicity - single exposure** | Narcotic effects. |
| **Specific target organ toxicity - repeated exposure** | May cause damage to organs through prolonged or repeated exposure. |
| **Aspiration hazard** | May be fatal if swallowed and enters airways. |
| **Chronic effects** | Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. |

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

| Product | | Species | Test Results |
|---|---|---|---|
| Belt Conditioner | | | |
| Fish | LC50 | Fish | 1621.4834 mg/l, 96 hours estimated |
| **Components** | | **Species** | **Test Results** |
| Isobutylene polymer (CAS 9003-29-6) | | | |
| *Acute* | | | |
| Crustacea | EC50 | Daphnia magna | > 10000 mg/l, 48 hours |
| | | | > 1000 mg/l, 48 hours |

| Components | | Species | Test Results |
|---|---|---|---|
| **Aquatic** | | | |
| *Acute* | | | |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | > 1000 mg/l, 96 hours |
| | | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | > 10000 mg/l, 96 hours |
| n-Hexane (CAS 110-54-3) | | | |
| **Aquatic** | | | |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 2.101 - 2.981 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

| | |
|---|---|
| 2-Methylpentane | 3.74 |
| n-Hexane | 3.9 |

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal of waste from residues / unused products** This material and its container must be disposed of as hazardous waste. If discarded, this product is considered a RCRA ignitable waste, D001. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

**DOT**

**UN number** UN1950
**UN proper shipping name** Aerosols, flammable, Limited Quantity
**Transport hazard class(es)**
**Class** 2.1
**Subsidiary risk** -
**Label(s)** 2.1
**Packing group** Not applicable.
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.
**Special provisions** N82
**Packaging exceptions** 306
**Packaging non bulk** None
**Packaging bulk** None

**IATA**

**UN number** UN1950
**UN proper shipping name** Aerosols, flammable, Limited Quantity
**Transport hazard class(es)**
**Class** 2.1
**Subsidiary risk** -
**Packing group** Not applicable.
**Environmental hazards** No.
**ERG Code** 10L
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.
**Other information**
**Passenger and cargo aircraft** Allowed.
**Cargo aircraft only** Allowed.

**IMDG**

**UN number** UN1950
**UN proper shipping name** AEROSOLS, LIMITED QUANTITY

**Transport hazard class(es)**

| | |
|---|---|
| **Class** | 2 |
| **Subsidiary risk** | - |
| **Packing group** | Not applicable. |
| **Environmental hazards** | |
| **Marine pollutant** | No. |
| **EmS** | Not available. |
| **Special precautions for user** | Read safety instructions, SDS and emergency procedures before handling. |

## 15. Regulatory information

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**SARA 304 Emergency release notification**

Not regulated.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

n-Hexane (CAS 110-54-3)

**CERCLA Hazardous Substance List (40 CFR 302.4)**

n-Hexane (CAS 110-54-3)

**CERCLA Hazardous Substances: Reportable quantity**

n-Hexane (CAS 110-54-3) 5000 lbs

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

n-Hexane (CAS 110-54-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

| | |
|---|---|
| **Safe Drinking Water Act (SDWA)** | Not regulated. |
| **Food and Drug Administration (FDA)** | Not regulated. |

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

| | |
|---|---|
| **Section 311/312 Hazard categories** | Immediate Hazard - Yes<br>Delayed Hazard - Yes<br>Fire Hazard - Yes<br>Pressure Hazard - Yes<br>Reactivity Hazard - No |
| **SARA 302 Extremely hazardous substance** | No |

**US state regulations**

**US. New Jersey RTK - Substances: Listed substance**

2-Methylpentane (CAS 107-83-5)
n-Hexane (CAS 110-54-3)

**US. Massachusetts RTK - Substance List**

2-Methylpentane (CAS 107-83-5)
n-Hexane (CAS 110-54-3)

**US. Pennsylvania RTK - Hazardous Substances**

2-Methylpentane (CAS 107-83-5)
n-Hexane (CAS 110-54-3)

**US. Rhode Island RTK**

n-Hexane (CAS 110-54-3)

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**Volatile organic compounds (VOC) regulations**

**EPA**

| | |
|---|---|
| **VOC content (40 CFR 51.100(s))** | 100 % |
| **Consumer products (40 CFR 59, Subpt. C)** | Not regulated |

**State**

| | |
|---|---|
| **Consumer products** | Not regulated |
| **VOC content (CA)** | 92.8 % |
| **VOC content (OTC)** | 92.8 % |

**International Inventories**

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|---|---|---|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

| | |
|---|---|
| **Issue date** | 02-12-2014 |
| **Prepared by** | Allison Cho |
| **Version #** | 01 |
| **Further information** | CRC # 439C/D |
| **HMIS® ratings** | Health: 2*<br>Flammability: 4<br>Physical hazard: 0<br>Personal protection: B |
| **NFPA ratings** | Health: 2<br>Flammability: 4<br>Instability: 0 |
| **Disclaimer** | The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries. |