

Safety Data Sheets

1. Identification

Product Name : ES3 ink Black
Order No. : SPC-0440K
General Use : Ink for ink jet plotter
Product Description : Solvent pigment ink
SDS Number : 037-S040316
Manufacture
Company Name : Mimaki Engineering Co., Ltd.
Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN
Telephone No. : +81-268-64-2413
Importer / Distributor Established in USA
Company Name : MIMAKI USA, INC.
Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.
Telephone No. : +1-678-730-0100
Emergency Telephone No. : +81-268-64-2281

2. Hazards Identification

[GHS Classification]

Physical Hazards

Flammable Liquids : Category 4

Health Hazards

Acute Toxicity – Oral : Not classified
Acute Toxicity – Dermal : Not classified
Acute Toxicity – Inhalation : Not classified
Skin Corrosion / Irritation : Category 2
Eye Damage / Irritation : Category 2
Sensitization – Respiratory : Not classified
Sensitization – Skin : Not classified
Germ Cell Mutagenicity : Not classified
Carcinogenicity : Not classified
Toxic to Reproduction : Category 1
Specific Target Organ Toxicity : Category 2 (central nerve)
(Single Exposure)

Safety Data Sheets

Specific Target Organ Toxicity : Not classified

(Repeated Exposure)

Aspiration Hazard : Not classified

Environmental Hazards

Hazardous to the Aquatic : Not classified

Environment - Acute Hazard

Hazardous to the Aquatic : Not classified

Environment - Long Term Hazard

Hazardous to the Ozone Layer : Not classified

The above list does not include category being non-classifiable or not-applicable.

[GHS Label Elements]

Symbol



Signal Word

Danger

Hazard Statements

H227 Combustible liquid

H315 Causes skin irritation

H319 Causes serious eye irritation

H360 May damage fertility or the unborn child

H371 May cause damage to organs (central nerve)

Precautionary Statements

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's operation manual before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from open flames and other ignition sources.-No smoking.

P260 Do not breathe gas/mist.

P264 Wash hands and eyes thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ eye protection/ face protection.

[Response]

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do.

Continue rinsing.

P308+P311 If exposed or concerned: Call a POISON CENTER/ doctor.

P321 Specific treatment (see 4-Response on our website/SDS URL:

Safety Data Sheets

www.mimaki.co.jp/msds).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use alcohol-resistant-related fire foam, dry chemical, carbon dioxide, water spray, dry sand for extinguish.

[Storage]

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national/ international regulation (to be specified).

HMIS Rating (scale 0 – 4)

Health = 3

Flammability= 2

Reactivity = 0

Protective Equipment =

③	Health
②	Flammability
①	Reactivity
○	Protective Equipment


NFPA Rating (scale 0 – 4)

Health = 3

Flammability = 2

Instability = 0

Special = 0



CANADIAN WHMIS SYMBOLS : Not applicable

3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.	Chemical Formula
1	Diethylene Glycol Diethyl ether	55-65	112-36-7	C ₈ H ₁₈ O ₃
2	Tetraethylene Glycol Dimethyl Ether	10-20	143-24-8	C ₁₀ H ₂₂ O ₅
3	γ-Butyrolactone	<20	96-48-0	C ₄ H ₆ O ₂
4	Proprietary organic materials	1-10	Trade Secret	-
5	Tetraethylene Glycol Monobutyl Ether	1-5	1559-34-8	C ₁₂ H ₂₆ O ₅
6	Carbon Black	1-5	1333-86-4	-

Safety Data Sheets

4. First Aid Measures

Inhalation	: IF exposed or concerned: Get medical advice/attention. Remove subject to ventilated fresh air. If not breathing, give artificial respiration right away. If breathing is difficult, give oxygen.
Eye Contact	: Immediately flush with room temperature, low pressure and clean water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention if eye irritation continues. If eye irritation persists, Get medical advice/ attention.
Skin Contact	: IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention.
Ingestion	: IF exposed or concerned: Call a POISON CENTER/ doctor. IF SWALLOWED: Do not induce vomiting.
Most important symptoms and effects, both acute and delayed	: Skin: Ink contact with skin may cause irritation, swelling or redness.
Note To Physician	: Not necessary

5. Fire Fighting Measures

Flammable Properties	: Combustible liquid under Hazard Communication Standard (HCS, U.S.A). Flash point : about 71°C (Closed cup) Autoflammability: None Explosive properties: 1.4~6.9v/v% as dipropylene glycol mono-methyl ether
Extinguishing Media	: Water spray, dry chemical, carbon dioxide or, alcohol foam
Unsuitable Extinguishing Media	: None
Fire Fighting Instructions	: Extinguish to use fire fighting media or plentiful fog water. Put protection wear without fail in case of firefighting work. Wear full fire-fighting turn-out gear (full bunker gear) and respiratory protection (self-contained breathing apparatus). Do not work in the leeward.

Safety Data Sheets

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Eye or Skin protection required during clean-up. Use proper ventilation.

For emergency responders : None

Environmental precautions: : Do not release to sewer, surface- or ground-water.

Methods and material for containment and cleaning up

Advice on how to contain a spill : Use sponges to wipe-up ink.

Advice how to clean-up a spill : Rinse area with damp cloth. Place waste in closed container for disposal.
Wash hands with soap and water.

Any other information: : Do not dispose of waste to the sewer.

Reference to other sections : Please refer SECTION 13 for disposal.

7. Handling and Storage

Handling : Obtain SDS (Safety Data Sheet) and printer's manual instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective equipment (see 8-section). Use proper ventilation and no fire in work place. Keep out of reach of children and do not drink ink. Do not dismantle cartridge. Make sure cartridge is dry before insertion into printer housing. Avoid contact with skin, eyes or clothing. In the case of skin contact, wash with soap and water.

Storage : Store locked up. Do not store the cartridge in high or freezing temperatures. Keep cartridge out of direct sunlight. Do not store the cartridge with oxidizing agents or explosives.

SPECIFIC USES : Not specified

Safety Data Sheets

8. Exposure Controls / Personal Protection

Exposure Limit Values

No	Chemical Name		TWA
1	Diethylene glycol diethyl ether (CAS No. 112-36-7)	California OELs	The 8-Hour TWA Exposure Value : 5 ppm (33mg/m ³)
2	Carbon Black	OSHA PEL	3.5mg/m ³
		ACGIH TLV	3.5mg/m ³
		CMRG	0.5mg/m ³

California OELs : California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

CMRG : Chemical Manufacturer Recommended Guideline

Exposure Controls

Occupational Exposure Controls

Engineering Controls : Use exhaust ventilation to avoid from exposure.

Personal Protection

Respiratory

Protection



: An air purifying respirator with organic vapor cartridge or canister may be permissible under certain circumstances where air-borne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or in any other circumstances where air-purifying respirators may not provide adequate protection.

Hand Protection



Gloves

: Wear gloves that resist organic solvents and chemicals.

Eye Protection



: Wear coverall, chemical goggles and face shield when handling.

Safety Data Sheets

Skin Protection



: To prevent any contact, wear impervious clothing such as gloves, apron, boots, or whole body suits made from neoprene, as appropriate.

Environmental Exposure Controls

: Not available

9. Physical and Chemical Properties

Appearance	- Physical State	: liquid
	- Color	: Black
Odor		: Slightly
pH		: Not Applicable
Boiling Point / Boiling Range		: Not available
Melting Point / Melting Range		: Not available
Decomposition Temperature		: Not available
Flash Point		: about 71°C (Closed cup)
Auto ignition temperature		: Not available
Explosive Properties		: Explosive limits: 1.4~6.9v/v% as γ -Butyrolactone
Relative Density		: Not available
Solubility (ies)		: Soluble
Viscosity		: Not available
Vapor Density		: Greater than 1 (air = 1)
Evaporation Rate		: Not available
VOC		: 735.6 g/L

10. Stability and Reactivity

Conditions to Avoid	: High and freezing temperatures
Stability	: Stable under normal temperature
Materials to Avoid	: Oxidizers and explosives
Hazardous Reactions / Decomposition Products	: To burn this product may be produce toxic gases.

Safety Data Sheets

11. Toxicological Information

Acute Toxicity	: Oral LD ₅₀ >2500mg/kg(rats)	Dermal LD ₅₀ >2000mg/kg(rats)
Eye Irritation	: Moderate irritant. (rabbit, OECD 405) Diethylene Glycol Diethyl ether : Category 2A (GHS Classification) γ-Butyrolactone : Category 2A (GHS Classification)	
Skin Irritation	: Mild irritant. (rabbit, OECD 404) Diethylene Glycol Diethyl ether : Category 2 (GHS Classification)	
Skin Sensitization	: Non-sensitizer(LLNA, OECD 429)	
Mutagenicity	: Negative (by Ames Test)	
Carcinogenicity	: With excessive exposure, carbon black has been listed as a possible human carcinogen. However, as engineered within this ink cartridge, emissions to air of carbon black during normal printing use have not been found. IARC, the International Agency for Research on Cancer, has found printing inks to be not classifiable as human carcinogens.	
Reproductive Toxicity	: Tetraethylene Glycol Dimethyl Ether : Category 1B (GHS Classification)	
Specific Target Organ Toxicity (Single Exposure)	: γ-Butyrolactone : Category 2 (central nerve) (GHS Classification) Category 3 (drowsiness or dizziness) (GHS Classification)	

12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ecotoxicity	: Not available
Persistence and Degradability	: Not available
Bioaccumulative Potential	: Not available

Safety Data Sheets

Results of PBT and vPvB assessment : Has not carried out PBT and vPvB assessment
Other Adverse Effects : Not available

13. Disposal Considerations

: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body of water.

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

Us Department of Transportation (DOT)

Hazardous Materials : Not Applicable

Sea Transport (IMDG)

Class : Not Applicable

Packing Group (PG) : Not Applicable

UN Number : Not Applicable

Proper Shipping Name : Not Applicable

Marine Pollutant : Not Applicable

Air Transport (ICAO/IATA)

Class : Not Applicable

Packing Group(PG) : Not Applicable

UN Number : Not Applicable

Proper Shipping Name : Not Applicable

Safety Data Sheets

15. Regulatory Information

TSCA Section 4(a)	: Not regulated
Final Test Rules	
Regulated	
TSCA Section 5	: Ingredient : Diethylene glycol diethyl ether (CAS No. 112-36-7)
Significant New Use	Reference: 76FR40850
Rule Regulation	Ingredient : Tetraethylene glycol dimethyl ether (CAS No. 143-24-8)
proposed	Reference: 76FR40850
TSCA Section 8(a)	: Not regulated
Preliminary Assessment	
Information Rule (PAIR)	
TSCA Section 12(b)	Ingredient : Diethylene glycol diethyl ether (CAS No. 112-36-7)
One-Time Export	Reference: TSCA 5 Proposed SNUR
Notification Regulated	Ingredient : Tetraethylene glycol dimethyl ether (CAS No. 143-24-8)
	Reference: TSCA 5 Proposed SNUR
Clean Air Act Section	: Diethylene glycol diethyl ether (CAS No. 112-36-7)
112, Hazardous Air	
Pollutants	
EPCRA	: Diethylene glycol diethyl ether (CAS No. 112-36-7)
(SARA Title III)	
Section 313	
California Proposition	: Not regulated
65	
Others	: Please refer to any other federal, state and local regulations.

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.