

KEM CANADA MFG.
4 BLAIR DRIVE
BRAMPTON, ONTARIO
L6T 2H5

EMERGENCY # CANUTEC (613) 996-6666
"USE IN CASE OF CHEMICAL EMERGENCY ONLY"

W.H.M.I.S. CLASSIFICATION: TEL# (905) 456-9444 B2, D1B, D2A, E MATERIAL REFERENCE NO: 579700 SECTION I - MATERIAL IDENTIFICATION AND USE -----|MATERIAL NAME/I.D.: KEMTREET RT 797 |CHEMICAL NAME : NOT APPLICABLE | CHEMICAL FAMILY : ALKALINE BLEND| \_\_\_\_\_ |CHEMICAL FORMULA: MIXTURE | MOLECULAR WEIGHT: NOT APPLICABLE| |SYNONYMS: NONE |MATERIAL USE: RETURN LINE TREATMENT SECTION II - HAZARDOUS INGREDIENTS OF MATERIAL \_\_\_\_\_ |MORPHOLINE |5.0-15.0 | 20 | 110-91-8 | 1450 MG/KG SECTION III - PHYSICAL DATA FOR MATERIAL |PHYSICAL STATE: LIQUID |ODOUR AND APPEARANCE: CLEAR, AMBER LIQUID; AMINE ODOUR. |ODOUR THRESHOLD (PPM) | SPECIFIC GRAVITY | VAPOUR PRESSURE (MM) | 0.1 | 0.964 | NOT AVAILABLE | | VAPOUR DENSITY (AIR=1) | EVAPORATION RATE | SOLUBILITY IN WATER | NOT ESTABLISHED | NOT ESTABLISHED | (20 $\alpha$ C) COMPLETE |SOLUBILITY IN WATER BOILING POINT (C) | FREEZING POINT (C) |% VOLATILE (BY WEIGHT)| | 100 (EST.) | NOT AVAILABLE | 100 | |ph (10% SOLUTION) | DENSITY (G/ML) | COEF.OF WATER/OIL DISTR| | 10.5-11.5 | NOT APPLICABLE | NOT AVAILABLE |



MATERIAL REFERENCE NO: 579700

SECTION IV - FIRE AND EXPLOSION HAZARD OF MATERIAL
FLAMMABILITY: FLAMMABLE    IF YES, UNDER WHICH CONDITIONS: VAPOURS MAY BE FLAMMABLE.
MEANS OF EXTINCTION: ALCOHOL FOAM, CO2, WATER FOG.
SPECIAL PROCEDURES: WEAR FULL PROTECTIVE GEAR INCLUDING SELF-    CONTAINED BREATHING APPARATUS. VAPOURS ARE HEAVIER THAN AIR AND MAY    TRAVEL TO IGNITION SOURCE AND FLASH BACK.
FLASH POINT (C) AND METHOD: MINIMUM 31.7 (C)
HAZARDOUS COMBUSTION PRODUCTS: MAY EVOLVE NITROGEN OXIDES, SMOKE,   SOOT, CARBON DIOXIDE, CARBON MONOXIDE, AMMONIA, FORMALDEHYDE,   ACETALDEHYDE.
UPPER EXPLOSION LIMIT   LOWER EXPLOSION LIMIT   AUTOIGNITION TEMP(C)   NOT AVAILABLE   NOT AVAILABLE
EXPLOSION DATA SENSITIVITY  RATE OF BURNING   EXPLOSIVE POWER    TO CHEMICAL IMPACT         NOT AVAILABLE   NOT AVAILABLE   NOT AVAILABLE
SENSITIVITY TO STATIC DISCHARGE: NOT AVAILABLE
SECTION V - REACTIVITY DATA  CHEMICAL STABILITY: STABLE
IF NO, UNDER WHICH CONDITIONS:
INCOMPATIBILITY TO OTHER SUBSTANCES: YES    IF SO, WHICH ONES: AVOID CONTACT WITH STRONG ACIDS, OXIDIZING AGENTS      REACTIVE METALS, NITRITES AND HALOGEN COMPOUNDS.
REACTIVITY AND UNDER WHAT CONDITIONS: NO     HAZARDOUS POLYMERIZATION WILL NOT OCCUR.
HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITION MAY EVOLVE     INITROUS OXIDES, CARBON MONOXIDE, CARBON DIOXIDE, AMMONIA,   FORMALDEHYDE, ACETALDEHYDES.
SECTION VI - HEALTH HAZARD DATA
ROUTE OF ENTRY:
SKIN CONTACT: YES



MATERIAL REFERENCE NO: 579700

.\_\_\_\_\_ | EFFECTS OF ACUTE EXPOSURE TO MATERIAL: | EYES-MAY CAUSE SEVERE IRRITATION, INTENSE WATERING. PROLONGED CONTACT MAY CAUSE PERMANENT EYE INJURY. | SKIN-MAY CAUSE IRRITATION, INFLAMMATION, POSSIBLE BURNS. | INHALATION-MAY CAUSE IRRITATION OF NOSE, EYES AND THROAT, COUGHING, | DIFFICULTY IN BREATHING. EXCESSIVE INHALATION MAY CAUSE BRONCHITIS, PULMONARY EDEMA AND CHEMICAL PNEUMONITIS. | INGESTION-MAY CAUSE IRRITATION AND BURNING SENSATION OF LIPS, MOUTH | AND THROAT, PAIN IN SWALLOWING, GASTRO-INTESTINAL IRRITATION, ABDOMINAL PAIN, NAUSEA AND VOMITING. | EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: CAN CAUSE KIDNEY AND/OR |LIVER DAMAGE. |LD 50 OF MATL. |LC 50 OF MATL. |EXPOSURE LIMIT(S)|IRRITANCY OF MATL| | NOT AVAILABLE | NOT AVAILABLE | TOXIC | | SYNERGISTIC MATERIALS |SENSITIZATION OF MATERIAL | NOT AVAILABLE NOT AVAILABLE \_\_\_\_\_\_ |CARCINOGENICITY, REPRODUCTIVE EFFECTS, TERATOGENICITY, MUTAGENICITY | | REPRODUCTIVE EFFECTS-CYCLOHEXYLAMINE CAUSES PATERNAL EFFECTS IN | ANIMAL STUDIES AT MODERATE TO HIGH DOSAGES. |MUTAGENICITY-CYCLOHEXYLAMINE CAUSES SOME CHROMOSOMAL ABBERATIONS IN | ANIMALS. SEVERAL OTHER INVESTIGATIONS HAVE NEGATIVE RESULTS. |TERATOGENICITY-CYCLOHEXYLAMINE CAUSES POST-IMPLANT MORTALITY IN | ANIMALS FROM DOSAGES NEAR THE LC50. |MORPHOLINE MAY REACT WITH NITRITES TO FORM N-NITROSAMINES (KNOWN |CARCINOGENS) SECTION VII - PREVENTIVE MEASURES | PERSONAL PROTECTIVE EQUIPMENT: GLOVES: BUTYL RUBBER | RESPIRATORY: NIOSH APPROVED FOR ORGANIC VAPOURS EYE: FACE SHIELD OR SAFETY GOGGLES CLOTHING: LONG SLEEVED SHIRTS, TROUSERS, BUTYL RUBBER BOOTS AND APRON. OTHER: EYE WASH AND SAFETY SHOWER | ENGINEERING CONTROLS (EG VENTILATION, ENCLOSED PROCESS): MECHANICAL | RECOMMENDED TO MAINTAIN CONCENTRATION BELOW TLV. \_\_\_\_\_ | LEAK AND SPILL PROCEDURE: WEAR RECOMMENDED PERSONAL PROTECTIVE | EQUIPMENT. STOP LEAKS AND CONTAIN SPILL. RECLAIM IF POSSIBLE. |SMALL SPILLS-WIPE UP OR MOP UP AND PLACE IN DISPOSAL CONTAINER. |LARGE SPILLS-ABSORB ONTO NON-COMBUSTIBLE ABSORBENT AND PLACE IN |APPROVED CONTAINER FOR DISPOSAL. DO NOT ALLOW LIQUID TO FLOW INTO |WATERWAYS. PRODUCT IS EXPECTED TO BE TOXIC TO AQUATIC LIFE. \_\_\_\_\_\_ | WASTE DISPOSAL: DISPOSE IN ACCORDANCE WITH LOCAL, PROVINCIAL AND | FEDERAL REGULATIONS.



MATERIAL REFERENCE NO: 579700

SECTION VIII - FIRST AID MEASURES	
PROCEDURES: EYES-IMMEDIATELY FLUSH EYES WITH RUNNING WATER FOR 15   MINUTES. IF PAIN OR IRRITATION PERSIST, SEEK MEDICAL ASSISTANCE.   SKIN-REMOVE CONTAMINATED CLOTHING AND FLUSH AFFECTED AREA WITH   WATER FOR 15 MINUTES. IF PAIN OR IRRITATION PERSIST, SEEK MEDICAL   ASSISTANCE. LAUNDER CLOTHING BEFORE REUSE.   INHALATION-MOVE VICTIM TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE   OXYGEN. GET MEDICAL ATTENTION.   INGESTION, IF SWALLOWED-DO NOT INDUCE VOMITING. GIVE WATER OR MILK.   IF VOMITING OCCURS, GIVE FLUIDS AGAIN. GET IMMEDIATE MEDICAL   ATTENTION.	
SOURCES USED: RAW MATERIAL SUPPLIER'S MATERIAL SAFETY DATA SHEETS	
ADDITIONAL INFORMATION: NONE	
SECTION IX - TDG SHIPPING INFORMATION	-
SHIPPING NAME   CLASS  UN NO.  PG   CORROSIVE LIQUID, FLAMMABLE, N.O.S.   8(3)   2920   II   (CYCLOHEXYLAMINE, MORPHOLINE)	
HANDLING PROCEDURES AND EQUIPMENT: HANDLE AND USE IN WELL VENTILATED   AREAS. AVOID CONTACT WITH EYES AND SKIN. WASH THOROUGHLY AFTER   HANDLING.	     
STORAGE REQUIREMENTS: STORE IN A COOL, DRY WELL VENTILATED AREA IN  ORIGINAL CONTAINER, AWAY FROM INCOMPATIBLE MATERIALS. KEEP CONTAINER  CLOSED WHEN NOT IN USE.	ا ۱ ۱
SPECIAL SHIPPING INFORMATION: NONE	
SECTION X - HMIS HAZARD RATING INFORMATION	-
FLAMMABILITY   REACTIVITY   HEALTH   3   0   2	
SECTION XI - PREPARATION DATE OF MSDS	
PREPARED BY: TECHNICAL DEPARTMENT TELEPHONE # (905) 456-9444  REVIEWED: OCTOBER 10, 2009	
PREPARED BY: TECHNICAL DEPARTMENT TELEPHONE # (905) 456-9444	   

#### DISCLAIMER:

THE INFORMATION CONTAINED HEREIN IS COMPILED FROM SOURCES BELIEVED TO BE RELIABLE. THE MANNER AND CONDITIONS OF USE AND HANDLING MAY INVOLVE OTHER AND ADDITIONAL CONSIDERATIONS. WE ACCEPT NO RESPONSIBILTY FOR THE ACCURACY, SUFFICIENCY, RELIABILITY OR FOR ANY LOSS OR INJURY RESULTING FROM THE USE OF THE INFORMATION.