



MATERIAL SAFETY DATA SHEET

KEM CANADA MFG.
4 BLAIR DRIVE
BRAMPTON, ONTARIO
L6T 2H5
TEL# (905) 456-9444

EMERGENCY # CANUTEC (613) 996-6666
"USE IN CASE OF CHEMICAL EMERGENCY ONLY"

W.H.M.I.S. CLASSIFICATION: D2A, D2B

MATERIAL REFERENCE NO: 581000

SECTION I - MATERIAL IDENTIFICATION AND USE

MATERIAL NAME/I.D.: GLYCOL"E-100 NI"	
CHEMICAL NAME : MIXTURE	CHEMICAL FAMILY :GLYCOLS
CHEMICAL FORMULA: MIXTURE	MOLECULAR WEIGHT: NOT AVAILABLE
SYNONYMS: NONE	
MATERIAL USE: FREEZE POINT DEPRESSANT	

SECTION II - HAZARDOUS INGREDIENTS OF MATERIAL

HAZARDOUS INGREDIENTS	APPROX. % CONCENT.	TLV PPM	C.A.S. N.A. U.N. NUMBERS	LD 50 ORAL, RAT
ETHYLENE GLYCOL	60.0-100.0	50	107-21-1	4700 MG/KG

SECTION III - PHYSICAL DATA FOR MATERIAL

PHYSICAL STATE: LIQUID		
ODOUR AND APPEARANCE: CLEAR LIQUID; ODOURLESS.		
ODOUR THRESHOLD (PPM)	SPECIFIC GRAVITY	VAPOUR PRESSURE (MM)
NOT ESTABLISHED	1.11-1.15	NOT ESTABLISHED
VAPOUR DENSITY (AIR=1)	EVAPORATION RATE	SOLUBILITY IN WATER
NOT ESTABLISHED	(BUTYL ACETATE=1) <1	(20°C) COMPLETE
BOILING POINT (C)	FREEZING POINT (C)	% VOLATILE (BY VOLUME)
>100	-29 (APPROX.)	100
pH (10% SOLUTION)	DENSITY (G/ML)	COEF.OF WATER/OIL DISTR
NO DATA	NOT APPLICABLE	NOT AVAILABLE



MATERIAL SAFETY DATA SHEET

MATERIAL REFERENCE NO: 581000

SECTION IV - FIRE AND EXPLOSION HAZARD OF MATERIAL

FLAMMABILITY: NONE FLAMMABLE			
IF YES, UNDER WHICH CONDITIONS:			
MEANS OF EXTINCTION: CO2, DRY CHEMICAL, WATER FOG, FOAM.			
SPECIAL PROCEDURES: NONE APPLICABLE			
FLASH POINT (C) AND METHOD: MINIMUM 116 (C)			
HAZARDOUS COMBUSTION PRODUCTS: OXIDES OF CARBON.			
UPPER EXPLOSION LIMIT	LOWER EXPLOSION LIMIT	AUTOIGNITION TEMP(C)	
ETHYLENE GLYCOL 15.3 %	ETHYLENE GLYCOL 3.2 %	ETHYLENE GLYCOL 400	
EXPLOSION DATA SENSITIVITY			
TO CHEMICAL IMPACT			
NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE	
SENSITIVITY TO STATIC DISCHARGE: NOT AVAILABLE			

SECTION V - REACTIVITY DATA

CHEMICAL STABILITY: STABLE			
IF NO, UNDER WHICH CONDITIONS:			
INCOMPATIBILITY TO OTHER SUBSTANCES: YES			
IF SO, WHICH ONES: STRONG OXIDIZING MATERIALS, ALUMINUM METAL.			
REACTIVITY AND UNDER WHAT CONDITIONS: EXPLOSIVE DECOMPOSITION MAY			
OCCUR WHEN COMBINED WITH STRONG ACIDS OR BASES.			
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.			
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON.			

SECTION VI - HEALTH HAZARD DATA

ROUTE OF ENTRY:			
SKIN CONTACT: NO	SKIN ABSORPTION: NO	EYE CONTACT: YES	
INHALATION: YES	INGESTION: YES		



MATERIAL SAFETY DATA SHEET

MATERIAL REFERENCE NO: 581000

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:
EYES- MAY EYE IRRITATION, TEARING, REDNESS, SWELLING OF CONJUNCTIVA.
SKIN-MAY CAUSE IRRITATION. PROLONGED CONTACT MAY CAUSE DERMATITIS IN SENSITIVE INDIVIDUALS.
INHALATION-MAY CAUSE IRRITATION OF EYES, NOSE, THROAT AND RESPIRATORY TRACT AND CNS DEPRESSION.
INGESTION-MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA.

EFFECTS OF CHRONIC EXPOSURE TO MATERIAL:
PROLONGED OR REPEATED EXPOSURE TO HIGH CONCENTRATIONS MAY CAUSE LOSS OF APPETITE, AND LIVER, KIDNEY AND NEURAL DISFUNCTION.
PRE-EXISTING SKIN, EYE OR RESPIRATORY DISORDERS, OR IMPAIRED KIDNEY FUNCTION MAY BE AGGRAVATED BY EXPOSURE TO ETHYLENE GLYCOL.
INHALATION-OF MIST MAY PRODUCE SIGNS OF CNS INVOLVEMENT, PARTICULARLY DIZZINESS AND NYSTAGMUS.

LD 50 OF MATL.	LC 50 OF MATL.	EXPOSURE LIMITS	IRRITANCY OF MATL
6100-8540 MG/KG	10,000 MG/M3	NOT ESTABLISHED	TOXIC

SENSITIZATION OF MATERIAL	SYNERGISTIC MATERIALS
NOT AVAILABLE	NOT AVAILABLE

CARCINOGENICITY, REPRODUCTIVE EFFECTS, TERATOGENICITY, MUTAGENICITY:
CARCINOGENIC-CLASSIFIED A4-NOT CLASSIFIED FOR HUMANS OR ANIMALS BY ACGIH. TERATOGEN-CLASSIFIED PROVEN FOR HUMANS.

SECTION VII - PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: GLOVES & GLASSES IF USING CONCENTRATE

GLOVES: RUBBER, PVC
RESPIRATORY: NIOSH APPROVED AIR-PURIFYING FOR CONC. UP TO 500PPM
AIR SUPPLIED RESPIRATOR IF CONC. IS HIGHER OR UNKNOWN.
EYE: CHEMICAL GOGGLES
FOOTWEAR: IMPERVIOUS
CLOTHING: IMPERVIOUS APRON
OTHER: EYE WASH
ENGINEERING CONTROLS (EG VENTILATION, ENCLOSED PROCESS): SUFFICIENT MECHANICAL (GENERAL OR LOCAL EXHAUST) TO MAINTAIN TLV BELOW BELOW ACCEPTABLE LIMITS.

LEAK AND SPILL PROCEDURE: WEAR PROPER PROTECTIVE CLOTHING. CONTAIN SPILL. TRANSFER TO SUITABLE CONTAINER FOR REUSE OR DISPOSAL. ABSORB REMAINING MATERIAL ONTO INERT ABSORBANT. KEEP OUT OF SEWERS, STORM DRAINS AND WATERWAYS.

WASTE DISPOSAL:
DISPOSE OF IN A LICENSED FACILITY IN ACCORDANCE WITH ALL FEDERAL, PROVINCIAL AND LOCAL REGULATIONS.



MATERIAL SAFETY DATA SHEET

MATERIAL REFERENCE NO: 581000

SECTION VIII - FIRST AID MEASURES

PROCEDURES:
EYE CONTACT-FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ASSISTANCE IF IRRITATION PERSISTS.
SKIN CONTACT-FLUSH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.
INHALATION-MOVE VICTIM TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. SEEK MEDICAL ATTENTION.
INGESTION-INDUCE VOMITING BY EITHER GIVING IPECAC SYRUP OR PLACING FINGER AT BACK OF THROAT. NEVER GIVE ANYTHING TO AN UNCONSCIOUS OR CONVULSING PERSON. GET IMMEDIATE MEDICAL ATTENTION.

SOURCES USED: RAW MATERIAL SUPPLIER'S MATERIAL SAFETY DATA SHEETS

ADDITIONAL INFORMATION: NONE

SECTION IX - TDG SHIPPING INFORMATION

SHIPPING NAME	CLASS	UN NO.	PACKING GROUP
NOT REGULATED			

HANDLING PROCEDURES AND EQUIPMENT: AVOID CONTACT WITH EYES AND SKIN. USE IN WELL VENTILATED AREAS. WASH THOROUGHLY AFTER HANDLING.

STORAGE REQUIREMENTS: STORE IN A COOL, DRY AREA AWAY FROM INCOMPATIBLE MATERIALS. KEEP CONTAINER CLOSED WHEN NOT IN USE.

SPECIAL SHIPPING INFORMATION: NONE

SECTION X - HAZARD RATING INFORMATION

FLAMMABILITY	REACTIVITY	TOXICITY
0	0	2

SECTION XI - PREPARATION DATE OF MSDS

PREPARED BY: TECHNICAL DEPARTMENT TELEPHONE # (905) 456-9444
REVIEWED: DECEMBER 14, 2002

DISCLAIMER:

THE INFORMATION CONTAINED HEREIN IS COMPILED FROM SOURCES BELIEVED TO BE RELIABLE. THE MANNER AND CONDITIONS OF USE AND HANDLING MAY INVOLVE OTHER AND ADDITIONAL CONSIDERATIONS. WE ACCEPT NO RESPONSIBILITY FOR THE ACCURACY, SUFFICIENCY, RELIABILITY OR FOR ANY LOSS OR INJURY RESULTING FROM THE USE OF THE INFORMATION.