SDS# 6000-10

Revision Date: 9/22/2014

# 1. PRODUCT IDENTIFICATION

PRODUCT NAME: 6000

PRODUCT COLOR: Cleaner

RECOMMENDED USE: Coding and Marking

Manufacturer/Supplier:

American Coding & Marking Ink Co., Inc. 1-908-756-0373

1220 North Avenue Plainfield, NJ 07062-1796

USA

**Emergency Telephone Number:** 

TRANSPORTATION: CHEMTREC: 1-800-424-9300 (North America)

1-703-527-3887 (International)

# 2. HAZARDS IDENTIFICATION

# **Emergency Overview:**

### **GHS Classification:**

Flammable liquids	Category 2
Skin corrosion/irritation	Category 3
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Reproductive toxicity	Category 1B

# GHS label elements, including precautionary statements



Signal Word Danger

**Hazard Statements** 

H225 Highly flammable liquid and vapor
H316 Causes mild skin irritation
H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness H360 May damage fertility or the unborn child

**Precautionary Statements** 

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking

P233 Keep container tightly closed P242 Use only non-sparking tools

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P271 Use only outdoors or in a well-ventilated area

P280 Wear protective gloves/protective clothing/eye protection/face protection
P303+P361+P353 Wear protective gloves/protective clothing/eye protection/face protection
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P501 Dispose of contents/container to an approved waste disposal plant

# 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Ethyl Acetate	141-78-6	40-60
2-Propanol	67-63-0	15-30
1-Methoxy-2-propanol	107-98-2	15-30

#### 4. FIRST AID MEASURES

**First Aid Measures** 

**Ingestion:** If swallowed, do NOT induce vomiting. Never give anything by mouth

to an unconscious person. Rinse mouth with water. Consult a

physician.

**Eyes:** Rinse thoroughly with plenty of water for at least 15 minutes and

consult a physician.

**Skin:** Wash off with soap and plenty of water. Consult a physician.

**Inhalation:** If breathed in, move person into fresh air. If not breathing, give

artificial respiration. Consult a physician.

Most important symptoms and effects

**Symptoms** Eye contact may result in redness, blurred vision, burning

sensation. Skin contact may result in irritation, defatting or dermatitis. Inhalation may cause drowsiness or dizziness. Inhalation may cause respiratory tract irritation. Ingestion may cause nausea, vomiting,

dizziness and headache.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically

Revision Date: 9/22/2014

### 5. FIREFIGHTING MEASURES

#### Suitable extinguishing media:

Water fog, Multipurpose foam, Dry chemical, CO<sub>2</sub>

#### Unsuitable extinguishing media:

Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards in case of fire:

Fight as volatile liquid fire Water spray may spread fire. Flashback fires may occur

#### Hazardous combustion products:

Carbon oxides, organic combustion products which may be toxic and/or irritating

### Protective equipment and precautions for fire fighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions:

Wear chemical goggles, gloves, boots and protective clothing. Wear respirator if necessary. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition and heat.

#### **Environmental precaution:**

Prevent additional discharge of material. Prevent material from entering sewers or water courses.

#### Methods and materials for containment and cleaning up:

Absorb small spills with sand, filter-aid, vermiculite or other inert absorbent material, them place in a chemical waste container. For large spills, contain with sand or earth dikes. Dispose of waste in accordance with applicable government regulations.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling:

Avoid contact with eyes. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink of smoke when using this product. Wear protective gloves/protective clothing and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Unscrew all caps slowly. Do not unscrew entirely until all pressure has been completely released. Keep away from heat/sparks/open flames/hot surfaces. Emptied containers may retain residues. Precautions apply to emptied containers.

#### Conditions for safe storage, including incompatibilities:

Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep storage temperature between 4-32 °C (40-90 °F). Incompatible with strong oxidizing agents, strong acids, strong bases, alkali metals and halogens.

# 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **Exposure Guidelines:**

Chemical Name and CAS#	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl Acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>
2-Propanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
1-Methoxy-2-propanol 107-98-2	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 360 mg/m³ STEL: 150 ppm STEL: 540 mg/m³	TWA: 100 ppm TWA: 360 mg/m³ STEL: 150 ppm STEL: 540 mg/m³

#### Appropriate engineering controls

Apply technical measures to comply with the occupational exposure limits. Local exhaust and mechanical ventilations are recommended to be used as engineering controls.

### Individual protection measures, such as personal protective equipment:

**Eye/Face protection:** Safety glasses with side shields or chemical goggles must be worn.

**Skin/Body protection:** Wear protective gloves. Wear suitable protective clothing and footwear

appropriate for the risk of exposure.

Respiratory protection: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA

approved respiratory protection should be worn. Respiratory protection must be

provided in accordance with current local regulations.

**General hygiene:** Handle in accordance with good industrial hygiene and safety practice.

# **SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

<u>Property</u> <u>Values</u> <u>Remarks-Methods</u>

Physical state: Liquid
Color: Colorless

Odor: Characteristic Acetate type

Odor threshold:

PH:

Not determined

Flash point: 3.3 °C / 26 °F Tag Closed Cup

**Evaporation Rate:** >1 butyl acetate = 1

Flammability (solid, gas):
Upper/lower flammability limits:
Vapor pressure:
Not determined
Not determined

Vapor density:>1air = 1Specific gravity:0.89water = 1

Water solubility:
Solubility in other solvents:
Partition Coefficient:
Auto-ignition Temperature:
Not determined
Not determined

Decomposition temperature:Not determinedViscosity:Not determinedVOC Content (%):100%VOC Content:7.4 lbs/gal

### 10. STABILITY AND REACTIVITY

### Reactivity:

Not reactive under normal conditions.

#### **Chemical Stability:**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions:

None under normal processing.

#### Conditions to avoid:

Keep out of reach of children. Keep away from heat, sparks and open flame. Keep away from contact with incompatible materials.

#### Incompatible materials:

Strong oxidizing agents, strong acids, halogens

#### Hazardous decomposition products:

Carbon oxides, thermal decomposition can lead to release of irritating and toxic gases and vapors.

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Eye contact:** Causes serious eye irritation

**Skin contact:** Causes skin irritation

**Inhalation:** May cause respiratory irritation. May cause drowsiness or dizziness.

**Ingestion:** May be harmful if swallowed

### **Component Information:**

Chemical Name and CAS#	Oral LD50	Dermal LD50	Inhalation LC50	
Ethyl Acetate	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit)	= 45000 mg/L (Mouse) 2 h	
141-78-6				
2-Propanol	= 5,045 mg/kg (Rat)	= 12,800 mg/kg (Rabbit)	= 16,000 mg/ m <sup>3</sup> (Rat) 8 h	
67-63-0				
1-Methoxy-2-propanol	= 11,700 mg/kg ( Mouse )	= 13,000 mg/kg ( Rabbit )	$= 10,000 \text{ mg/m}^3 \text{ (Rat) 5h}$	
107-98-2				

#### Information on physical, chemical and toxicological effects:

**Symptoms** Please see section 4 of this SDS for symptoms

# Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Carcinogenicity:

SDS# 6000-10

Revision Date: 9/22/2014

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Propanol		Group 3		
67-63-0				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Limited evidence of carcinogenicity

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

#### Numerical measures of toxicity:

Not determined

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity:**

### **Component Information**

Chemical Name and CAS#	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethyl Acetate	EC50 - Algae - 4300 mg/L -	LC50 – Pimephales		EC50 – Daphnia magna –
141-78-6	24h	promelas – 220-250 mg/L –		560 mg/L – 48h
		96h		
2-Propanol	1	LC50 - Pimephales promelas		EC50 - Daphnia magna –
67-63-0	subspicatus - 2000 mg/L –	– 9,640 mg/L – 96h		5,102 mg/L – 96h
	72h			
1-Methoxy-2-propanol		LC50 - Pimephales promelas		EC50 - Daphnia magna –
107-98-2		– 20,800 mg/L – 96h		23,300 mg/L – 48h

# Persistence/Degradability:

Not determined

Bioaccumulation:

Not determined

Mobility:

Not determined

Other Adverse Effects:

No data available

# 13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Disposal should be in accordance with applicable regional, national and local

laws and regulations.

Contaminated Packaging: Dispose of as unused product in accordance with applicable regional, national

and local laws and regulations.

.

# **SECTION 14 – TRANSPORTATION INFORMATION**

DOT

UN number 1210

Proper shipping name PRINTING INK RELATED MATERIAL

Hazard class 3 Packing group III ERG# 129

**IATA** 

UN number 1210

Proper shipping name PRINTING INK RELATED MATERIAL

Hazard class 3 Packing group III

**IMDG** 

UN number 1210

Proper shipping name PRINTING INK RELATED MATERIAL

Hazard class 3
Packing group III
Marine pollutant No

# **SECTION 15 – REGULATORY INFORMATION**

TSCA STATUS: All Components listed

OTHER REGULATORY:

Ingredient(s)	SARA 302	SARA 311/312	<b>SARA 313</b>	<b>RECRA</b>	<b>CERCLA</b>
Ethyl Acetate	No	F, A, C	No	U112	Yes
2-Propanol	No	F, A, C	Yes	No	No
1-Methoxy-2-propanol	No	F, A, C	No	No	No

SARA 311/312 Codes: R = Reactive Hazard

P = Pressure Hazard F = Fire Hazard A = Immediate/Acute C = Delayed/Chronic

**California Prop. 65 Components:** Chemicals known to the state of California to cause birth defects or other reproductive harm:

This product does not contain any chemicals known to the state of California to cause cancer, birth defects or any other reproductive harm.

# **SECTION 16 – OTHER INFORMATION**

HMIS:

# **SAFETY DATA SHEET**

SDS# 6000-10 Revision Date: 9/22/2014

Health: 1
Chronic Health Hazard \*
Flammability: 3
Reactivity: 0

Revision Date: 22-Sept-2014
Replaces: 6-Dec-2012
Revision Note: New SDS format

Prepared by: Thomas S. Sweet, VP

#### **DISCLAIMER OF LIABILITY**

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material described in this MSDS. Information contained herein is given in good faith and believed to be true and accurate, but all statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material, or results to be obtained from the use thereof. All of the listed ingredients in this product that are considered to present a health hazard as defined in Appendix A of the OSHA "Hazard Communication" standard (29CFR 1910.1200) as listed in Section II. All of the information given, including ingredient identification, CAS Number, and quantity, is proprietary information, which has been provided in order to meet the objective of the "Hazard Communication" standard. Data provided here are typical and not intended for use as product specifications. This formulation information is confidential, and only to be disclosed in accordance with Federal and State safety and health regulations. Permission to disclose any ingredient information for any other purpose is neither given nor implied.