MSDS057

Loctite® 290 Threadlocker Wicking Grade

MATERIAL SAFETY DATA SHEET

Chemical Product and Company Identification

LABEL IDENTIFIER: Loctite® 290 Threadlocker Wicking Grade

PRODUCT IDENTIFIER: P/N 603580 Sealant, Thread Locking

COMPANY IDENTIFICATION: MINE SAFETY APPLIANCES COMPANY

1100 Cranberry Woods Drive Cranberry Township, PA 16066

CUSTOMER SERVICE: 1-800-MSA-2222 (8:30 a.m. - 5:00 p.m., USA local time)

EMERGENCY: 1-800-255-3924 (CHEM-TEL, INC.)

Vendor Information

A Material Safety Data Sheet as furnished by Loctite for 290 Threadlocker Wicking Grade is attached (5 Pages).

Loctite MSDS REVISION DATE: 2/3/2006

Other Information

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using, or storing this product.

Revision 1: 07-03-2012 Page 1 of 1

LOCTITE.

Material Safety Data Sheet



Revision Date: 01/25/2006 Issue date: 02/03/2006

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

 Product name:
 Loctite(R) 290 Threadlocker Wicking Grade
 Item No. :
 29021

 Product type:
 Anaerobic Sealant
 Region:
 United States

 Product type:
 Anaerobic Sealant
 Region:
 United

 Company address:
 Contact Information:

 Henkel Corporation
 Telephone: 860.571.5100

1001 Trout Brook Crossing Emergency telephone: 860.571.5100 Rocky Hill, Connecticut 06067 Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

ACGIH TLV OSHA PEL **OTHER** Hazardous components <u>%</u> 60-100 Polyglycol dimethacrylate None None None 25852-47-5 Cumene hydroperoxide 1-5 1 ppm (6 mg/m3) Skin (WEEL) None None 80-15-9 Saccharin 1-5 None None None 81-07-2

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

 Physical state:
 Liquid
 HEALTH:
 2*

 Color:
 Green
 FLAMMABILITY:
 1

 Odor:
 Mild
 PHYSICAL HAZARD:
 1

 Personal Protection:
 See Section

Personal Protection: See Section 8

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation.

Skin contact: May cause allergic skin reaction. May cause skin irritation.

Eye contact: May cause irritation.

Ingestion: Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

Item No.: 29021 Product name: Loctite(R) 290 Threadlocker Wicking Grade

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse.

Get medical attention if symptoms occur.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding

eyelids open all the time. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point: Greater than 93°C (200°F) Tagliabue closed cup

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: Not available

Flammable/Explosive limits-upper %: Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapors.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Prevent product from entering drains or open waters.

Clean-up methods: Soak up with inert absorbent. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after

handling.

Storage: For safe storage, store at or below 38°C (100°F). Keep in a cool, well ventilated area away from heat,

sparks and open flame. Keep container tightly closed until ready for use.

Incompatible products: Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne

contamination below occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene

gloves. Butyl rubber gloves. Natural rubber gloves.

Eye/face protection: Safety goggles or safety glasses with side shields.

Item No.: 29021 Product name: Loctite(R) 290 Threadlocker Wicking Grade

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Green Odor: Mild

Vapor pressure: Less than 5 mm Hg at 27°C (80°F)

pH:

Not applicable Greater than 149°C (300°F)

Boiling point/range: Melting point/range:

Not available

Specific gravity: Vapor density: Evaporation rate: 1.07 at 26.7°C (80°F) Not available

Evaporation rate: Not available Solubility in water: Slight Partition coefficient (n-octanol/water): Not available

VOC content: 2.2713%; 22.1 grams/liter

10. STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: Will not occur.

Hazardous decomposition products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapors. Phenols.

Incompatability: Copper. Iron. Rust. Aluminum. Zinc. Strong oxidizers. Strong acids. Oxygen scavengers. Reducing

agents. Strong alkalis.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatability" (Section 10).

11. TOXICOLOGICAL INFORMATION

Product toxicity data: Acute LD50 (oral) :Greater than mg/kg(rat). (estimated). Acute dermal LD50 greater than 2000 mg/kg

(rabbit) (estimated).

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Polyglycol dimethacrylate 25852-47-5	No	No	No
Cumene hydroperoxide 80-15-9	No	No	No
Saccharin 81-07-2	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs	
Polyglycol dimethacrylate 25852-47-5	Allergen, Irritant	
Cumene hydroperoxide 80-15-9	Allergen, Central nervous system, Corrosive, Irritant, Mutagen	
Saccharin 81-07-2	No Target Organs	

12. ECOLOGICAL INFORMATION

Ecological information: Not available

Item No.: 29021 Product name: Loctite(R) 290 Threadlocker Wicking Grade

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Unrestricted Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Unrestricted Hazard class or division: None Identification number: None Packing group: None

WaterTransportation (IMO/IMDG):

Proper shipping name: Unrestricted Hazard class or division: None Identification number: None Packing group: None Marine pollutant: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: 4-Methoxyphenol (150-76-5).

CERCLA/SARA Section 302 EHS: None above reporting de minimus.

CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313

of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene

hydroperoxide (CAS# 80-15-9) .

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and birth defects or

other reproductive harm.

Canada Regulatory Information

Item No.:

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.

WHMIS hazard class: D.2.

29021

Product name: Loctite(R) 290 Threadlocker Wicking Grade

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 9

Prepared by: Kyra Kozak Woods, Product Safety and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Item No. : 29021 Product name: Loctite(R) 290 Threadlocker Wicking Grade