#### FLEXTILE LTD

# **Material Safety Data Sheet**

## FLEXTECH 700 SUPERIOR OUALITY MULTI-PURPOSE FLOORING ADHESIVE

MANUFACTURER: FLEXTILE LTD. **BRITISH COLUMBIA ONTARIO QUEBEC** 121-30th Street. 555. Rue locke 2829 Lake City Way Etobicoke, ON. Ville St. Laurent, OC Burnaby, BC M8W 3C1 V5A 2Z6 H4T 1X7 Tel: (416) 255-1111 Tel: (514) 345-6666 Tel: (644) 420-4914 FAX: (416) 255-1729 FAX: (514) 345-8825 FAX: (604) 420-0936 IN CASE OF EMERGENCY. CALL CANUTEC (613) 996-6666 **Material Identification** PRODUCT IDENTIFIER..... FLEXTECH 700 SUPERIOR QUALITY MULTI-PURPOSE FLOORING PRODUCT USE..... FOR INSTALLATION OF VINYL COMPOSITION TILE, SHEET VINYL & CARPET. WHMIS CLASSIFICATION..... NOT REGULATED UNDER WHMIS **Hazardous Ingredients of Materials** CHEMICAL IDENTITY CONCENTRATION CAS#/NA#/UN# OSHA (PEL) ACGIH (TLV-TWA) THIS PRODUCT CONTAINS NO HAZARDOUS INGREDIENT AS DEFINED BY US OSHA HAZARD COMMUNICATION STANDARD - 29 CFR 1910.1200 OR SECTION 13 OF THE CANADIAN HAZARDOUS PRODUCT ACT. All ingredients are listed within or exempted from US TSCA and Canadian DSL. **Physical Data For Product** PHYSICAL STATE..... **VISCOUS LIQUID** MILD ODOUR, CREAM COLOURED VISCOUS LIQUID ODOUR AND APPEARANCE..... ODOUR THRESHOLD..... **NOT DETERMINED** SPECIFIC GRAVITY..... 1.1 VAPOUR PRESSURE..... N/D VAPOUR DENSITY (air=1)..... N/D BOILING POINT.....  $212^{0}$ F ( $100^{0}$ C) EVAPORATION RATE(Butyl Acetate=1) Same as water FREEZING POINT..... N/D pH..... 9-10 CALCULATED VOC...... 0 gm/litre Fire and Explosion Hazard of Product CONDITIONS OF FLAMMABILITY...... NON-COMBUSTIBLE MEANS OF EXTINCTION..... Will not burn except under extreme temperature. Water spray, CO<sub>2</sub>, dry chemical or foam  $>212^{0}$ F ( $100^{0}$ C) FLASHPOINT..... UPPER EXPLOSION LIMIT (% BY VOL).. N/D LOWER EXPLOSION LIMIT (% BY VOL).. N/D AUTO-IGNITION TEMPERATURE...... N/D HAZARDOUS COMBUSTION PRODUCTS..... CO<sub>2</sub>, CO, FUMES EXPLOSION DATA..... N/D SENSITIVITY TO STATIC DISCHARGE... N/D SPECIAL FIRE FIGHTING PROCEDURES.... Wear standard fire fighting gear with self-contained breathing apparatus. **Reactivity Data** CHEMICAL STABILITY..... **STABLE** INCOMPATIBLE MATERIALS..... STRONG ACIDS, STRONG BASES & STRONG OXIDISING AGENTS. CONDITIONS TO AVOID..... NONE KNOWN. HAZARDOUS DECOMPOSITION PRODUCTS.. BURNING MAY PRODUCE CO AND/OR CO<sub>2</sub>.

WILL NOT OCCUR.

HAZARDOUS POLYMERIZATION......

Toxicological Properties of Product					
ROUTES OF ENTRY					
SKIN CONTACT	MAY CAUSE IRRITATION ON PROLONGED CONTACT				
SKIN ABSORPTION	NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION.				
EYE	MAY CAUSE IRRITATION				
INHALATION	MAY CAUSE HEADACHE, NAUSEA, VOMITING ANDIRRITATION OF THE				
	RESPIRATORY TRACT.				
INGESTION	MAY CAUSE ABDOMINAL DISCOMFORT OR PAIN, NAUSEA AND VOMITING.				
	MAY BE FATAL IF LARGE VOLUMES ARE SWALLOWED.				
EFFECTS OF ACUTE EXPOSURE	REFER TO ROUTE OF ENTRY.				
EFFECTS OF CHRONIC EXPOSURE	REPEATED CONTACT WITH SKIN MAY CAUSE DERMATITIS IN SENSITIVE				
INDIVIDUALS. PROLONGED INHALATION MAY PRODUCE SIGN OF CENTRAL					
NERVOUS	SYSTEM	INVOLVEMENT,	PARTICULARLY	DIZZINESS AND	
NYSTAGMUS.		,			
IRRITANCY OF PRODUCT	N/D SENSITIZATION TO MATERIAL N/D				
CARCINOGENICITY, REPRODUCTIVE EFFECTS:					
NO EVIDENCE THAT IT HAS CAUSED BIRTH DEFECTS IN HUMANS.					
TERATOGENICITY, MUTAGENICITY MINIMAL EVIDENCE OF TERATOGENICITY.					
TOXICOLOGICALLY SYNERGISTIC RODUCTS N/D					
Preventive Measures					

PERSONAL PROTECTIVE EQUIPMENT..... RUBBER GLOVES, RESPIRATOR IN ENCLOSE AREAS.

VENTILATION...... ADEQUATE VENTILATION

LEAK AND SPILL PROCEDURES....... SOAK UP WITH AN ABSORBENT MATERIAL. CLEAN WITH WATER. LET

DRY. MAY CLOG SEWERS.

WASTE DISPOSAL...... DISPOSE IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL AND

FEDERAL REGULATIONS.

HANDLING PROCEDURES AND EQUIPMENT. AVOID EYE CONTACT, REPEATED OR PROLONGED SKIN CONTACT

AND INHALING VAPOURS.

STORAGE REQUIREMENTS...... STORE AT 60-95°F (15-35°C) AND OUT OF THE SUN. USE ADEQUATE

VENTILATION TO AVOID BREATHING VAPOURS WHEN COVER IS REMOVED. PROTECT FROM FREEZING.

SPECIAL SHIPPING INFORMATION..... NOT REGULATED

#### FIRST AID MEASURES

FIRST AID PROCEDURES...

IMMEDIATELY FLUSH EYES WITH ABUNDANT WATER FOR AT LEAST 15 MINUTES, FORCIBLY HOLDING EYELIDS APART. SEEK MEDICAL ATTENTION. IN CASE OF INHALATION, REMOVE TO FRESH AIR. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN CASE OF SKIN CONTACT, REMOVE ANY CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP & WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN CASE OF INGESTION, DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

## PREPARATION DATE OF MATERIAL SAFETY DATA SHEET

PREPARED BY..... CHIEF CHEMIST

Flextile Ltd. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile ltd., assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

...FLEXTILE LTD.

N/D = NOT DETERMINED