MATERIAL SAFETY DATA SHEET 29 CFR 1910.1200 OSHA Hazard Communication Rule Format Chem-Tel 24 Hour Emergency # 1-800-255-3924 MINE SAFETY APPLIANCES COMPANY 1000 Cranberry Woods Drive Cranberry Twp. PA 16066 PHONE 724-776-8900

This product contains oxygen and nitrogen, substances subject to the Pennsylvania Worker and Community Right-To-Know Act.

# PRODUCT IDENTITY

LABEL IDENTITY - MSA P/N 710874 Calibration Check Gas, 990 ppm R - 134a in Air

CHEMICAL NAME - 1,1,1,2 - Tetrafluoroethane in Air

ADDITIONAL IDENTITIES - MSA P/N 710874 Calibration Gas 990 ppm HFC - 134a in Air

FORMULA - CF<sub>3</sub>CH<sub>2</sub>F in Air

### APPLICABLE CHEMICAL CONTENTS

NOTE: Gas under Pressure, 1000 PSIG at 70°F, and contains approx. 100 Liters Gas at Atmospheric Pressure

### PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR - Colorless, Faint hydrocarbon

Following information is for Nitrogen the main component of this gas mixture

BOILING POINT: -320.4 °F (-195.8 ° C) SPECIFIC GRAVITY (air = 1) @70°F (21.1 °C): 0.906

VAPOR PRESSURE @70°F (21.1 °C): N/A\* PERCENT VOLATILE BY VOLUME - N/A\*

GAS DENSITY @32°F (0 °C) and 1 atm: 0.072 lbs/ft<sup>3</sup> (1.153 kg/ m<sup>3)</sup>

VAPOR DENSITY (AIR = 1) - 1

SOLUBILITY IN WATER - CF<sub>3</sub>CH<sub>2</sub>F - approx. 36 cm<sup>3</sup>/100 ml (25°C)

Oxygen - 3.2 cm<sup>3</sup>/100 ml (25°C) Nitrogen - 2.3 cm<sup>3</sup>/100 ml (0°C)

\*N/A - Not Applicable

### PHYSICAL HAZARD INFORMATION

PHYSICAL HAZARD - Compressed gas, 1000 PSIG at 70°F

CONDITIONS OR MATERIALS TO AVOID - Avoid bases. Avoid powdered active metals such as aluminum, alkali metals or alkaline earth metals.

FLASH POINT - N/A

EXTINGUISHING MEDIA - This calibration gas mixture is non-flammable.

SPECIAL FIRE FIGHTING PROCEDURES - 1,1,1,2 - Tetrafluoroethane decomposes at high temperatures yielding toxic halogen compounds. Use self-contained pressure demand type breathing apparatus with full-face piece.

UNUSUAL FIRE AND EXPLOSION HAZARDS - Gas under pressure, 1000 PSIG at 70°F. Do Not Exceed 120°F.

<sup>\*</sup>suggested 1000 ppm TWA by refrigerant mfg.

#### **HEALTH HAZARDS**

HEALTH HAZARDS - No TWA has been established for 1,1,1,2 - Tetrafluoroethane by ACGIH.

SIGNS AND SYMPTOMS OF EXPOSURE: Inhalation of very high concentrations gas vapor may cause temporary alteration of the heart's electrical activity with irregular pulse, palpitations or inadequate circulation.

PRIMARY ROUTES OF ENTRY - Inhalation

TARGET ORGANS - Lungs

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE - No information.

EXPOSURE LIMITS - Not established for 1,1,1,2 - Tetrafluoroethane

CARCINOGENICITY DATA -Neither Air nor 1,1,1,2 - Tetrafluoroethane is listed by NIOSH, RTECS, IARC, NTP or OSHA.

EMERGENCY AND FIRST AID PROCEDURES - Remove victim from exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

#### SAFE HANDLING AND USE

HYGIENIC PRACTICES - Avoid breathing gas.

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate area

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust. Dispose of cylinder in accordance with local, state, and federal regulations.

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

## **CONTROL MEASURES**

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 6, June 2011.

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.