

# MATERIAL SAFETY DATA SHEET



Date Issued: 04/08/2008

MSDS No: 2108-12S

## Turbo-Coat Acrylic Coating

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Turbo-Coat Acrylic Coating**PRODUCT DESCRIPTION:** Acrylic conformal coating**PRODUCT CODE:** 2108-12S**ACTIVE INGREDIENT(S):** Acrylic Polymer (non-hazardous); n-Propyl acetate; Acetone**MANUFACTURER**

Techspray, L.P.  
1001 N.W. 1st Street  
P.O. Box 949  
Amarillo TX 79107

**Emergency Contact:** Chemtrec**Product Stewardship:** 1-800-858-4043**Service Number:** 1-800-858-4043**24 HR. EMERGENCY TELEPHONE NUMBERS****CHEMTREC (US Transportation) :** (800) 424 - 9300**CANUTEC (Canadian Transportation) :** (613) 996 - 6666**Emergency Phone :** (800) 858 - 4043

### 2. HAZARDS IDENTIFICATION

**HAZARD DESIGNATION**

"F" - Highly flammable

R11 - Highly flammable.

**EMERGENCY OVERVIEW****IMMEDIATE CONCERNS:** Flammable liquid and vapor. Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract.**POTENTIAL HEALTH EFFECTS****EYES:** Substance causes substantial eye irritation.**SKIN:** Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).**INGESTION:** Moderately toxic. May cause headaches and dizziness.**INHALATION:** Harmful if inhaled. Prolonged or repeated inhalation may cause lung damage and/or central nervous system disturbances.**SIGNS AND SYMPTOMS OF OVEREXPOSURE****EYES:** Symptoms of overexposure include: stinging, tearing, redness and pain.**SKIN:** Prolonged exposure causes redness, pain, drying and cracking of the skin.**INGESTION:** For large amounts; abdominal pain, nausea and vomiting.**INHALATION:** High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

# MATERIAL SAFETY DATA SHEET



Date Issued: 04/08/2008

MSDS No: 2108-12S

## Turbo-Coat Acrylic Coating

Chemical Name	Wt. %	CAS	EINECS
Acrylic Polymer (non-hazardous)	5 - 15		
n-Propyl acetate	20 - 40	109-60-4	2036861
n-Heptane	5 - 15	142-82-5	
Acetone	10 - 30	67-64-1	200-662-2
1-(2-Methoxy-Methyl-Ethoxy)-2-Propanol Acetate	1 - 5	88917-22-0	
1,1,1,2-Tetrafluoroethane	30 - 50	811-97-2	212-337-0

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

**SKIN:** Wash with soap and water. Get medical attention if irritation develops or persists.

**INGESTION:** Do not induce vomiting. Give milk or water. Get immediate medical attention immediately.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

### 5. FIRE FIGHTING MEASURES

**FLASHPOINT AND METHOD:** 1.4°C (35°F) TAG CC

**GENERAL HAZARD:** Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flash point.

**EXTINGUISHING MEDIA:** Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

**HAZARDOUS COMBUSTION PRODUCTS:** Smoke, fumes and oxides of carbon.

**EXPLOSION HAZARDS:** Vapors may form explosive mixture with air.

**FIRE FIGHTING PROCEDURES:** Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

**FIRE FIGHTING EQUIPMENT:** As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Absorb the liquid and scrub the area with detergent and water. Pick up wash liquid with additional absorbent and place in a disposable container. Do not flush to sewer.

**GENERAL PROCEDURES:** Forms smooth, slippery surfaces on floors, posing an accident risk. Wear a self-contained breathing apparatus and appropriate personal protective equipment. (See Exposure Controls/Personal Protection Section). Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust.



# MATERIAL SAFETY DATA SHEET

Date Issued: 04/08/2008

MSDS No: 2108-12S

## Turbo-Coat Acrylic Coating

### 7. HANDLING AND STORAGE

**HANDLING:** Ground and bond containers when transferring material.

**STORAGE:** Store in a cool place in original container and protect from sunlight. Keep away from heat and flame.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
n-Propyl acetate	TWA		200 ppm		200 ppm		
	STEL		250 ppm		250 ppm		
n-Heptane	TWA	400 ppm	1600 mg/m <sup>3</sup>	400 ppm			
	STEL	500 ppm	2000 mg/m <sup>3</sup>	500 ppm			
Acetone	TWA	750 ppm <sup>[1]</sup>	1800 mg/m <sup>3</sup> <sup>[1]</sup>	750 ppm	1780 mg/m <sup>3</sup>	NL ppm	NL mg/m <sup>3</sup>
	STEL	1000 ppm	2400 mg/m <sup>3</sup>	1000 ppm	2380 mg/m <sup>3</sup>	NL ppm	NL mg/m <sup>3</sup>
1,1,1,2-Tetrafluoroethane	TWA	NE		NE		1,000 ppm <sup>[2]</sup>	<sup>[2]</sup>

#### OSHA TABLE COMMENTS:

1. NL = Not Listed

2. \* (AEL)=Acceptable Exposure Limit as established by the manufacture

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

#### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear safety glasses with side shields (or goggles) and a face shield.

**SKIN:** The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Viton, Solvex, Butyl, Buna, Neoprene.

**RESPIRATORY:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**WORK HYGIENIC PRACTICES:** Avoid contact with eyes. Avoid fume inhalation. Limit skin contact.

**OTHER USE PRECAUTIONS:** Emergency shower and eyewash facility should be in close proximity.

### 9. PHYSICAL AND CHEMICAL PROPERTIES



# MATERIAL SAFETY DATA SHEET

Date Issued: 04/08/2008

MSDS No: 2108-12S

## Turbo-Coat Acrylic Coating

Chemical Name	Boiling Point (°C)	Freezing Point (°C)	Solubility in Water	Specific Gravity
1,1,1,2-Tetrafluoroethane	-26.4	-101	NEGLIGIBLE	1.21

**PHYSICAL STATE:** Liquid**ODOR:** Characteristic odor.**APPEARANCE:** Clear, Colorless liquid**PERCENT VOLATILE:** 93.4 at 25°C (68°F)**VAPOR PRESSURE:** 14.52 mmHg@20C (VOC Composite Vapor Pressure)**VAPOR DENSITY:** > 1 (Air=1)**BOILING POINT:** 39.4°C (103°F)**Notes:** Initial boiling point**FLASHPOINT AND METHOD:** 1.4°C (35°F) TAG CC**SOLUBILITY IN WATER:** Negligible**EVAPORATION RATE:** > 1 (n-Butyl Acetate=1)**DENSITY:** 0.834 at 25°C (77°F)**VISCOSITY #1:** 10 to 20 Centipoise at 25°C (77°F)**(VOC):** 33.240 % by weight

## 10. STABILITY AND REACTIVITY

**STABILITY:** Stable under normal conditions.**POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** Heat, flames, ignition sources, and incompatibles.**INCOMPATIBLE MATERIALS:** Metals. Acidic conditions. Oxidizing materials.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
n-Propyl acetate	9370 mg/kg	> 20 ml/kg	8000 ppm
Acetone	5800 mg/kg	20 g/kg	50100 ppm
1,1,1,2-Tetrafluoroethane			> 500000 ppm



# MATERIAL SAFETY DATA SHEET

Date Issued: 04/08/2008

MSDS No: 2108-12S

## Turbo-Coat Acrylic Coating

**EYES:** 20 mg**Notes:** Irritation eye rabbit, severe**DERMAL LD<sub>50</sub>:** > 20 mg/kg (rabbit)**ORAL LD<sub>50</sub>:** 9370 mg/kg (rat)**INHALATION LC<sub>50</sub>:** 8000 ppm, 4-hour**EYE EFFECTS:** High vapor concentrations may cause moderate to severe eye irritation.**SKIN EFFECTS:** The mixture is a mild to severe skin irritant but is not a skin sensitizer in animals.

### CARCINOGENICITY

Chemical Name	NTP Status	IARC Status	OSHA Status
n-Propyl acetate	NOT LISTED	NOT LISTED	NOT LISTED
Acetone	NOT LISTED	NOT LISTED	NOT LISTED
1,1,1,2-Tetrafluoroethane	NOT LISTED	NOT LISTED	NOT LISTED

**IARC:** NOT listed**NTP:** NOT listed**OSHA:** NOT listed

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** Oxygen Demand Data- (information for n-Propyl Acetate) BOD-5: 134 g oxygen/g ThOD: 2.04 g oxygen/g**ECOTOXICOLOGICAL INFORMATION:** Rainbow trout LC<sub>50</sub>=5540 mg/L/96H, Static conditions, 11-13 degrees C, Fathead Minnow LC<sub>50</sub>=7280 - 8120 mg/L/96H Flow-through conditions, Bluegill LC<sub>50</sub> = 8300 mg/L/96H

## 13. DISPOSAL CONSIDERATIONS

**GENERAL COMMENTS:** Dispose of in a manner consistent with federal, state, and local regulations.

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** CONSUMER COMMODITY ORM-D**UN/NA NUMBER:** NA**PACKING GROUP:** NA

### ROAD AND RAIL (ADR/RID)

**KEMLER NUMBER:** UN1950



# MATERIAL SAFETY DATA SHEET

Date Issued: 04/08/2008

MSDS No: 2108-12S

## Turbo-Coat Acrylic Coating

**HAZARD CLASS:** 2.1

### AIR (ICAO/IATA)

**SHIPPING NAME:** CONSUMER COMMODITY ID8000

**UN/NA NUMBER:** ID8000

**PRIMARY HAZARD CLASS/DIVISION:** 9

**PACKING GROUP:** NA

**NOTE:** Domestic shipments only. When shipping International contact TechSpray shipping department.

### VESSEL (IMO/IMDG)

**SHIPPING NAME:** AEROSOLS IN LIMITED QUANTITIES OF CLASS 2

**UN/NA NUMBER:** UN1950

**PRIMARY HAZARD CLASS/DIVISION:** 2.1

**PACKING GROUP:** NA

**NOTE:** Page 2102

## 15. REGULATORY INFORMATION

### UNITED STATES

#### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**311/312 HAZARD CATEGORIES:** IMMEDIATE / DELAYED

**FIRE:** Yes **ACUTE:** Yes **CHRONIC:** Yes

#### EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt. %	CAS
Acetone	10 - 30	67-64-1

#### CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

**CERCLA REGULATORY:** Acetone (67-64-1)

Chemical Name	Wt. %	CERCLA RQ
Acetone	10 - 30	5000 lbs.

**REPORTABLE SPILL QUANTITY:** 5000 lbs.

#### TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
n-Propyl acetate	109-60-4
Acetone	67-64-1
1,1,1,2-Tetrafluoroethane	811-97-2

**TSCA STATUS:** All chemicals in this product are listed in the TSCA inventory.

### CLEAN AIR ACT

# MATERIAL SAFETY DATA SHEET



Date Issued: 04/08/2008

MSDS No: 2108-12S

## Turbo-Coat Acrylic Coating

Chemical Name	Wt. %	CAS
1,1,1,2-Tetrafluoroethane	30 - 50	811-97-2

### OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

#### 29 CFR 1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS

**CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.

**CALIFORNIA PROPOSITION 65:** This product does not contain any chemicals known to the State of California to cause cancer.

**RCRA STATUS:** U002 D001

**OSHA HAZARD COMM. RULE:** Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### CANADA

**WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

**WHMIS CLASS:** Class A, B5, D2B (Aerosol, Flammable Aerosol, Toxic Materials)

### EUROPEAN COMMUNITY

#### EEC LABEL SYMBOL AND CLASSIFICATION



"F" - Highly flammable  
R11 - Highly flammable.

**GENERAL COMMENTS:** 1,1,1,2-tetrafluoroethane is subject to U.S. Environmental Agency Clean Air Act Regulations, (40CFR Part 82).

### 16. OTHER INFORMATION


**APPROVED BY:** Pierce A. Pillon      **TITLE:** Chemist

**REVISION SUMMARY:** New MSDS

#### HMIS RATING

<b>HEALTH:</b>	<b>1</b>
<b>FLAMMABILITY:</b>	<b>3</b>
<b>PHYSICAL HAZARD:</b>	<b>1</b>
<b>PERSONAL PROTECTION:</b>	

#### NFPA CODES



**MANUFACTURER DISCLAIMER:** To the best of our knowledge, the information contained herein is accurate. However, neither Tech Spray, L.P., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be

# MATERIAL SAFETY DATA SHEET



Date Issued: 04/08/2008  
MSDS No: 2108-12S

## Turbo-Coat Acrylic Coating

---

used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.