

Material Safety Data Sheet

ITW Texwipe[®] Non- Sterile 70% IPA

1. Product and company identification

Product name	: ITW Texwipe [®] Non- Sterile 70% IPA
Material uses	: For use in Environments in cleaning and/or dispensing solutions.
Code	: TX167
Supplier/Manufacturer	: ITW Texwipe 1210 South Park Drive Kernersville, NC 27284 Tel : 1-(336) 996-7046 (Toll Free : 1-(800) 839-9473) Fax : 1-(336) 996-6563 Web : www.texwipe.com
MSDS authored by	: KMK Regulatory Services Inc.
In case of emergency	: CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3887

2. Hazards identification

Emergency overview

Physical state	: Liquid. [Clear.]
Color	: Colorless.
Odor	: Alcohol-like. [Strong]
Signal word	: WARNING !
Hazard statements	: FLAMMABLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.
Precautionary measures	: Do not breathe vapor or mist. Use only with adequate ventilation. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Keep container tightly closed. Wash thoroughly after handling.
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Routes of entry	: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation	: Irritating to respiratory system.
Ingestion	: No known significant effects or critical hazards.
Skin	: Irritating to skin.
Eyes	: Irritating to eyes.

Potential chronic health effects

Chronic effects	: Contains material that may cause target organ damage, based on animal data.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Target organs	: Contains material which may cause damage to the following organs: central nervous system (CNS).

2. Hazards identification

Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Ingestion** : No specific data.
- Skin** : Adverse symptoms may include the following:
irritation
redness
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness

- Medical conditions aggravated by overexposure** : Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation.

See toxicological information (Section 11)

3. Composition/information on ingredients

United States

Name	CAS number	%
Propan-2-ol	67-63-0	70

Canada

Name	CAS number	%
Propan-2-ol	67-63-0	70

Mexico

Name	CAS number	UN number	%	IDLH	Classification			
					H	F	R	Special
Propan-2-ol	67-63-0	UN1219	70	2000 ppm	1	3	0	-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 20 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product : Flammable liquid.

Extinguishing media

Suitable : Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable : Do not use water jet.

Special exposure hazards : Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions : Use suitable protective equipment. Eliminate all ignition sources.

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Methods for cleaning up

Spill : Place spilled material in an appropriate container for disposal.

7. Handling and storage

Handling : Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. Wash thoroughly after handling.

Storage : Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
Propan-2-ol	ACGIH TLV (United States, 2/2010). STEL: 400 ppm 15 minute(s). TWA: 200 ppm 8 hour(s). NIOSH REL (United States, 6/2009). STEL: 1225 mg/m ³ 15 minute(s). STEL: 500 ppm 15 minute(s). TWA: 980 mg/m ³ 10 hour(s). TWA: 400 ppm 10 hour(s). OSHA PEL (United States, 6/2010). TWA: 980 mg/m ³ 8 hour(s). TWA: 400 ppm 8 hour(s).

Canada

<u>Occupational exposure limits</u>		TWA (8 hours)			STEL (15 mins)			Ceiling			Notations
Ingredient	List name	ppm	mg/m ³	Other	ppm	mg/m ³	Other	ppm	mg/m ³	Other	
Propan-2-ol	US ACGIH 2/2010	200	-	-	400	-	-	-	-	-	
	AB 4/2009	200	492	-	400	984	-	-	-	-	
	BC 9/2010	200	-	-	400	-	-	-	-	-	
	ON 7/2010	200	-	-	400	-	-	-	-	-	
	QC 6/2008	400	983	-	500	1230	-	-	-	-	

Mexico

Occupational exposure limits

8. Exposure controls/personal protection

Ingredient	Exposure limits
Propan-2-ol	NOM-010-STPS (Mexico, 9/2000). LMPE-CT: 1225 mg/m ³ 15 minute(s). LMPE-CT: 500 ppm 15 minute(s). LMPE-PPT: 980 mg/m ³ 8 hour(s). LMPE-PPT: 400 ppm 8 hour(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory : A respirator is not needed under normal and intended conditions of product use.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Rubber gloves.

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Recommended: Safety glasses.

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Body: Recommended: Lab coat.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state	: Liquid. [Clear.]
Flash point	: Closed cup: 21°C (69.8°F) [Tagliabue.]
Burning time	: Not applicable.
Burning rate	: Not applicable.
Auto-ignition temperature	: Not available.
Flammable limits	: Not available.
Color	: Colorless.
Odor	: Alcohol-like. [Strong]
Taste	: Not available.
Molecular weight	: Not applicable.
Molecular formula	: Not applicable.
pH	: Not available.

9. Physical and chemical properties

Boiling/condensation point	: Not available.
Melting/freezing point	: Not available.
Critical temperature	: Not available.
Relative density	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Volatility	: Not available.
Odor threshold	: Not available.
Evaporation rate	: Not available.
SADT	: Not available.
Viscosity	: Not available.
Ionicity (in water)	: Not available.
Dispersibility properties	: Not available.
Solubility	: Not available.
Physical/chemical properties comments	: Not available.

10. Stability and reactivity

Chemical stability	: The product is stable.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propan-2-ol	LD50 Dermal LD50 Oral	Rabbit Rat	12800 mg/kg 5000 mg/kg	- -

Chronic toxicity

There is no data available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Propan-2-ol	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	10 mg	-

Sensitizer

Skin : There is no data available.

Respiratory : There is no data available.

Carcinogenicity

There is no data available.

Classification

11. Toxicological information

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Propan-2-ol	A4	3	-	-	-	None.

Mutagenicity

There is no data available.

Teratogenicity

There is no data available.

Reproductive toxicity

There is no data available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Propan-2-ol	Acute LC50 1400000 to 1950000 ug/L Marine water Acute LC50 >1400000 ug/L	Crustaceans - Crangon crangon Fish - Gambusia affinis - 20 to 30 mm	48 hours 96 hours

Persistence/degradability

There is no data available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	-	ORM-D	-	-		-
TDG Classification	UN1219	ISOPROPYL ALCOHOL solution	3	II		- Limited Quantity Exemption

14. Transport information

Mexico Classification	UN1219	ISOPROPYL ALCOHOL solution	3	II		- Limited Quantity Exemption
IMDG Class	UN1219	ISOPROPYL ALCOHOL solution	3	II		- Limited Quantity Exemption
IATA-DGR Class	UN1219	ISOPROPYL ALCOHOL solution	3	II		- Limited Quantity Exemption

PG* : Packing group

Exemption to the above classification may apply.

AERG : 129

15. Regulatory information

United States

HCS Classification : Flammable liquid
Irritating material
Target organ effects

U.S. Federal regulations : **TSCA 8(a) IUR Exempt/Partial exemption**: Not determined
United States inventory (TSCA 8b): All components are listed or exempted.
SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: Propan-2-ol
SARA 311/312 MSDS distribution - chemical inventory - hazard identification:
Propan-2-ol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Propan-2-ol	67-63-0	70
Supplier notification	Propan-2-ol	67-63-0	70

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: Propan-2-ol

New York : None of the components are listed.

New Jersey : The following components are listed: Propan-2-ol

15. Regulatory information

Pennsylvania : The following components are listed: Propan-2-ol

California Prop. 65

No products were found.

Canada

WHMIS (Canada) : Class B-2: Flammable liquid
Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI : The following components are listed: Isopropyl alcohol


CEPA Toxic substances : None of the components are listed.

Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico

Classification :



16. Other information

Label requirements : FLAMMABLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.) : **Health** : 1 * **Flammability** : 3 **Physical hazards** : 0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) : **Health** : 1 **Flammability** : 3 **Instability** : 0

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue mm/dd/yyyy : 05/15/2012

Date of previous issue : 09/15/2011

Version : 2

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.