

KEM CANADA MFG.
4 BLAIR DRIVE
BRAMPTON, ONTARIO
L6T 2H5
TEL# (905) 456-9444

EMERGENCY # CANUTEC (613) 996-6666
"USE IN CASE OF CHEMICAL EMERGENCY ONLY"

W.H.M.I.S. CLASSIFICATION: D2B

MATERIAL REFERENCE NO: 780700

SECTION I - MATERIAL IDENTIFICATION AND USE

	_	-					
MATERIAL NAME/I.D.:	KEMTREET	ORGA	NIQUE				
CHEMICAL NAME : NOT	APPLICABLE		CHEMICAL	FAMILY	:ALKALINE	BLEND	
CHEMICAL FORMULA: MI	XTURE		MOLECULAR	WEIGHT	: MIXTURE		
SYNONYMS: NONE							

|MATERIAL USE: CORROSION AND SCALE PREVENTION

#### SECTION II - HAZARDOUS INGREDIENTS OF MATERIAL

HAZARDOUS   INGREDIENTS	APPROX.	TLV PPM	C.A.S. NUMBERS	LD 50     ORAL, RAT
HYDROXYPHOSPHONO   ACETIC ACID	1.0-5.0	NO DATA	   23783-26-8 	2750 MG/KG   
SODIUM TOLYTRIAZOLE	1.0-5.0	NO DATA	   64665-57-2 	920 MG/KG     920 MG/KG     (MALE)
  MALEIC ANHYDRIDE   POLYMER WITH ETHYL	1.0-5.0	NO DATA	   113221-69-5 	3870 MG/KG
ACRYLATE AND VINYL ACETATE, HYDROLYSED				

SECTION III - PHYSICAL DATA FOR MATERIAL

PHYSICAL STATE: LIQUID						
ODOUR AND APPEARANCE: CLEAR, AMBER LIQUID, LOW ODOUR.						
ODOUR THRESHOLD (PPM)   NOT AVAILABLE	SPECIFIC GRAVITY 1.018	VAPOUR PRESSURE (MM)				
VAPOUR DENSITY (AIR=1)    NOT ESTABLISHED	EVAPORATION RATE (WATER=1) APPROX. 1	SOLUBILITY IN WATER    (20 ø C) SOLUBLE				
BOILING POINT (C)   APPROX. 101	FREEZING POINT (C) APPROX2 C	% VOLATILE (BY WEIGHT)    >94				
ph ( CONCENTRATED )     10.5-11.0	DENSITY (G/ML) NOT APPLICABLE	COEF.OF WATER/OIL DISTR    NOT AVAILABLE				



MATERIAL REFERENCE NO: 780700 SECTION IV - FIRE AND EXPLOSION HAZARD OF MATERIAL \_\_\_\_\_\_ |FLAMMABILITY: NON-FLAMMABLE IF YES, UNDER WHICH CONDITIONS: \_\_\_\_\_\_ MEANS OF EXTINCTION: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM. \_\_\_\_\_ SPECIAL PROCEDURES: WEAR FULL PROTECTIVE GEAR INCLUDING SELF-CONTAINED BREATHING APPARATUS. | FLASH POINT (C) AND METHOD: NONE (TCC) HAZARDOUS COMBUSTION PRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN, PHOSPHOROUS OXIDES. \_\_\_\_\_\_ UPPER EXPLOSION LIMIT | LOWER EXPLOSION LIMIT | AUTOIGNITION TEMP(C)| NOT APPLICABLE | NOT APPLICABLE | NOT APPLICABLE -----EXPLOSION DATA SENSITIVITY RATE OF BURNING EXPLOSIVE POWER TO CHEMICAL IMPACT NOT AVAILABLE NOT APPLICABLE NOT AVAILABLE .\_\_\_\_\_ SENSITIVITY TO STATIC DISCHARGE: NOT AVAILABLE SECTION V - REACTIVITY DATA \_\_\_\_\_\_ CHEMICAL STABILITY: STABLE IF NO, UNDER WHICH CONDITIONS: INCOMPATIBILITY TO OTHER SUBSTANCES: YES IF SO, WHICH ONES: ACIDS, STRONG OXIDIZERS. REACTIVITY AND UNDER WHAT CONDITIONS: NOT ESTABLISHED HAZARDOUS POLYMERIZATION WILL NOT OCCUR. | HAZARDOUS DECOMPOSITION PRODUCTS: THERMAL DECOMPOSITIN GIVES OFF OXIDES OF CARBON, NITROGEN AND PHOSPHOROUS. SECTION VI - HEALTH HAZARD DATA ROUTE OF ENTRY: \_\_\_\_\_\_ EYE CONTACT: YES



MATERIAL REFERENCE NO: 780700

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:

EYES-CONTACT CAN CAUSE IRRITATION, POSSIBLE EYE DAMAGE.

SKIN-CONTACT CAN CAUSE IRRITATION.

-----

INHALATION-BREATHING OF MIST MAY IRRITATE THE NOSE, THROAT AND LUNGS INGESTION-MAY CAUSE GASTRIC DISTURBANCES, DIARRHEA. INGESTION OF LARGE AMOUNTS MAY CAUSE GASTROINTESTINAL TRACT, KIDNEY AND LIVER DAMAGE.

EFFECTS OF CHRONIC EXPOSURE TO MATERIAL:

EYES-REPEATED OR PROLONGED CONTACT MAY CAUSE PERMANENT EYE DAMAGE.

.\_\_\_\_\_

|LD 50 OF MATL. |LC 50 OF MATL. |EXPOSURE LIMIT(S)|IRRITANCY OF MATL|
| NOT AVAILABLE | NOT AVAILABLE | NOT AVAILABLE |

| SENSITIZATION OF MATERIAL | SYNERGISTIC MATERIALS | SKIN SENSITIZER | NOT AVAILABLE

|CARCINOGENICITY, REPRODUCTIVE EFFECTS, TERATOGENICITY, MUTAGENICITY | NONE KNOWN

' -----

#### SECTION VII - PREVENTIVE MEASURES

\_\_\_\_\_\_

### PERSONAL PROTECTIVE EQUIPMENT:

GLOVES: IMPERVIOUS

RESPIRATORY: APPROVED DUST/MIST RESPIRATOR WHEN MISTING OCCURS

EYE: CHEMICAL GOGGLES FOOTWEAR: IMPERMEABLE

CLOTHING: IMPERMEABLE

OTHER: EYE WASH AND SAFETY SHOWER

ENGINEERING CONTROLS (EG VENTILATION, ENCLOSED PROCESS): GENERAL ROOM VENTILATION OR LOCAL EXHAUST TO CONTROL AIRBORNE CONTAMINANTS.

|LEAK AND SPILL PROCEDURE: CONTAIN SPILL. WEAR RECOMMENDED SAFETY | EQUIPMENT. TRANSFER TO SUITABLE CONTAINER FOR REUSE OR DISPOSAL. | ABSORB REMAINING MATERIAL ONTO INERT ABSORBANT AND SCOOP INTO | DISPOSAL CONTAINER.

| WASTE DISPOSAL: DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

\_\_\_\_\_\_\_



MATERIAL REFERENCE NO: 780700

SECTION VIII - FIRST AID MEASURES

\_\_\_\_\_\_

#### PROCEDURES:

EYES-FLUSH WITH RUNNING WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

SKIN-FLUSH AFFECTED AREA WITH RUNNING WATER FOR 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. LAUNDER CLOTHING BEFORE REUSE.

INHALATION-REMOVE TO FRESH AIR.

INGESTION-DO NOT INDUCE VOMITING. RINSE MOUTH WITH WATER. GIVE 1-2 GLASSES OF WATER TO DILUTE CONTENTS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS OR CONVULSING PERSON. GET IMMEDIATE MEDICAL ATTENTION

SOURCES USED: RAW MATERIAL SUPPLIER'S MATERIAL SAFETY DATA SHEETS

\_\_\_\_\_

ADDITIONAL INFORMATION: NONE

-----

#### SECTION IX - TDG SHIPPING INFORMATION

					_
	SHIPPING NAME	CLASS	UN NO.	PACKING GROUP	
ĺ	NOT REGULATED				ĺ
		1 1		1	1

| HANDLING PROCEDURES AND EQUIPMENT: AVOID CONTACT WITH EYES, SKIN | AND CLOTHING. WASH THOROUGHLY AFTER HANDLING.

\_\_\_\_\_

STORAGE REQUIREMENTS: STORE IN A COOL, DRY AREA. KEEP FROM FREEZING. KEEP CONTAINER CLOSED WHEN NOT IN USE.

SPECIAL SHIPPING INFORMATION: HEATED

DIECTAL DITTING INFORMATION. HEATED

# SECTION X - HMIS HAZARD RATING INFORMATION

FLAMMABILITY	REACTIVITY	HEALTH
0	0	2

#### SECTION XI - PREPARATION DATE OF MSDS

.

| PREPARED BY: TECHNICAL DEPARTMENT | TELEPHONE # (905) 456-9444

REVIEWED: JANUARY 23, 2003

### DISCLAIMER:

THE INFORMATION CONTAINED HEREIN IS COMPILED FROM SOURCES BELIEVED TO BE RELIABLE. THE MANNER AND CONDITIONS OF USE AND HANDLING MAY INVOLVE OTHER AND ADDITIONAL CONSIDERATIONS. WE ACCEPT NO RESPONSIBILTY FOR THE ACCURACY, SUFFICIENCY, RELIABILITY OR FOR ANY LOSS OR INJURY RESULTING FROM THE USE OF THE INFORMATION.