

MATERIAL SAFETY DATA SHEET
29 CFR 1910.1200 OSHA Hazard
Communication Rule Format
Chem-Tel 24 Hour Emergency # 1-800-255-3924

MINE SAFETY APPLIANCES COMPANY
P.O. Box 426
Pittsburgh, PA 15230
PHONE (412) 967-3000

This product contains isobutene, oxygen and nitrogen, substances subject to the Pennsylvania Worker and Community Right-To-Know Act.

PRODUCT IDENTITY

LABEL IDENTITY - MSA P/N 815704 Calibration Check Gas, 100 ppm isobutylene in air
CHEMICAL NAME - Isobutylene, Oxygen, Nitrogen Mixture
ADDITIONAL IDENTITIES - MSA P/N 815704 calibration gas, MSA P/N 815704 Squirt Gas
FORMULA - C₄H₈ in Air

APPLICABLE CHEMICAL CONTENTS

| | <u>ppm</u> | <u>TWA</u> |
|--------------------------|------------|------------|
| Isobutene (CAS 115-11-7) | 100 | None |
| Air | Balance | None |

NOTE: Gas under pressure, 155 PSIG at 70°F, Approx. 11 liters gas at atmospheric pressure.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR - Colorless gas, faint odor
BOILING POINT - N/A
VAPOR PRESSURE - N/A
VAPOR DENSITY (AIR = 1) - > 1
SOLUBILITY IN WATER - Isobutylene - Insoluble
Oxygen - 3.2 cm³/100 ml (25°C)
Nitrogen - 2.3 cm³/100 ml (0°C)
SPECIFIC GRAVITY (H₂O = 1) - N/A
PERCENT VOLATILE BY VOLUME - N/A

N/A - Not Applicable

PHYSICAL HAZARD INFORMATION

PHYSICAL HAZARD - Compressed Gas, 155 PSIG at 70°F
CONDITIONS OR MATERIALS TO AVOID - None
FLASH POINT - N/A
LEL - N/A
UEL - N/A
EXTINGUISHING MEDIA - This calibration gas mixture is not flammable.
SPECIAL FIRE FIGHTING PROCEDURES - See next item.
UNUSUAL FIRE AND EXPLOSION HAZARDS - Gas under pressure, 155 PSIG at 70°F. Do not exceed 120°F.

HEALTH HAZARDS

HEALTH HAZARDS - None Known for 100 ppm Isobutylene in Air. Isobutylene Inhalation Rat LC₅₀: 620 Gm/M³/4H. Isobutylene Inhalation Mouse LC₅₀: 415 Gm/M³/2H.

SIGNS AND SYMPTOMS OF EXPOSURE - N/A to this gas mixture.

PRIMARY ROUTES OF ENTRY - Inhalation

TARGET ORGANS - No information. Isobutylene is an asphyxiant and a weak anesthetic.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE - No information

EXPOSURE LIMITS - None (ACGIH 2005)

CARCINOGENICITY DATA - Component gases are not listed by NIOSH RTECS, OSHA, NTP or IARC.

EMERGENCY AND FIRST AID PROCEDURES - None

SAFE HANDLING AND USE

HYGIENIC PRACTICES - Avoid breathing gas

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate area

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust. Dispose of cylinder in accordance with local, state and federal regulations.

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

CONTROL MEASURES

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - None

WORK PRACTICES - Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 5, June 2005.

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users assume all risks in handling, using or storing this product.