



Safety Data Sheet

Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% - VOC BULK

SDS ID: 820076B

*** Section 1 - Identification ***

Product Identifier

SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER <45% VOC - BULK

Product Code

32071, 32073

Synonyms

None

Recommended Use

Non-chlorinated brake cleaner. If this product is used in combination with other products, refer to the Safety Data Sheets for those products.

Restrictions on Use

THIS PRODUCT IS NOT FOR SALE OR USE IN THE STATE OF CALIFORNIA.

Manufacturer Information

Safety-Kleen Systems, Inc.
2600 North Central Expressway
Suite 400
Richardson, TX 75080

Phone: 1-800-669-5740

www.safety-kleen.com

Emergency # 1-800-468-1760

Issue Date

February 4, 2015

Supersedes Issue Date

August 23, 2011

Original Issue Date

August 23, 2011

*** Section 2 - Hazard(s) Identification ***

Classification in Accordance with 29 CFR 1910.1200.

Flammable Liquids, Category 2

Acute Toxicity (Oral), Category 4

Skin Corrosion / Irritation, Category 2

Eye Damage / Irritation, Category 2A

Toxic to Reproduction, Category 1B

Specific Target Organ Toxicity - Single Exposure, Category 1 (central nervous system, eyes, systemic toxicity, brain, liver, and blood)

Specific Target Organ Toxicity - Single Exposure, Category 3 (respiratory system and central nervous system)

Specific Target Organ Toxicity - Repeated Exposure, Category 2 (central nervous system and kidneys)

Aspiration Hazard, Category 1

Hazardous to the aquatic environment - acute hazard, Category 3

GHS LABEL ELEMENTS**Symbol(s)****Signal Word**

DANGER!

Safety Data Sheet

Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% VOC - BULK

SDS ID: 820076B

Hazard Statement(s)

Highly flammable liquid and vapor.
Harmful if swallowed.
Causes skin irritation and serious eye irritation.
May damage fertility or the unborn child.
Causes damage to central nervous system, eyes, and systemic toxicity
May cause respiratory irritation and drowsiness or dizziness.
May cause damage to central nervous system and kidneys through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
Harmful to aquatic life.

Precautionary Statement(s)

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Wear protective gloves/protective clothing/eye protection/face protection. Keep container tightly closed. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Do not breathe vapor or mist. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid release to the environment.

Response

In case of fire: Use carbon dioxide, alcohol resistant foam, regular dry chemical, and water spray for extinction. IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal

Dispose of in accordance with all applicable federal, state and local regulations.

Hazard(s) Not Otherwise Classified

None known.

*** Section 3 - Composition / Information on Ingredients ***

CAS	Component	Percent
67-64-1	Acetone	50-60
108-88-3	Toluene	20-30
67-56-1	Methyl alcohol	20-30

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Ketones, liquid, n.o.s.

*** Section 4 - First Aid Measures ***

Description of Necessary Measures

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Safety Data Sheet

Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% VOC - BULK

SDS ID: 820076B

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most Important Symptoms/Effects

Acute

Harmful if swallowed, skin irritation, severe eye irritation, respiratory tract irritation, central nervous system damage, eye damage, systemic toxicity, Aspiration hazard

Delayed

Reproductive effects, central nervous system damage, kidney damage

Indication of Immediate Medical Attention and Special Treatment Needed, If Needed

IF exposed: Call a POISON CENTER or doctor/physician. Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

*** Section 5 - Fire-Fighting Measures ***

Suitable Extinguishing Media

Carbon dioxide, alcohol-resistant foam, dry chemical, or water spray.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor Fire may produce irritating, poisonous and/or corrosive fumes. Vapors may cause drowsiness and dizziness. Vapors may form explosive mixture with air. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Runoff may create fire or explosion hazard. Containers may rupture or explode. Empty containers may contain product residue. Products are not sensitive to mechanical impact. Product may be sensitive to static discharge, which could result in fire or explosion.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce formaldehyde, and formic acid.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Fire Fighting Measures

Keep storage containers cool with water spray. Move container from fire area if it can be done without risk. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile). Stay upwind and keep out of low areas. Dike for later disposal.

NFPA Ratings: Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

Safety Data Sheet

Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% VOC - BULK

SDS ID: 820076B

Methods and Materials for Containment and Clean Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **Section 8: Exposure Controls/Personal Protection**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal. Isolate hazard area. There may be specific federal regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see **Section 15: Regulatory Information**.

* * * Section 7 - Handling and Storage * * *

Precautions for Safe Handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Wear protective gloves/protective clothing/eye protection/face protection. Keep container tightly closed. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment.

Conditions for Safe Storage, Including Any Incompatibilities

Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Empty product containers may retain product residue and can be dangerous. Store containers below 120°F (49°C) Protect from sunlight. See **Section 14: Transportation Information** for Packing Group information.

Incompatibilities

Acids, alkalies, oxidizing agencies, reducing agents, reactive halogens, or reactive metals.

Safety Data Sheet

Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% VOC - BULK

SDS ID: 820076B

*** Section 8 - Exposure Controls / Personal Protection ***

Component Exposure Limits

Acetone (67-64-1)

ACGIH: 500 ppm TWA
750 ppm STEL

OSHA Final: 1000 ppm TWA; 2400 mg/m³ TWA
OSHA Vacated: 750 ppm TWA; 1800 mg/m³ TWA
2400 mg/m³ STEL (The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors); 1000 ppm STEL

NIOSH: 250 ppm TWA; 590 mg/m³ TWA

Methyl alcohol (67-56-1)

ACGIH: 200 ppm TWA
250 ppm STEL
Skin - potential significant contribution to overall exposure by the cutaneous route

OSHA Final: 200 ppm TWA; 260 mg/m³ TWA
OSHA Vacated: 200 ppm TWA; 260 mg/m³ TWA
250 ppm STEL; 325 mg/m³ STEL
Prevent or reduce skin absorption

NIOSH: 200 ppm TWA; 260 mg/m³ TWA
250 ppm STEL; 325 mg/m³ STEL
Potential for dermal absorption

Toluene (108-88-3)

ACGIH: 20 ppm TWA
OSHA Final: 200 ppm TWA
300 ppm Ceiling
OSHA Vacated: 100 ppm TWA; 375 mg/m³ TWA
150 ppm STEL; 560 mg/m³ STEL
NIOSH: 100 ppm TWA; 375 mg/m³ TWA
150 ppm STEL; 560 mg/m³ STEL

Appropriate Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits. Where explosive mixtures may be present, equipment safe for such locations should be used.

Individual Protective Measures, such as Personal Protective Equipment

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, gloves, and lab coat or apron.

Eyes/Face Protection

Safety glasses with side shields should be worn at a minimum. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Contact lens use is not recommended.

Safety Data Sheet

Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% VOC - BULK

SDS ID: 820076B

Skin Protection

Where skin contact is likely, wear laminate (Ansell Edmont Barrier®, North Silver Shield®, Safety 4 4h®) or equivalent protective gloves; use of natural rubber (latex), polyvinyl chloride (PVC), neoprene or equivalent gloves is not recommended.

Respiratory Protection

Use NIOSH air-certified, air-supplied respirators (self-contained breathing apparatus or air-line) respiratory protective equipment when concentration of methanol may exceed applicable exposure limits. Otherwise, use NIOSH-certified P- or R-series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

*** Section 9 - Physical & Chemical Properties ***

Appearance/Odor : Liquid, clear and colorless,
mild odor

pH: Not applicable

Boiling Point: 271 °F (133 °C)

Odor Threshold: Not available

Solubility (H2O): 75% (approximately)

Melting Point: Not available.

Density: 7 LB/US gal (840 g/L)

Specific Gravity: 0.82 (water = 1)

Evaporation Rate: Not available

Octanol/H2O Coeff.: Not available

Auto Ignition Temperature: 385 °C (725 °F) minimum
(approximately)

LFL: 1.2 VOL% (Lowest
Component)

Flash Point: Less than -4°F (-20°C) Tag
Closed Cup

UFL: 7.1 VOL% (Lowest
Component)

Vapor Density: 2.0 (air = 1) maximum
(approximately)

Vapor Pressure: Not available.

Other Property Information

No information is available.

*** Section 10 - Stability & Reactivity ***

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures. Avoid heat, sparks, or flame.

Possibility of Hazardous Reactions

Will not polymerize under normal temperatures and pressures.

Conditions To Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Hazardous Decomposition Products

None under normal temperatures and pressures.

*** Section 11 - Toxicological Information ***

Toxicity Data and Information

Component Analysis - LD50/LC50

Acetone (67-64-1)

Inhalation LC50 Rat 50100 mg/m3 8 h

Safety Data Sheet

Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% VOC - BULK

SDS ID: 820076B

Methyl alcohol (67-56-1)

Inhalation LC50 Rat 22500 ppm 8 h; Oral LD50 Rat 6200 mg/kg

Toluene (108-88-3)

Dermal LD50 Rabbit 12000 mg/kg; Inhalation LC50 Rat 12.5 mg/L 4 h; Oral LD50 Rat 2600 mg/kg

Information on Likely Routes of Exposure

Inhalation

May cause respiratory tract irritation. May cause drowsiness and dizziness.

Ingestion

May be fatal if swallowed and enters airways.

Skin Contact

Causes skin irritation.

Eye Contact

Causes serious eye irritation.

Immediate Effects

Skin irritation, severe eye irritation, respiratory tract irritation, central nervous system damage, eye damage, systemic toxicity, aspiration hazard

Delayed Effects

Reproductive effects, central nervous system damage, kidney damage

Irritation/Corrosivity

Skin irritation, severe eye irritation

Respiratory Sensitization

No information available for the product.

Skin Sensitization

No information available for the product.

Carcinogenicity

Component Carcinogenicity

Acetone (67-64-1)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

Toluene (108-88-3)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))

Germ Cell Mutagenicity

No information available for the product.

Teratogenicity

No information available for the product.

Reproductive Effects

Available data characterizes components of this product as reproductive hazards.

Specific Target Organ Effects - Single Exposure

Central nervous system, eyes, systemic toxicity, respiratory system

Specific Target Organ Effects - Repeated Exposure

Central nervous system damage, kidney damage

Aspiration Hazard

This material is an aspiration hazard.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), cardiovascular, liver, kidney, central nervous system, eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

Safety Data Sheet

Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% VOC - BULK

SDS ID: 820076B

*** Section 12 - Ecological Information ***

Ecotoxicity

Harmful to aquatic life.

Component Analysis - Ecotoxicity - Aquatic Toxicity

Acetone (67-64-1)

Duration/Test/Species	Concentration/Conditions	Notes
96 Hr LC50 Oncorhynchus mykiss	4.74 - 6.33 mL/L	
96 Hr LC50 Pimephales promelas	6210 - 8120 mg/L [static]	
96 Hr LC50 Lepomis macrochirus	8300 mg/L	
48 Hr EC50 Daphnia magna	10294 - 17704 mg/L [Static]	
48 Hr EC50 Daphnia magna	12600 - 12700 mg/L	

Methyl alcohol (67-56-1)

Duration/Test/Species	Concentration/Conditions	Notes
96 Hr LC50 Pimephales promelas	28200 mg/L [flow-through]	
96 Hr LC50 Pimephales promelas	>100 mg/L [static]	
96 Hr LC50 Oncorhynchus mykiss	19500 - 20700 mg/L [flow-through]	
96 Hr LC50 Oncorhynchus mykiss	18 - 20 mL/L [static]	
96 Hr LC50 Lepomis macrochirus	13500 - 17600 mg/L [flow-through]	

Toluene (108-88-3)

Duration/Test/Species	Concentration/Conditions	Notes
96 Hr LC50 Pimephales promelas	15.22 - 19.05 mg/L [flow-through]	1 day old
96 Hr LC50 Pimephales promelas	12.6 mg/L [static]	
96 Hr LC50 Oncorhynchus mykiss	5.89 - 7.81 mg/L [flow-through]	
96 Hr LC50 Oncorhynchus mykiss	14.1 - 17.16 mg/L [static]	
96 Hr LC50 Oncorhynchus mykiss	5.8 mg/L [semi-static]	
96 Hr LC50 Lepomis macrochirus	11.0 - 15.0 mg/L [static]	
96 Hr LC50 Oryzias latipes	54 mg/L [static]	
96 Hr LC50 Poecilia reticulata	28.2 mg/L [semi-static]	
96 Hr LC50 Poecilia reticulata	50.87 - 70.34 mg/L [static]	
96 Hr EC50 Pseudokirchneriella subcapitata	>433 mg/L	
72 Hr EC50 Pseudokirchneriella subcapitata	12.5 mg/L [static]	
48 Hr EC50 Daphnia magna	5.46 - 9.83 mg/L [Static]	
48 Hr EC50 Daphnia magna	11.5 mg/L	

Persistence and Degradability

No information available for the product.

Bioaccumulation Potential

No information available for the product.

Mobility in Soil

No information available for the product.

Other Adverse Effects

No additional information is available.

*** Section 13 - Disposal Considerations ***

Disposal Methods

D001. D035. Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the waste code applicable to the disposal of this product.

Safety Data Sheet

Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% VOC - BULK

SDS ID: 820076B

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

*** Section 14 - Transport Information ***

Emergency Response Guide Number

127 Reference *North American Emergency Response Guidebook*

Transportation Regulations

DOT Shipping Name: Flammable liquids, toxic, n.o.s. (Contains: Acetone, Methyl alcohol)

UN/NA #: UN1992 **Hazard Class:** 3 **Packing Group:** II

Required Label(s): 3, 6.1

TDG Shipping Name: Flammable liquids, toxic, n.o.s. (Contains: Acetone, Methyl Alcohol)

UN/NA #: UN 1992 **Hazard Class:** 3 **Packing Group:** II

Required Label(s): 3, 6.1

*** Section 15 - Regulatory Information ***

Volatile Organic Compounds (As Regulated)

<45 WT% (max); 3.1 lb/ US gal; 372g/L

U.S EPA 40 CFR 51.100(s)

Acetone Vapor Pressure @20°C ~ 184 mmHg

Methanol Vapor Pressure @20°C ~ 98 mmHg

Toluene Vapor Pressure @20°C ~ 22 mmHg

Product contains 20 VOL% photochemically reactive solvent. (toluene)

Consult your state or local air district regulations for location specific information.

Federal Regulations

SARA 302/304

Component Analysis

Based on the ingredient(s) listed in Section 3, this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

SARA 311/312 Hazardous Categories

Acute Health: Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactive:** No

SARA Section 313

Component Analysis

This product contains a "toxic" chemical subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

Methyl alcohol (67-56-1) 1.0 % de minimis concentration

Toluene (108-88-3) 1.0 % de minimis concentration

CERCLA

Component Analysis

Based on the ingredient(s) listed in SECTION 3, this product contains the following "hazardous substance" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4 with the following reportable quantities (RQ):

Acetone (67-64-1) 5000 lb final RQ; 2270 kg final RQ

Methyl alcohol (67-56-1) 5000 lb final RQ; 2270 kg final RQ

Toluene (108-88-3) 1000 lb final RQ; 454 kg final RQ

Safety Data Sheet

Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% VOC - BULK

SDS ID: 820076B

TSCA Inventory

All the components of this product are listed on, or are automatically included as "naturally occurring chemical substances" on, or are exempted from the requirement to be listed on, the TSCA Inventory.

Component Analysis

Component	CAS #	TSCA
Acetone	67-64-1	Yes
Methyl alcohol	67-56-1	Yes
Toluene	108-88-3	Yes

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	MA	MN	NJ	PA	CA
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes
Methyl alcohol	67-56-1	Yes	Yes	Yes	Yes	Yes
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes

THIS PRODUCT IS NOT FOR SALE OR USE IN THE STATE OF CALIFORNIA.

Canadian Regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

Component Analysis

Component	CAS #	CAN
Acetone	67-64-1	DSL
Methyl alcohol	67-56-1	DSL
Toluene	108-88-3	DSL

Canadian WHMIS Information

B2, D1A, D2A, D2B

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Acetone (67-64-1) 1 %
Methyl alcohol (67-56-1) 1 %
Toluene (108-88-3) 1 %

***** Section 16 - Other Information *****

Revision Information

Reformat to OSHA HazCom 29 CFR 1910.1200 adoption of GHS Revision 3.

Safety Data Sheet

**Material Name: SAFETY-KLEEN PROFESSIONAL BRAKE CLEANER
<45% VOC - BULK**

SDS ID: 820076B

Key/Legend

ACGIH - American Conference of Governmental Industrial Hygienists; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

Disclaimer

User assumes all risks incident to the use of this (these) product(s). To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product(s) as supplied to the user.

End of Sheet 820076B