

# Safety Data Sheet



Hazardous Substance, Dangerous Goods

## 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **839-Line Dulux Solvent Based Alkyd Machine Primer**

### Synonyms:

Dulux Solvent Based Alkyd Machine Primer White VN, 200L  
Dulux Solvent Based Alkyd Machine Primer KeriKeri White, 200L  
Dulux Solvent Based Alkyd Machine Primer Satin, 200L  
Dulux Solvent Based Alkyd Machine Primer 10B17, 200L  
Dulux Solvent Based Alkyd Machine Primer Beige, 200L  
Dulux Solvent Based Alkyd Machine Primer Desert Tan, 200L  
Dulux Solvent Based Alkyd Machine Primer TF Grey, 200L  
Dulux Solvent Based Alkyd Machine Primer Moteuka Green, 200L  
Dulux Solvent Based Alkyd Machine Primer Otorohunga Grey, 200L

### Product Code

839G0013-200L  
83997652-200L  
839G0012-200L  
83956857-200L  
83997654-200L  
83997651-200L  
83997657-200L  
839G0062-200L  
83997535-200L

### Bar Code

-  
-  
-  
-  
-  
-  
-  
-  
-

**Recommended use:** Factory applied timber machine primer. Applied by brush, roller or spray.

**Supplier:** Dulux New Zealand, a division of  
DuluxGroup (New Zealand) Pty Ltd

**ABN:** 55 133 404 118 / Co. 2355191

**Street Address:** 150 Hutt Park Road  
Lower Hutt  
New Zealand

**Telephone:** 0800 800 424

**Emergency telephone number:** Australia – 1800 033 111 New Zealand – 0800 734 607

## 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of EPA New Zealand

**EPA Group Standard:** Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006; HSR002669



### Signal Word

Warning

### HSNO Hazard Classification

3.1C Flammable liquids  
6.3B Substances that are mildly irritating to the skin  
6.5B Substances that are contact sensitisers  
6.7B Substances that are suspected human carcinogens  
6.9 Narcotic  
9.1C Substances that are harmful in the aquatic environment

# Safety Data Sheet



## Hazard Statement(s)

|      |                                                   |
|------|---------------------------------------------------|
| H226 | Flammable liquid and vapour                       |
| H316 | Causes mild skin irritation                       |
| H317 | May cause an allergic skin reaction               |
| H336 | May cause drowsiness or dizziness                 |
| H351 | Suspected of causing cancer                       |
| H412 | Harmful to aquatic life with long lasting effects |

## Prevention Precautionary Statement(s)

|      |                                                                               |
|------|-------------------------------------------------------------------------------|
| P102 | Keep out of reach of children                                                 |
| P103 | Read label before use                                                         |
| P201 | Obtain special instructions before use                                        |
| P202 | Do not handle until all safety precautions have been read and understood      |
| P210 | Keep away from all sources of ignition - No smoking                           |
| P233 | Keep container tightly closed                                                 |
| P240 | Ground/bond container and receiving equipment                                 |
| P241 | Use explosion-proof electrical, ventilating, lighting and all other equipment |
| P242 | Use only non-sparking tools                                                   |
| P243 | Take precautionary measures against static discharge                          |
| P261 | Avoid breathing mist, vapours or spray                                        |
| P271 | Use only outdoors or in a well-ventilated area                                |
| P272 | Contaminated work clothing should not be allowed out of the workplace         |
| P273 | Avoid release to the environment                                              |
| P281 | Use personal protective equipment as required                                 |

## Response Precautionary Statement(s)

|              |                                                                                                                            |
|--------------|----------------------------------------------------------------------------------------------------------------------------|
| P101         | If medical advice is needed, have product container or label at hand                                                       |
| P304+341     | IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing |
| P308+313     | IF exposed or concerned: Get medical advice/attention                                                                      |
| P302+352     | IF ON SKIN: Wash with soap and water                                                                                       |
| P303+361+353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower                  |
| P363         | Wash contaminated clothing before reuse                                                                                    |
| P333+313     | If skin irritation or a rash occurs: Get medical advice/attention                                                          |
| P370+378     | In case of fire: Use alcohol resistant foam for extinction                                                                 |

## Storage Precautionary Statement(s)

|          |                                             |
|----------|---------------------------------------------|
| P403+235 | Store in a well ventilated place. Keep cool |
| P405     | Store locked up                             |

## Disposal Precautionary Statement(s)

|      |                                                                                                          |
|------|----------------------------------------------------------------------------------------------------------|
| P501 | Dispose of contents/container in accordance with local, regional, national and international regulations |
|------|----------------------------------------------------------------------------------------------------------|

## DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

**Class:** 3 Flammable Liquid

# Safety Data Sheet



## 3. COMPOSITION INFORMATION

| CHEMICAL ENTITY                            | CAS NO.    | PROPORTION |
|--------------------------------------------|------------|------------|
| White spirit                               | 8052-41-3  | 10 - 30%   |
| Naphtha (petroleum), medium aliphatic      | 64742-88-7 | 10 - 30%   |
| Methyl ethyl ketoxime                      | 96-29-7    | < 1%       |
| Ingredients determined to be non-hazardous | -          | Balance    |
|                                            |            | <hr/> 100% |

## 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

**Skin contact:** For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** If in eyes wash out immediately with water. Seek medical attention.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**PPE for First Aiders:** Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Notes to physician:** Treat symptomatically.

# Safety Data Sheet



## 5. FIRE-FIGHTING MEASURES

**Hazchem Code:** •3Y

**Suitable extinguishing media:** Alcohol resistant foam is the preferred fire-fighting medium. If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Flammable liquid. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

**Fire fighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning may emit toxic fumes, including oxides of carbon and nitrogen. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

## 6. ACCIDENTAL RELEASE MEASURES

### SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

### LARGE SPILLS

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Use a spark-free shovel. If contamination of sewers or waterways has occurred advise local emergency services.

**Dangerous Goods – Initial Emergency Response Guide No: 14**

## 7. HANDLING AND STORAGE

**Handling:** Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Dangerous Good Class 3 Flammable Liquid as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

# Safety Data Sheet



## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**National occupational exposure limits:** No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

However for:

|              | TWA |       | STEL |       | CARCINOGEN | NOTICES |
|--------------|-----|-------|------|-------|------------|---------|
|              | ppm | mg/m3 | ppm  | mg/m3 | CATEGORY   |         |
| White spirit | 100 | 525   | -    | -     | -          | -       |

As published by the Safe Work Australia or Department of Labour New Zealand.

**WES-TWA** (Workplace Exposure Standard – Time-weighted Average). The time-weighted average exposure standard designed to protect the worker for the effects of long-term exposure.

**WES-STEL** (Workplace Exposure Standard - Short-Term Exposure Limit). The 15-minute average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue changes, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the “National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)” the ingredients in this material do not have a Biological Limit Allocated.

**Engineering measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

**Personal protection equipment:** G: OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.

Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid skin and eye contact and inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

# Safety Data Sheet



## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Form / Colour / Odour:** Coloured, viscous liquid with a solvent odour.

|                                         |                                                  |
|-----------------------------------------|--------------------------------------------------|
| <b>Solubility:</b>                      | Soluble in organic solvents. Insoluble in water. |
| <b>Specific Gravity (20 °C):</b>        | 1.0 – 1.4                                        |
| <b>Relative Vapour Density (air=1):</b> | >1                                               |
| <b>Vapour Pressure (20 °C):</b>         | N Av                                             |
| <b>Flash Point (°C):</b>                | >23                                              |
| <b>Flammability Limits (%):</b>         | N Av                                             |
| <b>Autoignition Temperature (°C):</b>   | N Av                                             |
| <b>% Volatile by Volume:</b>            | N Av                                             |
| <b>Melting Point/Range (°C):</b>        | N Av                                             |
| <b>Boiling Point/Range (°C):</b>        | N Av                                             |
| <b>Decomposition Point (°C):</b>        | N Av                                             |
| <b>pH:</b>                              | N Av                                             |
| <b>Viscosity (40 °C):</b>               | >21 mm <sup>2</sup> /sec                         |
| <b>Total VOC (g/Litre):</b>             | N Av                                             |

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

## 10. STABILITY AND REACTIVITY

**Reactivity:** No reactivity hazards are known for the material.

**Chemical stability:** This material is thermally stable when stored and used as directed.

**Hazardous reactions:** No known hazardous reactions.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### Acute Effects

**Inhalation:** Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

**Skin contact:** Contact with skin may result in mild irritation. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

# Safety Data Sheet



**Ingestion:** Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is uncoordinated there is greater likelihood of vomit entering the lungs and causing subsequent complications.

**Eye contact:** May be an eye irritant.

## Acute toxicity

**Inhalation:** This material has been classified as non-hazardous.

**Skin contact:** This material has been classified as non-hazardous.

**Ingestion:** This material has been classified as non-hazardous.

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes.  
Skin: this material has been classified as a Category 6.3B Hazard (mild irritant to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser.  
Skin: this material has been classified as a Category 6.5B Hazard (skin sensitiser).

**Aspiration hazard:** This material has been classified as non-hazardous.

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 6.9 Hazard. Exposure via inhalation may result in depression of the central nervous system.

## Chronic Toxicity

**Mutagenicity:** This material has been classified as non-hazardous.

**Carcinogenicity:** This material has been classified as a Category 6.7B Hazard.

**Reproductive toxicity (including via lactation):** This material has been classified as non-hazardous.

**Specific target organ toxicity (repeat exposure):** This material has been classified as non-hazardous.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as a Category Acute 9.1C Hazard.  
Acute toxicity estimate (based on ingredients): 10 - 100 mg/L

**Long-term aquatic hazard:** No information is available to complete an assessment.

**Ecotoxicity:** No information available.

**Persistence and degradability:** No information available.

**Bioaccumulative potential:** No information available.

**Mobility:** No information available.

# Safety Data Sheet



## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

## 14. TRANSPORT INFORMATION

### ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

**UN No:** 1263  
**Dangerous Goods Class:** 3 Flammable Liquid  
**Packing Group:** III  
**Hazchem Code:** •3Y  
**Emergency Response Guide No:** 14

**Proper Shipping Name:** PAINT

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2) or radioactive substances (Class 7), however exemptions may apply.

### MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

**UN No:** 1263  
**Dangerous Goods Class:** 3 Flammable Liquid  
**Packing Group:** III

**Proper Shipping Name:** PAINT

### AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

**UN No:** 1263  
**Dangerous Goods Class:** 3 Flammable Liquid  
**Packing Group:** III

**Proper Shipping Name:** PAINT

## 15. REGULATORY INFORMATION

**This material is not subject to the following international agreements:**

Montreal Protocol (Ozone depleting substances)  
The Stockholm Convention (Persistent Organic Pollutants)  
The Rotterdam Convention (Prior Informed Consent)

**This material is subject to the following international agreements:**

Basel Convention (Hazardous Waste)

- Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish
- International Convention for the Prevention of Pollution from Ships (MARPOL)
- Annex III - Harmful Substances carried in Packaged Form

**This material/constituent(s) is covered by the following requirements:**

- The Standard for the *Uniform Scheduling of Medicines and Poisons (SUSMP)* established under the *Therapeutic Goods Act (Commonwealth)*.
- All the constituents of this material are listed on the *Australian Inventory of Chemical Substances (AICS)*.

## 16. OTHER INFORMATION

### Literary reference

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd ([chemdata.com.au](http://chemdata.com.au)) on behalf of its client.

Reason(s) For Issue: 5 Yearly Revision  
Product Name Change  
Format change  
Change in Hazardous Substance Classification  
Minor Text Changes.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.