page : 1/4

Revision: 9 (09-06-2004) Version: 1 (31-08-2004)

50111/P - LAKEONE wood rebuilder powdered catalyst



SAFETY DATA SHEET

1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Preparation:

Name: LAKEONE wood rebuilder powdered catalyst

Product code: 50111/P Company/business:

Registered company name: INITIATIVES DECORATION.

Address: 7 rue goulebeneze.17770.ECOYEUX.france.

Telephone: 05-46-95-48-00. Fax:05-46-95-95-06. Telex:.

Emergency telephone No.: 01-45--42-59-59. Association/Organisation: ORPHILA.

Normal use:

N/A!

Anglais: "Wood stopping...."

2 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous substances present on their own.

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)

A154 PEROXYDE DE BENZOILE PLASTIFIE A 50 | Concentration >=10.00% and <25.00%. Symbol: Xi R: 7-43-36

Other substances representing a hazard:

No known substance in this category present.

Substances present at a concentration below the minimum danger threshold.

No known substance in this category present.

Other substances with occupational exposure limits.

No known substance in this category present.

3 - IDENTIFICATION OF HAZARDS

This product is not classed as flammable. Refer to the recommendations regarding the other products present on the site

This product is classed: Oxidizing.

May cause fire

Possibility of irritation to the eves.

Possibility of skin sensitisation. The preparation may also irritate the skin and prolonged contact may aggravate this effect.

4 - FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing in an unconscious person.

In the event of exposure by inhalation.

N/A!

In the event of splashes or contact with eyes.

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin.

N/A!

In the event of swallowing.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

SAFETY DATA SHEET (91/155/EEC - 2001/58/CE - ISO 11014-1)

Revision: 9 (09-06-2004) Version: 1 (31-08-2004)

page: 2/4

50111/P - LAKEONE wood rebuilder powdered catalyst

Call a doctor immediately and show him the label.

5 - FIRE-FIGHTING MEASURES

Not relevant.

In the event of fire, the recommended extinguishing agents are:

In the event of fire, use specifically suitable extinguishing agents. Never use water.

foam

CO₂

powder

Extinguishing agents not to be used

N/A!

Special equipment for fire-fighting personnel.

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

6 - ACCIDENTAL RELEASE MEASURES

Safety precautions:

Avoid any contact with the skin and eyes.

Consult the safety measures listed under headings 7 and 8.

Environmental safety precautions:

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Cleaning methods:

Clean preferably with a detergent, do not use solvents.

N/A!

N/A!

7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

Anyone with a history of skin sensitisation must on no account handle such products

Fire prevention:

Prevent access by unauthorised personnel.

Recommended equipment and procedures

For personal safety, see §8.

Observe precautions stated on label and also industrial safety regulations

Avoid contact of product with the skin and eyes

Prohibited equipment and procedures.

Smoking, eating and drinking are prohibited in premises where the preparation is used

Never open the packages under pressure

Storage.

Keep the container tightly closed in a dry place.

Keep well away from combustible materials and reducing agents (amines), acids, bases, heavy metal compounds (accelerators, drying agents, metal, salts)

N/A!

N/A!

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Anyone with a history of skin sensitisation must on no account handle such products.

Safety breathing apparatus:

N/A!

Hand protection.

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.

In the event of prolonged or repeated contact with the hands, use appropriate gloves.

SAFETY DATA SHEET (91/155/EEC - 2001/58/CE - ISO 11014-1)

Revision: 9 (09-06-2004) Version: 1 (31-08-2004)

page: 3/4

50111/P - LAKEONE wood rebuilder powdered catalyst

Eye and face protection.

Avoid contact with eyes.

Wear safety goggles.

Provide eye washes in workshops where the product is constantly handled

Skin protection.

For further information, see § 11 of S.D.S. - Toxicological information.

9 - PHYSICAL AND CHEMICAL PROPERTIES				
Density:	<1			
Acid/base character of preparation:	not relevant.			
Solubility of preparation in water:	Insoluble.			
Vapour tension at 50°C of volatile constituents:	not specified.			
Physical state:	powder or dust			
The pH is impossible to measure or its value is not relevant.				
Self-ignition temperature:	not specified.			
Decomposition temperature:	not specified.			
Melting temperature interval:	not relevant.			

not relevant.

10 - STABILITY AND REACTIVITY

This preparation is reactive and may cause a fire

Average distillation temperature of solvents contained:

Conditions to avoid:

protect from heat

Materials to avoid:

reducers

peroxide accelerator

potent acids

Hazardous decomposition products:

benzoic acid

benzene phenylbenzoate

11 - TOXICOLOGICAL INFORMATION

No data is available regarding the preparation itself.

It is generally agreed that substances contained are likely to cause, when applied to the eye of an animal, the appearance of major lesions which persist for at least twenty-four hours

It is generally agreed that substances contained are likely to cause, among certain predisposed subjects, a sensitisation reaction by cutaneous route

In the event of splashes or contact with eyes.

N/A!

12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

The product must not be allowed to run into drains or waterways.

13 - DISPOSAL CONSIDERATIONS

Do not pour into drains or waterways.

14 - TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport UN1479=OXIDIZING SOLID, N.O.S.

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.
	5.1	O2	III	5.1	50	LQ12	274
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	
	5.1	-	III	5 kg	F-A,S-Q	223 274	

SAFETY DATA SHEET (91/155/EEC - 2001/58/CE - ISO 11014-1)

page : 4/4

Revision: 9 (09-06-2004) Version: 1 (31-08-2004)

50111/P - LAKEONE wood rebuilder powdered catalyst

						900 944		
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note
	5.1	-	III	516	25 kg	518	100 kg	A3
	5.1	-	Ш	Y516	10 kg	-	-	-

15 - STATUTORY INFORMATION

This preparation was classified in compliance with the directive known as <All preparations> 1999/45/EC and its adaptations In addition directive 2001/59/EC with the 28° adaptation of directive 67/548/EC (Hazardous substances) have been taken into account. This product is not classed as flammable.

Preparation classification.







Oxidizing

Contains:

A154 PEROXYDE DE BENZOILE PLASTIFIE A 50 %

Particular hazards associated with the preparation and safety recommendations:

R 43	May cause sensitization by skin contact.
R 36	Irritating to eyes.
R 7	May cause fire.
S 2	Keep out of reach of children.
S 24	Avoid contact with skin.
S 37	Wear suitable gloves.
S 46	If swallowed, seek medical advice immediately and show this container or label.
S 22	Do not breathe dust.
S 25	Avoid contact with eyes.
S 14	Conserver à l'écart des agents réducteurs (amines), des acides, des alcalis et des dérivés de métaux
	lourds
S 50	Do not mix with peroxide accelerators

16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties