#### AMERICAN INTERNATIONAL INDUSTRIES



# MATERIAL SAFETY DATA SHEET

# **Section 1. Product and Company Identification**

Product Name: Ardell LashGrip Adhesive For Strip Lashes - Clear DATE: 2/8/2011

Formula: 87-3524 REV. 01

Item#: 65056, 680250

Manufacturer: American International Industries

2220 Gaspar Ave

Los Angeles, CA 90040

Chem-Tel: (800) 255-3924

# Section 2. Composition / Information on Ingredients

### **Hazardous Ingredients:**

Component	CAS#	용	Exposure Limits ppm	
			ACGIH-TWA	OSHA
 Formaldehyde	50-00-0	<0.20%	0.3 ppm (Ceiling)	0.75 ppm, STEL (OSHA) = 2 ppm
Ammonium Hydroxide	1336-21-6	<0.30%	None Established	None Established

#### Section 3. Hazardous Identification

### Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: Inhalation, Eye, Skin

Eye: Product is alkaline and direct eye contact may cause irritation.

Skin: Product is alkaline and prolonged skin contact may cause irritation.

Ingestion: May cause mucus membrane and respiratory tract damage.

Inhalation: Excessive breathing of vapors may cause mild respiratory irritation.

#### **Section 4. First Aid Measures**

First Aid for Eye: Immediately flush with water for at least 15 minutes, keeping eyelids open. Seed medical attention if

irritation persists.

First Aid for Skin: After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the

contaminated skin with running water and soap. Seek medical attention if irritation persists.

First Aid for Inhalation: If symptoms of prolonged exposure to concentrated material vapors appear, remove to fresh air. If

breathing is difficult, loosen any restrictive clothing and provide oxygen and get medical care if

necessary.





# MATERIAL SAFETY DATA SHEET

First Aid for Ingestion: Rinse mouth out with water. Only induce vomiting if directed by physician. Never give anything by

mouth to an unconscious person. Seek prompt medical attention

## **Section 5. Fire Fighting Measures**

Flash Point (°F/°C): Not available

Flammable Limit

(vol%):

Not available.

Auto-ignition Temp.

(vol%)

Not available.

Extinguisher Media: Water fog, carbon dioxide, dry chemical foam.

Fire Fighting

Use of SCBA is recommended.

Procedures:

Unusual Fire and

None known.

Explosion Hazards:

### Section 6. Accidental Release Measures

Spill or Release Procedures: Absorb with an inert material and place in an appropriate waste disposal container. Provide adequate ventilation. Clean up personnel should use protective equipment to reduce eye contact, inhalation and prolonged skin contact. Personnel safety, handling and exposure recommendation described elsewhere in this data sheet apply to exposure during clean up of spilled material and must be followed.

#### Section 7. Handling and Storage

Handling: Observe precautions found on the label. Wash face and hands thoroughly with soap and water after

handling and before eating, drinking or smoking. Avoid contamination.

Storing: Store in a cool, dry place away from heat, sparks, flame and direct sunlight. Store away from

combustibles and incompatible materials. Keep from freezing.

# Section 8. Exposure Controls / Personal Protective Equipment

Engineering Controls: Good general ventilation should be sufficient to control airborne levels in small quantity use. Local

exhaust is recommended for bulk repackaging or continuous large quantity use.

Eyes: Safety glasses.





# MATERIAL SAFETY DATA SHEET

Body: Synthetic apron.

Respiratory: Wear appropriate respirator when ventilation is inadequate.

Hands. Gloves (impervious).

Feet: Wear chemical resistant shoes.

Personal Protection in A self contained breathing apparatus should be used to avoid inhalation of the product. Boots. Full

case of a Large Spill: suit. Gloves. Safety glasses.

### Section 9. Physical and Chemical Properties

Appearance @ 25°C: White to off-white Viscosity: 3,800 - 7,800

colored adhesive

Odor @ 25°C:Characteristic OdorVapor Pressure:Not applicablepH9.2 - 9.6Vapor Density:Not applicable

pH 9.2 - 9.6 Vapor Density: Not applicable

Specific Gravity: 0.940 - 0.980 Evaporation Rate: Not applicable

Ignition: Not applicable

Total Solids, % 40.0 - 46.0%

Boiling / Not available

**Condensation Point:** 

**Solubility in water** Partially soluble

### Section 10. Stability and Reactivity

Stability: Stable

**Hazardous Decomposition Products:** 

Oxides of carbon form thermal decomposition.

Incompatibility (Materials to Avoid):

Acidic materials cause product to coagulate.

**Hazardous Polymerization:** 

Will not occur.

## **Section 11. Toxicological Information**

Toxicity to Animals: No data available

### **AMERICAN INTERNATIONAL INDUSTRIES**



# MATERIAL SAFETY DATA SHEET

**Chronic Effects on Humans** 

No data available

Other Toxic Effects on Humans

No data available

**Special Remarks on Toxicity to Animals** 

No data available

Special Remarks on Chronic Effects on Humans

No data available

# **Section 12. Ecological Information**

**Ecotoxicity:** No data available

**BOD5** and **COD**: No data available

Biodegradable/OECD:

No data available

Mobility: No data available

**Products of Degradation** 

No data available

**Toxicity of the Products of Biodegradation** 

No data available

Special Remarks on the Products of Biodegradation

No data available

# Section 13. Disposable Considerations

Landfill or incinerate in accordance with applicable Federal, State and Local regulations.

### **Section 14. Transportation Information**

<DOT Information>

## **AMERICAN INTERNATIONAL INDUSTRIES**



# MATERIAL SAFETY DATA SHEET

Proper Shipping Name (49CFR 172.101): Non Regulated Material

Hazard Class: N/A UN/NA: N/A Packing Group: N/A

### Section 15. Regulatory Information

OSHA Regulated: Formaldehyde is a potential human carcinogen.

NTP: Formaldehyde is a potential human carcinogen.

IARC Monographs: Formaldehyde is a potential human carcinogen.

Formaldehyde is listed on California's Propositon 65

Additional regulatory information available upon request.

### Section 16. Other Information

Additional information available upon request.