

# SAFETY DATA SHEET

According to EC 1907/2006 (REACH)

## 1. Identification of the substance/mixture and of the company/undertaking

**MSDS** : 22606  
**Product code 12nc** : 9898 031 21381  
**Supplier** : PANASONIC INDUSTRIAL COMPANY

Two Panasonic Way  
07094 Secaucus  
New Jersey  
United States of America  
TEL: +1-877-726-2228  
FAX: +1-847-468-5750

**Tradename** : HS1 BATTERY PACK (M5070A) [5.04 G LITHIUM]  
**General description** : BATTERY  
**Use** : Various  
**Date last update** : 2011-01-04  
**Publicationdate** : 2005-06-17  
**General information** : dangerous.goods@philips.com  
**Emergency phonenumber** : +31 (0)497-598315

## 2. Hazards identification

### GHS Classification

Not classified according to GHS classification.

### EC Classification

Not classified according to EC classification.

## 3. Composition/information on ingredients

Component	CAS-no	EC-no	Catalogue-no	Percentage(%)	GHS-label EC-label
LITHIUM	7439-93-2	231-102-5	003-001-00-4		GHS02 GHS05 H260 Water-react. 1 H314 Skin corr. 1B EUH014 F,C;R: 14/15 34
MANGANESE DIOXIDE	1313-13-9	215-202-6	025-001-00-3		GHS07 GHS08 H302 Acute tox. 4 H332 Acute tox. 4 H361fd Repr. 2 Xn;R: 62 63 20/22 Repr.Cat. 3
LITHIUM TRIFLUOROMETHANESULPHONATE	33454-82-9	251-528-5			GHS07 H315 Skin irrit. 2 H319 Eye irrit. 2 H335 STOT SE 3 Xi;R: 36/37/38
PROPYLENE CARBONATE	108-32-7	203-572-1	607-194-00-1		GHS07 H319 Eye irrit. 2 Xi;R: 36
DIMETHOXYETHANE, 1,2-	110-71-4	203-794-9	603-031-00-3		GHS02 GHS07 GHS08 H225 Flam. liq. 2 H332 Acute tox. 4 H360FD Repr. 1B EUH019 F,T;R: 60 61 11 19 20 Repr.Cat. 2

## 4. First aid measures

**Skin** : Not applicable.  
**Ingestion** : Not applicable.  
**Inhalation** : Not applicable.  
**Eyes** : Not applicable.  
**Remarks first aid** : none

## 5. Firefighting measures

**Fire-extinguisher** : determined by surrounding  
**Unsuitable fire-extinguisher** : not traceable  
**Special fire-fighting equipment** : In the event of fire, wear protective clothing and use breathing apparatus that is independent of the ambient air.  
**Hazardous decomposition products in fire** : lithium oxide, manganese oxides, carbon monoxide, hydrogen fluoride, sulphur oxides

## 6. Accidental release measures

**Spillage procedure** : not applicable  
**Emergency procedure** : not applicable

## 7. Handling and storage

**Local exhausting** : Under normal circumstances not applicable.  
**Storage conditions** : Store product protected from proximity to other sources of heat, dry.  
**Storage code (on behalf of PGS 15)** : M4

## 8. Exposure controls/personal protection

### Exposure limits :

#### applicable to: The Netherlands (20 °C; 1013 mbar)

No TWA has been laid down. LITHIUM  
TWA(8 hours): 1 mg/m3 MANGANESE DIOXIDE(as manganese)  
TWA(15 minutes): 3 mg/m3 MANGANESE DIOXIDE(as manganese)  
No TWA has been laid down. LITHIUM  
TRIFLUOROMETHANESULPHONATE  
No TWA has been laid down. PROPYLENE CARBONATE  
No TWA has been laid down. DIMETHOXYETHANE, 1,2-

#### applicable to: Belgium (20 °C; 1013 mbar)

TWA(8 hours): 0.2 mg/m3 MANGANESE DIOXIDE(as manganese)

#### applicable to: Germany (20 °C; 1013 mbar)

TWA(8 hours): 0.5 mg/m3 MANGANESE DIOXIDE(as manganese, inhalable dust)

#### applicable to: United States of America (25 °C; 1013 mbar)

TWA(8 hours): 0.2 mg/m3 MANGANESE DIOXIDE(as manganese)

#### applicable to: Sweden (20 °C; 1013 mbar)

TWA(8 hours): 0.2 mg/m3 MANGANESE DIOXIDE(as manganese, dust)  
TWA(8 hours): 0.1 mg/m3 MANGANESE DIOXIDE(as manganese, respirable dust)

#### applicable to: Switzerland (20 °C; 1013 mbar)

TWA(8 hours): 0.5 mg/m3 MANGANESE DIOXIDE(as manganese, inhalable dust)

#### applicable to: China (20 °C; 1013 mbar)

TWA(8 hours): 0.15 mg/m3 MANGANESE DIOXIDE

C=Ceiling; S=Skin

### Remarks exposure limits :

none

### Odour threshold (20°C; 1013 mbar) :

not traceable

### DNEL (Derived No Effect Level)

not traceable

**PNEC (Predicted No Effect Concentration)**

not traceable

**Advised personal protection :**

Hands	:	not applicable
Breakthrough time	:	not applicable
Eyes	:	not applicable
Inhalation	:	not applicable
Skin	:	none (when used normally)

**9. Physical and chemical properties**

Physical state	:	battery
Colour	:	type dependent
Odour	:	odourless
Vapor rate/range	:	not applicable
Boiling point/range	:	not traceable
Melting point/range	:	not traceable
Flash point/range	:	not applicable
Explosive limits	:	not applicable
Dust explosions possible in air	:	not applicable
Density	:	not traceable
Vapour pressure	:	not applicable
Solubility in water	:	not applicable
Solubility in fat	:	not applicable
pH	:	not applicable
Viscosity	:	not applicable
Autoignition temperature	:	not applicable
Decomposition temperature	:	not traceable
Electrostatic chagement	:	not traceable

**10. Stability and reactivity**

Conditions to avoid	:	none
Reactions with water	:	no
Hazardous reactions with	:	none
Hazardous decomposition products at heating	:	none

**11. Toxicological information****Symptoms**

Skin	local	:	Not applicable.
	general	:	Not applicable.
Ingestion	local	:	Not applicable.
	general	:	Not applicable.
Inhalation	local	:	Not applicable.
	general	:	Not applicable.
Eyes	local	:	Not applicable.
Remarks symptoms		:	None

**Toxicity :**

LD-50: >3.478 g/kg (ORL-RAT), MANGANESE DIOXIDE	Source	:	ChemDat (Merck)
LD-50: 29 g/kg (ORL-RAT), PROPYLENE CARBONATE	Source	:	IUCLID
LD-50: 5.37 mg/kg (ORL-RAT), DIMETHOXYETHANE, 1,2-	Source	:	ChemDat (Merck)
LD-50: 3.2 g/kg (ORL-MUS), DIMETHOXYETHANE, 1,2-	Source	:	Sigma-Aldrich
LD-50: >5 g/kg (SKN-RAT), DIMETHOXYETHANE, 1,2-	Source	:	ChemDat (Merck)

**Ames test :** negative PROPYLENE CARBONATE  
negative DIMETHOXYETHANE, 1,2-

Source : IUCLID  
Source : ChemDat (Merck)

**12. Ecological information**

Biological oxygen demand (5)	:	0.025 g/g PROPYLENE CARBONATE	Source	:	IUCLID
Chemical oxygen demand	:	1.29 g/g PROPYLENE CARBONATE	Source	:	IUCLID
Biological(5)/chemical oxygen demand ratio	:	0.019 PROPYLENE CARBONATE			
Degradability	:	not biodegradable MANGANESE DIOXIDE readily biodegradable PROPYLENE CARBONATE	Source	:	ACROS IUCLID
Biochemical factor	:	not traceable			
Log Po/w	:	<0 MANGANESE DIOXIDE -0.49 LITHIUM TRIFLUOROMETHANESULPHONATE	Source	:	IUCLID Easi View

<b>Henry Constant</b>	-0.48 PROPYLENE CARBONATE	<b>Source</b> : IUCLID
	-0.21 DIMETHOXYETHANE, 1,2-	<b>Source</b> : ChemDat (Merck)
	: 9.92E-8 atm m3/mol LITHIUM TRIFLUOROMETHANESULPHONATE	<b>Source</b> : Easi View
	3.63E-4 atm m3/mol PROPYLENE CARBONATE	<b>Source</b> : Easi View

#### Ecotoxicity :

LC-50: 5300 mg/l/96H (Fish), PROPYLENE CARBONATE  
 EC-50: >500 mg/l/48H (Daphnia), PROPYLENE CARBONATE  
 IC-50: >500 mg/l/72H (Algae), PROPYLENE CARBONATE  
 LC-50: >500 mg/l/96H (Fish), DIMETHOXYETHANE, 1,2-

**Source** : IUCLID  
**Source** : IUCLID  
**Source** : IUCLID  
**Source** : ACROS

**Remarks on ecotoxicity** : none

## 13. Disposal considerations

Remainder material has to be incinerated in\_a proper installation or dumped on an approved landfill, in accordance with local and national legislation.

## 14. Transport information

<b>ADR/RID</b>	<b>UN-number</b>	: 3090 LITHIUM METAL BATTERIES
	<b>Hazard identification number</b>	: none
	<b>Class</b>	: 9
	<b>Packinggroup</b>	: II
<b>IMO</b>	<b>UN-number</b>	: 3090 LITHIUM METAL BATTERIES
	<b>Class</b>	: 9
	<b>Packinggroup</b>	: II
	<b>Marine pollutant</b>	: no
<b>IATA/ICAO</b>	<b>UN-number</b>	: 3090 LITHIUM METAL BATTERIES
	<b>Class</b>	: 9
	<b>Packinggroup</b>	: II
	<b>* Remarks</b>	: The product must be transported in accordance with the regulations of IATA PACKING INSTRUCTION 968 - SECTION I.

## 15. Regulatory information

### GHS Labelling

**GHS-Label** : not applicable

**\* Remarks on GHS-labelling** : none

### Labelling according to EC directives

**EC-Label** : not applicable

**Remarks on EC-labelling** : none

## 16. Other information

**\* Remarks on MSDS** : The presence of lithium-batteries gives an enlarged risk of fire.

#### Overview relevant H-sentences from all components in section 3 :

H225	Highly flammable liquid and vapour.
H260	In contact with water releases flammable gases which may ignite spontaneously.
H302	Harmful if swallowed.
H314	Causes severe skin burns.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360FD	May damage fertility. May damage the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
EUH014	Reacts violently with water.
EUH019	May form explosive peroxides.

#### Overview relevant R-sentences from all components in section 3 :

11	Highly flammable.
14/15	Reacts violently with water, liberating extremely flammable gases.
19	May form explosive peroxides.

20	Harmful by inhalation.
20/22	Harmful by inhalation and if swallowed.
34	Causes burns.
36	Irritating to eyes.
36/37/38	Irritating to eyes, respiratory system and skin.
60	May impair fertility.
61	May cause harm to the unborn child.
62	Possible risk of impaired fertility.
63	Possible risk of harm to the unborn child.

---

\* Point to alterations with regard to the previous version.

The information provided in this Material Safety Data Sheet is correct to the best of the knowledge, information and belief of Philips Electronics Nederland B.V. at the date of its printing.