

# **SAFETY DATA SHEET**

**Issue Date:** 08/18/2015 **Revision Date:** 08/18/2015

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product name ST-400 Spray Trim Adhesive

Recommended use of the chemical

and restrictions on use

Product code 891.400

<u>Product Type</u> Extremely flammable aerosol

Synonyms None

Supplier's details

Recommended Use spray adhesive.

Uses advised against No information available

Manufactured For: Winzer Corporation

4060 E. Plano Parkway Plano, TX 75074

Company Phone Number: 800-527-4126

Emergency telephone number

24 Hour Emergency Number: INFOTRAC 1-800-535-5053 (USA & Canada)

WINTER

### 2. HAZARDS IDENTIFICATION

#### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements

#### **Emergency Overview**

#### DANGER

#### Hazard Statements

Causes skin irritation

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs (central nervous system, eyes, kidney, liver, respiratory system, and skin) through prolonged or repeated exposure.

May be fatal if swallowed and enters airways

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance No information available

Physical state No information available

Odor No information available

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

Specific treatment (see first aid on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing and wash before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

WNZER.

\_\_\_\_\_

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physic Do NOT induce vomiting

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

None

#### Other information

· Harmful to aquatic life with long lasting effects

0% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
ACETONE	67-64-1	30-40
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
METHYL ACETATE	79-20-9	10-20
PETROLEUM DISTILLATES	8030-30-6	1-10
TOLUENE	108-88-3	1-10

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

### First aid measures for different exposure routes

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. If symptoms persist, call a physician.

**Skin contact**Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If symptoms persist, call a physician.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen

may be necessary. If breathing has stopped, contact emergency medical services

immediately.

**Ingestion** Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Drink plenty of water. Call a physician or Poison Control Center immediately.

### Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin and eye irritation. May cause respiratory irritation. Harmful if swallowed.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.



### 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Decomposition by contact with water may generate vapors which can be ignited by heat or open flame.

#### Specific hazards arising from the chemical

No information available.

**Explosion Data** 

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge none.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Absorb with sand, clay, or other suitable material. Hard surfaces may be mopped with Personal precautions

> water. Remove all sources of ignition. Avoid contact with the skin and the eyes. Evacuate personnel to be safe areas. Keep people away from and upwind of spill/leak. Contents under pressure. Do not puncture or incinerate cands. Wear protective gloves/clothing and

eye/face protection.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate **Environmental precautions** 

ground water system. Prevent product from entering drains. Do not flush into surface water

or sanitary sewer system. Should not be released into the environment.

Methods and materials for containment and cleaning up

**Methods for Containment** Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so.

Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Methods for cleaning up

Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take

precautionary measures against static discharges.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial

hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures

against static discharges. Do not breathe vapors or spray mist.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, or oxidizing agents. 3

**Aerosol Level** 



### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> 106-97-8:TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup> 75-28-5:TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
METHYL ACETATE 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m³ (vacated) TWA: 200 ppm (vacated) TWA: 610 mg/m³ (vacated) STEL: 250 ppm (vacated) STEL: 760 mg/m³	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m³ STEL: 250 ppm STEL: 760 mg/m³
PETROLEUM DISTILLATES 8030-30-6	-	TWA: 100 ppm TWA: 400 mg/m³ TWA: 500 ppm TWA: 2000 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 400 mg/m³	IDLH: 1000 ppm TWA: 100 ppm TWA: 400 mg/m³
TOLUENE 108-88-3  CGIH: (American Conference of Gov	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m³ STEL: 150 ppm STEL: 560 mg/m³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Exposure controls** 

Engineering Measures Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields.

**Skin and body protection** Chemical resistant apron. Protective gloves.

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.



\_\_\_\_\_\_

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Physical and chemical properties

Physical stateNo information availableAppearanceNo information availableColorNo information available

Odor No information available Odor Threshold No information available

Remarks • Methods

<u>Property</u> <u>Values</u>

**pH** 0

Melting/freezing pointNo information availableBoiling point/boiling rangeNo information availableFlash PointNo information availableEvaporation rateNo information availableFlammability (solid, gas)No information available

Flammability Limits in Air

upper flammability limit No information available lower flammability limit No information available Vapor pressure No information available Vapor density No information available **Specific Gravity** No information available Water solubility Practically insoluble Partition coefficient: n-octanol/waterNo information available **Autoignition temperature** No information available **Decomposition temperature** No information available **Viscosity** No information available **Explosive properties** No information available

**Other information** 

VOC Content(%) 35.78

### 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Conditions to Avoid**

Extremes of temperature and direct sunlight.

#### **Incompatible Materials**

Strong acids, alkalis, or oxidizing agents.

### **Hazardous Decomposition Products**

None known based on information supplied.

### 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

**Product Information** 



Inhalation Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness

based on components. May cause irritation of respiratory tract. Avoid breathing vapors or

mists.

**Eye contact** Irritating to eyes. Avoid contact with eyes.

Skin contact Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin

contact may defat the skin and produce dermatitis. Avoid contact with skin.

Ingestion May be harmful if swallowed. Aspiration into the lungs during swallowing may cause serious

lung damage which may be fatal.

**Component Information** 

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	-	= 50100 mg/m³(Rat)8 h
METHYL ACETATE 79-20-9	> 5 g/kg (Rat)	> 5 g/kg(Rabbit)	= 16000 ppm (Rat) 4 h
PETROLEUM DISTILLATES 8030-30-6	> 5 g/kg(Rat)	-	-
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg(Rabbit)	= 12.5 mg/L (Rat)4 h

### Information on toxicological effects

Symptoms Inhalation may cause nose, throat , and respiratory tract irritation. Irritation to skin and eyes.

May be harmful if swallowed.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization None known.

Germ Cell Mutagenicity None known.

Carcinogenicity The table below indicates whether each agency has evaluated a listed ingredient as a

carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE	-	Group 3	-	-
108-88-3		•		

IARC: (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans

**Reproductive toxicity** This product does not contain any known or suspected reproductive hazards.

Specific target organ systemic

May cause respiratory irritation. May cause drowsiness and dizziness.

toxicity (single exposure)
Specific target organ systemic

May cause damage to organs through prolonged or repeated exposure.

toxicity (repeated exposure)
Chronic toxicity

May cause adverse liver effects.

Target Organ EffectsCentral nervous system, Eyes, Kidney, Liver, Respiratory system, Skin.

**Aspiration hazard** May be fatal if swallowed and enters airways.

#### Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document ...

 ATEmix (oral)
 113062 mg/kg

 ATEmix (dermal)
 178817 mg/kg

#### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to fish Toxicity to	
			microorganisms	other aquatic invertebrates



ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8	-	-	-	-
METHYL ACETATE 79-20-9	120 mg/L EC50 Desmodesmus subspicatus 72h	295 - 348 mg/L LC50 Pimephales promelas 96h flow-through 250 - 350 mg/L LC50 Brachydanio rerio 96h static	-	1026.7 mg/L EC50 Daphnia magna 48h
PETROLEUM DISTILLATES 8030-30-6	4700 mg/L EC50 Pseudokirchneriella subcapitata 72h	9.2 mg/L LC50 Lepomis macrochirus 96h static	-	-
TOLUENE 108-88-3	433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static	15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 12.6 mg/L LC50 Pimephales promelas 96h static 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 54 mg/L LC50 Oryzias latipes 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static	<del>-</del>	5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h

### Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

Chemical Name	log Pow
ACETONE 67-64-1	-0.24
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	<=2.8
METHYL ACETATE 79-20-9	0.18
TOLUENE 108-88-3	2.65

Other adverse effects No information available

## 13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

**Contaminated packaging** Do not re-use empty containers.

\_<u>\_\_\_</u>\_\_\_\_



### 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D

or

LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

### **15. REGULATORY INFORMATION**

#### **International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ACETONE	Х	Х	X	Х	Х	Х	X	Х
PROPANE/ISOBUTA NE/N-BUTANE	Х	Х	Х	Not listed	Х	Х	Х	Х
METHYL ACETATE	Х	Х	Х	Х	Х	Х	X	Х
PETROLEUM DISTILLATES	Х	Х	Х	Not listed	Х	Х	Х	Х
TOLUENE	Х	Х	Х	Х	Х	Х	Х	Х

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	1-10	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

### **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

\_\_\_\_



Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	Х	Х	Х

### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

### **U.S. State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65	
TOLUENE - 108-88-3	Developmental	

### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
METHYL ACETATE 79-20-9	X	X	X
PETROLEUM DISTILLATES 8030-30-6	X	X	X
TOLUENE 108-88-3	X	X	X

EPA Pesticide Registration Number Not applicable

### <u>Canada</u>

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

### 16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical

hazards 
HMIS Health Hazard 2 Flammability 4 Physical Hazard 1 Personal protection B

Prepared By: Regulatory Affairs

Issuing date 18-Aug-2015
Revision Date 18-Aug-2015
Revision Note

No information available



Disclaimer The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its

publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet** 

