### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.

# W. F. Taylor Co., Inc.

11545 Pacific Avenue Fontana, CA 92337-8228 951/360-6677

CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: CERAMIC TILE ADHESIVE ODYSSEY 901

ITEM NUMBER: 901-1

ITEM DESCRIPTION: 901 Ceramic Tile Adhesive Odyssey 901 1-gal

PRODUCT DESCRIPTION: MASTIC

CHEMICAL FAMILY: SYNTHETIC LATEX BLEND

REVISION DATE: 09/26/14 REVIEW DATE: / / PRINT DATE:10/13/14 PRINT TIME:12:00

HMIS HAZARD RATING

LEAST: 0 HEALTH: 1
SLIGHT: 1 FLAMMABLE: 0
MODERATE: 2 REACTIVITY: 0

HIGH: 3
EXTREME: 4

PREPARED BY: ROBERT DDAMULIRA PREEMPTS PREVIOUS MSDS SHEETS

### SECTION II HAZARDOUS INGREDIENTS

RESIDUAL AMOUNTS OF MONOMERS AND FORMALDEHYDE

## SECTION III PHYSICAL DATA

Hazard			CAS #	WT/Wt % Less Than	1
SOLVENT NAPHTHA			64742-887	< 2.0	SARA Rep.
ACGIH TLV: 100	PPM	(TWA);			
OSHA PEL: 500	PPM	(TWA);			
ETHYLENE GLYCOL			107-21-1	< 2.0	SARA Rep.
ACGIH TLV: 50 P	PM	(TWA);			
OSHA PEL: 50 P	PM	(TWA);			

BOILING POINT: NO DATA LBS / GAL: 12 - 14

VAPOR PRESSURE, MMHG AT 20 DEGREES C: ND

EVAPORATION RATE: SAME AS WATER VAPOR DENSITY: SAME AS WATER SOLUBILITY IN WATER: DILUTABLE

PERCENT VOLATILE: 32 - 36 (BY WEIGHT)

COLOR: WHITE ODOR: NIL

SECTION IV FIRE AND EXPLOSION HAZARD DATA

(Continued) Page 2

PRODUCT NAME: CERAMIC TILE ADHESIVE ODYSSEY 901

ITEM NUMBER: 901-1

ITEM DESCRIPTION: 901 Ceramic Tile Adhesive Odyssey 901 1-gal

REVISION DATE: 09/26/14 REVIEW DATE: / / PRINT DATE:10/13/14 PRINT TIME:12:00

FLASH POINT, TAG C.C.: N.A. AUTO IGNITION TEMPERATURE, F: N.A.

FLAAMABLE LIMITS IN AIR, VOLUME %: LOWER: N.A. UPPER: N.A.

FIRE EXTINGUISING MEDIA: WATER SPRAY, CARBON DIOXIDE, FOAM, DRY CHEMICAL SPECIAL FIREFIGHTING PROCEDURES: WEAR SELF CONTAINED BREATHING APPARATUS

UNUSUAL FIRE AND EXPLOSION HAZARD: NONE KNOWN

### SECTION V HEALTH HAZARD IDENTIFICATION

SYMPTOMS OF OVER EXPOSURE:

INHALATION: MAY IRRITATE RESPIRATORY TRACT

EYES: MAY RESULT IN IRRITATION SKIN: MAY RESULT IN IRRITATION

INGESTION: MAY RESULT IN GASTRIC DISTURBANCES

PRIMARY ROUTE OF EXPOSURE:

ROUTES OF ENTRY FOR SOLIDS AND LIQUIDS INCLUDE EYE AND SKIN CONTACT, INGESTION AND

INHALATION.

ACUTE OVEREXPOSURE:

EYES AND SKIN CONTACT MAY RESULT IN IRRITATION. INHALATION MAY RESULT IN RESPIRATORYIRRITATION, INGESTION MAY RESULT IN GASTRIC DISTURBANCES.

CHRONIC EXPOSURE:

NONE KNOWN

## SECTION VI FIRST AID PROCEDURES

FIRST AID PROCEDURES:

EYES: FLUSH WITH WATER

SKIN: WASH WITH SOAP AND WATER

INHALATION: REMOVE TO FRESH AIR IF NEEDED

INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

#### SECTION VII HANDLING AND STORAGE

PRECAUTION FOR HANDLING AND STORING: DO NOT PUNCTURE. PROTECT AGAINST PHYSICAL DAMAGE.

AVOID BREATHING BUILD-UP OF VAPORS. USE WITH ADEQUATE VENTILLATION.

KEEP OUT OF THE REACH OF CHILDREN.

PROTECT FROM FREEZING. STORE IN A DRY PLACE (50 - 90 DEGREES F).

CAUTION: DO NOT TAKE INTERNALLY. IF INGESTION , DO NOT INDUCE VOMITING, CALL PHYSICIAN IMMEDIATELY.

### SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NONE NEEDED

VENTILATION: LOCAL EXHAUST

PROTECTIVE GLOVES: NONE REQUIRED

EYES: GOGGLES

OTHER PROTECTIVE EQUIPMENT: NONE

(Continued) Page 3

PRODUCT NAME: CERAMIC TILE ADHESIVE ODYSSEY 901

ITEM NUMBER: 901-1

ITEM DESCRIPTION: 901 Ceramic Tile Adhesive Odyssey 901 1-gal

REVISION DATE: 09/26/14 REVIEW DATE: / / PRINT DATE:10/13/14 PRINT TIME:12:00

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED

KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS. USE ABSORBENT MATERIAL TO COLLECT AND/OR SCRAPE UP EXCESS AND PLACE INTO CLOSED DOT APPROVED CONTAINERS FOR DISPOSAL.

### SECTION X STABILITY AND REACTIVITY DATA

STABILITY: STABLE

FREEZE THAW STABILITY: UP TO 5 CYCLES AT 10 DEGREES F

CONDITIONS TO AVOID: KEEP AWAY FROM EXTREME TEMPERATURE CONDITIONS

INCOMPATIBILTY-MATERIALS TO AVOID: NONE KNOWN HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

### SECTION XI TOXICOLOGICAL PROPERTIES

CHRONIC/SUBCHRONIC DATA:

FORMALDEHYDE IS A MINOR VOLATILE COMPONENT OF THIS PRODUCT. RECENT TEST RESULTS HAVE SHOWN FORMALDEHYDE TO CAUSE CANCER IN LABORATORY ANIMALS. FORMALDEHYDE IS READILY DETECTED BY ITS IRRITANT PROPERTIES. THE ODOR DETECTION LEVEL VARIES WITH INDIVIDUALS BETWEEN 0.2 PPM TO 1 PPM. ALSO ACCLIMATION OCCURS FROM REPEATED EXPOSURE BUT SENSITIVITY RETURNS FOLLOWING REST PERIODS AWAY FROM ATMOSPHERES CONTAINING FORMALDEHYDE. WHETHER RISK EXISTS AT LEVELS BELOW THE ODOR THRESHOLD HAS NOT BEEN DETERMINED.

### SECTION XII ECOLOGICAL INFORMATION

NOT AVAILABLE

### SECTION XIII DISPOSAL CONSIDERATION

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS

# SECTION XIV: TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: NOT APPLICABLE PROPER HAZARD CLASS: NOT HAZARDOUS

HAZARD CODE: NOT HAZARDOUS

### SECTION XV REGULATORY INFORMATION

ALL COMPONENTS IN THIS PRODUCT ARE LISTED IN TSCA INVENTORY
OSHA HAZARD COMMUNICATION STANDARD (29CFR 1910.1200) HAZARD CLASS (ES): NONE
SARA TITLE III SECTION 312 HAZARD CLASS: NONE
EPA SARA TITLE III SECTION 313: NONE

CALIFORNIA PROPOSITION 65: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR REPRODUCTIVE HARM.

#### SECTION XVI OTHER INFORMATION

(Continued) Page 4

PRODUCT NAME: CERAMIC TILE ADHESIVE ODYSSEY 901

ITEM NUMBER: 901-1

ITEM DESCRIPTION: 901 Ceramic Tile Adhesive Odyssey 901 1-gal

REVISION DATE: 09/26/14 REVIEW DATE: / / PRINT DATE:10/13/14 PRINT TIME:12:00

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.