

# MATERIAL SAFETY DATA SHEET

<b>Manufacturer:</b> Schaeffer Mfg. Company <b>Address:</b> 102 Barton Street <b>Address:</b> St. Louis, MO 63104		<b>Emergency Response Number:</b> <b>314-865-4105 (24-hr emergency number) or</b> <b>800-325-9962</b>				
<b>SECTION 1 – PRODUCT INFORMATION</b>						
<b>Chemical Family:</b> Petroleum Hydrocarbons and Additives		<b>Trade Name:</b> #206-00 Cotton Picker Spindle Grease				
<b>Formula:</b> Proprietary Mixture						
<b>SECTION 2 – HAZARDOUS INGREDIENTS</b>						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	%	Exposure Limits			
			TVL		PEL	
			ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
100% Paraffin Petroleum Base Oils	64742-65-0, 64742-54-7, 64742-62-7 64742-88-1	90-97		5		5
Antimony Diamylldithiocarbamate	15890-25-2	0.5 – 1		.5		.5
Sodium Nitrate	7631-99-4	0.4 – 1	NE		NE	
Polytetrafluoroethylene	9002-84-0	0.5 -1	NE		NE	
Organophilic Clay	71011-25-1	1-3	NE		NE	
<b>Section 3 – PHYSICAL DATA</b>						
<b>Boiling Point:</b>	600°F/315.5°C	<b>Specific Gravity:</b>	1.01			
<b>Vapor Pressure (mm, Hg):</b>	Not Determined	<b>% Volatile:</b>	Not Determined			
<b>Vapor Density (Air = 1):</b>	Not Determined	<b>Evaporation Rate: (=1)</b>	Not Established			
<b>Solubility in Water:</b>	Insoluble	<b>pH:</b>	Not Applicable			
<b>Appearance and Odor:</b> Tan color, slight smell						
<b>SECTION 4 - FIRE AND EXPLOSION HAZARD DATA</b>						
<b>Flash Point (Method) °F/°C:</b> 439°F/226.11°C C.O.C. (ASTM D-92)		<b>Flammability Limits UEL &amp; LEL</b> ----Not Determined				
<b>Extinguishing Media:</b> Carbon dioxide foam, dry chemical foam, sand, earth, waterfog.						
<b>Special Fire Fighting Procedures:</b> For fires involving this material, do not enter any enclosed or confined space without protective equipment including self-contained breathing apparatus.						
<b>Unusual Fire &amp; Explosion Hazards:</b> None expected.						
<b>SECTION 5 - REACTIVITY HAZARD DATA</b>						
<b>STABILITY</b>	<input checked="" type="checkbox"/> STABLE	<input type="checkbox"/> UNSTABLE	<b>Hazardous Decomposition</b> <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR			
<b>Conditions to Avoid:</b> High heat, high energy ignition sources						
<b>Incompatibility (Mat. to avoid):</b> Strong oxidizers, zinc and nitrogen.						
<b>Hazardous Decomposition Products:</b> Oxides of carbon, sulfur, antimony, zinc and nitrogen						
<b>Conditions to Avoid:</b> None						
<b>SECTION 6 - HEALTH HAZARD DATA</b>						
<b>Threshold Limit Value and Sources:</b> 5.0/mg/m <sup>3</sup> for oil mist. OSHA & ACGIH.						
<b>Acute Effects of Overexposure:</b>						
<b>Ingestion:</b>	Nausea and Diarrhea. Tackiness agents in this product may be possibly coagulated by stomach acids.					
<b>Eye Contact:</b>	Irritation and redness to eyes					
<b>Skin Contact:</b>	Prolonged and repeated contact with the skin may cause a mild skin irritation.					
<b>Inhalation:</b>	Vapors can be given off under high heat conditions excessive breathing of vapors can cause irritation of the respiratory tract.					
<b>CHRONIC EFFECTS OF OVEREXPOSURE:</b> If ingested in large amounts or repeatedly, damage to the cardiovascular system and respiratory tract can occur.						
<b>Emergency and First Aid Procedures:</b>						
<b>Swallowing:</b>	If a large amount of this material is swallowed give a large amount of water to drink. Do not induce vomiting. Seek medical attention immediately.					
<b>Skin:</b>	Wash skin thoroughly with soap and water. Launder contaminated clothing.					
<b>Inhalation:</b>	Remove victim to fresh air. If breathing is labored administer oxygen. If breathing has stopped start artificial respiration immediately.					
<b>Eyes:</b>	Flush eyes with clear, cool, clean water for 15 minutes. Seek medical attention immediately					
<b>SECTION 7 – SPILL OR LEAK PROCEDURES</b>						
<b>Environmental Impact:</b> This material is not expected to present any environmental problems other than those associated with oil spills. If spilled into a watercourse, call the Coast Guard Toll Free No. 800-424-8802.						
<b>Procedures To Be Taken If Material Is Released or Spilled:</b> Scoop up material in a waste drum for used oils. Absorb spilled material with absorbent clay, or other suitable material. Keep out of sewers and waterways.						
<b>Waste Disposal Method:</b> Dispose of at an approved waste or disposal site facility in accordance with all applicable federal, state and local laws and regulations. This product is not considered to be an RCRA hazardous waste.						
<b>SECTION 8 – SPECIAL PROTECTION INFORMATION</b>						
<b>Respiratory Protection:</b>	None required under ordinary conditions of use.					
<b>Ventilation:</b>	No special requirement under ordinary conditions of use and with adequate ventilation.					
<b>Eye Protection:</b>	Chemical resistant goggles of face shield.					
<b>Protective Clothing:</b>	Oil resistant gloves.					

Date Prepared: 12/15/2008

OF-1049 Rev. (1999)

SECTION 9 – SPECIAL PRECAUTIONS		
<b>Precautions To Be Taken In Handling and Storage:</b> Do not store near heat, spark, flame or strong oxidizers. Keep containers closed when not in use.		
<b>Special Comments:</b> Remove oil soaked clothing, launder before reuse. Wash skin thoroughly with soap and water after handling and before eating, smoking or using toilet facilities. Keep away from food and feed products		
SECTION 10 – ADDITIONAL HEALTH AND TOXICOLOGICAL DATA		
<p align="center"><b>HMIS &amp; NFPA Ratings:    Health = 1            Fire = 1            Reactivity = 0</b></p> <p>This product does not contain any of the chemicals listed on the National Toxicology Program Annual Reports on Carcinogens, The International Agency for Cancer Research Monographs and OSHA's 1910.10 Subpart Z List.</p> <p>This product does not contain any chemicals that are found on the State of California's Proposition 65 List for chemicals classified as potential reproductive or cancer causing agent.</p> <p>For SARA Title III Information, see below.</p> <p>All of the components in this material are on the US TSCA Inventory. All components are in compliance with the Canadian Environmental Act.</p>		

## SARA Title III Information

## Title III Section 302/304 Extremely Hazardous

Component	CAS#	%	RQ (lbs.)	TPQ (lbs.)	RQ*
None					

## CERCLA Section 102 (a) Hazardous Substances

Component	CAS#	%	RQ (lbs.)	RQ*
Antimony Dialkyldithiocarbamate	5890-25-2	0.5 -1	5,000	59,644 lbs
Sodium Nitrite	7632-00-0	0.4 – 1	100	1,193 lbs

## Section 313 Chemicals

Component	CAS#	%
Antimony Dialkyldithiocarbamate	5890-25-2	0.5-1
Sodium Nitrite	7632-00-0	0.4-1

\*Product RQ for Stationary Sources in case of a spill needed to release the component RQ.

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any natures whatsoever resulting from the use or reliance upon information. **No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers.**