

SAFETY DATA SHEET

Revision Date 06-Nov-2014 Creation Date 06-Nov-2014 **Revision Number 1**

1. Identification

Shandon Rapid-Chrome Kwik Diff Solution 1 - Methanol Fixative **Product Name**

Cat No.: 9990700, 9990705

Carbbinol; Methyl, Alcohol; Methyl hydroxide; Monohydroxymethane; Wood alcohol; Wood **Synonyms**

naptha; Wood spirits; Columbian spirits

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Emergency Telephone Number Company

Richard Allan Scientific Chemtrec US: (800) 424-9300 A Subsidiary of Thermo Fisher Scientific Chemtrec EU: 001 (202) 483-7616

4481 Campus Drive Kalamazoo, MI 49008 Tel: (800) 522-7270

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2 Acute oral toxicity Category 3 Category 3 Acute dermal toxicity Acute Inhalation Toxicity - Dusts and Mists Category 3 Specific target organ toxicity (single exposure) Category 1 Target Organs - Respiratory system, Central nervous system (CNS), Optic nerve. Specific target organ toxicity - (repeated exposure) Category 1

Target Organs - Respiratory system, Skin, Gastrointestinal tract (GI), Kidney, Liver, spleen, Blood.

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor

Toxic if swallowed

Toxic in contact with skin

Toxic if inhaled

May cause respiratory irritation May cause drowsiness or dizziness

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

IF exposed: Call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Rinse mouth

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

3. Composition / information on ingredients

Component	CAS-No	Weight %
Methyl alcohol	67-56-1	>99

4. First-aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.

Revision Date 14-Aug-2014

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a

respiratory medical device. Immediate medical attention is required.

Ingestion Call a physician or Poison Control Center immediately. Do not induce vomiting.

Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like Most important symptoms/effects

headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

CO₂, dry chemical, dry sand, alcohol-resistant foam. Use water spray to cool unopened **Suitable Extinguishing Media**

containers.

Unsuitable Extinguishing Media Water may be ineffective

12 °C / 53.6 °F **Flash Point**

Method -No information available

Autoignition Temperature 455 °C / 851 °F

Explosion Limits

31.00 vol % Upper Lower 6.0 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

11--14-

Carbon monoxide (CO) Formaldehyde

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Health	Flammability	Instability	Physical hazards
3	3	0	N/A

6. Accidental release measures

Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to **Personal Precautions**

safe areas. Keep people away from and upwind of spill/leak. Take precautionary measures

against static discharges. Do not get in eyes, on skin, or on clothing.

Environmental Precautions Should not be released into the environment. See Section 12 for additional ecological

information. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary Up

measures against static discharges. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling Use only under a chemical fume hood. Use explosion-proof equipment. Keep away from

open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on

clothing.

Storage Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly

closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat and

sources of ignition.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m ³	TWA: 200 ppm
	Skin	(Vacated) STEL: 250 ppm	TWA: 260 mg/m ³
		(Vacated) STEL: 325 mg/m ³	STEL: 250 ppm
		Skin	STEL: 325 mg/m ³
		TWA: 200 ppm	-
		TWA: 260 mg/m ³	

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Methyl alcohol	TWA: 200 ppm TWA: 262 mg/m³ STEL: 250 ppm STEL: 328 mg/m³ Skin	TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 310 mg/m³	TWA: 200 ppm STEL: 250 ppm Skin

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Use only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

FN166

Skin and body protection

Respiratory Protection

Wear appropriate protective gloves and clothing to prevent skin exposure. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorAlcohol-like

Odor Threshold
pHNo information available
No information availableMelting Point/Range-98 °C / -144.4 °F

 Boiling Point/Range
 64.7 °C / 148.5 °F @ 760 mmHg

 Flash Point
 12 °C / 53.6 °F

Flash Point 12 °C / 53.6 °F
Evaporation Rate 5.2 (Ether = 1.0)
Flammability (solid,gas) No information available

Flammability or explosive limits

Upper 31.00 vol % 6.0 vol %

Shandon Rapid-Chrome Kwik Diff Solution 1 - Methanol Fixative

 Vapor Pressure
 128 hPa @ 20 °C

 Vapor Density
 1.11 (Air = 1.0)

 Relative Density
 0.791

SolubilityMiscible with waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature455 °C / 851 °FDecomposition TemperatureNo information availableViscosity0.55 °C P at 20 °C

Molecular Formula C H3 OH
Molecular Weight 32.04

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Heat, flames and sparks.

Incompatible Materials Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides, Strong bases,

Metals, Peroxides

Hazardous Decomposition Products Carbon monoxide (CO), Formaldehyde

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Methyl alcohol	6200 mg/kg (Rat)	Not listed	22500 ppm (Rat) 8 h	

Toxicologically Synergistic Carbon tetrachloride

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and skin

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	Component CAS-No IARC NTP		ACGIH	OSHA	Mexico	
Methyl alcohol	67-56-1	Not listed				

Mutagenic Effects Mutagenic effects have occurred in experimental animals.

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals.

Developmental EffectsDevelopmental effects have occurred in experimental animals.

Teratogenicity Teratogenic effects have occurred in experimental animals.

STOT - single exposure Respiratory system Central nervous system (CNS) Optic nerve

STOT - repeated exposure Respiratory system Skin Gastrointestinal tract (GI) Kidney Liver spleen Blood

Aspiration hazard No information available

Shandon Rapid-Chrome Kwik Diff Solution 1 - Methanol Fixative

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

delayed

Endocrine Disruptor Information No information available

Other Adverse Effects

The toxicological properties have not been fully investigated. See actual entry in RTECS for

complete information.

12. Ecological information

Ecotoxicity

.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	_
			EC50 = 43000 mg/L 5 min	

Persistence and Degradability

No information available

Bioaccumulation/ Accumulation

No information available.

Mobility .

Component	log Pow
Methyl alcohol	-0.74

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes	
Methyl alcohol - 67-56-1	U154	-	

14. Transport information

DOT

UN-No UN1230 Proper Shipping Name METHANOL

Hazard Class 3
Packing Group ||

<u>TDG</u>

UN-No UN1230

Proper Shipping Name METHANOL Hazard Class 3

Subsidiary Hazard Class 6.1 Packing Group

<u>IATA</u>

UN-No UN1230

Proper Shipping Name METHANOL

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group ||

IMDG/IMO

UN-No UN1230

Proper Shipping Name METHANOL

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group ||

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Methyl alcohol	Х	Χ	-	200-659-6	-		Χ	Χ	Χ	Х	Х

Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	>99	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act Not applicable

Clean Air Act

out All Act				
Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors	
Methyl alcohol	X		-	

OSHA Occupational Safety and Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-

California Proposition 65 This product does not contain any Proposition 65 chemicals

Component	CAS-No	CAS-No California Prop. 65 Prop		Category		
Methyl alcohol	67-56-1	Developmental	-	Developmental		
State Right-to-Know						

ĺ	Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
	Methyl alcohol	Х	X	Х	X	Х

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class B2 Flammable liquid

D2A Very toxic materials D1A Very toxic materials



Other information

Prepared By Regulatory Affairs

Richard Allan Scientific

A Subsidiary of Thermo Fisher Scientific

Tel: (800) 522-7270

 Creation Date
 06-Nov-2014

 Revision Date
 14-Aug-2014

 Print Date
 14-Aug-2014

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS