

XEROX

Material Safety Data Sheet

MSDS No: A-0001 OBSOLETE

Date: 4/15/81

Revision: 12/14/91

Manufacturer: Xerox Corporation
Rochester, NY 14644

Health Emergency Tel No.: (716)422-2177
Transportation Emergency: (716)422-1230
Safety Information Tel No.:(800)828-6571

Section I Product Identification

Trade Names/Synonyms: Copyflo II, Copyflo 24 Toner,
Copyflo Toner PN-1

Part No. : 6R20, 6R21, 6R176

Chemical Name: None

Ingredients

Styrene/acrylate polymer (75-80%)

Polyvinylbutyral resin (10.15%)

Carbon black (10.15%)

CAS No.

25213-39-2

63148-65-2

1333-86-4

Section II Emergency and First Aid

Eyes: Flush with water.

Skin: Wash with soap and water.

Inhalation: Remove from exposure.

Ingestion: Dilute stomach contents with several glasses of water.

Primary Route of Entry: Inhalation

Symptoms of Overexposure: Minimal respiratory tract irritation may occur as with exposure to large amounts of any non-toxic dust.

Medical Conditions Generally

Aggravated by Exposure: None when used as described by product literature.

Additional Information: See Sections V and VII. Further information on file in Poisindex

Section III Toxicology and Health Information

This material has been evaluated by Xerox Corporation.

Oral LD₅₀: >16 g/kg (rats) practically non-toxic.

Dermal LD₅₀: >3 g/kg (rabbits) practically non-toxic.

Inhalation LC₅₀: >8 mg/l (rats, 4 hr exposure) practically non-toxic.
>32 mg/l (calculated 1 hr exposure) non-poisonous, DOT.

Eye Irritation: Not an irritant.

Skin Sensitization: Not a sensitizer.

Skin Irritation: Not an irritant.

Human Patch: Non-irritating, non-sensitizing

Mutagenicity: No mutagenicity detected in Ames, and WP2 Assays.

Carcinogens: None present

Aquatic LC₅₀: >500 mg/l (fathead minnows) non-toxic.

Additional Information: In a Xerox sponsored chronic inhalation study in rats using a special test toner, there were no lung changes at all in the lowest exposure level (1mg/m³), the most relevant level to potential human exposures. A very slight degree of fibrosis was noted in 25% of the animals at the middle exposure level (4 mg/m³) while a slight degree of fibrosis was observed at the highest exposure level (16 mg/m³) in all animals. These findings are attributed to "lung overloading," a generic response to excessive amounts of any dust retained in the lungs for a prolonged interval. The special test toner was ten times more respirable than commercially available Xerox toner to comply with EPA testing protocol and would not function properly in Xerox equipment.

TLV: 10 mg/m³ (total dust)

PEL: 15 mg/m³ (total dust)
5 mg/m³ (respirable dust)

STEL: None established

Ceiling: None established

XEL¹: 2.5 mg/m³ (total dust)

0.4 mg/m³ (respirable dust)

¹XEL-Xerox Exposure Limit

Trade Name: Copyflo II, Copyflo 24 Toner, Copyflo Toner PN-I

MSDS No.: A-0001

Section IV Physical Data

Appearance/Odor:	Black powder / faint odor	Softening Range:	85°C to 100°C
Boiling Point:	N.A.	Melting Point:	N.A.
Solubility in Water:	Negligible	Specific Gravity (H ₂ O=1):	-1
Evaporation Rate:	N.A.	Vapor Pressure (mm Hg):	N.A.
Vapor Density (Air=1):	N.A.	pH=	N.A.
Volatile	N.A.% (Wgt) N.A. % (Vol.)		

Section V Fire and Explosion Data

Flash Point (Method Used):	N.A.	Flammable Limits	LEL: N.A. UEL: N.A.
Extinguishing Media:	Water, dry chemical, carbon dioxide or foam.		
Special Fire Fighting Procedures:	Avoid inhalation of smoke. Wear protective clothing and self-contained breathing apparatus.		
Fire and Explosion Hazards:	Toner is a combustible powder. Like most organic materials in powder form, when dispersed in air, it can form explosive mixtures.		

Section VI -Reactivity Data

Stability:	Stable	Hazardous Polymerization:	Will Not Occur
Hazardous Decomposition Products:	Products of combustion may be toxic. Avoid breathing smoke		
Incompatibility (Materials to Avoid):	None known		

Section VII Special Protection Information

Respiratory Protection:	None required when used as intended in Xerox equipment.
Eye Protection:	None required when used as intended in Xerox equipment.
Protective Gloves:	None required when used as intended in Xerox equipment.
Other:	For use other than normal customer operating procedures (such as in bulk toner processing facilities), goggles and respirators may be required. For more information, contact Xerox.

Section VIII Special Precautions

Handling and Storage:	None
Conditions to Avoid:	Avoid prolonged inhalation of excessive dust

Section IX- Spill, Leak, and Disposal Procedures

For Spills or Leakage:	Sweep up or vacuum spilled toner and carefully transfer into sealable waste container. Sweep slowly to minimize generation of dust during clean-up. If a vacuum is used, the motor must be rated as dust tight. A conductive hose bonded to the machine should be used to reduce static buildup (See Section V). Residue can be removed with soap and cold water. Garments may be washed or dry cleaned, after removal of loose toner.
Waste Disposal Method:	When disposed, this material is not a hazardous waste according to Federal Regulation 40 CFR 261. However, State and Local requirements may be more restrictive. Therefore, consultation with the appropriate State and Local waste disposal authorities is advised. Incinerate only in a closed container.

Section X Transportation Information

DOT Proper Shipping Name:	Not Regulated
Hazard Classification:	N.A.
ID Number:	N.A.